



Triangle Block

PRODUCT NAME

Triangle Block Bearing Unit (Three-Bolt Flange Bearing)

Purpose of Product

This unit is used to support rotating shafts in applications where a three-point mounting provides better stability and load distribution. It is especially useful in setups with higher vibration or where secure, evenly distributed mounting is required.

Key Features

- Triangular three-bolt flange design for enhanced mounting stability
- Even load distribution across three fixing points
- Compact and rigid housing for improved alignment
- Integrated insert bearing for quick installation and replacement
- Set screw or eccentric locking collar options
- Durable construction suitable for demanding environments
- Pre-lubricated with provision for re-lubrication

Detailed Specifications

- **Type:** Three-bolt flange (triangle block)
- **Housing Material:** Cast iron or ductile iron
- **Bearing Type:** UC series insert bearing
- **Mounting Configuration:** 3-hole triangular flange
- **Shaft Diameter Range:** Typically ~12 mm to ~90 mm (varies by model, e.g., FT204–FT218)
- **Locking Mechanism:** Set screw locking or eccentric collar
- **Lubrication:** Grease nipple for periodic maintenance
- **Sealing:** Rubber seals or metal shields (depending on bearing insert)
- **Operating Temperature:** Approx. -20°C to +120°C
- **Finish:** Painted or anti-corrosion coated
- **Applications:** Agricultural machinery, conveyors, packaging equipment, fans, and industrial systems requiring firm flange mounting