


[Home](#) » [Enterprise Java](#) » [hibernate](#) » [Hibernate Foreign Key Example](#)

ABOUT SHAGUN MITTAL



Shagun is an enthusiastic Java developer with 5 + years of Industry experience in various Java and Web technologies. She is a certified Java Programmer and has worked extensively with other programming languages and framework, such as Hibernate, Spring MVC, Spring Boot, RDBMS, Unix, etc. As part of delivery services she has created and implemented efficient applications and programs in various industries, including insurance, retail, public sector, telecommunication etc.

[in](#)

Hibernate Foreign Key Example

Posted by: [Shagun Mittal](#) in [hibernate](#) August 20th, 2018 1 Comment 7551 Views

1. Introduction

In this post, we feature a comprehensive Example on Hibernate Foreign Key. Foreign key refers to single column or group of columns in table that link data present in another table through its primary key. A Foreign key can't exist without its parent key but viceversa is not true.

Example – A Menu can have submenus. It can be represented in tabular form as shown below where column

Menu_ID

is Primary key of

T_MENU

table and it is acting as Foreign Key (link between both tables) for

T_SUBMENU

table:

Menu_id -> PRIMARY KEY	Description	Submenu_id -> PRIMARY KEY	Description	Menu_id -> Foreign Key
1	User	1	Manager	1
2	Courses	2	Administrator	1
3	Department	3	Student	1
		4	B-tech	2
		5	Accounts	3
		6	Information Technology	3
		7	MBA	2

NEWSLETTER

157,977 insiders are already enjoying weekly updates and complimentary whitepapers!

Join them now to gain **EX ACCESS** to the latest news in the Java as well as insights about Android, Spring, Groovy and other related technologies!

Email address:

Your email address

☒ Receive Java & Developer job alerts in your Area

Sign up



In order to help you master JPA and database programming with Hibernate, we have compiled a kick-ass guide with all the major Hibernate features and use cases! Besides studying them online you may download the eBook in PDF format!

Download NOW!



guest writer
Code Geeks at
writing skills!

Java Persistence Specifications provide different ways to create Foreign Key mappings as mentioned below:

- 1 – Using Association Mappings
- 2 – By Saving Collections using

@ElementCollection

In this article we will show Foreign Key Creation using **One to Many bi-directional Association Mapping**.

Association Mapping – It is a feature provided by JPA to link two tables using below associations. Each Association can be Uni-Directional or Bi-Directional.

Association	Example
One to One	One Person can have One Unique Identification Number
One to Many	One Menu can have Many Sub-Menu
Many to One	Many Sub-Menu can have One Parent Menu (Reverse of Many to One)
Many to Many	One Student can enrol for many courses and a course can be enrolled by many students.

2. Technologies Used

We will be building this project from scratch using following tools and technologies:

- Eclipse
- Spring Boot 1.5.10
- Maven
- Oracle
- Hibernate
- Java 8 or above

3. Create Project

We are creating Spring Boot project using Spring initializer. Steps are mentioned below:

- 1 – Go to <http://start.spring.io/>
- 2 – Select the following:

SPRING INITIALIZR bootstrap your application now

Generate a Maven Project with Java and Spring Boot 1.5.15

Project Metadata

Artifact coordinates

Group

com.example

Artifact

hibernateExample



Dependencies

Add Spring Boot Starters and dependencies to your application

Search for dependencies

Web, Security, JPA, Actuator, Devtools...

Selected Dependencies

Web X JPA X

This spring project is ready to deploy and you can run it as Java Application in Eclipse. Now we will build our One To Many Mapping Example. For Simplicity, we'll be creating Service, Repository and Model classes in same package –

```
com.example.hibernateExample
```

3.1 Project Configurations

[pom.xml](#)

```

01 <?xml version="1.0" encoding="UTF-8"?>
02 <project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
03     xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 http://maven.apache.org/xsd/maven-4.0.0.xsd">
04     <modelVersion>4.0.0</modelVersion>
05
06     <groupId>com.example</groupId>
07     <artifactId>hibernateExample</artifactId>
08     <version>0.0.1-SNAPSHOT</version>
09     <packaging>jar</packaging>
10
11     <name>hibernateExample</name>
12
13     <parent>
14         <groupId>org.springframework.boot</groupId>
15         <artifactId>spring-boot-starter-parent</artifactId>
16         <version>1.5.16.BUILD-SNAPSHOT</version>
17         <relativePath/> <!-- lookup parent from repository -->
18     </parent>
19
20     <properties>
21         <project.build.sourceEncoding>UTF-8</project.build.sourceEncoding>
22         <project.reporting.outputEncoding>UTF-8</project.reporting.outputEncoding>
23         <java.version>1.8</java.version>
24     </properties>
25
26     <dependencies>
27         <dependency>
28             <groupId>org.springframework.boot</groupId>
29             <artifactId>spring-boot-starter-web</artifactId>
30         </dependency>
31
32         <dependency>
33             <groupId>org.springframework.boot</groupId>
34             <artifactId>spring-boot-starter-data-jpa</artifactId>
35         </dependency>
36
37         <dependency>
38             <groupId>javax.xml.bind</groupId>
39             <artifactId>jaxb-api</artifactId>
40             <version>2.3.0</version>
41         </dependency>
42
43         <dependency>
44             <groupId>org.springframework.boot</groupId>
45             <artifactId>spring-boot-starter-test</artifactId>
46             <scope>test</scope>
47         </dependency>
48     </dependencies>
49
50     <build>
51         <plugins>
52             <plugin>
53                 <groupId>org.springframework.boot</groupId>
54                 <artifactId>spring-boot-maven-plugin</artifactId>
55             </plugin>
56         </plugins>
57     </build>
58 </project>

```

Dependencies used in pom.xml: Spring Boot MVC(

```
spring-boot-starter-web
```

), Hibernate (

```
spring-boot-starter-data-jpa
```

) and

```
jaxb-api
```



```

10 # logging
11 logging.pattern.console=%d{yyyy-MM-dd HH:mm:ss} %-5level %logger{36} - %msg%n
12 logging.level.org.hibernate.SQL=debug

```

application.properties

file is present in

src/main/resources

folder of a Spring Boot project. We are doing Hibernate Configurations here using Oracle JDBC driver (Since Oracle restricts automatic download of OJDBC dependency by Maven, one need to explicitly download

ojdbc6.jar/ojdbc7.jar

from Oracle's site and need to include it in

ClassPath

)

3.2 Model Classes – MainMenu and SubMenu

In this section, we will design our model or entity classes using JPA and Hibernate provided annotations. Hibernate framework will be using these annotations to create tables and their Foreign Key Relationship in database. Variables of Entity class will be created as **Columns** in database table.

MainMenu.java

```

01 package com.example.hibernateExample;
02 import java.io.Serializable;
03 import java.util.HashSet;
04 import java.util.List;
05 import java.util.Set;
06 import javax.persistence.CascadeType;
07 import javax.persistence.Column;
08 import javax.persistence.Entity;
09 import javax.persistence.FetchType;
10 import javax.persistence.GeneratedValue;
11 import javax.persistence.GenerationType;
12 import javax.persistence.Id;
13 import javax.persistence.OneToMany;
14 import javax.persistence.Table;
15
16 @Entity
17 @Table(name = "T_Menu")
18 public class MainMenu implements Serializable{
19
20     @Id
21     @GeneratedValue(strategy=GenerationType.AUTO)
22     private int id;
23
24     private String description;
25
26     @OneToMany(mappedBy="mainMenu", cascade = CascadeType.ALL)
27     Set subMenu = new HashSet();
28
29     public MainMenu() {
30     }
31
32     public MainMenu(String description) {
33         this.description = description;
34     }
35
36     // Getters and Setters (Omitted for brevity)

```

MainMenu

class is One(Reference) side of relationship and

SubMenu

class represents Many(owning) side of relationship as 'One Menu can have many Sub Menu'. In Database terminology, the table that has foreign key is Owner of association mapping. Let's understand few annotations in detail which are used by Hibernate framework to create and manage Entity classes.

Line 16:

@Entity



will be same as entity class name.

Line 20:

```
@Id
```

specify the variable as Primary key column for database table.

Line 21:

```
@GeneratedValue
```

specify the Generation strategy for Primary Key.

Line 26:

```
mappedBy
```

is used with

```
@OneToMany
```

side of association. It indicates that the entity in this side is the **inverse** of the relationship, and the owner resides in the "other" entity. It is used to make a relationship Bi-directional, that means the SubMenu class can be persisted or fetched through Menu class as well.

```
mainMenu
```

in

```
mappedBy="mainMenu"
```

is the ManyToOne annotated field/variable of SubMenu class as shown below:

```
@OneToMany(mappedBy="mainMenu", cascade = CascadeType.ALL);
Set<SubMenu> subMenu = new HashSet<SubMenu>();

@ManyToOne
@JoinColumn(name = "FK_MainMenuId")
private MainMenu mainMenu;
```

Association Mapping

```
CascadeType.ALL
```

will perform all **EntityManager** operations (

```
PERSIST, REMOVE, REFRESH, MERGE, DETACH
```

) to the related entities/ collection e.g when Menu will be Persisted, SubMenu will also be Persisted.

SubMenu.java

```
01 package com.example.hibernateExample;
02
03 import java.io.Serializable;
04
05 import javax.persistence.Column;
06 import javax.persistence.Entity;
07 import javax.persistence.GeneratedValue;
08 import javax.persistence.GenerationType;
09 import javax.persistence.Id;
10 import javax.persistence.JoinColumn;
11 import javax.persistence.ManyToOne;
12 import javax.persistence.Table;
13
14 @Entity
15 @Table(name = "T_SubMenu")
16 public class SubMenu implements Serializable{
17
18     @Id
19     @GeneratedValue(strategy=GenerationType.AUTO)
20     private int id;
21
22     @Column(name="SUBMENU_DESC", nullable=false, length=50)
23     private String description;
24
25
26     @ManyToOne
27     @JoinColumn(name = "FK_MainMenuId")
28     private MainMenu mainMenu;
29
30     public SubMenu() {
31
```

will be used by Hibernate to create

T_Submenu

table in database.

@JoinColumn

annotation in line 27 indicates that this entity is the **owner** of the relationship (which will contain Foreign Key in Database perspective). This annotation is always used with

@ManyToOne

side of association.

name

attribute is used to give logical name to Foreign Key column, though it is not mandatory.

3.3 Repository Interface

MainMenuRepository.java

```
1 package com.example.hibernateExample;
2
3 import org.springframework.data.repository.CrudRepository;
4 import org.springframework.stereotype.Repository;
5
6 @Repository
7 public interface MainMenuRepository extends CrudRepository<MainMenu, Integer>{
8
9 }
```

In this section we are creating

MainMenuRepository

interface that is a Marker interface(which doesn't define any methods). When using Spring Data we need to define a *Repository* interface corresponding to each domain Entity. It will be extending Spring Data's

CrudRepository

interface which declares standard CRUD operations that can be performed on an entity. Use of

CrudRepository

interface will prevent us from writing a lot of boilerplate code to access data source, writing SQL queries, Result Set etc. It will accept two parameters:

- 1 – Entity class corresponding to the Marker interface.
- 2 – Data type of Primary key defined within Entity class.

3.4 Runner

HibernateExampleApplication.java

```
01 package com.example.hibernateExample;
02
03 import java.util.List;
04 import org.springframework.beans.factory.annotation.Autowired;
05 import org.springframework.boot.CommandLineRunner;
06 import org.springframework.boot.SpringApplication;
07 import org.springframework.boot.autoconfigure.SpringBootApplication;
08
09
10 @SpringBootApplication
11 public class HibernateExampleApplication implements CommandLineRunner
12 {
13     @Autowired
14     MenuService menuService;
15
16     public static void main( String[] args )
17     {
18         SpringApplication.run(App.class, args);
19     }
20
21     @Override
22     public void run(String... args) throws Exception {
23         menuService.addMenu();
24     }
25 }
```



@SpringBootApplication

that is equivalent of using

@Configuration

,
@EnableAutoConfiguration

, and

@ComponentScan

. We will be adding new Menus and subMenus in

addMenu()

of service class, which is invoked in overridden

run()

of

CommandLineRunner

interface.

3.5 Service Layer

In this section we will be creating new Menus and their Sub-Menus using methods provided by Spring Data's

CrudRepository

interface. The newly created Menus and their associated Sub-Menus will be added as rows in

T_menu

and

T_submenu

table by Hibernate framework.

MenuService.java

```
1 package com.example.hibernateExample;
2
3 public interface MenuService {
4     public void addMenu();
5 }
```

MenuServiceImpl.java

```
01 package com.example.hibernateExample;
02
03 import java.util.HashSet;
04 import java.util.Set;
05 import javax.transaction.Transactional;
06 import org.springframework.beans.factory.annotation.Autowired;
07 import org.springframework.stereotype.Service;
08
09 @Service
10 public class MenuServiceImpl implements MenuService{
11
12     @Autowired
13     MainMenuRepository mainMenuRepository;
14
15     @Transactional
16     public void addMenu(){
17         // For User MainMenu
18         MainMenu menu1 = new MainMenu("User");
19         //Creating sub-menus for user
20         Set subMenu1 = new HashSet();
21         subMenu1.add(new SubMenu("Manager", menu1));
22         subMenu1.add(new SubMenu("Administrator", menu1));
23         subMenu1.add(new SubMenu("Student", menu1));
24         menu1.setSubMenu(subMenu1);
25
26         // For Guest MainMenu
```





```
39         subMenu3.add(new SubMenu("Accounts", menu3));
40         subMenu3.add(new SubMenu("Information Technology", menu3));
41         subMenu3.add(new SubMenu("Sports", menu3));
42         menu3.setSubMenu(subMenu3);
43
44         //Save MainMenu
45         Set mainMenu = new HashSet();
46         mainMenu.add(menu1);
47         mainMenu.add(menu2);
48         mainMenu.add(menu3);
49         mainMenuRepository.save(mainMenu);
50     }
51 }
52 }
```

addMenu()

of

MenuServiceImpl

class is adding 3 MainMenu named as Course, Department and User and their submenus using CrudRepository's

save()

On Executing this project as a Java Application in Eclipse, we will get following output where

FK_MAIN_MENU_ID

is foreign key in

T_submenu

table:

ID	DESCRIPTION
1	Department
5	Course
9	User

ID	SUBMENU_DESC	FK_MAIN_MENU_ID
2	Sports	1
3	Information Technology	1
4	Accounts	1
6	B-Tech	5
7	BCA	5
8	MBA	5
10	Manager	9
11	Student	9
12	Administrator	9

4. Summary

To Summarize, we have created a Spring Boot project that is adding 3 mainMenu in

T_menu

table i.e Course, Department and User. Each mainMenu can have multiple submenu which are stored in

T_submenu



Entity classes.

5. Download the Source Code

This was an example of creating a Hibernate Foreign Key.

Download

You can download the full source code of this example here: [hibernateExample.zip](#)

Tagged with: [CORE JAVA](#) [HIBERNATE](#) [SPRING](#) [SPRING BOOT](#) [SPRING DATA](#)



(0 rating, 2 votes) 1 Comment 7551 Views Tweet it!

Do you want to know how to develop your skillset to become a **Java Rockstar**?

Subscribe to our newsletter to start Rocking right now!
To get you started we give you our best selling eBooks for **FREE!**

1. JPA Mini Book
2. JVM Troubleshooting Guide
3. JUnit Tutorial for Unit Testing
4. Java Annotations Tutorial
5. Java Interview Questions
6. Spring Interview Questions
7. Android UI Design

and many more

Email address:

☒ Receive Java & Developer job alerts in your Area

Sign up

LIKE THIS ARTICLE? READ MORE FROM JAVA CODE GEEKS

1 Leave a Reply



Join the discussion...

1 0 0 0 0

1

Subscribe

newest oldest most voted



Michael Murphy



I have no idea if you guys monitor these comments but I just wanted to say you've saved me with this tutorial, I was having trouble finding something to explain this simple functionality! This was very clear, and very easy to extend to my own project!

Guest



KNOWLEDGE BASE	FILE OF FNAME	ABOUT JAVA CODE GEKS
Courses	Android Alert Dialog Example	JCGs (Java Code Geeks) is an independent online community focused on creating the ultimate Java to Java developers resource center; targeted at the technical and project manager and junior developer. JCGs serve the Java, SOA, Agile and Telecom communities with daily news, domain experts, articles, tutorials, reviews, announcements, code snippets and source projects.
Minibooks	Android OnClickListener Example	
News	How to convert Character to String and a String to Character Array in Java	
Resources	Java Inheritance example	
Tutorials	Java write to File Example	
THE CODE GEEKS NETWORK	java.io.FileNotFoundException – How to solve File Not Found Exception	DISCLAIMER
.NET Code Geeks	java.lang.arrayindexoutofboundsexception – How to handle Array Index Out Of Bounds Exception	All trademarks and registered trademarks appearing on Java Code Geeks are property of their respective owners. Java is a trademark or registered trademark of Oracle Corporation in the United States and other countries. Examples Java Code Geeks is not connected to Oracle Corporation and is not sponsored by Oracle Corporation.
Java Code Geeks	java.lang.NoClassDefFoundError – How to solve No Class Def Found Error	
System Code Geeks	JSON Example With Jersey + Jackson	
Web Code Geeks	Spring JdbcTemplate Example	

Examples Java Code Geeks and all content copyright © 2010-2019, Exelisis Media P.C. | [Terms of Use](#) | [Privacy Policy](#) | [Contact](#)



We care about your privacy!

We use cookies to understand how you use our site and to improve your experience. This includes personalizing content and advertising. Find out more.

[Manage choices](#)

[Agree & Proceed](#)

