

Architecture Validation Problems Report

1. Executive Summary

Overall Architecture Validation Result: **FAILED**

2. Structural Analysis

Metric	Observed Value
Component Count	11
Relationship Count	16
Undefined References	0
Self Loops	0
Invalid Relationship Types	0

Metric Definitions and Calculation Rules

Component Count: The total number of components explicitly declared in the architectural description.

Relationship Count: The total number of relationships declared between components.

Undefined References: The number of relationships whose source or target does not match any declared component name.

Self-Loops: The number of relationships where the source and target components are identical.

Invalid Relationship Types: The number of relationships whose interaction type is not recognized by the validation rules.

Structural Evaluation Interpretation

Structural validation assesses the syntactic and referential correctness of the architecture. Any non-zero value in Undefined References, Self-Loops, or Invalid Relationship Types indicates an invalid architectural description.

3. Quality Analysis

Component	Fan-In	Fan-Out	Coupling
CV Comparison Module	3	2	5
Cosine Similarity Calculator	1	1	2
Answer Screening Questions Module	0	2	2
View and Edit CV Module	1	1	2
ChatGPT Validator	2	2	4
CV Parser	1	1	2
Screening Question Validator	1	1	2
Get Rating for CV Module	1	0	1
Rating Generator	4	0	4
Submit CV Module	1	5	6

Jaccard Similarity Calculator	1	1	2
-------------------------------	---	---	---

Calculation Formulae

Fan-In(component) = Number of relationships where component is the target.
Fan-Out(component) = Number of relationships where component is the source.
Coupling(component) = Fan-In(component) + Fan-Out(component).

Quality Evaluation Interpretation

Components with high coupling are strongly dependent on other components. High coupling increases maintenance effort, change propagation, and the risk of cascading failures across the architecture.

4. Domain Analysis

Metric	Observed Value
Stateless Ratio	1.0
State Concentration	4
Communication Style	synchronous

Calculation Rules

Stateless Ratio: Inferred value representing the proportion of components without explicitly declared state.
State Concentration: Maximum Fan-In value observed across all components.
Communication Style: Determined by comparing the number of event-driven relationships to synchronous data-flow relationships.

Domain Evaluation Interpretation

High state concentration and synchronous communication patterns indicate centralized coordination and strong runtime dependencies, which negatively impact scalability, resilience, and fault tolerance.

5. Suggested Improvements

- High Coupling in Component 'CV Comparison Module': The component participates in a large number of dependencies.
- High Coupling in Component 'Submit CV Module': The component participates in a large number of dependencies.
- Synchronous Communication Pattern: Components are dependent on immediate responses from other components at runtime.
- State Concentration: System state handling is concentrated in a small number of components.

6. Final Validation Conclusion

The architecture failed validation due to accumulated structural, quality, and domain-level violations. Although the architecture may be executable, it does not conform to recommended architectural quality standards.