

Architecture Validation Problems Report

1. Executive Summary

Overall Architecture Validation Result: **FAILED**

2. Structural Analysis

Metric	Observed Value
Component Count	8
Relationship Count	1
Undefined References	1
Self Loops	1
Invalid Relationship Types	1

Metric Definitions and Calculation Rules

Component Count: The total number of components explicitly declared in the architectural description.

Relationship Count: The total number of relationships declared between components.

Undefined References: The number of relationships whose source or target does not match any declared component name.

Self-Loops: The number of relationships where the source and target components are identical.

Invalid Relationship Types: The number of relationships whose interaction type is not recognized by the validation rules.

Structural Evaluation Interpretation

Structural validation assesses the syntactic and referential correctness of the architecture. Any non-zero value in Undefined References, Self-Loops, or Invalid Relationship Types indicates an invalid architectural description.

3. Quality Analysis

Component	Fan-In	Fan-Out	Coupling
The applicants shall submit their CVs	0	0	0
Recruiters shall be able to assign each screening question its model answer	0	0	0
Recruiters and hiring managers can use the ResuFit website to track applicants	0	0	0
The system shall create an approach that uses cosine similarity and Jaccard similarity	0	0	0
The applicants shall answer the provided screening questions	0	0	0
Recruiters shall be able to provide job vacancies	0	0	0
The system shall utilize the Spacy Python library to accurately extract relevant CV content	0	0	0
The applicants shall view the parsing results and edit them	0	0	0

Calculation Formulae

Fan-In(component) = Number of relationships where component is the target.

Fan-Out(component) = Number of relationships where component is the source.

$\text{Coupling}(\text{component}) = \text{Fan-In}(\text{component}) + \text{Fan-Out}(\text{component})$.

Quality Evaluation Interpretation

Components with high coupling are strongly dependent on other components. High coupling increases maintenance effort, change propagation, and the risk of cascading failures across the architecture.

4. Domain Analysis

Metric	Observed Value
Stateless Ratio	1.0
State Concentration	1
Communication Style	event-driven

Calculation Rules

Stateless Ratio: Inferred value representing the proportion of components without explicitly declared state.

State Concentration: Maximum Fan-In value observed across all components.

Communication Style: Determined by comparing the number of event-driven relationships to synchronous data-flow relationships.

Domain Evaluation Interpretation

High state concentration and synchronous communication patterns indicate centralized coordination and strong runtime dependencies, which negatively impact scalability, resilience, and fault tolerance.

5. Suggested Improvements

- Undefined References: One or more relationships reference components that are not declared in the architectural model.
- Self-Loops: One or more components have relationships where the source and target are the same component.
- Invalid Relationship Types: One or more relationships use interaction types outside the supported architectural vocabulary.

6. Final Validation Conclusion

The architecture failed validation due to accumulated structural, quality, and domain-level violations. Although the architecture may be executable, it does not conform to recommended architectural quality standards.