When Is the Vector Enough? Frozen Residual Readouts versus Answer-Token Scoring

Hanan Herzog
hanan.herzog@gmail.com

Abstract

When does a language model's frozen residual already support the answer, and when does answer-token scoring add value? We compare a small supervised classifier on final-token residual states with zero-/few-shot closed-set answer-token scoring across six open-weight models on BoolQ, RuleTaker, and ARC-Challenge. The methods use the same frozen backbone but different task supervision and prompt lengths. Their relative performance is structured rather than universal: the final-layer readout is numerically higher than requested eight-shot scoring in five of six RuleTaker cases and two of six BoolQ cases, whereas scoring is higher in all six ARC cases. On ARC the scorer's advantage is ordered by readout competence across all six models, falling from 10.6 points where the readout is weakest to under one point for the two strongest readouts.

Existing small-budget refits qualify the result. Stored 64-label readouts fall below the eight-shot scorer in 17 of 18 cells, and BoolQ class-balanced refits do not preserve the full-training readout's advantage, so that advantage is not established as supervision-independent. Intermediate layer sweeps show that answer-relevant information is often accessible before the final layer: in 12 of 18 cells the best swept layer exceeds the final one by more than a crude selection-noise scale, although evaluation-selected maxima still do not establish held-out gains or early exit. The scorer is the stored product-of-token-probabilities heuristic, not marginalized answer likelihood or free-form generation. The contribution is therefore a protocol-specific regime map: readouts are often competitive on rule- and passage-grounded tasks, while scoring is most useful when the residual readout is still weak.

1 Introduction

A frozen language model offers more than one interface for classification. One can use its answer-token outputs, or train a separate classifier on its internal representations. These interfaces need not give the same accuracy: the output head was trained for next-token prediction, while a supervised readout is fitted to the target task's labels. A useful empirical question is how the two procedures compare under explicitly stated training and inference budgets, rather than whether an answer is literally present in a vector.

We compare a one-hidden-layer MLP on final-token residual states with zero-/few-shot answer-token scoring. Both use a frozen backbone and one prompt forward pass per example, but they do not use identical prompts or equal amounts of task-specific supervision. In the main experiments, the classifier is fitted on thousands of labeled examples; the scorer receives a small number of labeled demonstrations in its prompt. The scorer is allowed a longer context, which can preserve more passage text and demonstrations but does not compensate in a controlled way for the classifier's training labels.

Our contribution is a cross-model, cross-task map of when these two readouts separate, together with a supervision-budget qualification and layerwise readouts. This is not a supervision-matched superiority result or a test of generated iterative reasoning. The main observations are:

1. **Scoring's value is regime-dependent.** The final-layer classifier is numerically higher than the fixed eight-shot scorer in five RuleTaker cases and two BoolQ cases, while the scorer is higher in all six ARC cases. The largest scorer gaps occur where the readout is weakest: across all six ARC models the gap falls monotonically with readout accuracy, apart from a 0.4-point inversion between the two strongest readouts (Table 1).

2. **Supervision changes the comparison.** Stored 64-label readouts exist for all 18 cells and fall below the corresponding eight-shot scorer in 17 of them, including all six RuleTaker cells. On BoolQ, where matched requested-shot arms exist, matching the number of classifier training labels to the requested number of demonstrations does not preserve the full-training classifier's advantage (Table 2). These artifacts match declared counts, not independently verified example identities or retained prompt counts.

3. **Answer-relevant information is often accessible before the final layer.** Several intermediate layers support higher readout accuracy than the final layer, and in 12 of 18 cells by more than the scale of the optimism that picking a maximum introduces. These evaluation-selected maxima still do not establish held-out gains from layer selection or justify stopping the backbone early (Table 3).

The interpretation is further limited by the implemented scoring heuristic: its aggregation of alternative tokens differs from probability marginalization. We describe the exact rule below and retain its measured accuracies without presenting it as the strongest available output baseline.

2 Setup and Method

2.1 Supervised residual readout

Let $h_T \in \mathbb{R}^d$ denote the last nonpadding token's output from the final transformer block of a frozen model, before subsequent model-level normalization or output processing. For DeepSeek, grouped trailing output dimensions are flattened into a feature vector, giving an effective input width of 16384 (the other model widths range from 1024 to 4096). The readout capacity is therefore not constant across models: at a fixed hidden width the first layer holds 16 times as many parameters for DeepSeek as for Qwen3-0.6B. DeepSeek has the highest readout accuracy on BoolQ and ARC, and this asymmetry is a candidate explanation that the present runs do not separate from backbone quality. The prompt includes the question and, where supplied by the task, the passage. Gold answers are not appended to the readout's input. Prompts are left-truncated to 384 tokens, retaining the prompt suffix and trailing answer slot, but not necessarily the complete question. We standardize features using training-set means and standard deviations and fit a width-128, one-hidden-layer ReLU MLP. The implementation uses full-batch Adam with learning rate 10^{-3} for 150 epochs, with binary or multiclass cross-entropy as appropriate. The backbone is never updated; the MLP is nevertheless a task-supervised model.

The main readout statistic is the mean accuracy over four training seeds, with their standard deviation. It is neither the accuracy of the best seed nor that of a seed-vote ensemble. Logistic-regression readouts and other feature transformations are secondary analyses; selection of regularization or projection dimension on evaluation accuracy is exploratory.

2.2 Implemented answer-token scorer

The baseline processes a task prompt with zero or k balanced demonstrations from the training split. Demonstrations are selected in class round-robin order from the shuffled training rows; selection is not averaged over different exemplar sets or orders. The round-robin is deterministic and cycles the classes in a fixed order, so for the binary tasks at even k the demonstration immediately preceding the query always carries the same label. Few-shot predictions are known to be sensitive to exactly this kind of exemplar order and label balance [28], and the stored runs do not vary either. Both methods choose from the same closed answer set: Yes/No for BoolQ and RuleTaker, and A–D for ARC. The baseline does not generate intermediate reasoning or a free-form answer. The stored artifacts and table columns name these arms `loop.zero` and `loop.`k for historical reasons; we call them scorer arms throughout.

For each answer class c, the implementation constructs a token-ID set S_c from bare and space-prefixed answer variants tokenized after `Answer:`. It slices off the number of tokens in the standalone prefix, unions the remaining IDs, and removes IDs shared by classes. At the last prompt token, it computes

$$s_c(x) = \sum_{t \in S_c} \log p_\theta(t \mid x), \qquad \hat{y} = \operatorname*{argmax}_c s_c(x). \tag{1}$$

Thus it ranks the *product* of the individual token probabilities, not the sum of probability mass for mutually exclusive answer variants. Marginalization over single-token alternatives would instead use $\log \sum_{t \in S_c} p_\theta(t \mid x)$. Collecting IDs from a multi-token variant also does not compute that variant's sequence likelihood.

A local tokenizer audit found two IDs per Yes/No class for each of the six model tokenizers. On ARC, Mistral and Granite have two IDs per class; the Qwen and DeepSeek tokenizers yield one retained ID per class. In the latter cases, bare letter variants change the prefix tokenization and contribute no suffix IDs under the implemented slicing rule. Consequently, even where sum and marginalization coincide for the retained singleton, the procedure does not establish coverage of all intended answer variants.

All reported scorer accuracies use this existing heuristic. Its numerical difference from a corrected scorer is unmeasured. The pipeline saves aggregate accuracies and, on fresh runs, class predictions rather than the token probabilities needed to rescore offline. These results should not be read as comparisons against standard answer-likelihood scoring generally. The corrections we do not apply are well studied: raw answer-token probability is confounded by surface form and benefits from probability-ratio scoring [19], closed-set prompted predictions benefit from contextual calibration [28], and multiple-choice evaluation is conventionally length- or unconditional-probability-normalized [4]. Token-level decision rules of the kind implemented here are also known to be suboptimal relative to hidden-state criteria on the same frozen model [8], which is independent evidence that our scorer is a weak rather than a strong output baseline, and hence that the readout-favorable cells below are the ones to treat with most caution.

2.3 Supervision, context, and reporting

The main readouts use 9427 training labels on BoolQ, 10000 on RuleTaker, and 1000 on ARC. The ARC filter leaves 1117 four-choice training rows and 1165 test rows; the reported training set is a seed-0 subsample of 1000 rows. We report zero- and eight-shot scorer arms separately, without selecting the stronger arm for the main comparison. This is a reporting choice for the present descriptive analysis, not a preregistered experimental design. Additional BoolQ runs requested up to 64 demonstrations.

The scorer's token cap is 8192 for Qwen BoolQ runs and 2048 otherwise, compared with the readout's 384. Left truncation can remove passage content, complete demonstrations, or parts of demonstrations. The stored results do not measure per-row truncation or the number of retained complete demonstrations. We therefore use *requested shots*, not effective shots. Equal question identities and answer sets do not imply equal token-level inputs or supervision.

Table 1 reports seed means and SDs for the classifier and single accuracies for the scorer. SD describes training-seed variation on the fixed evaluation set, not a confidence interval for population performance. Historical paired tests used separately fitted four-seed vote predictions; they do not directly test the displayed seed-mean differences. We do not attach those tests to the present descriptive tables. Small numerical differences are not evidence of equivalence, and no count of significant wins or corrected discoveries is claimed.

2.4 Models and datasets

The models are Qwen3-0.6B, Qwen3-4B, Qwen3-8B, Mistral-7B-v0.3, Granite-3.1-8B-base, and DeepSeek-V4-Flash (the stored model slug is `DeepSeek-V4-Flash-0731`). These are six models from four families, including dense and mixture-of-experts architectures, not a controlled architecture or parameter-count ablation. Reported backbone runs use batch size 8; DeepSeek uses the local quantized checkpoint loading path. Training-seed SD does not include variation from backbone numerical execution.

BoolQ [10] uses the `google/boolq` training split and its 3270-row validation split. RuleTaker [12] uses `tasksource/ruletaker`, with 10000 sampled training rows and 4000 sampled rows from the official *test* split. The artifacts call the latter `val`; this is an evaluation-set name, not the official validation split. ARC-Challenge [11] uses `allenai/ai2_arc`, retaining four-choice items, with 1117 filtered training rows and 1165 test rows. The reported 1000-row training set is a seed-0 subsample. No retrieval corpus is supplied for ARC, but the question and choices themselves remain part of the input.

3 Results

Figure 1 visualizes the fixed final-layer and separate scorer arms reported in Table 1.

3.1 BoolQ: full-training and small-budget readouts

Table 1 shows that BoolQ is a mixed but informative regime. Qwen3-0.6B has a classifier mean of 0.746 versus 0.645 for eight-shot scoring, while Qwen3-8B is nearly even at 0.878 versus 0.876. The other models favor scoring numerically, so the result is not a universal readout win. It is nevertheless consistent with the broader map: once both channels are strong, their difference is small; where the residual readout is weaker, the scorer can retain an advantage. Small differences are not interpreted as statistical ties.

The existing requested-shot sweep qualifies the Qwen3-8B comparison: its full-training readout (0.878) is below the recorded 16-, 32-, and 64-shot scorer arms (0.886, 0.880, and 0.883, rounded). For Qwen3-0.6B, by contrast, the readout (0.746) exceeds every recorded scorer arm; its scorer rises from 0.631 at zero shots to 0.715 at both 32 and 64 shots (rounded), reducing the readout's lead to about 3.0 percentage points. Similar 32- and 64-shot accuracies in this one protocol do not establish saturation: context truncation and the single exemplar ordering are not separately controlled.

Table 1: Fixed final-layer readout and closed-set scorer accuracies (accuracy). Readout is the stored `last.mlp` mean ± seed SD (four seeds; SD uses divisor four, not a confidence interval). `loop.zero` and `loop.8` are the stored artifact keys for the zero-shot and requested 8-shot scorer arms (§2.2); they are accuracies under the manuscript's product-of-token-probabilities heuristic, not marginalized answer probabilities or free-form generation. Δ = readout mean − `loop.8`, with no baseline selection or significance testing. Artifact-declared train/evaluation/loop counts: BoolQ 9427/3270/3270; RuleTaker 10000/4000/4000; ARC-Challenge 1000/1165/1165. BoolQ Mistral/Granite readouts use sweep files and loops use full-evaluation reruns, not the sweeps' 405-row loops. Readout token cap is 384; loop cap is 8192 for BoolQ Qwen and 2048 otherwise. These are different input and supervision protocols, not a matched-label-budget comparison; requested demonstrations are not measured retained counts.

Task	Model	Readout mean ± SD	`loop.zero`	`loop.8`	Δ vs. 8-shot
BoolQ	Qwen3-0.6B	0.746 ± 0.004	0.631	0.645	+0.101
	Qwen3-4B	0.856 ± 0.002	0.855	0.865	−0.009
	Qwen3-8B	0.878 ± 0.002	0.862	0.876	+0.001
	Mistral-7B	0.841 ± 0.002	0.824	0.863	−0.022
	Granite-3.1-8B	0.854 ± 0.001	0.800	0.865	−0.011
	DeepSeek-V4-Flash	0.896 ± 0.001	0.888	0.906	−0.009
RuleTaker	Qwen3-0.6B	0.684 ± 0.004	0.593	0.580	+0.103
	Qwen3-4B	0.782 ± 0.003	0.678	0.690	+0.092
	Qwen3-8B	0.782 ± 0.003	0.678	0.736	+0.046
	Mistral-7B	0.682 ± 0.005	0.522	0.571	+0.111
	Granite-3.1-8B	0.823 ± 0.002	0.564	0.703	+0.119
	DeepSeek-V4-Flash	0.797 ± 0.002	0.600	0.813	−0.016
ARC-Challenge	Qwen3-0.6B	0.492 ± 0.007	0.502	0.597	−0.106
	Qwen3-4B	0.841 ± 0.001	0.826	0.882	−0.041
	Qwen3-8B	0.909 ± 0.002	0.902	0.913	−0.004
	Mistral-7B	0.728 ± 0.003	0.750	0.779	−0.051
	Granite-3.1-8B	0.708 ± 0.006	0.732	0.790	−0.082
	DeepSeek-V4-Flash	0.951 ± 0.001	0.961	0.959	−0.008

Table 2 reports existing cache-refit artifacts for 8, 16, 32, and 64 training labels on the three Qwen models. They contain both first-n and class-balanced refits. In all 12 model–budget settings, both refit means are below the corresponding requested-shot scorer. For example, the 0.6B class-balanced 64-label readout scores 0.640, compared with 0.715 for requested-64-shot scoring and 0.746 for the full-training readout. At 64 labels the corresponding balanced readouts are 0.855 and 0.849 for 4B and 8B, versus scorer accuracies of 0.867 and 0.883.

These comparisons do not prove that label count explains the whole full-training difference. They do show that the observed advantage is not established as supervision-independent. The refit metadata declares label counts and subset protocols, but the exact balanced subset identities and the cache-refit generator have not been recovered. We treat these as documented existing measurements, not a fully reproduced identical-example experiment.

Figure 2 shows these refits alongside the requested-shot curves and the full-training readout reference.

3.2 RuleTaker and ARC-Challenge

On the 4000-row RuleTaker evaluation subset, the final-layer classifier mean is higher than the eight-shot scorer for five models, with differences from approximately +4.6 to +11.9 percentage




Figure 1: Cross-model accuracy under different supervision protocols. Readout points are final-layer four-seed means. Seed SD spans 0.11 to 0.71 accuracy points across the 18 cells, which is shorter than the plotted markers, so it is stated here rather than drawn; it is training-seed spread on a fixed evaluation set, not a confidence interval. Scorer points retain both zero-shot and requested eight-shot arms of the implemented token-probability heuristic. Readouts use 9427 BoolQ, 10000 RuleTaker, or 1000 ARC training labels; scorers do not fit task-specific weights. Prompt lengths and token caps differ (Table 1). No significance tests are shown.

points. This is the clearest readout-favorable regime in the study: a task-grounded classifier on the frozen residual substantially improves on the stored answer-token decision rule for several backbones. DeepSeek's classifier is lower by about 1.6 points, showing that the pattern is not universal. Zero-shot scoring is higher than eight-shot scoring for Qwen3-0.6B; against zero-shot its readout difference is about +9.0 rather than +10.3 points. The main table keeps both scorer arms visible rather than selecting one using evaluation accuracy.

The stored RuleTaker `depth` field is parsed from the release's configuration name, not measured from a proof for each question. In particular, `depth-3`, `depth-3ext`, and `depth-3ext-NatLang` contribute to the same numeric group. We do not interpret the historical configuration-stratified results as an experiment isolating question-level deduction depth, nor infer a serial reasoning threshold from them.

On ARC, the eight-shot scorer is numerically higher in all six cases. This is the clearest scorer-favorable regime, and its size is ordered by readout competence across the whole model set rather than within one family. Sorting the six cells by readout accuracy gives gaps of 10.6 points (Qwen3-0.6B, readout 0.492), 8.2 (Granite-3.1-8B, 0.708), 5.1 (Mistral-7B, 0.728), 4.1 (Qwen3-4B, 0.841), 0.4 (Qwen3-8B, 0.909), and 0.8 (DeepSeek-V4-Flash, 0.951): monotone in four of five steps, with the only inversion a 0.4-point difference between the two strongest readouts. Granite is the clearest case that the ordering tracks readout accuracy and not parameter count, since its 8.2-point gap accompanies the second-weakest readout in an eight-billion parameter model. The pattern is an empirical association, not a causal size law: readout accuracy and readout-minus-scorer share a term mathematically, and the readout has only 1000 training labels here versus 9427 on BoolQ and 10000 on RuleTaker. The 1000 ARC rows are most of the 1117 filtered training rows, so historical

Table 2: BoolQ label-budget descriptions (accuracy). First-n and class-balanced columns are stored refit seed means from `budget` and `budget.balanced` in the same model's `samek` JSON; loop values are that JSON's `loop.k`. $n = k$ compares artifact-declared readout label counts with requested demonstration counts, not measured retained demonstration counts. Exact subset identity is unavailable, so equal counts do not establish identical labeled examples. The declared training pool has 9427 rows; readout and loop evaluation counts are both 3270. Readout/loop token caps are 384/8192. No significance tests are reported.

Model	$n = k$	First-n refit	Class-balanced refit	`loop.k`
Qwen3-0.6B	8	0.622	0.612	0.645
	16	0.607	0.594	0.669
	32	0.625	0.619	0.715
	64	0.660	0.640	0.715
Qwen3-4B	8	0.850	0.851	0.865
	16	0.828	0.829	0.862
	32	0.839	0.844	0.861
	64	0.853	0.855	0.867
Qwen3-8B	8	0.826	0.825	0.876
	16	0.821	0.812	0.886
	32	0.834	0.845	0.880
	64	0.850	0.849	0.883

1117-label Qwen results provide only corroborating, not drop-in, evidence about the endpoint. Qwen3-0.6B's readout accuracy of 0.492 is well above the 0.25 uniform-guess baseline for four choices; its lower accuracy does not show that no other classifier could extract useful information.

3.3 Exploratory layer sweeps

Table 3 summarizes the recorded layer sweeps using the highest seed-mean accuracy among the swept layers and the final-layer readout from the same source run. The result is not merely that the final state is readable: intermediate states often support stronger task readouts. For example, the recorded RuleTaker Mistral sweep has a selected mean of 0.732 at layer 16 versus 0.682 at the final layer. The selected layer varies across models and tasks; several ARC maxima occur at the final layer.

Selection uses the same evaluation labels on which accuracy is reported, so the selected maxima are optimistic estimates of a layer-selection procedure's generalization. The optimism has a magnitude a reader can check. Taking the binomial standard error at the observed accuracy on each evaluation set and multiplying by the expected maximum of as many independent standard normals as there are swept candidates gives a scale of 0.7 to 2.1 accuracy points, varying with evaluation size and with the 4 to 10 candidates per cell (Table 3). Twelve of the 18 selected-minus-final gaps exceed that scale, including all six RuleTaker cells and five of six BoolQ cells but only one of six on ARC, where the evaluation set is smallest. This yardstick is deliberately crude and, if anything, too strict: layer readouts are positively correlated across depth, which shrinks the real inflation below the independent-candidate figure. It is arithmetic on the stored accuracies, not a hypothesis test, and it is reproduced by `--report` in the table generator.

The gaps that clear the scale are therefore harder to explain as selection artifacts alone; the six that do not are BoolQ DeepSeek and every ARC cell except Qwen3-4B, three of which are exactly zero because the maximum falls at the final layer. Clearing the scale is not a significance claim: it bounds the optimism from picking a maximum, not the evaluation-sampling uncertainty of the




Figure 2: BoolQ supervision-budget descriptions. At $n = k \in \{8, 16, 32, 64\}$, readout curves show first-n and class-balanced refit means; scorer curves show requested-k-shot accuracy. Refit seed SD spans 0.06 to 0.35 accuracy points and is stated rather than drawn, for the reason given in Figure 1. Dashed lines mark the 9427-label readout mean, not a matched-budget arm. Equal counts do not certify identical examples or retained demonstrations; readout/scorer token caps are 384/8192. Lines connect recorded settings, not fitted scaling laws. Sources match Table 2.

underlying difference, and the reported means average four training seeds rather than one draw. A paired test at the selected layer, followed only by correction across the 18 cells, would still not account for the within-cell layer search, so we report no selection-unadjusted significance and make no claim that intermediate layers never lose. These sweeps describe predictive readouts, not the behavior of a backbone stopped early.

Figure 3 displays all recorded MLP sweep points rather than highlighting evaluation-selected maxima.

3.4 Control readouts

Table 4 gives label-shuffle, random-projection, noise, and mean-pooled-context results. Context pooling averages all retained nonpadding prompt tokens, not just passage tokens. Shuffling training labels generally reduces predictive accuracy, but this is not a dataset-overlap audit and does not rule out leakage. On imbalanced datasets, uniform guessing and majority-class prediction have different expected accuracies, so the constant-predictor rate is the reference these controls should be read against: it is 0.6217 on the BoolQ validation split, 0.5035 on the RuleTaker evaluation subset, and 0.2652 on the ARC evaluation split, the last against a 0.25 uniform rate. Against those references the BoolQ shuffle controls (0.522–0.542) fall well below a constant predictor, whereas five of the six ARC shuffle controls sit slightly above 0.2652. Table 2 should be read the same way: the Qwen3-0.6B refits span 0.594 to 0.660, straddling the BoolQ constant-predictor rate, so the smallest-budget readouts there are near or below trivial rather than merely weak.

Gaussian projections retain substantial predictive accuracy at the tested dimensions (64 or 256, reported per row in Table 4). The reported dimension is selected on evaluation accuracy; these are descriptive results. An isotropic Gaussian projection is distributionally invariant to a coordinate permutation, so similar permuted-coordinate results cannot establish that no privileged subspace




Figure 3: Exploratory layer sweeps. Curves connect recorded MLP seed means; bands show ± seed SD (0.07 to 1.17 accuracy points), not confidence intervals. Diamonds mark the final-layer readout from the same sweep JSON, including the separately stored ARC Qwen3-0.6B final L27; their seed SD is not drawn, for the reason given in Figure 1. Sources match Table 3, not necessarily the headline runs. Layer indices are zero-based. No winning layer or significance is marked; evaluation-selected maxima are not held-out gains.

Table 3: Descriptive readout placement sweeps (accuracy). Selected layer maximizes the stored MLP seed mean over recorded sweep entries (including the final layer where swept). Layer indices are zero-based. Selected and final means come from the same sweep JSON; the final column uses that sweep file's `last.mlp`, not a value imported from Table 1. ARC Qwen3-0.6B has no L27 sweep entry; its final mean is stored separately in the same file. *Cand.* is the number of recorded sweep entries the maximum was taken over. It varies from 4 to 10 across cells, and the optimism of a maximum grows with it, so the column is needed to read the selected means; see §3.3 for the resulting noise scale. These evaluation-selected maxima are optimistic, not held-out gains; no significance tests are reported. Sweep train/evaluation counts are 9427/3270 (BoolQ), 10000/4000 (RuleTaker), and 1000/1165 (ARC-Challenge). RuleTaker uses the separate 10k/4k sweep files because the headline 10k/4k files contain no sweep. Source runs and protocols may differ from the headline sources even when displayed final means coincide.

Task	Model	Cand.	Selected layer	Selected mean	Final layer	Final mean
BoolQ	Qwen3-0.6B	7	L18	0.761	L27	0.746
	Qwen3-4B	7	L24	0.868	L35	0.856
	Qwen3-8B	7	L30	0.889	L35	0.878
	Mistral-7B	10	L16	0.863	L31	0.841
	Granite-3.1-8B	10	L20	0.868	L39	0.854
	DeepSeek-V4-Flash	7	L36	0.900	L42	0.896
RuleTaker	Qwen3-0.6B	7	L18	0.720	L27	0.684
	Qwen3-4B	7	L24	0.796	L35	0.782
	Qwen3-8B	7	L24	0.797	L35	0.782
	Mistral-7B	10	L16	0.732	L31	0.682
	Granite-3.1-8B	10	L20	0.845	L39	0.823
	DeepSeek-V4-Flash	7	L29	0.807	L42	0.797
ARC-Challenge	Qwen3-0.6B	4	L26	0.500	L27	0.492
	Qwen3-4B	6	L29	0.856	L35	0.841
	Qwen3-8B	6	L35	0.909	L35	0.909
	Mistral-7B	10	L20	0.741	L31	0.728
	Granite-3.1-8B	10	L39	0.708	L39	0.708
	DeepSeek-V4-Flash	7	L42	0.951	L42	0.951

exists. Finally, the tested mean-pooled-context MLPs are less accurate than the final-token MLPs. This is a comparison of feature summaries, not evidence that a verdict is causally computed at the final token or that passage-level shortcuts are absent.

4 Discussion and Limitations

The central result is a regime map, not a universal winner. A task-specific classifier on a frozen residual is often competitive with the stored closed-set scorer and is substantially better on most of the RuleTaker models. Conversely, scoring has its clearest advantage on ARC when the residual readout is weak, and that advantage narrows as the readout becomes more accurate. The comparison changes both the readout and the training objective, supervision budget, and prompt, so these patterns should not be read as supervision-independent superiority or as proof that the residual alone contains a model belief.

Scorer validity. The product-of-token-probabilities heuristic is not standard marginal answer likelihood. Correcting tokenization and aggregation could change the baseline rankings and numerical conclusions; the stored class predictions cannot quantify that change. All comparative claims are conditional on the implemented scorer, not claims about the best use of the model's output

Table 4: Descriptive control readouts (accuracy). All entries use the headline readout JSONs and train/evaluation counts of Table 1. Shuffle is the stored mean for an MLP refit on permuted training labels (`last.mlp.shufl`); context and final are `ctx.mlp` and `last.mlp` seed means. RP max, its dimension, perm, and noise are the stored `last.randproj` values: linear probes on Gaussian random projections, feature-column-permuted inputs, and Gaussian noise inputs. RP dimension is selected on evaluation accuracy from 64 and 256 using three-seed means; perm and noise use the selected dimension. These are descriptive measurements, not leakage tests or causal evidence.

Task	Model	Shuffle	RP max	RP d	RP perm	RP noise	Context	Final
BoolQ	Qwen3-0.6B	0.535	0.734	256	0.725	0.601	0.667	0.746
	Qwen3-4B	0.542	0.861	256	0.859	0.604	0.717	0.856
	Qwen3-8B	0.528	0.874	256	0.874	0.607	0.739	0.878
	Mistral-7B	0.537	0.810	256	0.803	0.607	0.685	0.841
	Granite-3.1-8B	0.532	0.848	256	0.849	0.607	0.679	0.854
	DeepSeek-V4-Flash	0.522	0.889	256	0.891	0.602	0.678	0.896
RuleTaker	Qwen3-0.6B	0.498	0.657	256	0.663	0.502	0.532	0.684
	Qwen3-4B	0.516	0.748	256	0.752	0.490	0.619	0.782
	Qwen3-8B	0.506	0.760	256	0.755	0.502	0.634	0.782
	Mistral-7B	0.503	0.656	256	0.646	0.502	0.521	0.682
	Granite-3.1-8B	0.504	0.792	256	0.785	0.502	0.599	0.823
	DeepSeek-V4-Flash	0.509	0.768	256	0.759	0.503	0.526	0.797
ARC-Challenge	Qwen3-0.6B	0.278	0.470	64	0.470	0.254	0.278	0.492
	Qwen3-4B	0.269	0.802	64	0.803	0.255	0.349	0.841
	Qwen3-8B	0.287	0.869	256	0.867	0.251	0.399	0.909
	Mistral-7B	0.259	0.679	256	0.678	0.251	0.277	0.728
	Granite-3.1-8B	0.284	0.598	256	0.588	0.251	0.279	0.708
	DeepSeek-V4-Flash	0.269	0.942	256	0.940	0.236	0.439	0.951

distribution.

Supervision is part of the result. Headline label budgets are unequal. Stored first-n readouts at $n = 64$ exist for all 18 headline cells and are below the corresponding eight-shot scorer in 17 of 18 cells, including all six RuleTaker cells. The sole exception is BoolQ Qwen3-0.6B, at 0.657 against 0.645 – the same cell that carries the largest readout-favorable BoolQ margin at full training, so the one budget-restricted survivor is also the one case the headline comparison most favors. This is not matched-budget evidence: RuleTaker and ARC have no 64-shot scorer arm, and these stored refits are first-n, not class-balanced. The BoolQ class-balanced refits provide a complementary qualification for three models on one dataset, with incomplete subset provenance. Neither result establishes general sample efficiency. Effective demonstration counts, truncation rates, and sensitivity to exemplar selection and order remain unmeasured.

Evaluation and selection. This is a retrospective descriptive analysis of existing runs. Evaluation sets informed earlier layer, hyperparameter, and reporting choices; there is no new untouched test set. Seed SD does not capture dataset-sampling or prompt-selection uncertainty. The RuleTaker results cover a sampled subset rather than its full test set. Duplicate and train–evaluation overlap counts have not been audited here; the shuffle controls do not replace those checks.

Computation and mechanisms. Both main methods use a single prompt forward pass, with different lengths; neither generates intermediate reasoning tokens. The experiments therefore do not compare one-pass computation with iterative computation, locate a circuit-complexity boundary, or explain why a particular model favors one method. We make no latency, throughput, early-exit, or production-serving claim, and no comparison to fine-tuned specialists under matched resources.

Artifact coverage. Table sources are explicit in `scripts/build_descriptive_tables.py`, which regenerates the descriptive tables from stored JSONs. Sweep and headline entries are distinct in the source mapping only where separate files are used; some entries share a file or cached computation, so the tables do not provide a run-to-run variability estimate. Where the same quantity was stored twice by different runs it does not always agree: the BoolQ Qwen3-0.6B first-n readout at $n = 64$ is 0.657 in the headline file and 0.660 in the label-budget file. Both readings support the statements that use them, and the difference indicates the scale of run-to-run drift rather than an error in either. Local full-size paired scorer/readout predictions are incomplete for BoolQ Qwen3-0.6B, Qwen3-8B, and DeepSeek; scalar results exist for all 18 cells. Persisted best-seed heads, seed means, and separately fitted vote ensembles are different objects and should not be substituted for one another.

5 Related Work

Frozen representations for prediction. Prior work studies differences between hidden-state classifiers and prompted or token-level decisions [1, 5, 8, 9]. Hazenoot et al. [18] compare frozen-activation probes with prompted yes/no predictions for ESG concept measurement. Our study adds a cross-model, three-dataset comparison under the particular protocols described here, not a new claim that supervised probes can predict task labels.

Scoring closed answer sets. How a frozen model's output distribution is turned into a closed-set decision is itself a literature. Raw answer-token probability is confounded by surface form, motivating probability-ratio scoring [19]; few-shot prompted predictions are sensitive to exemplar choice and order and improve under contextual calibration [28]; multiple-choice evaluation conventionally normalizes by length or unconditional probability [4]; and calibration itself varies with depth [20]. The scorer implemented here applies none of these corrections (§2.2), which places our baseline below the standard of that work and is the main reason our comparative claims are conditional rather than general.

Beliefs and correctness. CCS [6] studies unsupervised recovery of truth-related directions; other work examines belief timing and self-knowledge [3, 13, 21]. Correctness prediction, candidate reranking, and hidden-knowledge studies [7, 15, 22, 24] address related but distinct targets. Our classifier predicts gold task labels from a prompt representation; that operational distinction does not identify the model's beliefs or prove that its output hides an already-computed answer.

Layerwise readouts and adaptive computation. The logit lens [23] and tuned lens [2] map intermediate representations toward vocabulary predictions. Patchscopes [16] and representation engineering [30] provide additional tools for inspecting or intervening on representations. Our supervised layer sweeps measure a different readout objective. Early-exit methods [14, 26, 27, 29] evaluate stopping policies, which we do not implement. Likewise, continuous latent reasoning and looped transformers [17, 25] involve trained iterative computation absent from our main comparison.

6 Conclusion

Across the evaluated models and datasets, frozen residual readouts and closed-set answer-token scoring exhibit structured rather than universal differences. Readouts are higher in most Rule-Taker cases and remain competitive on BoolQ, while scoring has its clearest advantage on ARC models whose residual readouts are weak. Across all six ARC models the gap falls with readout accuracy, suggesting that scoring is most useful when the residual does not yet provide an easily

extractable task decision. Existing small-budget refits show that the full-training readout advantage depends partly on task supervision and should not be interpreted as supervision-independent superiority. Intermediate-layer sweeps further indicate that answer-relevant information is often accessible before the final layer, by margins that in two thirds of cells exceed the optimism of selecting a maximum, although they do not establish early exit. The contribution is a bounded empirical regime map, conditional on the stored scorer and evaluated protocols, rather than a claim that scoring is unnecessary or that every answer is already in the vector.

Data availability

The experiments use public releases of BoolQ [10], RuleTaker [12], and ARC-Challenge [11], with splits, subsampling, and filtering described in §2. Stored result JSONs and the descriptive table generator accompany the manuscript in the repository at https://github.com/hanan-herz/residual-readout-bench. No new model inference or classifier fitting was performed for this revision.

Acknowledgments

Large language models assisted with running experiments and drafting this manuscript: Grok 4.5 (xAI), DeepSeek-V4-Flash, and Kimi K3. OpenAI models assisted with the methodological audit and manuscript revision. The author designed the study and is responsible for reviewing the results and claims.

References

[1] Momin Abbas, Yi Zhou, Parikshit Ram, Nathalie Baracaldo, Horst Samulowitz, Theodoros Salonidis, and Tianyi Chen. Enhancing in-context learning via linear probe calibration. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2024.

[2] Nora Belrose, Zach Furman, Logan Smith, Danny Halawi, Igor Ostrovsky, Lev McKinney, Stella Biderman, and Jacob Steinhardt. Eliciting latent predictions from transformers with the tuned lens. *arXiv preprint arXiv:2303.08112*, 2023.

[3] Siddharth Boppana, Annabel Ma, Max Loeffler, Raphael Sarfati, Eric Bigelow, Atticus Geiger, Owen Lewis, and Jack Merullo. Reasoning theater: Disentangling model beliefs from chain-of-thought. *arXiv preprint arXiv:2603.05488*, 2026.

[4] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[5] Marcus Buckmann and Edward Hill. Logistic regression makes small LLMs strong and explainable "tens-of-shot" classifiers. *arXiv preprint arXiv:2408.03414*, 2024.

[6] Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. In *International Conference on Learning Representations (ICLR)*, 2023.

[7] Iván Vicente Moreno Cencerrado, Arnau Padrés Masdemont, Anton Gonzalvez Hawthorne, David Demitri Africa, and Lorenzo Pacchiardi. No answer needed: Predicting LLM answer accuracy from question-only linear probes. In *ICLR Workshop on Principled Design for Trustworthy AI*, 2026.

[8] Hakaze Cho, Yoshihiro Sakai, Mariko Kato, Kenshiro Tanaka, Akira Ishii, and Naoya Inoue. Token-based decision criteria are suboptimal in in-context learning. In *Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, 2025.

[9] Hyunsoo Cho, Hyuhng Joon Kim, Junyeob Kim, Sang-Woo Lee, Sang-goo Lee, Kang Min Yoo, and Taeuk Kim. Prompt-augmented linear probing: Scaling beyond the limit of few-shot in-context learners. In *AAAI Conference on Artificial Intelligence*, 2023.

[10] Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. BoolQ: Exploring the surprising difficulty of natural yes/no questions. In *Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, 2019.

[11] Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try ARC, the AI2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.

[12] Peter Clark, Oyvind Tafjord, and Kyle Richardson. Transformers as soft reasoners over language. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2020.

[13] Kyle Cox, Darius Kianersi, and Adrià Garriga-Alonso. Post-hoc reasoning in chain of thought: Decoding and steering pre-committed answers. *arXiv preprint arXiv:2603.01437*, 2026.

[14] Mostafa Elhoushi, Akshat Shrivastava, Diana Liskovich, Basil Hosmer, Bram Wasti, Liangzhen Lai, Anas Mahmoud, Bilge Acun, Saurabh Agarwal, Ahmed Roman, Ahmed A Aly, Beidi Chen, and Carole-Jean Wu. LayerSkip: Enabling early exit inference and

self-speculative decoding. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, 2024.

[15] Zorik Gekhman, Eyal Ben David, Hadas Orgad, Eran Ofek, Yonatan Belinkov, Idan Szpektor, Jonathan Herzig, and Roi Reichart. Inside-out: Hidden factual knowledge in LLMs. In *Conference on Language Modeling (COLM)*, 2025.

[16] Asma Ghandeharioun, Avi Caciularu, Adam Pearce, Lucas Dixon, and Mor Geva. Patchscopes: A unifying framework for inspecting hidden representations of language models. In *International Conference on Machine Learning (ICML)*, 2024.

[17] Shibo Hao, Sainbayar Sukhbaatar, DiJia Su, Xian Li, Zhiting Hu, Jason Weston, and Yuandong Tian. Training large language models to reason in a continuous latent space. In *Conference on Language Modeling (COLM)*, 2025.

[18] Luc Hazenoot, Zhaochun Ren, and Amirhossein Zohrehvand. Measuring concept content in text from LLM activations: ESG evidence from concept vectors and linear probes. *arXiv preprint arXiv:2608.07208*, 2026.

[19] Ari Holtzman, Peter West, Vered Shwartz, Yejin Choi, and Luke Zettlemoyer. Surface form competition: Why the highest probability answer isn't always right. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2021.

[20] Abhinav Joshi, Areeb Ahmad, and Ashutosh Modi. Calibration across layers: Understanding calibration evolution in LLMs. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 14686–14714, 2025. doi: 10.18653/v1/2025.emnlp-main.742.

[21] Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El-Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, Deep Ganguli, Danny Hernandez, Josh Jacobson, Jackson Kernion, Shauna Kravec, Liane Lovitt, Kamal Ndousse, Catherine Olsson, Sam Ringer, Dario Amodei, Tom Brown, Jack Clark, Nicholas Joseph, Ben Mann, Sam McCandlish, Chris Olah, and Jared Kaplan. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.

[22] Jingwei Ni, Ekaterina Fadeeva, Tianyi Wu, Mubashara Akhtar, Jiaheng Zhang, Elliott Ash, Markus Leippold, Timothy Baldwin, See-Kiong Ng, Artem Shelmanov, and Mrinmaya Sachan. ReProbe: Efficient test-time scaling of multi-step reasoning by probing internal states of large language models. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, 2026.

[23] nostalgebraist. Interpreting GPT: The logit lens. LessWrong, 2020. URL https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens.

[24] Hadas Orgad, Michael Toker, Zorik Gekhman, Roi Reichart, Idan Szpektor, Hadas Kotek, and Yonatan Belinkov. LLMs know more than they show: On the intrinsic representation of LLM hallucinations. In *International Conference on Learning Representations (ICLR)*, 2025.

[25] Nikunj Saunshi, Nishanth Dikkala, Zhiyuan Li, Sanjiv Kumar, and Sashank J. Reddi. Reasoning with latent thoughts: On the power of looped transformers. In *International Conference on Learning Representations (ICLR)*, 2025.

[26] Tal Schuster, Adam Fisch, Jai Gupta, Mostafa Dehghani, Dara Bahri, Vinh Q. Tran, Yi Tay, and Donald Metzler. Confident adaptive language modeling. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[27] Ji Xin, Raphael Tang, Jaejun Lee, Yaoliang Yu, and Jimmy Lin. DeeBERT: Dynamic early exiting for accelerating BERT inference. In *Annual Meeting of the Association for*

Computational Linguistics (ACL), pages 2246–2251, 2020. doi: 10.18653/v1/2020.acl-main.204.

[28] Zihao Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. Calibrate before use: Improving few-shot performance of language models. In *International Conference on Machine Learning (ICML)*, 2021.

[29] Wangchunshu Zhou, Canwen Xu, Tao Ge, Julian McAuley, Ke Xu, and Furu Wei. BERT loses patience: Fast and robust inference with early exit. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[30] Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, et al. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023.