

Module Interface Specification for a Library of Simplex Method Solvers (LoSMS)

Hanane Zlitni

November 24, 2018

1 Revision History

Date	Version		Notes
December 2018	06,	1.2	Applied Olu Owojaiye's Comments Posted on GitHub
December 2018	03,	1.1	Corrected solveLP() and pivot() pseudo-code in 8.4.4 and 8.4.5
November 2018	24,	1.0	First draft

2 Symbols, Abbreviations and Acronyms

See SRS Documentation at <https://github.com/hananezlitni/HZ-CAS741-Project/blob/master/docs/SRS/CA.pdf>.

The following are additional symbols, abbreviations or acronyms used in this document:

symbol	description
Z	Optimal solution(s) of the objective function
K	The points where the optimal solution(s) occur
Z'	The negation of the objective function
n	A number in $[0, \mathbb{N})$ representing the rows in the simplex tableau
m	A number in $[0, \mathbb{N})$ representing the columns in the simplex tableau
x	A number in \mathbb{N} representing the size of the list of optimal solutions

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Introduction	1
4	Notation	1
5	Module Decomposition	1
6	MIS of the Input Module	3
6.1	Module	3
6.2	Uses	3
6.3	Syntax	3
6.3.1	Exported Constants	3
6.3.2	Exported Access Programs	3
6.4	Semantics	3
6.4.1	State Variables	3
6.4.2	Environment Variables	4
6.4.3	Assumptions	4
6.4.4	Access Routine Semantics	4
6.4.5	Local Functions	5
7	MIS of the Tableau Module	6
7.1	Template Module	6
7.2	Uses	6
7.3	Syntax	6
7.3.1	Exported Constants	6
7.3.2	Exported Access Programs	6
7.4	Semantics	6
7.4.1	State Variables	6
7.4.2	Environment Variables	7
7.4.3	Assumptions	7
7.4.4	Access Routine Semantics	7
7.4.5	Local Functions	9
8	MIS of the Simplex Method Solver	10
8.1	Module	10
8.2	Uses	10
8.3	Syntax	10
8.3.1	Exported Constants	10
8.3.2	Exported Access Programs	10

8.4	Semantics	10
8.4.1	State Variables	10
8.4.2	Environment Variables	10
8.4.3	Assumptions	10
8.4.4	Access Routine Semantics	11
8.4.5	Local Functions	12
9	MIS of the Output Module	13
9.1	Module	13
9.2	Uses	13
9.3	Syntax	13
9.3.1	Exported Constants	13
9.3.2	Exported Access Programs	13
9.4	Semantics	13
9.4.1	State Variables	13
9.4.2	Environment Variables	13
9.4.3	Assumptions	13
9.4.4	Access Routine Semantics	13
9.4.5	Local Functions	14
10	Appendix	16

3 Introduction

The following document details the Module Interface Specifications for the Library of Simplex Method Solvers (LoSMS) tool.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at <https://github.com/hananezlitni/HZ-CAS741-Project>.

4 Notation

The structure of the MIS for modules comes from Hoffman and Strooper (1995), with the addition that template modules have been adapted from Ghezzi et al. (2003). The mathematical notation comes from Chapter 3 of Hoffman and Strooper (1995). For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by LoSMS.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	\mathbb{N}	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$

The specification of LoSMS uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, LoSMS uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding Module	
Behaviour-Hiding Module	
Software Decision Module	Input Tableau Simplex Method Solver Output

Table 1: Module Hierarchy

6 MIS of the Input Module

6.1 Module

input

6.2 Uses

None

6.3 Syntax

6.3.1 Exported Constants

None

6.3.2 Exported Access Programs

Name	In	Out	Exceptions
readInputs	\mathbb{R}^m , \mathbb{R}^{n*m} , lctEnum ⁿ⁻¹ , gEnum	-	MISSING_INPUT
validateInputs	-	-	INVALID_INPUT
getObjcFunc	-	\mathbb{R}^m	-
getLCs	-	\mathbb{R}^{n*m}	-
getLCsType	-	lctEnum ⁿ⁻¹	-
getGoal	-	gEnum	-

[Explanation: —HZ]

[1. *lctEnum*: an enumerated type that can be 0 (\leq), 1 (=) or 2 (\geq) depending on the type of each linear constraint. *lctEnum*ⁿ⁻¹ is an array in which the first element is the type of the first linear constraint, the second element is the second linear constraint type and so on. Its length is the number of rows of the tableau minus the first row (because we want to exclude the objective function). —HZ]

[2. *gEnum*: an enumerated type representing the LP goal: 0 (min) or 1 (max). —HZ]

6.4 Semantics

6.4.1 State Variables

- objcFunc: \mathbb{R}^m
- LCs: \mathbb{R}^{n*m}

- $\text{LCsType:lctEnum}^{n-1}$; where $\text{lctEnum} = \{0, 1, 2\}$
- goal:gEnum ; where $\text{gEnum} = \{0, 1\}$

6.4.2 Environment Variables

None

6.4.3 Assumptions

None

6.4.4 Access Routine Semantics

$\text{getObjcFunc}()$:

- transition: -
- output: $\text{out} := \text{objcFunc}$
- exception: -

$\text{getLCs}()$:

- transition: -
- output: $\text{out} := \text{LCs}$
- exception: -

$\text{getLCsType}()$:

- transition: -
- output: $\text{out} := \text{LCsType}$
- exception: -

$\text{getGoal}()$:

- transition: -
- output: $\text{out} := \text{goal}$
- exception: -

$\text{readInputs}(\text{obFunc}, \text{lnrConstr}, \text{lnrConstrT}, \text{goal})$:

- transition: -

- output: -

- exception: *exc* :=

At least one input missing

\Rightarrow MISSING_INPUT

validateInputs():

- transition: -

- output: -

- exception: *exc* :=

$\neg(\text{Last element of LCsType} == 2 \text{ AND Last element of LCs} == 0) \Rightarrow \text{INVALID_INPUT}$

[Explanation: —HZ]

[I'm checking if the non-negativity constraint is present in the LCs matrix. If it isn't, an exception will be generated. —HZ]

6.4.5 Local Functions

None

7 MIS of the Tableau Module

7.1 Template Module

tableauADT

7.2 Uses

input

7.3 Syntax

7.3.1 Exported Constants

None

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
TableauT	$\mathbb{R}^m, \mathbb{R}^{n*m}$	TableauT	-
toCanonical	-	-	-
getTableau	-	TableauT	-
getLCsType	-	lctEnum^{n-1}	-
getGoal	-	gEnum	-
updateTableau	operEnum	-	-
setGoal	gEnum	-	-
setLCsType	lctEnum^{n-1}	-	-
setWasMin	boolean	-	-

[Explanation: —HZ]

[*TableauT* is an abstract data type that represents a matrix in which the first row is the coefficients of the objective function and the rest of the rows are the coefficients of the linear constraints. The constructor will receive the coefficient array of the objective function and the coefficient matrix of the LCs and will form the simplex tableau. —HZ]

[*operEnum* is an enumerated type that represents the type of operation that will be performed on the tableau to update its values. —HZ]

7.4 Semantics

7.4.1 State Variables

- sTableau:TableauT

- $LCsType:lctEnum^{n-1}$; where $lctEnum = \{0, 1, 2\}$
- $goal:gEnum$; where $gEnum = \{0, 1\}$
- $wasMin:boolean$

[Explanation: —HZ]

[*wasMin* is a way to tell whether the original LP was a min problem or not. If it's a min problem, *goal* state variable will be changed to max but information about what it was originally would be lost. Therefore, *wasMin* will be set to "True" if the original LP is a min problem and will be checked after the optimal solution is calculated in the solver module. If *wasMin* is true, *Z* will be multiplied by -1 because that's the optimum of a min problem. —HZ]

7.4.2 Environment Variables

None

7.4.3 Assumptions

None

7.4.4 Access Routine Semantics

$new\ TableauT(objcFunc, lnrConstr):$

- transition: -
- output: $out := self$

The output consists of a matrix in which the first row is the coefficients of the objective function and the rest of the rows are the coefficients of the linear constraints.

- exception: -

$toCanonical():$

- transition:

- | | |
|--|--|
| 1. $\neg(self.getGoal() == 1)$ | $\Rightarrow self.setWasMin(True)$ |
| | $\Rightarrow self.setGoal(1)$ |
| | $\Rightarrow self.updateTableau(0)$ |
| 2. $(self.getLCsType() \text{ contains } 0)$ | $\Rightarrow self.setLCsType([1,1,1,...,1])$ |
| | $\Rightarrow self.updateTableau(1)$ |

- output: -
- exception: -

getTableau():

- transition: -
- output: *out* := sTableau
- exception: -

getLCsType():

- transition: -
- output: *out* := LCsType
- exception: -

getGoal():

- transition: -
- output: *out* := goal
- exception: -

updateTableau(*operation*):

- transition: *operation* is of type operEnum, where operEnum = {0,1} for negating the objective function row in sTableau and adding slack variables to sTableau, respectively.
 1. (operation == 0) \Rightarrow multiply the first row of sTableau by -1
 2. (operation == 1) \Rightarrow add slack variables coefficients to sTableau
- output: -
- exception: -

setGoal(*newGoal*):

- transition:
self.goal := newGoal
- output: -
- exception: -

setLCsType(*newLCsType*):

- transition:
self.LCsType := newLCsType
- output: -
- exception: -

7.4.5 Local Functions

None.

8 MIS of the Simplex Method Solver

8.1 Module

simplexSolver

8.2 Uses

tableauADT

8.3 Syntax

8.3.1 Exported Constants

None

8.3.2 Exported Access Programs

Name	In	Out	Exceptions
solveLP	TableauT, boolean	-	NO_OPTIMAL_SOLUTION
getZ	-	R^x	-
getK	-	R^m	-
setZ	R^x	-	-
setK	R^m	-	-

8.4 Semantics

8.4.1 State Variables

- $Z : \mathbb{R}^x$
- $K : \mathbb{R}^m$

8.4.2 Environment Variables

None

8.4.3 Assumptions

None

8.4.4 Access Routine Semantics

`solveLP(tableau, wasMin):`

- transition:
 1. `findPivot(tableau)`
 2. `pivot(tableau, pivotRow, pivotColumn)`
 3. Repeat 1 and 2 until there are no negative values in the last row (excluding the last column)
 4. `setZ(optimalSolution)`
 5. `setK(points)`
- output: -
- exception: *exc* :=
 $(Z == \text{NULL}) \quad \Rightarrow \text{NO_OPTIMAL_SOLUTION}$

`getZ():`

- transition: -
- output: *out* := *Z*
- exception: -

`getK():`

- transition: -
- output: *out* := *K*
- exception: -

`setZ(newZ):`

- transition:
 $Z := \text{newZ}$
- output: -
- exception: -

`setK(newK):`

- transition:
 $K := \text{newK}$
- output: -
- exception: -

8.4.5 Local Functions

```
findPivot(tableau):  
  start  
    for each entry in tableau except for the last column  
      min(negative entry)  
      if entry is found:  
        pivotColumn = j  
        #j is the column where the most negative entry was found  
    for each element in column pivotColumn and constant in the last column  
      min(element / constant)  
      pivotRow = i  
      #i is the row where the most minimum ratio was found  
    return pivotRow, pivotColumn  
  end  
  
pivot(tableau, pivotRow, pivotColumn):  
  start  
    for each row in pivotColumn  
      perform a row operation to make entry 0  
    return tableau  
  end
```

9 MIS of the Output Module

9.1 Module

output

9.2 Uses

simplexSolver

9.3 Syntax

9.3.1 Exported Constants

None

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
output	-	-	-

9.4 Semantics

9.4.1 State Variables

None

9.4.2 Environment Variables

screen: The device screen of the driver program's user

9.4.3 Assumptions

None

9.4.4 Access Routine Semantics

output():

- transition: Display to the environment variable the optimal solution(s) and the points where they occur by calling *simplexSolver.getZ()* and *simplexSolver.getK()*.
- output: -
- exception: -

9.4.5 Local Functions

None.

References

- Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. *Fundamentals of Software Engineering*. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.
- Daniel M. Hoffman and Paul A. Strooper. *Software Design, Automated Testing, and Maintenance: A Practical Approach*. International Thomson Computer Press, New York, NY, USA, 1995. URL <http://citeseer.ist.psu.edu/428727.html>.

10 Appendix

There are no additional information to provide.