Medium Power Amplifiers and Switches

NO.	POLA- RITY	CASE	MAXIMUM RATINGS				HFE			VCE(sat)		n	Cob	COMPLE-
			Pd (mW)	IC (A)	VCEO (V)	min	IMAX	IC (mA)	VCE (V)	max (V)	(A)	min (MHz)	max (pF)	MENTARY TYPE
28C1175	N	TO-92B	300	0.2	50	40	320 #	50	6	1.5	0.1	170+		28A659
2SC1209	N	TO-92B	500	0.7	20	55	300 #	500	1	0.5	0.5	150+	4.2+	1
28C1317	N	TO-92B	400	0.5	25	60	340 #	150	10	0.6	0.5	200+	15	28A719
2SC1318	N	TO-92B	400	0.5	50	60	340 #	150	10	0.6	0.5	200+	15	25A720
2SC1346	N	TO-92B	600	0.5	25	60	340 #	150	10	0.6	0.5	200+	15	28A730
28C1347	N	TO-92B	600	0.5	50	60	340 #	150	10	0.6	0.5	200+	15	2SA731
2SC1672	N	TO-92B	600	0.3	80	70	240 #	50	2	0.4	0.2	100+	10÷	2SA817
2SC1788	N	TO-92B	600	0.5	20	65	220 #	500	2	0.4	0.5	150+	15	
2SC1851	N	TO-92A	625	0.5	25	60	340 #	150	10	0.6	0.5	200+	15	2SA890
28C1852	N	TO-92A	625	0.5	50	90	340 #	150	10	0.6	0.5	200+	15	2SA891
2SC2001	N	TO-92B	600	0.7	25	90	400 #	100	1	0.6	0.7	50	25	
28C2120	N	TO-92B	600	0.8	25	100	320 #	100	1	0.5	0.5	120	13+	2SA950
2SD227	N	TO-92B	250	0.3	15	65	400 #	50	1	0.5	0.3	120+		2SA642
2SD327	N	TO-92B	250	0.5	20	60	285 ₩	100	ı	0.6	0.5	120+		28A723
2SD471	N	TO-92B	1000	1	25	90	400 W	100	l t	0.35	ı	-		2SB564
28D545	N	TO-92B	500	1	20	60	560 #	50	2	0.3	0.5	180+	15+	2SA598
2SD592	N	TO-92B	750	1	25	85	340 M	500	10	0.4	0.5	200+	20	2SB621
2SD592A	N	TO-92B	750	1	50	85	340 #	500	10	0.4	0.5	200+	20	25B621A
92PU01	N	TO-237A	2500□	2	30	60		100	ı	0.5	1	50	30	92PU51
92PLX01A	N :	TO-237A	2500□	2	40	60	-	100	ı	0.5	1	50	30	92PU51A
92PU02	N	TO-237A	2000□	0.8	40	50	300	150	10	0.4	0.15	150	10	92PU52
92PU05	N	TO-237A	2500□	2	60	20	-	500	1	0.5	0.25	50	30	92PU55
92PU06	N	TO-237A	25000	2	80	2:0		500	1	0.5	0.25	50	30	92PU56
92PU07	N	TO-237A	25000	2	100	20	-	500	ı	0.5	0.25	50	30	92PL!57
92PU45	N	TO-237A	2000	2	40*	15K	-	500	5	1.5	,	100	١.	92PU95
92PU45A	N	TO-237A	20000	2	50*	15K		500	3	1.5	l i	100		92PU95A
92PU51	P	TO-237A	2500□	2	50	60		100	i	0.5	i	50	30	92PU01
92PU51A	P	TO-237A	25000	2	50	60		100	1	0.5	1	50	30	92PU01A
92PU52	P	TO-237A	2000	0.8	40	50	300	150	10	0.4	0.15	- 150	24	92PU02
92PU55	P	TO-237A	2500□	2	60	20	-	500	1	0.5		50	30	92PU05
92PU56	P	TO-237A	2500□	2	80	20		500	i	0.5	ì	50	30	92PU06
92PU57	P	TO-237A	2500□	2	100	29	-	500	i	0.5	i	50	30	92PU07
92PU95	P	TO-237A	2000□	2	40*	15K		500	5	1.5	i	50	".	92PU45

HFE grouping available + typical value To=25°C + VCER