

Write a Python program to calculate the final movie ticket price for a customer based on the following conditions:

DAY 8 (10/11/2025)

→ Ticket Base Prices:

Adults (age 18-60): ₹ 250

Children (age < 18): ₹ 150

Senior citizens (age > 60): ₹ 200

→ Additional options:

If the customer wants popcorn, add ₹ 100.

If they want a drink, add ₹ 50.

If they take both popcorn and drink, give a combo discount of ₹ 25 (on total).

→ Extra Conditions -

If it's a weekend (Saturday or Sunday): increase total price by 10%.

If the total bill exceeds ₹ 350: apply a 5% discount on the final bill.


```
age = int(input("enter your age:"))
```

```
if (age >= 18 and age <= 60):
```

```
    tbp = 250
```

```
elif (age < 18):
```

```
    tbp = 150
```

```
elif (age > 60):
```

```
    tbp = 200
```

```
Sa = float(input("press 1 only for popcorn \n press 2 only for  
drink \n press 3 for both \n press 4 for exit"))
```

```
if (Sa == 1):
```

```
    Sta = 100
```

```
elif (Sa == 2):
```

```
    Sta = 50
```

```
elif (Sa == 3):
```

```
    Sta = 125
```

```
else:
```

```
    Sta = 0
```

```
fta = tbp + Sta
```

```
day = input("enter a day:")
```

```
if (day == "Saturday" or day == "Sunday"):
```

```
    fta = fta + (fta * 0.1)
```

```
    if (fta > 350):
```

```
        fta = fta - (fta * 0.05)
```

```
    else:
```

```
        fta = fta
```

```
elif (fta > 350):
```

```
    fta = fta - (fta * 0.05)
```

```
else:
```

```
    fta = fta
```

```
print("the total bill amount is:", fta)
```

o/p ->

enter your age: 48

press 1 only for popcorn

press 2 only for drink

Press 3 for both

Press 4 for exit

3
enter a day: Sunday

the total bill amount is: 389.5

print("hi A good evening")

print("hi B good evening")

print("hi C good evening")

print("hi D good evening")

print("hi E good evening")

O/P=> hi A good evening

hi B good evening

hi C good evening

hi D good evening

hi E good evening

↳ Here hi, good evening are same the only changing is name.

For 5 names i can write, but 50, 100, 500 names means I can't write like this. ~~for~~ So for, this we use loops.

l1 = ['A', 'B', 'C', 'D', 'E']

for i in l1:

print(f"hi {i} good evening").

Loops: loops in python are used to execute a block of code repeatedly until a certain condition is met.

Python mainly provides two types of loops:

1) for loop

2) While loop.

3) Nested loops

* for loop inside for loop

* for loop inside while loop

* while loop inside for loop

* while loop inside while loop.

For loop - for loops are used for iterating over sequences like lists, tuples, strings and ranges.

- * A for loop always allows you to apply the same operation to every item within the loop.
- * Using a for loop avoids the need to manually manage the index.
- * A for loop can iterate over any iterable object, such as a dictionary, list or custom iterator.

There are two -

- 1) for loop with sequence.
- 2) for loop with range.

1) For loop with sequence - A loop with a sequence means repeating an action for every item in a sequence - like a list, tuple, string.

The most common loop for this is the "for loop".

Syntax -

for i in sequence-name: # i is iterative variable for every iteration i value will change.

for loop with sequence ex -
name = "poojyy"
for i in name:
 print(i)

for finding out position and value -
with a function - enumerate

```
for i in enumerate(name):
```

```
    print(i)
```

```
    print(f"pos = {i[0]}, char = {i[1]}")
```

here we are using i[0] and i[1] because it
defaultly takes as tuple so we wrote for first
value 0 and for second value 1.

O/p=)

(0, 'p')

pos = 0, char = p

(1, 'o')

pos = 1, char = o

(2, 'o')

pos = 2, char = o

(3, 'j')

pos = 3, char = j

(4, 'y')

pos = 4, char = y

(5, 'y')

pos = 5, char = y

2nd method -

p = 0

for i in name:

```
    print(f"pos = {p}, value = {i}")
```

p = p + 1

O/p=)

pos = 0, value = p

pos = 1, value = o

pos = 2, value = o

pos = 3, value = j

pos = 4, value = y

pos = 5, value = y

For loop with range - This is used to repeat a block of code a specific number of times by generating a sequence of numbers using the range() function

Initialization

Condition

Incrementation / Decrementation

range(start value, stop value, step size)

range (i=0, i<11, i=i+1)

default start value = 0

step size : 1

Syntax -

for i in range():
 Statements

Q) for i in range (1,11,1):
 print (f" i={i}")
 print ("Hello")

o/p

i=1

Hello

i=2

Hello

i=3

Hello

i=4

Hello

i=5

Hello

i=6

Hello

i=7

Hello

i=8

Hello

i=9

Hello

i=10

Hello.

Q) print numbers from 1 to 20.

for i in range(1, 21, 1):

print(i)

o/p

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20

Q) print even numbers from 1 to 10;

for i in range(0, 11, 2):

print(i)

o/p

0

2

4

6

8

10

Q) print odd numbers from 91 to 100

for i in range(91, 100, 2):

print(i)

o/p

91

93

95

97

99