Airbnb Price Prediction — Complete ML Pipeline

AIGC 5003 — Machine Learning in Cloud Computing

This notebook implements a complete machine learning pipeline to predict Airbnb nightly listing prices using Amazon SageMaker.

Student: Haneen altaie **Dataset:** Airbnb listings — 953 rows
Target variable: price(in_dollar)
Region: Canada Central (ca-central-1)

Pipeline Overview:

Step	Description
1	Data Loading & Analysis
2	Data Cleaning & Feature Engineering
3	SageMaker Built-in XGBoost Training Job
4	Hyperparameter Tuning Job
5	Model Hosting & Endpoint Deployment
6	Inferencing & Evaluation
7	Resource Cleanup

In [1]:
```
# Import all required libraries
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
import os
import re
import tarfile
import joblib
import boto3
import sagemaker

from sagemaker import get_execution_role
from sagemaker.inputs import TrainingInput
from sagemaker.image_uris import retrieve
from sagemaker.tuner import IntegerParameter, ContinuousParameter, HyperparameterTu
from sagemaker.sklearn.model import SKLearnModel
from sagemaker.serializers import CSVSerializer
```

```
from sagemaker.deserializers import StringDeserializer

from sklearn.ensemble import RandomForestRegressor
from sklearn.model_selection import train_test_split
from sklearn.metrics import mean_absolute_error, r2_score, mean_squared_error
from sklearn.preprocessing import LabelEncoder

# SageMaker session setup
session = sagemaker.Session()
bucket  = session.default_bucket()
role    = get_execution_role()
region  = session.boto_region_name

print("✅ Libraries loaded successfully")
print(f"Bucket: {bucket}")
print(f"Role:   {role}")
print(f"Region: {region}")
```

```
sagemaker.config INFO - Not applying SDK defaults from location: /etc/xdg/sagemake
r/config.yaml
sagemaker.config INFO - Not applying SDK defaults from location: /home/ec2-user/.c
onfig/sagemaker/config.yaml
✅ Libraries loaded successfully
Bucket: sagemaker-ca-central-1-263245924849
Role:   arn:aws:iam::263245924849:role/service-role/AmazonSageMaker-ExecutionRole-
20260323T193815
Region: ca-central-1
```

Step 1 — Data Loading & Analysis

We load two datasets:

File	Description
`final_airbnb_ml.csv`	Preprocessed file — 953 rows, 671 columns with anonymous boolean features
`airbnb.csv`	Original raw dataset — 953 rows, 7 meaningful columns

Both files are stored locally in the SageMaker JupyterLab environment.

The preprocessed file is used for the SageMaker built-in training job.
The raw file is used for feature engineering to build a better model.

In [2]:
```
# Load the preprocessed dataset
df = pd.read_csv("final_airbnb_ml.csv", header=None)

# Rename first 4 meaningful columns
new_cols = ['price(in_dollar)', 'beds', 'rating', 'num_reviews'] + \
           [f'feature_{i}' for i in range(4, df.shape[1])]
df.columns = new_cols

# Convert boolean values to 1/0
df = df.replace({True: 1, False: 0})
```

```
print(f"Dataset shape: {df.shape}")
print(f"Columns sample: {df.columns[:5].tolist()}")
print(f"\nBasic Statistics:")
print(df[['price(in_dollar)', 'beds', 'rating', 'num_reviews']].describe())

# ── Plot 1: Price Distribution ──
plt.figure(figsize=(12, 4))

plt.subplot(1, 2, 1)
sns.histplot(df['price(in_dollar)'], bins=30, kde=True)
plt.title("Price Distribution")
plt.xlabel("Price (in Dollar)")
plt.ylabel("Count")

plt.subplot(1, 2, 2)
sns.boxplot(x=df['price(in_dollar)'])
plt.title("Price Boxplot — Outliers Visible")
plt.xlabel("Price (in Dollar)")

plt.tight_layout()
plt.show()

# ── Plot 2: Feature Correlations ──
corr = df[['price(in_dollar)', 'beds', 'rating', 'num_reviews']].corr()
plt.figure(figsize=(8, 5))
sns.heatmap(corr, annot=True, cmap='coolwarm')
plt.title("Correlation Heatmap")
plt.show()

# ── Plot 3: Beds vs Price ──
plt.figure(figsize=(8, 4))
sns.scatterplot(x=df['beds'], y=df['price(in_dollar)'])
plt.title("Beds vs Price")
plt.xlabel("Number of Beds")
plt.ylabel("Price (in Dollar)")
plt.show()

print(f"\nKey Findings:")
print(f"Median price:     ${df['price(in_dollar)'].median():.2f}")
print(f"Mean price:       ${df['price(in_dollar)'].mean():.2f}")
print(f"Listings > $500:  {(df['price(in_dollar)'] > 500).sum()}")
print(f"Listings > $800:  {(df['price(in_dollar)'] > 800).sum()}")
```

```
/tmp/ipykernel_26602/2088213224.py:10: FutureWarning: Downcasting behavior in `rep
lace` is deprecated and will be removed in a future version. To retain the old beh
avior, explicitly call `result.infer_objects(copy=False)`. To opt-in to the future
behavior, set `pd.set_option('future.no_silent_downcasting', True)`
  df = df.replace({True: 1, False: 0})
```

```
Dataset shape: (953, 671)
Columns sample: ['price(in_dollar)', 'beds', 'rating', 'num_reviews', 'feature_4']

Basic Statistics:
       price(in_dollar)        beds      rating  num_reviews
count        953.000000  953.000000  953.000000    953.00000
mean         171.356768    2.182581    4.817508    187.92235
std          141.661126    1.641835    0.141141    185.38656
min           16.000000    1.000000    3.600000      0.00000
25%           83.000000    1.000000    4.800000     53.00000
50%          135.000000    2.000000    4.817508    136.00000
75%          221.000000    3.000000    4.900000    266.00000
max         1463.000000   22.000000    5.000000   1239.00000
```








```
Key Findings:
Median price:     $135.00
Mean price:       $171.36
Listings > $500:  28
Listings > $800:  6
```

Step 2 — Data Cleaning & Feature Engineering

The 667 anonymous boolean features in the preprocessed file carry very little predictive signal. We therefore engineer meaningful features from the original raw dataset (airbnb.csv).

New features created:

Feature	Description
`beds`	Number of beds extracted from text
`rating`	Numerical score extracted from review column
`num_reviews`	Review count extracted from parentheses
`is_luxury`	Keyword flag from listing description
`has_hot_tub`	Keyword flag from listing description
`has_pool`	Keyword flag from listing description
`has_pets`	Keyword flag from listing description
`property_type`	Extracted from title, one-hot encoded
`detail_length`	Character count of listing description
`discount_pct`	Percentage discount between price and offer price

Preprocessing steps:

- Outliers above 95th percentile ($441) removed → 953 rows to 905 rows
- Log transformation applied to price using log1p()
- Categorical columns label encoded
- Missing values filled with median
- Target variable moved to first column (SageMaker requirement)
- Saved as CSV without headers (SageMaker requirement)

In [3]:
```
# Load the raw dataset
df_raw = pd.read_csv("airbnb.csv")
print(f"Raw dataset shape: {df_raw.shape}")
print(df_raw.head(3))

# ── Extract features from raw columns ──

# 1. Target variable
df_raw['price'] = pd.to_numeric(df_raw['Price(in dollar)'], errors='coerce')

# 2. Offer price & discount
df_raw['offer_price']   = pd.to_numeric(df_raw['Offer price(in dollar)'], errors='c
df_raw['discount']      = df_raw['price'] - df_raw['offer_price']
df_raw['discount_pct']  = (df_raw['discount'] / df_raw['price']).clip(0, 1)

# 3. Rating and number of reviews
df_raw['rating']      = df_raw['Review and rating'].str.extract(r'(\d+\.\d+)').asty
df_raw['num_reviews'] = df_raw['Review and rating'].str.extract(r'\((\d+)\)').astyp

# 4. Number of beds
df_raw['beds']     = df_raw['Number of bed'].str.extract(r'(\d+)').astype(float)
df_raw['is_queen'] = df_raw['Number of bed'].str.contains('queen', case=False).asty
df_raw['is_king']  = df_raw['Number of bed'].str.contains('king',  case=False).asty

# 5. Property type from title
df_raw['property_type'] = df_raw['Title'].str.extract(r'^(\w+)\s+in')

# 6. Text features from description
df_raw['detail_length'] = df_raw['Detail'].str.len()
df_raw['is_luxury']     = df_raw['Detail'].str.contains('luxury|Luxury',         na
df_raw['has_hot_tub']   = df_raw['Detail'].str.contains('hot tub|Hot tub',       na
df_raw['has_pool']      = df_raw['Detail'].str.contains('pool|Pool',             na
df_raw['has_pets']      = df_raw['Detail'].str.contains('pet|Pet',               na
df_raw['is_treehouse']  = df_raw['Detail'].str.contains('treehouse|Treehouse',   na

# ── Build model dataframe ──
features = [
    'beds', 'rating', 'discount_pct', 'is_luxury',
    'detail_length', 'is_treehouse', 'has_pool',
    'has_hot_tub', 'has_pets', 'num_reviews', 'property_type'
]

df_model = df_raw[features + ['price']].copy()

# One-hot encode property_type
```

```python
df_model = pd.get_dummies(df_model, columns=['property_type'])

# Fill NaNs with median
df_model = df_model.fillna(df_model.median(numeric_only=True))
df_model = df_model.dropna(subset=['price'])

print(f"\n✅ Feature engineering complete")
print(f"Model dataset shape: {df_model.shape}")
print(f"NaNs remaining: {df_model.isnull().sum().sum()}")

# ── Remove outliers & log transform ──
df_clean = df_model[df_model['price'] <= 441].copy()
df_clean['log_price'] = np.log1p(df_clean['price'])

print(f"\n✅ Outliers removed: {len(df_model) - len(df_clean)} rows dropped")
print(f"Clean dataset shape: {df_clean.shape}")

# ── Prepare SageMaker training file ──
# Target must be first column, no header, no index
sagemaker_df = df_clean.drop('log_price', axis=1).copy()
target = sagemaker_df.pop('price')
sagemaker_df.insert(0, 'price', target)
sagemaker_df.to_csv("sagemaker_train.csv", index=False, header=False)

print(f"\n✅ sagemaker_train.csv saved")
print(f"Shape: {sagemaker_df.shape}")
```

```
Raw dataset shape: (953, 7)
                                Title  \
0  Chalet in Skykomish, Washington, US
1       Cabin in Hancock, New York, US
2   Cabin in West Farmington, Ohio, US

                                            Detail         Date  \
0                           Sky Haus - A-Frame Cabin  Jun 11 - 16
1    The Catskill A-Frame - Mid-Century Modern Cabin   Jun 6 - 11
2  The Triangle: A-Frame Cabin for your city retreat   Jul 9 - 14

  Price(in dollar) Offer price(in dollar) Review and rating Number of bed
0           306.00                 229.00        4.85 (531)        4 beds
1           485.00                 170.00        4.77 (146)        4 beds
2           119.00                 522.00        4.91 (515)        4 beds

✅ Feature engineering complete
Model dataset shape: (953, 42)
NaNs remaining: 0

✅ Outliers removed: 48 rows dropped
Clean dataset shape: (905, 43)

✅ sagemaker_train.csv saved
Shape: (905, 42)
```

Step 3 — SageMaker Built-in XGBoost Training Job

We use SageMaker's managed XGBoost built-in algorithm to run a training job on a **separate ml.m5.xlarge instance** — no local CPU or memory from this notebook is used.

Why XGBoost?

- Best suited for tabular regression tasks
- Handles large feature sets efficiently
- Native built-in support in SageMaker

Steps:

1. Split data into train / validation / test
2. Upload splits to Amazon S3
3. Define SageMaker Estimator with XGBoost container
4. Set hyperparameters and run training job

Hyperparameters used:

Parameter	Value
objective	reg:squarederror
num_round	100
max_depth	5
eta	0.2
subsample	0.8

In [4]:
```
# ── Upload data splits to S3 ──
full_df = pd.read_csv("sagemaker_train.csv", header=None)

train_split, temp     = train_test_split(full_df, test_size=0.2, random_state=42)
val_split, test_split = train_test_split(temp,    test_size=0.5, random_state=42)

train_split.to_csv("xgb_train.csv", index=False, header=False)
val_split.to_csv("xgb_val.csv",     index=False, header=False)
test_split.to_csv("xgb_test.csv",   index=False, header=False)

print(f"Train: {train_split.shape}, Val: {val_split.shape}, Test: {test_split.shape

# Upload to S3
train_s3 = session.upload_data("xgb_train.csv", bucket=bucket,
                               key_prefix="airbnb-xgb/train")
val_s3   = session.upload_data("xgb_val.csv",   bucket=bucket,
                               key_prefix="airbnb-xgb/validation")
test_s3  = session.upload_data("xgb_test.csv",  bucket=bucket,
                               key_prefix="airbnb-xgb/test")

print(f"\n✅ Data uploaded to S3")
print(f"Train S3: {train_s3}")
```

```python
print(f"Val S3:   {val_s3}")

# ── Define XGBoost Estimator ──
xgboost_image = retrieve("xgboost", region=region, version="1.7-1")

xgb_estimator = sagemaker.estimator.Estimator(
    image_uri=xgboost_image,
    role=role,
    instance_count=1,
    instance_type="ml.m5.xlarge",
    output_path=f"s3://{bucket}/airbnb-xgb/output",
    sagemaker_session=session
)

# Set hyperparameters
xgb_estimator.set_hyperparameters(
    objective="reg:squarederror",
    num_round=100,
    max_depth=5,
    eta=0.2,
    subsample=0.8
)

# ── Run Training Job ──
train_input = TrainingInput(train_s3, content_type="text/csv")
val_input   = TrainingInput(val_s3,   content_type="text/csv")

print("\n⏳ Starting SageMaker training job...")
print("This runs on a separate ml.m5.xlarge instance — not this notebook\n")

xgb_estimator.fit({"train": train_input, "validation": val_input})

print("\n✅ Training job complete!")
print(f"Job name: {xgb_estimator.latest_training_job.name}")
```

```
Train: (724, 42), Val: (90, 42), Test: (91, 42)

✅ Data uploaded to S3
Train S3: s3://sagemaker-ca-central-1-263245924849/airbnb-xgb/train/xgb_train.csv
Val S3:   s3://sagemaker-ca-central-1-263245924849/airbnb-xgb/validation/xgb_val.c
sv
```

```
INFO:sagemaker:Creating training-job with name: sagemaker-xgboost-2026-03-30-15-17
-18-094
```

```
⏳ Starting SageMaker training job...
This runs on a separate ml.m5.xlarge instance — not this notebook

2026-03-30 15:17:20 Starting - Starting the training job...
2026-03-30 15:17:53 Downloading - Downloading input data...
2026-03-30 15:18:18 Downloading - Downloading the training image......
2026-03-30 15:19:19 Training - Training image download completed. Training in prog
ress.
2026-03-30 15:19:19 Uploading - Uploading generated training model/miniconda3/lib/
python3.9/site-packages/sagemaker_containers/_server.py:22: UserWarning: pkg_resou
rces is deprecated as an API. See https://setuptools.pypa.io/en/latest/pkg_resourc
es.html. The pkg_resources package is slated for removal as early as 2025-11-30. R
efrain from using this package or pin to Setuptools<81.
  import pkg_resources
[2026-03-30 15:19:14.421 ip-10-0-113-38.ca-central-1.compute.internal:7 INFO util
s.py:28] RULE_JOB_STOP_SIGNAL_FILENAME: None
[2026-03-30 15:19:14.484 ip-10-0-113-38.ca-central-1.compute.internal:7 INFO profi
ler_config_parser.py:111] User has disabled profiler.
[2026-03-30:15:19:14:INFO] Imported framework sagemaker_xgboost_container.training
[2026-03-30:15:19:14:INFO] Failed to parse hyperparameter objective value reg:squa
rederror to Json.
Returning the value itself
[2026-03-30:15:19:14:INFO] No GPUs detected (normal if no gpus installed)
[2026-03-30:15:19:14:INFO] Running XGBoost Sagemaker in algorithm mode
[2026-03-30:15:19:14:INFO] Determined 0 GPU(s) available on the instance.
[2026-03-30:15:19:14:INFO] Determined delimiter of CSV input is ','
[2026-03-30:15:19:14:INFO] Determined delimiter of CSV input is ','
[2026-03-30:15:19:14:INFO] File path /opt/ml/input/data/train of input files
[2026-03-30:15:19:14:INFO] Making smlinks from folder /opt/ml/input/data/train to
folder /tmp/sagemaker_xgboost_input_data
[2026-03-30:15:19:14:INFO] creating symlink between Path /opt/ml/input/data/train/
xgb_train.csv and destination /tmp/sagemaker_xgboost_input_data/xgb_train.csv-6709
080157586611485
[2026-03-30:15:19:14:INFO] files path: /tmp/sagemaker_xgboost_input_data
[2026-03-30:15:19:14:INFO] Determined delimiter of CSV input is ','
[2026-03-30:15:19:14:INFO] File path /opt/ml/input/data/validation of input files
[2026-03-30:15:19:14:INFO] Making smlinks from folder /opt/ml/input/data/validatio
n to folder /tmp/sagemaker_xgboost_input_data
[2026-03-30:15:19:14:INFO] creating symlink between Path /opt/ml/input/data/valida
tion/xgb_val.csv and destination /tmp/sagemaker_xgboost_input_data/xgb_val.csv-632
9913410859182362
[2026-03-30:15:19:14:INFO] files path: /tmp/sagemaker_xgboost_input_data
[2026-03-30:15:19:14:INFO] Determined delimiter of CSV input is ','
[2026-03-30:15:19:14:INFO] Single node training.
[2026-03-30:15:19:14:INFO] Train matrix has 724 rows and 41 columns
[2026-03-30:15:19:14:INFO] Validation matrix has 90 rows
[2026-03-30 15:19:14.855 ip-10-0-113-38.ca-central-1.compute.internal:7 INFO json_
config.py:92] Creating hook from json_config at /opt/ml/input/config/debughookconf
ig.json.
[2026-03-30 15:19:14.856 ip-10-0-113-38.ca-central-1.compute.internal:7 INFO hook.
py:206] tensorboard_dir has not been set for the hook. SMDebug will not be exporti
ng tensorboard summaries.
[2026-03-30 15:19:14.856 ip-10-0-113-38.ca-central-1.compute.internal:7 INFO hook.
py:259] Saving to /opt/ml/output/tensors
[2026-03-30 15:19:14.857 ip-10-0-113-38.ca-central-1.compute.internal:7 INFO state
_store.py:77] The checkpoint config file /opt/ml/input/config/checkpointconfig.jso
```

```
n does not exist.
[2026-03-30:15:19:14:INFO] Debug hook created from config
[0]#011train-rmse:145.69408#011validation-rmse:135.83306
[2026-03-30 15:19:14.861 ip-10-0-113-38.ca-central-1.compute.internal:7 INFO hook.
py:427] Monitoring the collections: metrics
[2026-03-30 15:19:14.864 ip-10-0-113-38.ca-central-1.compute.internal:7 INFO hook.
py:491] Hook is writing from the hook with pid: 7
[1]#011train-rmse:125.31517#011validation-rmse:117.11782
[2]#011train-rmse:109.50040#011validation-rmse:102.74483
[3]#011train-rmse:97.73431#011validation-rmse:93.48180
[4]#011train-rmse:88.34989#011validation-rmse:86.67610
[5]#011train-rmse:82.31477#011validation-rmse:81.53511
[6]#011train-rmse:77.29592#011validation-rmse:78.82866
[7]#011train-rmse:73.43074#011validation-rmse:76.54092
[8]#011train-rmse:70.92963#011validation-rmse:75.81884
[9]#011train-rmse:68.45961#011validation-rmse:74.28343
[10]#011train-rmse:66.96899#011validation-rmse:74.11164
[11]#011train-rmse:65.54384#011validation-rmse:74.50156
[12]#011train-rmse:63.92196#011validation-rmse:74.42820
[13]#011train-rmse:63.21730#011validation-rmse:74.62070
[14]#011train-rmse:62.43146#011validation-rmse:75.16098
[15]#011train-rmse:61.05818#011validation-rmse:75.63620
[16]#011train-rmse:59.91146#011validation-rmse:76.20373
[17]#011train-rmse:58.83729#011validation-rmse:76.37386
[18]#011train-rmse:57.83281#011validation-rmse:76.98858
[19]#011train-rmse:56.86298#011validation-rmse:77.62858
[20]#011train-rmse:56.02459#011validation-rmse:77.56110
[21]#011train-rmse:55.71377#011validation-rmse:77.55246
[22]#011train-rmse:55.26955#011validation-rmse:77.45878
[23]#011train-rmse:54.99145#011validation-rmse:77.47622
[24]#011train-rmse:54.61944#011validation-rmse:77.56536
[25]#011train-rmse:54.29517#011validation-rmse:77.65311
[26]#011train-rmse:53.58791#011validation-rmse:78.07698
[27]#011train-rmse:52.86661#011validation-rmse:78.65763
[28]#011train-rmse:52.68059#011validation-rmse:78.47988
[29]#011train-rmse:51.18644#011validation-rmse:78.30112
[30]#011train-rmse:50.95905#011validation-rmse:78.26752
[31]#011train-rmse:49.96301#011validation-rmse:78.45856
[32]#011train-rmse:49.44279#011validation-rmse:78.99152
[33]#011train-rmse:49.00216#011validation-rmse:79.19351
[34]#011train-rmse:48.51951#011validation-rmse:79.27913
[35]#011train-rmse:47.89469#011validation-rmse:79.58263
[36]#011train-rmse:47.25977#011validation-rmse:79.71879
[37]#011train-rmse:46.98002#011validation-rmse:79.61647
[38]#011train-rmse:46.65528#011validation-rmse:79.42656
[39]#011train-rmse:46.15239#011validation-rmse:79.96039
[40]#011train-rmse:45.72058#011validation-rmse:79.88219
[41]#011train-rmse:45.19022#011validation-rmse:80.03451
[42]#011train-rmse:44.48578#011validation-rmse:80.13876
[43]#011train-rmse:43.91757#011validation-rmse:80.59236
[44]#011train-rmse:43.73597#011validation-rmse:80.66317
[45]#011train-rmse:43.12561#011validation-rmse:80.46608
[46]#011train-rmse:43.08946#011validation-rmse:80.39981
[47]#011train-rmse:42.67126#011validation-rmse:80.71364
[48]#011train-rmse:42.28802#011validation-rmse:80.62448
[49]#011train-rmse:41.66447#011validation-rmse:80.88928
```

```
[50]#011train-rmse:41.48799#011validation-rmse:80.81669
[51]#011train-rmse:41.23980#011validation-rmse:80.84827
[52]#011train-rmse:40.87847#011validation-rmse:81.05699
[53]#011train-rmse:40.46954#011validation-rmse:80.72152
[54]#011train-rmse:39.93182#011validation-rmse:81.31403
[55]#011train-rmse:39.38586#011validation-rmse:81.82150
[56]#011train-rmse:38.85124#011validation-rmse:82.09656
[57]#011train-rmse:38.57519#011validation-rmse:82.44201
[58]#011train-rmse:38.52466#011validation-rmse:82.33420
[59]#011train-rmse:37.88767#011validation-rmse:82.49701
[60]#011train-rmse:37.54720#011validation-rmse:82.79817
[61]#011train-rmse:37.35289#011validation-rmse:82.79331
[62]#011train-rmse:36.82283#011validation-rmse:83.10972
[63]#011train-rmse:36.49842#011validation-rmse:83.49915
[64]#011train-rmse:36.05323#011validation-rmse:83.41292
[65]#011train-rmse:35.98611#011validation-rmse:83.40406
[66]#011train-rmse:35.66103#011validation-rmse:83.41491
[67]#011train-rmse:35.25357#011validation-rmse:83.48563
[68]#011train-rmse:35.07091#011validation-rmse:83.32455
[69]#011train-rmse:34.67293#011validation-rmse:83.60859
[70]#011train-rmse:34.36836#011validation-rmse:83.69200
[71]#011train-rmse:34.02034#011validation-rmse:84.02513
[72]#011train-rmse:33.89337#011validation-rmse:84.18413
[73]#011train-rmse:33.68031#011validation-rmse:84.28269
[74]#011train-rmse:33.25143#011validation-rmse:84.62552
[75]#011train-rmse:32.96491#011validation-rmse:84.65045
[76]#011train-rmse:32.69156#011validation-rmse:84.52728
[77]#011train-rmse:32.31147#011validation-rmse:84.55083
[78]#011train-rmse:32.13936#011validation-rmse:84.29954
[79]#011train-rmse:31.73934#011validation-rmse:84.77904
[80]#011train-rmse:31.62583#011validation-rmse:84.80304
[81]#011train-rmse:31.54482#011validation-rmse:84.70489
[82]#011train-rmse:31.39090#011validation-rmse:84.75914
[83]#011train-rmse:31.06409#011validation-rmse:84.96802
[84]#011train-rmse:30.84620#011validation-rmse:85.11238
[85]#011train-rmse:30.65949#011validation-rmse:85.24822
[86]#011train-rmse:30.45530#011validation-rmse:85.32177
[87]#011train-rmse:30.24848#011validation-rmse:85.50499
[88]#011train-rmse:29.88324#011validation-rmse:85.15670
[89]#011train-rmse:29.41311#011validation-rmse:84.79990
[90]#011train-rmse:29.19500#011validation-rmse:84.54521
[91]#011train-rmse:28.78996#011validation-rmse:83.95478
[92]#011train-rmse:28.70328#011validation-rmse:84.16199
[93]#011train-rmse:28.24099#011validation-rmse:84.53988
[94]#011train-rmse:27.94909#011validation-rmse:84.61527
[95]#011train-rmse:27.70923#011validation-rmse:84.75703
[96]#011train-rmse:27.49062#011validation-rmse:84.93584
[97]#011train-rmse:27.11885#011validation-rmse:84.94366
[98]#011train-rmse:26.78811#011validation-rmse:84.87390
[99]#011train-rmse:26.34541#011validation-rmse:84.78250

2026-03-30 15:19:32 Completed - Training job completed
Training seconds: 99
Billable seconds: 99
```

```
✅ Training job complete!
Job name: sagemaker-xgboost-2026-03-30-15-17-18-094
```

Step 4 — Hyperparameter Tuning Job

Instead of manually guessing hyperparameters, SageMaker's HyperparameterTuner automatically runs 10 training jobs with different parameter combinations and finds the best one.

Objective:

Minimize **validation:rmse**

Search ranges:

Parameter	Range
max_depth	3 to 10
eta	0.01 to 0.3
subsample	0.5 to 1.0
num_round	50 to 200

Solo training result (baseline to beat):

- train:rmse = 26.35
- validation:rmse = 84.78

In [ ]:

```
# ── Define hyperparameter search ranges ──
hyperparameter_ranges = {
    "max_depth": IntegerParameter(3, 10),
    "eta":       ContinuousParameter(0.01, 0.3),
    "subsample": ContinuousParameter(0.5, 1.0),
    "num_round": IntegerParameter(50, 200)
}

# ── Create tuner ──
tuner = HyperparameterTuner(
    estimator=xgb_estimator,
    objective_metric_name="validation:rmse",
    objective_type="Minimize",
    hyperparameter_ranges=hyperparameter_ranges,
    max_jobs=10,
    max_parallel_jobs=2
)

# ── Run all 10 tuning jobs ──
print("⏳ Starting hyperparameter tuning job...")
print("Running 10 jobs — this takes about 15-20 minutes\n")
```

```
tuner.fit({"train": train_input, "validation": val_input})
tuner.wait()

# ── Print best result ──
best_job_name = tuner.best_training_job()
print(f"\n✅ Tuning complete!")
print(f"Best job: {best_job_name}")

# Get best objective metric
sm_client = boto3.client('sagemaker', region_name=region)
job_info = sm_client.describe_training_job(TrainingJobName=best_job_name)
for metric in job_info['FinalMetricDataList']:
    print(f"{metric['MetricName']}: {metric['Value']}")

# Get best hyperparameters
best_estimator = tuner.best_estimator()
print(f"\nBest hyperparameters:")
print(best_estimator.hyperparameters())
```

```
INFO:sagemaker:Creating hyperparameter tuning job with name: sagemaker-xgboost-260
330-1521
⏳ Starting hyperparameter tuning job...
Running 10 jobs — this takes about 15-20 minutes

.............................................................!
!

✅ Tuning complete!
Best job: sagemaker-xgboost-260330-1521-009-481aa39c
ObjectiveMetric: 73.28936767578125
train:rmse: 70.21636199951172
validation:rmse: 73.28936767578125

2026-03-30 15:27:13 Starting - Found matching resource for reuse
2026-03-30 15:27:13 Downloading - Downloading the training image
2026-03-30 15:27:13 Training - Training image download completed. Training in prog
ress.
2026-03-30 15:27:13 Uploading - Uploading generated training model
2026-03-30 15:27:13 Completed - Resource retained for reuse

Best hyperparameters:
{'_tuning_objective_metric': 'validation:rmse', 'eta': '0.03091311739896027', 'max
_depth': '3', 'num_round': '118', 'objective': 'reg:squarederror', 'subsample':
'0.6625305497797208'}
```

Step 5 — Model Hosting & Endpoint Deployment

The best trained Random Forest model is packaged and deployed as a real-time SageMaker endpoint.

Deployment details:

Setting	Value
Framework	scikit-learn 1.4-2
Instance type	ml.m5.large
Serializer	CSVSerializer
Deserializer	StringDeserializer

Deployment steps:

1. Train Random Forest v3 on engineered features
2. Save model as model.joblib
3. Package into model.tar.gz
4. Upload to Amazon S3
5. Deploy using SKLearnModel

Troubleshooting encountered:

- sklearn version mismatch → fixed by retraining with 1.4.2
- ml.t2.medium memory issues → fixed by switching to ml.m5.large
- KeyError on price(in_dollar) → fixed by using positional indexing

In [6]:
```
# ── Train Random Forest v3 on engineered features ──
X = df_clean.drop(['price', 'log_price'], axis=1)
y = df_clean['log_price']  # train on log price

X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.2, random_state=42
)

# Also keep raw price for evaluation
_, _, y_train_raw, y_test_raw = train_test_split(
    X, df_clean['price'], test_size=0.2, random_state=42
)

rf_model = RandomForestRegressor(
    n_estimators=300,
    max_depth=8,
    min_samples_leaf=2,
    random_state=42
)
rf_model.fit(X_train, y_train)
print("✅ Random Forest v3 trained successfully")

# ── Evaluate locally ──
rf_pred = np.expm1(rf_model.predict(X_test))
mae  = mean_absolute_error(y_test_raw, rf_pred)
rmse = np.sqrt(mean_squared_error(y_test_raw, rf_pred))
r2   = r2_score(y_test_raw, rf_pred)

print(f"\n📊 Local Model Results:")
```

```
print(f"MAE:  ${mae:.2f}")
print(f"RMSE: ${rmse:.2f}")
print(f"R²:   {r2:.4f}")

# ── Save and package model ──
joblib.dump(rf_model, "model.joblib")
print("\n✅ model.joblib saved")

with tarfile.open("model.tar.gz", "w:gz") as tar:
    tar.add("model.joblib")
print("✅ model.tar.gz created")

# ── Upload model to S3 ──
model_s3_path = session.upload_data(
    path="model.tar.gz",
    bucket=bucket,
    key_prefix="airbnb-price-final"
)
print(f"✅ Model uploaded to S3: {model_s3_path}")

# ── Write inference script ──
%%writefile inference.py
import os
import joblib
import numpy as np

def model_fn(model_dir):
    model = joblib.load(os.path.join(model_dir, "model.joblib"))
    return model

def input_fn(request_body, request_content_type):
    if request_content_type == "text/csv":
        data = np.array([float(x) for x in request_body.split(",")])
        return data.reshape(1, -1)
    raise ValueError("Unsupported content type")

def predict_fn(input_data, model):
    log_pred = model.predict(input_data)
    return np.expm1(log_pred)

def output_fn(prediction, content_type):
    return str(prediction[0])
```

```
✅ Random Forest v3 trained successfully

📊 Local Model Results:
MAE:  $56.30
RMSE: $75.43
R²:   0.1852

✅ model.joblib saved
✅ model.tar.gz created
✅ Model uploaded to S3: s3://sagemaker-ca-central-1-263245924849/airbnb-price-fin
al/model.tar.gz
```

```
UsageError: Line magic function `%%writefile` not found.
```

In [7]:
```
%%writefile inference.py
import os
import joblib
import numpy as np

def model_fn(model_dir):
    model = joblib.load(os.path.join(model_dir, "model.joblib"))
    return model

def input_fn(request_body, request_content_type):
    if request_content_type == "text/csv":
        data = np.array([float(x) for x in request_body.split(",")])
        return data.reshape(1, -1)
    raise ValueError("Unsupported content type")

def predict_fn(input_data, model):
    log_pred = model.predict(input_data)
    return np.expm1(log_pred)

def output_fn(prediction, content_type):
    return str(prediction[0])
```

```
Overwriting inference.py
```

In [8]:
```
# ── Deploy model as real-time SageMaker endpoint ──
sk_model = SKLearnModel(
    model_data=model_s3_path,
    role=role,
    entry_point="inference.py",
    framework_version="1.4-2"
)

print("⏳ Deploying endpoint — this takes about 5 minutes...")

predictor = sk_model.deploy(
    initial_instance_count=1,
    instance_type="ml.m5.large"
)

predictor.serializer   = CSVSerializer()
predictor.deserializer = StringDeserializer()

print("\n✅ Endpoint deployed successfully!")
print(f"Endpoint name: {predictor.endpoint_name}")
```

```
⏳ Deploying endpoint — this takes about 5 minutes...
INFO:sagemaker:Creating model with name: sagemaker-scikit-learn-2026-03-30-15-33-5
2-524
INFO:sagemaker:Creating endpoint-config with name sagemaker-scikit-learn-2026-03-3
0-15-33-53-024
INFO:sagemaker:Creating endpoint with name sagemaker-scikit-learn-2026-03-30-15-33
-53-024
-----!
✅ Endpoint deployed successfully!
Endpoint name: sagemaker-scikit-learn-2026-03-30-15-33-53-024
```

Step 6 — Inferencing & Endpoint Validation

We send test data to the live endpoint and compare predicted prices to actual prices to validate the model's performance.

Process:

1. Take sample rows from test set (features only, no price)
2. Convert to CSV format
3. Send to live endpoint
4. Compare predictions to actual prices
5. Calculate MAE, RMSE and R^2 on full test set

Why validate on the endpoint?

To confirm the deployed model produces identical results to the local model — proving the deployment is correct.

In [10]:
```
# ── Delete old endpoint first ──
predictor.delete_endpoint()
print("✅ Old endpoint deleted")

# ── Retrain on correct features ──
joblib.dump(rf_model, "model.joblib")
print("✅ Correct model saved")

# ── Repackage ──
with tarfile.open("model.tar.gz", "w:gz") as tar:
    tar.add("model.joblib")
print("✅ model.tar.gz repackaged")

# ── Re-upload to S3 ──
model_s3_path = session.upload_data(
    path="model.tar.gz",
    bucket=bucket,
    key_prefix="airbnb-price-final-v2"
)
print(f"✅ Uploaded: {model_s3_path}")

# ── Redeploy ──
sk_model = SKLearnModel(
    model_data=model_s3_path,
    role=role,
    entry_point="inference.py",
    framework_version="1.4-2"
)

print("⏳ Redeploying endpoint...")

predictor = sk_model.deploy(
```

```
    initial_instance_count=1,
    instance_type="ml.m5.large"
)

predictor.serializer   = CSVSerializer()
predictor.deserializer = StringDeserializer()

print("\n✅ Endpoint redeployed successfully!")
print(f"Endpoint name: {predictor.endpoint_name}")
```

```
INFO:sagemaker:Deleting endpoint configuration with name: sagemaker-scikit-learn-2
026-03-30-15-33-53-024
INFO:sagemaker:Deleting endpoint with name: sagemaker-scikit-learn-2026-03-30-15-3
3-53-024
✅ Old endpoint deleted
✅ Correct model saved
✅ model.tar.gz repackaged
✅ Uploaded: s3://sagemaker-ca-central-1-263245924849/airbnb-price-final-v2/model.
tar.gz
⏳ Redeploying endpoint...
INFO:sagemaker:Creating model with name: sagemaker-scikit-learn-2026-03-30-15-40-2
6-484
INFO:sagemaker:Creating endpoint-config with name sagemaker-scikit-learn-2026-03-3
0-15-40-26-950
INFO:sagemaker:Creating endpoint with name sagemaker-scikit-learn-2026-03-30-15-40
-26-950
----!
✅ Endpoint redeployed successfully!
Endpoint name: sagemaker-scikit-learn-2026-03-30-15-40-26-950
```

In [13]:

```
%%writefile inference.py
import os
import joblib
import numpy as np
import json

def model_fn(model_dir):
    model = joblib.load(os.path.join(model_dir, "model.joblib"))
    return model

def input_fn(request_body, request_content_type):
    if request_content_type == "text/csv":
        values = [float(x) for x in request_body.strip().split(",")]
        return np.array(values).reshape(1, -1)
    raise ValueError(f"Unsupported content type: {request_content_type}")

def predict_fn(input_data, model):
    # Model was trained on log price, convert back to dollars
    log_pred = model.predict(input_data)
    return np.expm1(log_pred)

def output_fn(prediction, accept):
    return str(float(prediction[0]))
```

```
Overwriting inference.py
```

In [14]:
```
# Delete current endpoint
predictor.delete_endpoint()
print("✅ Old endpoint deleted")

# Repackage with fixed inference.py
with tarfile.open("model.tar.gz", "w:gz") as tar:
    tar.add("model.joblib")
    tar.add("inference.py")
print("✅ Repackaged with fixed inference.py")

# Upload to S3
model_s3_path = session.upload_data(
    path="model.tar.gz",
    bucket=bucket,
    key_prefix="airbnb-price-final-v3"
)
print(f"✅ Uploaded: {model_s3_path}")

# Redeploy
sk_model = SKLearnModel(
    model_data=model_s3_path,
    role=role,
    entry_point="inference.py",
    framework_version="1.4-2"
)

print("⏳ Redeploying...")

predictor = sk_model.deploy(
    initial_instance_count=1,
    instance_type="ml.m5.large"
)

predictor.serializer   = CSVSerializer()
predictor.deserializer = StringDeserializer()

print("\n✅ Endpoint redeployed!")
print(f"Endpoint name: {predictor.endpoint_name}")
```

```
INFO:sagemaker:Deleting endpoint configuration with name: sagemaker-scikit-learn-2
026-03-30-15-40-26-950
INFO:sagemaker:Deleting endpoint with name: sagemaker-scikit-learn-2026-03-30-15-4
0-26-950
✅ Old endpoint deleted
✅ Repackaged with fixed inference.py
✅ Uploaded: s3://sagemaker-ca-central-1-263245924849/airbnb-price-final-v3/model.
tar.gz
⏳ Redeploying...
INFO:sagemaker:Creating model with name: sagemaker-scikit-learn-2026-03-30-15-46-3
0-454
INFO:sagemaker:Creating endpoint-config with name sagemaker-scikit-learn-2026-03-3
0-15-46-30-947
INFO:sagemaker:Creating endpoint with name sagemaker-scikit-learn-2026-03-30-15-46
-30-947
```

```
-----!
✅ Endpoint redeployed!
Endpoint name: sagemaker-scikit-learn-2026-03-30-15-46-30-947
```

In [18]:

```
# ── Convert booleans to int in X_test ──
X_test_fixed = X_test.replace({True: 1, False: 0}).astype(float)
X_train_fixed = X_train.replace({True: 1, False: 0}).astype(float)

# ── Single prediction test ──
sample = X_test_fixed.iloc[0].values
sample_csv = ",".join(str(x) for x in sample)

result = predictor.predict(sample_csv)
print("📊 Single Prediction Test:")
print(f"Predicted Price: ${float(result):.2f}")
print(f"Actual Price:    ${y_test_raw.iloc[0]:.2f}")

# ── Full test set evaluation ──
print("\n⏳ Running predictions on full test set...")

all_predictions = []
for i in range(len(X_test_fixed)):
    sample     = X_test_fixed.iloc[i].values
    sample_csv = ",".join(str(x) for x in sample)
    pred       = predictor.predict(sample_csv)
    all_predictions.append(float(pred))

y_pred   = np.array(all_predictions)
y_actual = y_test_raw.values

# ── Calculate metrics ──
mae  = mean_absolute_error(y_actual, y_pred)
rmse = np.sqrt(mean_squared_error(y_actual, y_pred))
r2   = r2_score(y_actual, y_pred)

print("\n" + "="*45)
print("📊 Endpoint Evaluation Results")
print("="*45)
print(f"MAE:  ${mae:.2f}")
print(f"RMSE: ${rmse:.2f}")
print(f"R²:   {r2:.4f}")
print("="*45)

# ── Plot predictions vs actual ──
plt.figure(figsize=(8, 5))
plt.scatter(y_actual, y_pred, alpha=0.5)
plt.plot([y_actual.min(), y_actual.max()],
         [y_actual.min(), y_actual.max()],
         'r--', lw=2, label='Perfect prediction')
plt.xlabel("Actual Price ($)")
plt.ylabel("Predicted Price ($)")
plt.title("Actual vs Predicted Airbnb Prices")
plt.legend()
plt.tight_layout()
plt.show()
```

```
print("\n✅ Inferencing complete!")
```

```
/tmp/ipykernel_26602/3216894761.py:2: FutureWarning: Downcasting behavior in `repl
ace` is deprecated and will be removed in a future version. To retain the old beha
vior, explicitly call `result.infer_objects(copy=False)`. To opt-in to the future
behavior, set `pd.set_option('future.no_silent_downcasting', True)`
  X_test_fixed = X_test.replace({True: 1, False: 0}).astype(float)
/tmp/ipykernel_26602/3216894761.py:3: FutureWarning: Downcasting behavior in `repl
ace` is deprecated and will be removed in a future version. To retain the old beha
vior, explicitly call `result.infer_objects(copy=False)`. To opt-in to the future
behavior, set `pd.set_option('future.no_silent_downcasting', True)`
  X_train_fixed = X_train.replace({True: 1, False: 0}).astype(float)
```

```
📊 Single Prediction Test:
Predicted Price: $125.20
Actual Price:    $302.00

⏳ Running predictions on full test set...

============================================
📊 Endpoint Evaluation Results
============================================
MAE:  $56.30
RMSE: $75.43
R²:   0.1852
============================================
```




```
✅ Inferencing complete!
```

In [16]:

```
import boto3

logs_client = boto3.client('logs', region_name=region)

log_group = f"/aws/sagemaker/Endpoints/{predictor.endpoint_name}"
```

```python
# Get latest log stream
streams = logs_client.describe_log_streams(
    logGroupName=log_group,
    orderBy='LastEventTime',
    descending=True,
    limit=1
)

stream_name = streams['logStreams'][0]['logStreamName']

# Get log events
events = logs_client.get_log_events(
    logGroupName=log_group,
    logStreamName=stream_name,
    limit=30
)

print("=== CloudWatch Logs ===")
for event in events['events']:
    print(event['message'])
```

```
=== CloudWatch Logs ===
169.254.178.2 - - [30/Mar/2026:15:49:13 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:49:18 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:49:23 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:49:28 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:49:33 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:49:38 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:49:43 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:49:48 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:49:53 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:49:58 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:03 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
2026-03-30 15:50:05,936 ERROR - inference - Exception on /invocations [POST]
Traceback (most recent call last):
  File "/usr/local/lib/python3.10/dist-packages/sagemaker_containers/_functions.p
y", line 93, in wrapper
    return fn(*args, **kwargs)
  File "/opt/ml/code/inference.py", line 12, in input_fn
    values = [float(x) for x in request_body.strip().split(",")]
  File "/opt/ml/code/inference.py", line 12, in <listcomp>
    values = [float(x) for x in request_body.strip().split(",")]
ValueError: could not convert string to float: 'False'
During handling of the above exception, another exception occurred:
Traceback (most recent call last):
  File "/usr/local/lib/python3.10/dist-packages/flask/app.py", line 2446, in wsgi_
app
    response = self.full_dispatch_request()
  File "/usr/local/lib/python3.10/dist-packages/flask/app.py", line 1951, in full_
dispatch_request
    rv = self.handle_user_exception(e)
  File "/usr/local/lib/python3.10/dist-packages/flask/app.py", line 1820, in handl
e_user_exception
    reraise(exc_type, exc_value, tb)
  File "/usr/local/lib/python3.10/dist-packages/flask/_compat.py", line 39, in rer
aise
    raise value
  File "/usr/local/lib/python3.10/dist-packages/flask/app.py", line 1949, in full_
dispatch_request
    rv = self.dispatch_request()
  File "/usr/local/lib/python3.10/dist-packages/flask/app.py", line 1935, in dispa
tch_request
    return self.view_functions[rule.endpoint](**req.view_args)
  File "/usr/local/lib/python3.10/dist-packages/sagemaker_containers/_transformer.
py", line 199, in transform
    result = self._transform_fn(
```

```
  File "/usr/local/lib/python3.10/dist-packages/sagemaker_containers/_transformer.
py", line 227, in _default_transform_fn
    data = self._input_fn(content, content_type)
  File "/usr/local/lib/python3.10/dist-packages/sagemaker_containers/_functions.p
y", line 95, in wrapper
    six.reraise(error_class, error_class(e), sys.exc_info()[2])
  File "/usr/local/lib/python3.10/dist-packages/six.py", line 702, in reraise
    raise value.with_traceback(tb)
  File "/usr/local/lib/python3.10/dist-packages/sagemaker_containers/_functions.p
y", line 93, in wrapper
    return fn(*args, **kwargs)
  File "/opt/ml/code/inference.py", line 12, in input_fn
    values = [float(x) for x in request_body.strip().split(",")]
  File "/opt/ml/code/inference.py", line 12, in <listcomp>
    values = [float(x) for x in request_body.strip().split(",")]
sagemaker_containers._errors.ClientError: could not convert string to float: 'Fals
e'
169.254.178.2 - - [30/Mar/2026:15:50:05 +0000] "POST /invocations HTTP/1.1" 500 29
0 "-" "AHC/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:08 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:13 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:18 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:23 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:28 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:33 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:38 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:43 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:48 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:53 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:50:58 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
169.254.178.2 - - [30/Mar/2026:15:51:03 +0000] "GET /ping HTTP/1.1" 200 0 "-" "AH
C/2.0"
```

Step 7 — Resource Cleanup

All AWS resources are deleted after validation to avoid unnecessary charges.

Why this matters:

- SageMaker endpoints charge **per hour** while running
- Deleting immediately after validation saves cost
- This is a required step before presentation

Resources deleted:

- Real-time inference endpoint

In [19]:
```
# ── Delete endpoint to avoid unnecessary AWS charges ──
predictor.delete_endpoint()

print("✅ Endpoint deleted successfully!")
print("✅ No more charges — all resources cleaned up!")
print("\n" + "="*45)
print("🏆 ML Pipeline Complete!")
print("="*45)
print(f"\n📊 Final Results Summary:")
print(f"Dataset:          953 Airbnb listings")
print(f"Features:         42 engineered features")
print(f"Best Model:       Random Forest v3")
print(f"Outliers removed: 48 listings above $441")
print(f"")
print(f"Local Model:")
print(f"  MAE:            $56.30")
print(f"  RMSE:           $75.43")
print(f"  R²:             0.1852")
print(f"")
print(f"SageMaker Training Job:")
print(f"  train:rmse:     26.35")
print(f"  validation:rmse: 84.78")
print(f"")
print(f"HP Tuning Best Job:")
print(f"  validation:rmse: 73.29  ← improved from 84.78!")
print(f"")
print(f"Endpoint Inference:")
print(f"  MAE:            $56.30")
print(f"  RMSE:           $75.43")
print(f"  R²:             0.1852")
print("="*45)
```

```
INFO:sagemaker:Deleting endpoint configuration with name: sagemaker-scikit-learn-2
026-03-30-15-46-30-947
INFO:sagemaker:Deleting endpoint with name: sagemaker-scikit-learn-2026-03-30-15-4
6-30-947
```

```
✅ Endpoint deleted successfully!
✅ No more charges — all resources cleaned up!

============================================
🏆 ML Pipeline Complete!
============================================

📊 Final Results Summary:
Dataset:          953 Airbnb listings
Features:         42 engineered features
Best Model:       Random Forest v3
Outliers removed: 48 listings above $441

Local Model:
  MAE:            $56.30
  RMSE:           $75.43
  R²:             0.1852

SageMaker Training Job:
  train:rmse:     26.35
  validation:rmse: 84.78

HP Tuning Best Job:
  validation:rmse: 73.29  ← improved from 84.78!

Endpoint Inference:
  MAE:            $56.30
  RMSE:           $75.43
  R²:             0.1852
============================================
```

In [ ]: