


STARTING OUT WITH JAVA™

4th Edition



Chapter 12


JavaFX: GUI Programming
and Basic Controls

Topics

- Graphical User Interfaces
- Introduction to JavaFX
- Creating Scenes
- Displaying Images
- More About the HBox, VBox, and GridPane Layout Containers
- Button Controls and Events
- Reading Input with TextField Controls
- Using Lambda Expressions to Handle Events
- The BorderPane Layout Container
- The ObservableList Interface


Graphical User Interfaces (1 of 3)

- Many Java application use a *graphical user interface* or *GUI* (pronounced “gooey”).
- A GUI is a graphical window or windows that provide interaction with the user.



Graphical User Interfaces (2 of 3)

- A window in a GUI commonly consists of several *controls* that present data to the user and/or allow interaction with the application.
- Some of the common GUI *controls* are buttons, labels, text fields, check boxes, and radio buttons.



Graphical User Interfaces (3 of 3)

- Programs that operate in a GUI environment must be *event-driven*.
- An *event* is an action that takes place within a program, such as the clicking of a button.
- Part of writing a GUI application is creating event listeners.
- An *event listener* is a method that automatically executes when a specific event occurs.

Introduction to JavaFX (1 of 7)


- *JavaFX* is a Java library for developing rich applications that employ graphics.
- You can use it to create:
 - GUI applications, as well as applications that display 2D and 3D graphics
 - standalone graphics applications that run on your local computer
 - applications that run from a remote server
 - applications that are embedded in a Web page

Introduction to JavaFX (2 of 7)

- JavaFX uses a theater metaphor to describe the structure of a GUI.
- A theater has a stage
- On the stage, a scene is performed by actors


Introduction to JavaFX (3 of 7)

- In JavaFX, the stage is an empty window




Introduction to JavaFX (4 of 7)

- The scene is a collection of GUI objects (controls) that are contained within the window.
- You can think of the GUI objects as the actors that make up the scene.



Introduction to JavaFX (5 of 7)

- In memory, the GUI objects in a scene are organized as nodes in a *scene graph*, which is a tree-like hierarchical data structure.



Introduction to JavaFX (6 of 7)

- The scene graph has three types of nodes:
 - **Root Node:** There is only one root node, which is the parent of all the other nodes in the scene graph.
 - **Branch Node:** A node that can have other nodes as children
 - **Leaf Node:** A node that cannot have children


Introduction to JavaFX (7 of 7)

- The Application Class
 - An abstract class that is the foundation of all JavaFX applications
 - JavaFX applications must extend the Application class
 - The Application class has an abstract method named `start`, which is the entry point for the application
 - Because the `start` method is abstract, you must override it

General Layout of a JavaFX Program

- Various import statements
- A class that extends the `Application` class
- A start method
- A main method

```
import javafx.application.Application;
import javafx.stage.Stage;
import javafx.scene.Scene;
Other import statements...
```



Necessary import statements

```
public class ClassName extends Application
{
    public static void main(String[] args)
    {
        // Launch the application.
        launch(args);
    }

    @Override
    public void start(Stage primaryStage)
    {
        // Insert startup code here.
    }
}
```

```
import javafx.application.Application;
import javafx.stage.Stage;
import javafx.scene.Scene;
```

Necessary import
statements

Other import statements...

```
public class ClassName extends Application
{
    public static void main(String[] args)
    {
        // Launch the application.
        launch(args);
    }

    @Override
    public void start(Stage primaryStage)
    {
        // Insert startup code here.
    }
}
```

A class that extends
the Application
class

```
import javafx.application.Application;
import javafx.stage.Stage;
import javafx.scene.Scene;
```

Necessary import
statements

Other import statements...

```
public class ClassName extends Application
{
    public static void main(String[] args)
    {
        // Launch the application.
        launch(args);
    }

    @Override
    public void start(Stage primaryStage)
    {
        // Insert startup code here.
    }
}
```

A static main method
that calls the inherited
launch method

A class that extends
the Application
class


```
import javafx.application.Application;
import javafx.stage.Stage;
import javafx.scene.Scene;
```

Necessary import
statements

Other import statements...

```
public class ClassName extends Application
{
    public static void main(String[] args)
    {
        // Launch the application.
        launch(args);
    }

    @Override
    public void start(Stage primaryStage)
    {
        // Insert startup code here.
    }
}
```

A static main method
that calls the inherited
launch method

A class that extends
the Application
class

A start method that
accepts a Stage
argument. This method
is called by the inherited
launch method.

MyFirstGUI.java

```
1 import javafx.application.Application;
2 import javafx.stage.Stage;
3
4 /**
5  * A simple JavaFX GUI application
6  */
7
8 public class MyFirstGUI extends Application
9 {
10     public static void main(String[] args)
11     {
12         // Launch the application.
13         launch(args);
14     }
15
16     @Override
17     public void start(Stage primaryStage)
18     {
19         // Set the stage title.
20         primaryStage.setTitle("My First GUI Application");
21
22         // Show the window.
23         primaryStage.show();
24     }
25 }
```



Creating Controls (1 of 2)

- Process for creating a control:
 - Import the class for the control from the necessary javafx package. Example:
 - Instantiate the class, calling the desired constructor. Example:

```
import javafx.scene.control.Label;
```

```
Label messageLabel = new Label("Hello World");
```

Creating Controls (2 of 2)

- Another example: Creating a Button
 - Import the Button class from the necessary javafx package:

```
import javafx.scene.control.Button;
```



- Instantiate the class, calling the desired constructor:

```
Button mybutton = new Button("Click Me");
```

Layout Containers (1 of 2)

- You use layout containers to arrange the positions of controls on the screen.
- JavaFX provides many layout containers.
- We will start with these:
 - HBox: Arranges controls in a single horizontal row.
 - VBox: Arranges controls in a single vertical row.
 - GridPane: Arranges controls in a grid with rows and columns.

Layout Containers (2 of 2)



The layout container classes are in the `javafx.scene.layout` package.

Adding Controls to a Layout Container

VBox



```
Button b1 = new Button("Button 1");  
Button b2 = new Button("Button 2");  
Button b3 = new Button("Button 3");
```

```
VBox vbox = new VBox(b1, b2, b3);
```

Creating a Scene (1 of 2)

- To create a scene, you instantiate the Scene class (in the `javafx.scene` package)
- Then, you add your root node to the scene

Creating a Scene (2 of 2)

```
// Create a Label control.  
Label messageLabel = new Label("Hello World");  
  
// Create an HBox container and add the Label.  
HBox hbox = new HBox(messageLabel);  
  
// Create a Scene and add the HBox as the root node.  
Scene scene = new Scene(hbox);
```

Adding the Scene to the Stage

- Once you've created a Scene object, you add it to the application's stage.
- The stage is an instance of the Stage class (from the `javafx.stage` package)
- You do not have to instantiate the Stage class, however. It is created automatically, and passed as an argument to the start method.

```
@Override  
public void start(Stage primaryStage)  
{  
  
}
```

```
import javafx.application.Application;
import javafx.stage.Stage;
import javafx.scene.Scene;
import javafx.scene.control.Label;
import javafx.scene.layout.VBox;
```

```
public class HelloWorld extends Application
{
```

```
    public static void main(String[] args)
    {
        launch(args);
    }
```


```
    @Override
```

```
    public void start(Stage primaryStage)
    {
```

```
        Label messageLabel = new Label("Hello World"); ← Make a Label control
        VBox vbox = new VBox(messageLabel); ← Put the Label in a VBox
        Scene scene = new Scene(vbox); ← Make the VBox the root node in the scene
        primaryStage.setScene(scene); ← Set the scene to the stage
        primaryStage.show(); ← Show the stage (display it)
```

```
    }
```

```
}
```



```
import javafx.application.Application;
import javafx.stage.Stage;
import javafx.scene.Scene;
import javafx.scene.control.Label;
import javafx.scene.layout.VBox;
import javafx.geometry.Pos;
```

```
public class HelloWorld extends Application
{
    public static void main(String[] args)
    {
        launch(args);
    }
}
```

```
@Override
```

```
public void start(Stage primaryStage)
{
```

```
    Label messageLabel = new Label("Hello World");
```

```
    VBox vbox = new VBox(messageLabel);
```

```
    vbox.setAlignment(Pos.CENTER);
```


```
    Scene scene = new Scene(vbox , 300, 100);
```

```
    primaryStage.setScene(scene);
```

```
    primaryStage.show();
```

```
}
```

```
}
```



Width

Height

Displaying Images

- You need two JavaFX classes:
 - The Image class, from the `javafx.scene.image` package
 - Use this class to load an image into memory
 - The ImageView class, also from the `javafx.scene.image` package
 - Use this class to create a node that displays the image

```
@Override
public void start(Stage primaryStage)
{
    // Create an Image object.
    Image image = new Image("file:HotAirBalloon.jpg");

    // Create an ImageView object.
    ImageView imageView = new ImageView(image);


    // Put the ImageView in an HBox.
    HBox hbox = new HBox(imageView);

    // Create a Scene with the HBox as its root node.
    Scene scene = new Scene(hbox);

    // Add the Scene to the Stage.
    primaryStage.setScene(scene);

    // Set the stage title.
    primaryStage.setTitle("Hot Air Balloon");

    // Show the window.
    primaryStage.show();
}
```



More About HBox and VBox Containers

(1 of 2)

- To add spacing between the items in an HBox or VBox:

```
HBox hbox = new HBox(10, label1, label2, label3);
```

↑
Spacing

```
VBox vbox = new VBox(20, button1, button2, button3);
```

↑
Spacing

More About HBox and VBox Containers


(2 of 2)

- *Padding* is space that appears around the inside edge of a container.
- The HBox and VBox containers have a `setPadding` method.
- You pass an `Insets` object as an argument to the `setPadding` method.
- The `Insets` object specifies the number of pixels of padding.
- The `Insets` class is in the `javafx.geometry` package.

```
hbox.setPadding(new Insets(10));
```


The GridPane Layout Container (1 of 5)

- Arranges its contents in a grid with columns and rows.
- The columns and rows are identified by indexes.



The GridPane Layout Container (2 of 5)

- The GridPane class is in the `javafx.scene.layout` package.
- First, you instantiate the GridPane class, using the no-arg constructor:

```
GridPane gridpane = new GridPane();
```

- Then, you add controls to the container using the add method:

```
gridPaneObject.add(control, column, row);
```

The GridPane Layout Container (3 of 5)

```
// Create some Label controls.  
Label label1 = new Label("This is label1");  
Label label2 = new Label("This is label2");  
Label label3 = new Label("This is label3");  
Label label4 = new Label("This is label4");  
  
// Create a GridPane.  
GridPane gridpane = new GridPane();  
  
// Add the Labels to the GridPane.  
gridpane.add(label1, 0, 0); // Column 0, Row 0  
gridpane.add(label2, 1, 0); // Column 1, Row 0  
gridpane.add(label3, 0, 1); // Column 0, Row 1  
gridpane.add(label4, 1, 1); // Column 1, Row 1
```

The GridPane Layout Container (4 of 5)

- By default, there is no space between the rows and columns in a GridPane.
- To add horizontal spacing between the columns in a GridPane, call the container's setHgap method.
- To add vertical spacing between the rows in a GridPane, call the container's setVgap method.

```
GridPane gridpane = new GridPane();  
gridpane.setHgap(10);  
gridpane.setVgap(10);
```


The GridPane Layout Container (5 of 5)

- The GridPane container also has a `setPadding` method to set the padding around the container's inside edge:

```
GridPane gridpane = new GridPane();  
gridpane.setPadding(new Insets(10));
```

Using Multiple Layout Containers


- To get the particular screen layout that you desire, you will sometimes have to nest layout containers.



Handling Events (1 of 2)

- An *event* is an action that takes place within a program, such as the clicking of a button.
- When an event takes place, the control that is responsible for the event creates an *event object* in memory.
- The event object contains information about the event.
- The control that generated the event object is known as the *event source*.
- It is possible that the event source is connected to one or more event listeners.

Handling Events (2 of 2)



Event Objects

- Event objects are instances of the Event class (from the `javafx.event` package), or one of its subclasses.
- For example, a Button click generates an `ActionEvent` object. `ActionEvent` is a subclass of the Event class.

Event Handlers (1 of 2)

- Event handlers are objects.
- You write event handler classes that implement the `EventHandler` interface (from the `javafx.event` package).
- The `EventHandler` interface specifies a `void` method named `handle` that has a parameter of the `Event` class (or one of its subclasses).

Event Handlers (2 of 2)

```
class ButtonClickHandler implements EventHandler<ActionEvent>
{
    @Override
    void handle(ActionEvent event)
    {
        // Write event handling code here.
    }
}
```

Registering an Event Handler



- The process of connecting an event handler object to a control is called *registering* the event handler.
- Button controls have a method named `setOnAction` that registers an event handler:

```
mybutton.setOnAction(new ButtonClickHandler());
```

- When the user clicks the button, the event handler object's `handle` method will be executed.

Event Handling Example

- Let's look at an application that initially displays this screen:
- When the user clicks the button, the screen changes to:



```
import javafx.application.Application;
import javafx.stage.Stage;
import javafx.scene.Scene;
import javafx.scene.layout.VBox;
import javafx.scene.control.Label;
import javafx.scene.control.Button;
import javafx.geometry.Pos;
import javafx.event.EventHandler;
import javafx.event.ActionEvent;

public class EventDemo extends Application
{
    private Label myLabel;

    public static void main(String[] args)
    {
        launch(args);
    }
}
```

Continued...

```

@Override
public void start(Stage primaryStage)
{
    // Create a Label and a Button.
    myLabel = new Label("Click the button to see a message.");
    Button myButton = new Button("Click Me");

    // Register an event handler.
    myButton.setOnAction(new ButtonClickHandler());

    // Put the Label and Button in a VBox with 10 pixels of spacing.
    VBox vbox = new VBox(10, myLabel, myButton);
    vbox.setAlignment(Pos.CENTER);

    // Create a Scene and display it.
    Scene scene = new Scene(vbox, 300, 100);
    primaryStage.setScene(scene);
    primaryStage.show();
}

class ButtonClickHandler implements EventHandler<ActionEvent>
{
    @Override
    public void handle(ActionEvent event)
    {
        myLabel.setText("Thanks for clicking the button!");
    }
}
}

```

Reading Input with TextField Controls

(1 of 2)

- At runtime, the user can type text into a TextField control.
- In the program, you can retrieve the text that the user entered.
- The TextField class is in the `javafx.scene.control` package.
- To create an empty TextField:

```
TextField myTextField = new TextField();
```


Reading Input with TextField Controls

(2 of 2)

- To retrieve the text that the user has typed into a TextField control, call the control's `getText` method.
- The method returns the value that has been entered, as a `String`.
- Example:

```
String input;  
input = myTextField.getText();
```

- See [KiloConverter.java](#) in your textbook

Anonymous Inner Classes as Event Handlers

- When an event handler class is instantiated only once, you can write it as an anonymous inner class.

```
import javafx.application.Application;
import javafx.stage.Stage;
import javafx.scene.Scene;
import javafx.scene.layout.VBox;
import javafx.scene.control.Label;
import javafx.scene.control.Button;
import javafx.geometry.Pos;
import javafx.event.EventHandler;
import javafx.event.ActionEvent;

public class EventDemo2 extends Application
{
    private Label myLabel;

    public static void main(String[] args)
    {
        launch(args);
    }
}
```

Continued...

```

@Override
public void start(Stage primaryStage)
{
    // Create a Label and a Button.
    myLabel = new Label("Click the button to see a message.");
    Button myButton = new Button("Click Me");

    // Register an event handler.
    myButton.setOnAction(new EventHandler<ActionEvent>()
    {
        @Override
        public void handle(ActionEvent event)
        {
            myLabel.setText("Thanks for clicking the button!");
        }
    });

    // Put the Label and Button in a VBox with 10 pixels of spacing.
    VBox vbox = new VBox(10, myLabel, myButton);
    vbox.setAlignment(Pos.CENTER);

    // Create a Scene and display it.
    Scene scene = new Scene(vbox, 300, 100);
    primaryStage.setScene(scene);
    primaryStage.show();
}
}

```

Lambda Expressions as Event Handlers

- Recall that a functional interface is an interface that has one, and only one, abstract method.
- The `EventHandler` interface has only one abstract method is a functional interface.
- Any time you are writing Java code to instantiate an anonymous class that implements a functional interface, you should consider using a lambda expression instead.
- A lambda expression is more concise than the code for instantiating an anonymous class.

```
import javafx.application.Application;
import javafx.stage.Stage;
import javafx.scene.Scene;
import javafx.scene.layout.VBox;
import javafx.scene.control.Label;
import javafx.scene.control.Button;
import javafx.geometry.Pos;

public class EventDemo3 extends Application
{
    private Label myLabel;

    public static void main(String[] args)
    {
        launch(args);
    }
}
```

Continued...

```

@Override
public void start(Stage primaryStage)
{
    // Create a Label and a Button.
    myLabel = new Label("Click the button to see a message.");
    Button myButton = new Button("Click Me");

    // Register an event handler.
    myButton.setOnAction(e ->
    {
        myLabel.setText("Thanks for clicking the button!");
    });


    // Put the Label and Button in a VBox with 10 pixels of spacing.
    VBox vbox = new VBox(10, myLabel, myButton);
    vbox.setAlignment(Pos.CENTER);

    // Create a Scene and display it.
    Scene scene = new Scene(vbox, 300, 100);
    primaryStage.setScene(scene);
    primaryStage.show();
}
}

```

The BorderPane Layout Container (1 of 4)

- The BorderPane layout container manages controls in five regions:



The BorderLayout Container (2 of 4)

- Only one object at a time may be placed into a BorderLayout region.
- You do not usually put controls directly into a BorderLayout region.
- Typically, you put controls into another type of layout container, then you put that container into one of the BorderLayout regions.

The BorderLayout Container (3 of 4)

- The BorderLayout class is in the `javafx.scene.layout` package.
- Summary of constructors:

Constructor	Description
<code>BorderPane()</code>	The no-arg constructor creates an empty BorderLayout container.
<code>BorderPane(<i>center</i>)</code>	This constructor accepts one argument. The node that is passed as the argument is placed in the BorderLayout's center region.
<code>BorderPane(<i>center, top, right, bottom, left</i>)</code>	This constructor accepts five nodes as arguments: one to place in each region.

The BorderLayout Container (4 of 4)

- The BorderLayout class provides the following methods to add controls to specific regions:
 - setCenter
 - setTop
 - setBottom
 - setLeft
 - setRight
- See [BorderPaneDemo1.java](#) in your textbook.

The ObservableList Interface (1 of 5)

- Widely used in JavaFX
- Learning a few basic ObservableList operations gives you more control over the JavaFX containers with which you will be working.

The ObservableList Interface (2 of 5)

- A few ObservableList methods:

Method	Description
<code>add(<i>item</i>)</code>	Adds a single item to the list. (This method is inherited from the Collection interface.)
<code>addAll(<i>item...</i>)</code>	Adds one or more items to the list, specified by the variable argument list.
<code>clear()</code>	Removes all of the items from the list.
<code>remove(<i>item</i>)</code>	Removes the object specified by <i>item</i> from the list. (This method is inherited from the Collection interface.)
<code>removeAll(<i>item...</i>)</code>	Removes one or more items to the list, specified by the variable argument list.
<code>setAll(<i>item...</i>)</code>	Clears the current contents of the list and adds all of the items specified by the variable argument list.
<code>size()</code>	Returns the number of items in the list. (This method is inherited from the Collection interface.)

The ObservableList Interface (3 of 5)

- For example, layout containers keep their children nodes in an ObservableList.
- All layout containers have a method named `getChildren()` that returns their ObservableList of nodes.

The ObservableList Interface (4 of 5)

- Example: creating an empty HBox, then using the ObservableList's addAll method to add nodes to the HBox:

```
// Create three Label controls.  
Label label1 = new Label("This is label1.");  
Label label2 = new Label("This is label2.");  
Label label3 = new Label("This is label3.");  
  
// Create an empty HBox container.  
HBox hbox = new HBox();  
  
// Add the Label controls to the HBox.  
hbox.getChildren().addAll(label1, label2, label3);
```

The ObservableList Interface (5 of 5)

- Example: removing label1 from the HBox:

```
hbox.getChildren().remove(label1);
```


Copyright



This work is protected by United States copyright laws and is provided solely for the use of instructions in teaching their courses and assessing student learning. dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted. The work and materials from it should never be made available to students except by instructors using the accompanying text in their classes. All recipients of this work are expected to abide by these restrictions and to honor the intended pedagogical purposes and the needs of other instructors who rely on these materials.