

MESSAGE HUB API DOCUMENTATION

(VERSION 1.4)

1. Overview

All APIs under the Message Hub API are based on REST architecture and are accessed via HTTPS at specified URLs. The base URL for all request is <https://api.messagehub.com.mm>. The complete URL varies depending on the endpoint of the resource being accessed. For instance, you can get messages via a POST request to this URL: <https://api.messagehub.com.mm/api/services/app/MessageAPI/GetListMessage>.

2. Document revision information

Version	Date	Amendment
1.0	11.06.2023	Initial Release
1.1	14.06.2023	- Add API get remaining SMS number (Heading 3.8) - Update ErrorCode API send message (Heading 4.2) - Return CampaignId in dataResult object when sent message successfully (Heading 4.1)
1.2	17.06.2023	- Change ErrorCode API from text to number digits
1.3	20.06.2023	- Add Http Error Code
1.4	12.07.2023	- Add API get message status (Heading 3.5) - Add API send a single message(Heading 3.2)

3. Description

3.1. Authenticate

Use this API to get access token.

- Request

- Method: POST
- URL: /api/TokenAuth/AuthenticateAPI
- Headers:

Key	Value	Description
Content-Type	application/json	

- Body: raw (json)
 - Parameters:

Key	Data Type	Description
-----	-----------	-------------


```
hNjAtZjk2ZS00NjhLWI5MTItMjFhZWU0NTUyMjk3IiwidXNlcl9pZGVudGlmaWVyljoiODRANjAiLCJ0b2t1b90eXBlljoiMCIsIm5iZiI6MTY3NzU0ODYwMSwiZXhwIjoxNjc3NjM1MDAxLCJpc3MiOiJQTVMiLCJhdWQiOiJQTVMifQ.vC--4LAUrWIIE6QQUG8KmUbLML2PT5pJuQ5ZuMZMGDY",
  "expireInSeconds": 86400,
  "message": null,
  "isError": null,
},
}
```

3.2. Send a single message

Use this API to send an SMS message to phone number.

- Request:

- Method: POST
- URL: api/services/app/MessageAPI/CreateSingleMessage
- Headers

Key	Value	Description
Content-Type	application/json	
Authorization	Bearer <accessToken>	Replace <accessToken> by the value got from Authenticate request

- Body: raw (json)

■ Parameters:

Parameter	Data Type	Description	Required
brandName	String	The brandname will be used to send the messages	Yes
isSendNow	Boolean	true: The system will send messages immediately after request be invoked false: The system will send messages at the time specified by <i>scheduleDate</i> parameter.	Yes
scheduleDate	DateTime	If isSendNow is equal to true, this is the date and time when the message(s) will be sent.	No
content	String	Message content	Yes
phoneNumber	String	Phone number will be received the message	Yes

■ Example body:

```
{
  "brandName": "MESSAGE HUB",
  "isSendNow": true,
  "scheduleDate": null,
  "content": "This is test message",
  "phoneNumber": "95969111111"
}
```

- **Response:**

○ **Headers:**

Key	Value	Description
Content-Type	application/json	

○ **Schema**

Field	Data Type	Description
IsSuccessful	Boolean	True: Send message successfully False: Send message unsuccessfully
errorCode	String	System error code (See Error code definition)
errorMessage	String	System error message
dataResult	Object	Additional data returned for customer's system (See Data result definition)

○ **Example:**

```
{
  "result": {
    "dataResult": {
      "campaignId": 29,
      "messageId": "dfff6eb5-7a21-4174-b582-395ea3562ff6",
    },
    "isSuccessful": true,
    "errorCode": "ERR000",
    "errorMessage": ""
  }
}
```

3.3. Send multiple messages

Use this API to send SMS messages to many phone numbers.

- **Request:**

- Method: POST

- URL: api/services/app/MessageAPI/CreateMessage
- Headers

Key	Value	Description
Content-Type	application/json	
Authorization	Bearer <accessToken>	Replace <accessToken> by the value got from Authenticate request

- Body: raw (json)

- Parameters:

Parameter	Data Type	Description	Required
brandName	String	The brandname will be used to send the messages (s)	Yes
isSendNow	Boolean	true: The system will send messages immediately after request be invoked false: The system will send messages at the time specified by <i>scheduleDate</i> parameter.	Yes
scheduleDate	DateTime	If isSendNow is equal to true, this is the date and time when the message(s) will be sent.	No
content	String	Message content	Yes
listPhoneNumber	Array string	The list of phone numbers will be received the message	

- Example body:

```
{
  "brandName": "MESSAGE HUB",
  "isSendNow": true,
  "scheduleDate": null,
  "content": "This is test message",
  "listPhoneNumber": [ "95969111111", "95969222222", "95969333333" ]
}
```

- Response:

- Headers:

Key	Value	Description
Content-Type	application/json	

- **Schema**

Field	Data Type	Description
IsSuccessful	Boolean	True: Send message successfully False: Send message unsuccessfully
errorCode	String	System error code (See Error code definition)
errorMessage	String	System error message
dataResult	Object	Additional data returned for customer's system (See Data result definition)

- **Example:**

```
{
  "result": {
    "dataResult": {
      "campaignId": 29
    },
    "isSuccessful": true,
    "errorCode": "ERR000",
    "errorMessage": ""
  }
}
```

3.4. Search messages

Use this API to search messages was submitted to MessageHub gateway by your account.

- **Request:**

- Method: POST
- URL: /api/services/app/MessageAPI/GetListMessage
- Headers

Key	Value	Description
Content-Type	application/json	
Authorization	Bearer <accessToken>	Replace <accessToken> by the value got from Authenticate request

- Body: (raw json)

- Parameters:

Key	Data Type	Description	Required
fromDate	DateTime	From date	No

toDate	DateTime	To date	No
telCo	Number	The telco which the recipient is belong to 1: Mytel 2: MPT 3: Ooredoo 4: Telenor	No
brandName	String	Brandname	No
status	Number	1: Wait for sending 2: Sent successfully 3: Sent unsuccessfully 4: Wait for approval (message contains banned keyword)	No
filter	String	Filter by phone number	No
maxResultCount	Number	The number of records that system will returns.	Yes
skipCount	Number	The system will skip over <i>skipCount</i> records before return the result	Yes

▪ Example:

```
{
  "fromDate": null,
  "toDate": null,
  "brandName": null,
  "status": 1,
  "telco": 1,
  "filter": null,
  "maxResultCount": 10,
  "skipCount": 0
}
```

- Response:

○ Headers:

Key	Value	Description
Content-Type	application/json	

○ Schema:

Field	Data Type	Description
totalCount	number	Total records

items	array	
brandName	String	Brandname
contactId	Number	Contact Id
contactName	String	Contact name
phoneNumber	String	The phone number of the recipient
scheduleDate	DateTime	Scheduled date
sendDate	DateTime	The date and time that the message will be delivered to the recipient
content	String	Message content
creationTime	DateTime	Creation time
status	Number	The status of the message 1: Wait for sending 2: Sent successfully 3: Sent unsuccessfully 4: Wait for approval (message contains banned keyword)
statusName	String	The status of the message
totalSMS	Number	Total number of SMS
telCo	Number	The Telco corresponding to the recipient's phone number 1: Mytel 2: MPT 3: Ooredoo 4: Telenor
telCoName	String	Telco name
sendResult	String	The result of sending message(s)
id	Number	The Id of message

○ Example

```
{
  "result": {
    "totalCount": 10,
    "items":
    [
      {
        "id": 330,
        "brandName": "datech",
        "creationTime": "2023-02-28T14:30:47.150844",
        "contactName": "",
        "contactId": null,
        "phoneNumber": "959691111111",

```

```

        "scheduleDate": null,
        "sendDate": null,
        "content": "This is test message ",
        "status": 1,
        "statusName": "Wait for sending",
        "totalSMS": 1,
        "telCo": 1,
        "telCoName": "Mytel",
        "sendResult": null,
    }
}
}
}

```

3.5. Query message status

Use this API to get message status by its identifier.

- Request:

- Method: GET
- URL: /api/services/app/MessageAPI/GetMessageById
- Headers

Key	Value	Description
Content-Type	application/json	
Authorization	Bearer <accessToken>	Replace <accessToken> by the value got from Authenticate request

- Parameter: (url parameter)
 - Parameters:

Key	Data Type	Description	Required
messageId	String	Identity of message	Yes

- Example:

/api/services/app/MessageAPI/GetMessageById?messageId=9c29edb1-1d1e-4c17-97d3-ccaecb7a4d

- Response:

- Headers:

Key	Value	Description
Content-Type	application/json	

○ Schema:

Field	Data Type	Description
brandName	String	Brandname
contactId	Number	Contact Id
contactName	String	Contact name
phoneNumber	String	The phone number of the recipient
scheduleDate	DateTime	Scheduled date
sendDate	DateTime	The date and time that the message will be delivered to the recipient
content	String	Message content
creationTime	DateTime	Creation time
status	Number	The status of the message 1: Processing 2: Sent successfully 3: Sent unsuccessfully 4: Wait for approval (message contains banned keyword)
statusName	String	The status of the message
totalSMS	Number	Total number of SMS
telCo	Number	The Telco corresponding to the recipient's phone number 1: Mytel 2: MPT 3: Ooredoo 4: Telenor
telCoName	String	Telco name
sendResult	String	The result of sending message
id	Number	The Id of message

○ Example

```
{
  "result": {
    "brandName": "MESSAGE HUB",
    "creationTime": "2023-07-12T11:29:58",
    "contactName": null,
    "contactId": null,
    "phoneNumber": "959682942468",
    "scheduleDate": null,
    "sendDate": null,
    "content": "This is test message",
```

```

    "status": 1,
    "statusName": "Processing",
    "telCo": 1,
    "telCoName": "Mytel",
    "sendResult": null,
    "totalSMS": 1,
    "id": "9c29edb1-1d1e-4c17-97d3-ccaecb7a4d89"
  }
}

```

3.6. Check balance

Use this API to get the current balance (MMK) of your Message Hub account.

- Request

- Method: GET
- URL: /api/services/app/Session/GetBalanceAccount
- Headers:

Key	Value	Description
Content-Type	application/json	
Authorization	Bearer <accessToken>	Replace <accessToken> by the value got from Authenticate request

- Response:

- Headers:

Key	Value	Description
Content-Type	application/json	

- Schema:

Field	Data Type	Description
result	number	The current balance of your Message Hub account (Currency Unit: MMK)

- Example

```

{
  "result": 123450.00
}

```

3.7. Check remaining SMS quota

Use this API to get the current usable SMS of your Message Hub account.

- **Request**

- Method: GET
- URL: /api/services/app/Session/GetSMSAccount
- Headers:

Key	Value	Description
Content-Type	application/json	
Authorization	Bearer <accessToken>	Replace <accessToken> by the value got from Authenticate request

- **Response:**

- Headers:

Key	Value	Description
Content-Type	application/json	

- Schema:

Field	Data Type	Description
myTelRemainingSMS	number	The current usable Mytel SMS
mptRemainingSMS	number	The current usable MPT SMS
telenorRemainingSMS	number	The current usable Telenor SMS
ooredooRemainingSMS	number	The current usable Ooredoo SMS

- Example

```
{
  "result": {
    "myTelRemainingSMS": 189,
    "mptRemainingSMS": 0,
    "telenorRemainingSMS": 99,
    "ooredooRemainingSMS": 0
  }
}
```

4. Annex

4.1. Data result definition

No	Field	Data Type	Description
1	campaignId	Number	Campaign identity returned to track and

			manage outcomes
2	messageId	String	Message identity returned to track information (send a single message)

4.2. Error code definition

No	Error Code	Description
1	ERR000	Sent message successfully
2	ERR001	There is no recipient
3	ERR002	The maximum amount of recipient is lower than your request
4	ERR003	Brandname not found
5	ERR004	Brandname is not active
6	ERR005	Unregistered IP
7	ERR006	Send message to phone number doesn't support
8	ERR007	Empty schedule date but it is required
9	ERR008	Package is not enough to send message
10	ERR009	Trial brandname is not available to be used
11	ERR010	Message has no content
12	ERR999	Unknown error has occurred

4.3. Http Error Code

No	Code	Description
1	200	Ok
2	401	Unauthorized
3	500	Internal Server Error