

LEARNED INDEX FOR SIMILAR TRAJECTORY SEARCH IN DISTRIBUTED IN-MEMORY SYSTEM

Hani Ramadhan*, Hudzaifah E. Nursantio, Joonho Kwon

Pusan National University

Presented at Korean Database Conference 2019


October 11th, 2019, Chuncheon, South Korea

Outline

1. Problem
2. Challenges
3. Proposed Method
4. Experiment
5. Conclusion

Problem & Motivation

- Existing systems [1][2] on similar trajectory search still suffer from false positive results before verification
 - Inefficient query processing
- Machine learning-based index [3][4] (learned index) may provide better approximation of the trajectory location in partition



[1] D. Xie and F. P. J. M. Li, "Distributed Trajectory Similarity Search," PVLDB 2017.

[2] Z. Shang, G. Li and Z. Bao, "DITA: Distributed In-Memory Trajectory Analytics," in SIGMOD 2018.

[3] T. Kraska, A. Beutel, E. Chi, J. Dean and N. Polyzotis, "The Case for Learned Index Structures," in SIGMOD 2018.

[4] T. Kraska, M. Alizadeh, A. Beutel, E. Chi, A. Kristo, G. Leclerc, S. Madden, H. Mao and V. Nathan, "SageDB: A Learned Database System," in CIDR 2019.

Related Works

- [1] (uses segmentation) and DITA [2] (uses global-local partitioning) still suffers inefficiency of exploring false positive partitions
- Learned index improves the time efficiency and the index size from the traditional indexing (disk-based) [3]
- Different learned index is deployed for nearest neighbor search of large dataset of points [5].
 - Using a representation of codebook, proved for large dataset of points
 - Contextually, it is a modified similar search. But, still not applied to trajectory

[1] D. Xie and F. P. J. M. Li, "Distributed Trajectory Similarity Search," PVLDB 2017.

[2] Z. Shang, G. Li and Z. Bao, "DITA: Distributed In-Memory Trajectory Analytics," in SIGMOD 2018.

[3] T. Kraska, A. Beutel, E. Chi, J. Dean and N. Polyzotis, "The Case for Learned Index Structures," in SIGMOD 2018

[5] C.-Y. Chiu, A. Prayoonwong and Y.-C. Liao, "Learning to Index for Nearest Neighbor Search," IEEE Transactions on Pattern Analysis and Machine Intelligence, pp. 1-15, 2019.

Contributions


- We provide a learned index for an existing similarity trajectory search indexing (DITA) to minimize the exploration of irrelevant partitions/cluster thus improving the efficiency of the query processing
- We develop a probabilistic distance, applicable to learned index, to model the similarity between trajectories

Proposed Method

Modify the DITA indexing approach

The **probabilistic distance** to model the similarity between trajectories

Trajectory Similarity Search Query





- Task:

- Given a query trajectory T_Q
- With a distance threshold of τ
- Return all trajectories in set \mathcal{T} whose distance $\leq \tau$

$$SimTS_{\tau}^{T_Q} = \{\langle T_s \rangle, T_s \in \mathcal{T}\}$$

Trajectory Similarity Search Query



Distance (DTW)	T ₁	T ₂	T ₃
T ₁	0	0.4	10
T ₂	0.4	0	9
T ₃	10	9	0

- Example query:
 - Given T₁ as query to set {T₁, T₂, T₃}
 - Using threshold $\tau = 0.5$
 - Result: {T₁, T₂}

$$\text{DTW}(T, Q) = \begin{cases} \sum_{i=1}^m \text{dist}(t_i, q_1) & \text{if } n = 1 \\ \sum_{j=1}^n \text{dist}(t_1, q_j) & \text{if } m = 1 \\ \text{dist}(t_m, q_n) + \min(\text{DTW}(T^{m-1}, Q^{n-1}), \text{DTW}(T^{m-1}, Q), \text{DTW}(T, Q^{n-1})) & \text{otherwise} \end{cases}$$

DTW → widely used in trajectory similarity functions in many experiments [6]

[6] C. S. Myers and L. R. Rabiner. A comparative study of several dynamic time warping algorithms for connected-word recognition. Bell System Technical Journal, 60:1389–1409, 1981


DITA Comparison with/out learned Index

Global Partition




\leq threshold

Input: first, last point



1. Compute distance between first and last point to each global partition separately (2 trees)
2. Then, explore a global partition if first+last **total distance** less than threshold

Input: first, last, k pivot point



1. Compute similarity between first, last, and pivot points to each global partition (only 1 time)
2. Then, explore a global partition if their distance less than threshold


DITA Comparison with/without learned Index

Local Partition




\leq threshold

Input: first, last, k pivot points




DITA Local Index

Have to dive 2+k levels of partition indexing (+pruning)




Goes to the local partitions that contains similar trajectories directly from single inference

Learned Index Approach for Trajectory Similarity Search




Build Dataset for Similarity Search Query

- Example:
 - Query Set Q : $\{Q_1, Q_2\}$
 - Trajectory set \mathcal{T} : $\{T_1, T_2, T_3, T_4, T_5\}$
 - $H = \{0.1, 0.5, 1\}$




Build Dataset for Similarity Search Query

- Query result




Learn this using Machine Learning!



Probabilistic Distance $d_p(T_Q|T_C)$


- A parameter $p \rightarrow$ uncovered threshold from H
- Also interchangeable with the partitions
 - $T_C \leftrightarrow G_i \leftrightarrow l_{i,j}$



$$d_p(T_Q|T_C) = \begin{cases} 1, & T_C \in SimTS_{\tau}^{T_Q}, \tau = \min(H) \\ p, & T_C \notin SimTS_{\tau}^{T_Q}, \tau = \max(H) \\ p + \frac{\max(H) - \tau_{i-1}}{\max(H)} \times (1 - p), & T_C \in SimTS_{\tau}^{T_Q} \wedge T_C \notin SimTS_{\tau-1}^{T_Q} \end{cases}$$

Example: $p = 0.05$
 $d_p(Q_1|T_1) = 0.05$
 $d_p(Q_2|T_2) = 0.905$
 $d_p(Q_1|G_3) = 0.48$
 $d_p(Q_2|l_{2,1}) = 1$


Train the ML Model (Single Level)




Sample input:

- First point (x_f, y_f)
- Last point (x_l, y_l)
- K pivot points $\{(x_1, y_1), (x_2, y_2), \dots, (x_k, y_k)\}$


Global Partition




Local Partition




Train the ML Model (Multi-level)



Global Partition



Local Partition



Predict the Partitions & Trajectories

- Suppose we have a query with different threshold τ'
- Find All $T_i \in \mathcal{T}$ that satisfies $d_p(T_Q|T_i) \geq d_p(T_i|T_Q, \tau')$
 - T_i = similar trajectories/partitions containing
 - $d_p(T_i|T_Q, \tau') = \begin{cases} \frac{\max(H) - \tau'}{\max(H)} \times (1 - p), & \tau' \leq \max(H) \\ \frac{\max(H)}{\tau'} \times p, & \tau' > \max(H) \end{cases}$

Example: $\tau' = 3$

$p = 0.05, \max(H) = 7.5$

$d_p(T_i|T_Q, \tau') = 0.6333$

$d_p(Q_A|G_3) = 0.47$

$d_p(Q_A|l_{2,1}) = 0.97$

G_3 is NOT IN the result

$l_{2,1}$ is IN the result

Experiment Setup


- Dataset: DITA example trajectories of taxi driving. Using (<https://github.com/TsinghuaDatabaseGroup/DITA>)
 - 10,000 trajectories
- Input: first point, last point, pivot point ($k=1$)
- Model type: Simple Deep Neural Network
 - 1-level model
 - 2-level model, similar to RMI [3]
- Training dataset: random sampling of 1,381 trajectories Q , threshold $H = \{0.001, 0.005, 0.01, 0.05, 0.1, 0.5, 1, 2.5, 5, 7.5, 10\}$, and distance: DTW
- Test dataset: 60 trajectories $\notin Q$ and $H' = \{0.075, 0.03, 0.4, 6\}$
- Evaluation Metric: precision, compared to ground truth (DITA)

[3] T. Kraska, A. Beutel, E. Chi, J. Dean and N. Polyzotis, "The Case for Learned Index Structures," in SIGMOD 2018

Experiment Setup

- Hardware
 - Intel(R) Core(TM) 3.60GHz
 - 16 GB RAM
- Software
 - Hadoop-2.6 for Windows, Spark 2.2.0, TensorFlow and TensorFlow Java API 1.13.1, and Python 3.6
 - Train the model in Python first, then call the model using Scala (*DITA is built using Scala)

Result



- Our developed model nearly achieved the ground truth performance within p variations
- The 2-level recursive model has better performance than the single model
 - Slightly similar to DITA original structure, however more complex

Discussion and Future Works

- This is still preliminary work
- The input of the ML model (the first, last, and pivot points) may not quite represent the trajectory for machine learning
 - Trajectory representation using Vector [6] & Cluster [7]
 - However, implementation for in-memory approach still need to be discussed

[6] X.Li, K.Zhao, G. Cong, C.S. Jensen, W. Wei, "Deep Representation Learning for Trajectory Similarity Computation," ICDE 2018.


[7] D. Yao, C. Zhang, Z. Zhu, J. Huang, J. Bi, "Trajectory Clustering via Deep Representation Learning," in IJCNN 2017.

Conclusion

- We developed a learned index approach for an existing similarity trajectory search indexing (DITA) to minimize the exploration of irrelevant partitions/cluster
- We developed a probabilistic distance, applicable to learned index, to model the similarity between trajectories

Thank you for your attention

Trajectory Similarity Search Query



Distance (DTW)	T_1	T_2	T_3
T_1	0	0.4	10
T_2	0.4	0	9
T_3	10	9	0

- Task:
 - Given a query trajectory T_Q
 - With a distance threshold of τ
 - Return all trajectories in set \mathcal{T} whose distance $\leq \tau$
$$SimTS_{\tau}^{T_Q} = \{\langle T_s \rangle, T_s \in \mathcal{T}\}$$
- Example query:
 - Given T_1 as query to set $\{T_1, T_2, T_3\}$
 - Using threshold $\tau = 0.5$
 - Result: $\{T_1, T_2\}$
- Learned index: learn the similarity relationship between the trajectories

Build Dataset for Similarity Search Query

