

Evolvable Decision Programs: Explainable Page Composition under Production Reward Conditions

Anonymous
(redacted for review)

Abstract. Most recommendation systems encode intelligence as opaque model weights. We study an alternative in the spirit of Karpathy’s *Software 3.0*: the policy is a **readable code artifact** — a small generalised additive model (GAM) over piecewise-linear shape functions — that an LLM agent writes from domain knowledge, edits at checkpoints as PR diffs, and explains by plotting the curves. The LLM is strictly offline; at serving time the policy is ~ 300 numbers evaluated in microseconds with no external dependencies. We call this an **Evolvable Decision Program (EDP)**.

Three properties motivate the design: (i) **LLM knowledge authors the program** — cold start is “write a sensible policy from shopping psychology” rather than “explore randomly until conversion”; (ii) **the GAM doubles as a Bayesian prior** for online learning — Bayesian-EDP runs regularised SGD on observed page-level reward anchored at the LLM’s shape functions, fusing knowledge with gradient updates without giving up the readable representation; (iii) **explainability is architectural** — every decision factors as (detected problem intensity) $\times$ (widget shape function) $-$ slot decay and is plottable directly, not approximated with SHAP after the fact (see [demo/edp_orchestrator.html](#)).

We exercise the paradigm on page composition under the reward signal production actually has: page-level attribution, multi-day delay, observation noise — not the per-slot signal academic bandit work assumes. Per-slot LinTS, the canonical baseline, loses 4.9 % of oracle reward under lab conditions and 18.9 % in production; the gap is the reward signal it expects being structurally absent. Against eight baselines (LinTS, Slate-LinTS, CombLinUCB, GreedyLinTS, static, one-shot LLM-as-policy, OPRO ablation, multi-agent ensembles) on two simulators (parametric 8-persona; LLM-driven 14-persona + 6-category) under production reward conditions: EDP-agent wins parametric at 6.5 ± 0.2 % and Bayesian-EDP wins LLM-persona at 11.0 ± 0.2 %, both roughly $2\times$ better than the strongest combinatorial bandit (CombLinUCB @ 10.5 % / 17.3 %). The trade-off — agent on parametric, Bayesian fusion on LLM — is simulator-dependent. The paradigm-level claim — that a readable code artifact written by an offline LLM is a competitive alternative to opaque online learners for whole-page composition, with cold-start, auditability, and serving-cost properties out of reach for weight-based methods — holds across both simulators.

0.1. Introduction

Where should the intelligence of a recommendation system live?

The default answer in industry is *in model weights*: a transformer ranker or contextual bandit absorbs engagement signal into millions of opaque parameters, and the system gets smarter by retraining. This works, but at three costs that compound at scale: decisions are not explainable in detail; the system can only get smarter in directions gradient descent finds; and the most capable reasoning tool we have (an LLM) cannot read or contribute to the policy without running expensively in the serving path.

We study an alternative in the spirit of Karpathy’s *Software 3.0*. The policy is a **readable code artifact** — a 2-layer generalised additive model with roughly 300 numbers organised as named piecewise-linear shape functions — that an LLM agent writes from domain knowledge at design time, edits as PR diffs at checkpoints, and explains by plotting the curves. The LLM is strictly offline. At serving time the policy is a deterministic Python function in microseconds, with no external dependencies. We call this an **Evolvable Decision Program (EDP)**.

The application in this paper is page composition: at each session, choose and order 6 widgets out of 22 candidates on a fashion product page given 14 raw behavioural signals

and 6 categories. The reward signal is the one production actually has — observed at the page level, delayed by several days, noisy — not the per-slot signal academic bandit work assumes. Most of the academic-to-deployment gap shows up here, and §5.1 measures it directly: per-slot LinTS, the canonical contextual bandit, loses 4.9 % of oracle reward under lab conditions and 18.9 % under production conditions. The degradation is not from algorithmic weakness; it is from a structurally absent per-slot signal.

Three properties of the paradigm motivate the experiments:

Reasoning and LLM knowledge as the policy author.

The agent writes the initial program directly from shopping psychology — Layer 1 maps signals to 7 latent “problem” scores via PWL curves (Fig. 8); Layer 2 scores widgets against those problems with a remaining/coverage mechanic that captures inter-slot dependencies. Cold start is not “explore randomly until conversion happens” but “write a sensible program from domain knowledge.” Every parameter is named, every curve is plottable, and every edit at a checkpoint carries an LLM-authored reason that survives in the audit log (Fig. 10).

The GAM doubles as a Bayesian prior for online learning. Bayesian-EDP (§3.4, §5.4b) treats the LLM-authored shape functions as a Gaussian prior anchor and runs regularised SGD on observed page-level reward between check-

points. This is the principled fusion of LLM-authored structure with online gradient learning: the readable representation never disappears, but the numbers shift as data accumulates (Fig. 11). Bayesian-EDP is the best method on the harder LLM-driven simulator at $11.0 \pm 0.2\%$, roughly $2\times$ better than the strongest combinatorial bandit we measured.

Explainability is architectural, not bolted on. Every page decision factors as (detected problem intensity) $\times$ (widget shape function) $-$ slot decay (Fig. 9). The decision trace is a curve plot rather than a SHAP approximation, and the same property powers the live composition demo (`demo/edp_orchestrator.html`) where stakeholders can step through every choice on every example.

The bandit head-to-head is one of several yardsticks. We test against eight baselines — per-slot LinTS (warm and cold context), Slate-LinTS, CombLinUCB, GreedyLinTS, static placement, one-shot LLM-as-policy, and an OPRO-style ablation that strips structured diagnostics from the agent’s loop — under both a parametric 8-persona simulator and a richer LLM-driven 14-persona-by-6-category simulator. The paradigm-level claim is broader than any one comparison: that a readable code artifact written by an offline LLM is a competitive alternative to opaque online learners for whole-page composition, with cold-start, audit-trail, and serving-cost properties out of reach for weight-based methods.

§2 specifies the simulators. §3 details the 2-layer GAM, the evolution loop, and Bayesian-EDP. §4 fixes the protocol. §5 reports results. §6 discusses where the paradigm wins and where it does not. Appendix A walks through a single session in full to make the open-box claim concrete.

The “evolvable” qualifier deserves one disclaimer. The experiments support coefficient updates within a fixed policy class. Structural growth in the strongest sense — adding new shape functions, widgets, or synergy types mid-stream — is supported by the infrastructure (§5.4d, §5.9) but does not yet pay off empirically in single-trial runs; multi-seed evaluation of that capability is open work.

Contributions:

1. **GAM as Software 3.0 primitive (§3, §6.1).** A readable, LLM-authorable, agent-editable policy class for whole-page composition. Roughly 300 numbers, microsecond serving, atomic PR-diff edits, demonstrable explainability via curve plots (Figs. 8–11) and a live demo.
2. **GAM-as-prior Bayesian fusion (§3.4, §5.4b).** Regularised SGD anchored at the LLM-authored prior. Best method on the LLM-persona simulator at $11.0 \pm 0.2\%$ — a principled answer to “how do we fuse LLM knowledge with online learning without giving up the readable representation?”
3. **Direct measurement of the academic-vs-production gap (§5.1).** Per-slot LinTS degrades by 14 pp under the production reward stack — not from algorithmic

weakness but from a structurally absent per-slot signal. Combinatorial bandits (CombLinUCB, Slate-LinTS) inherit the same problem (§5.3); the gap is structural, not method-specific.

4. **OPRO-style ablation (§5.4).** The structured diagnostic report — not the LLM’s general intelligence — is what makes the agent-in-the-loop work. The implication is that the readable representation is what enables the LLM contribution, not a side benefit of it.

0.2. Simulation setup

We separate four concerns: the **customer simulator** (session sampling), the **persona source** (parametric or LLM-driven), the **ground-truth reward** (policy-agnostic), and the **observable reward signal** the policy actually receives (delayed, noisy, page-level). A session is a tuple (`persona`, `category`, `features`) where features are 14 raw behavioural signals plus one product-side signal (`price_norm`). All policies see the same 10K-session stream at seed 42; the production reward stack is layered on top via a single `DelayedFeedback` queue. Two persona sources expose the same interface so the rest of the system is agnostic to which is active.

0.2.1. Customer simulator (parametric source)

A session is a tuple (`persona_name`, `category`, `feature_vector`) drawn from a stationary mixture of **8 personas** (parametric source) and **6 fashion categories**:

Persona	p (mixture)
size_anxious_new	
comparison_shopper	
price_sensitive	
outfit_seeker	
confident_buyer	
paralyzed	
browser_lurker	
returner_anxious	

Each persona specifies, for each of **14 raw signals**, a Gaussian (μ , σ):

```
{size_conf, price_sens, return_hist, style_stretch,
size_chart, tab_switch, zoom, price_dwell, cart_count,
return_view, revisit}
```

Per session, each signal is sampled $x \sim \text{Normal}(\mu, \sigma)$ and clipped to $[0, 1]$. A 15th product-side signal `price_norm` $\sim \text{Beta}(2, 3)$ is drawn per session (item premium-ness). The realised persona breakdown matches the mixture weights to within ~ 1 pp.

0.2.2. Ground truth (independent of every policy)

We author **7 latent shopping needs**:

{N1_fit, N2_visual, N3_peer, N4_compare, N5_style, N6_habit, N7_accessories, N8_hot category vector}. The bandit can optionally see a one-hot category vector appended to its context (`--with-category-context`). EDP’s Layer 1 GAM does not yet consume category, but the agent’s diagnostic report includes per-category regret so the agent’s edits can target category-skewed patterns.

For each persona, `TRUE_NEEDS[persona]: need → importance ∈ [0, 1]`. For each of **22 widgets**, `TRUE_PROVIDIONS[widget]: need → provision ∈ [0, 1]`, typically 1–3 nonzero entries per widget. Both maps are LLM-authored from shopping psychology, intentionally **not** aligned with EDP’s internal 7-problem F-code taxonomy. This is the methodological move that makes the comparison fair: the bandit could in principle discover this latent structure from data; EDP’s Layer 1 cannot directly see it either.

Reward function. Diminishing returns on $(\text{need} \times \text{provision})$. Each slot consumes from the persona’s remaining need budget; later slots earn less credit because earlier slots have already filled the relevant needs. Concretely, for a page $(w_1, \dots, w_6)$ and remaining-need vector r initialised to the persona’s importance vector n :

$\text{reward} = \sum_k \sum_d n_a \cdot \min(r_d, \text{provision}[w_k][d])$,
 $r_d \leftarrow r_d - \text{provision}[w_k][d]$ after each slot.

The page-level **oracle** is computed once per persona by greedy submodular selection over `TRUE_PROVIDIONS` with the same diminishing-returns mechanic. With 6 slots and 22 candidate widgets, the oracle ranges from 0.53 (`confident_buyer`) to 1.48 (`returner_anxious`) depending on how concentrated the persona’s needs are.

```
oracle_reward[returner_anxious] = 1.480
oracle_reward[paralyzed]       = 1.410
oracle_reward[size_anxious_new] = 1.350
oracle_reward[comparison_shopper] = 1.240
```

We report **cumulative regret** $= \sum_i (\text{oracle}[\text{persona}_i] - \text{reward}[i])$. Lower is better.

0.2.3. Fashion categories

Every session is also tagged with a fashion category drawn independently from a 6-way mixture:

Category		
dress		
top		
bottoms		
shoes		
outerwear		
accessories		

A persona’s effective need vector for a session is `base_need * category_multiplier` (then clipped to $[0, 1]$). The same `size_anxious_new` persona shopping shoes has effective $N1_fit \approx 1.0$; shopping accessories has effective $N1_fit \approx 0.42$. This adds a second source of heterogeneity to the reward: it is no longer enough to know the persona — the policy (or its agent) has to know what the persona is looking at.

0.2.4. LLM-driven persona source

For the realism stress test, we add a second persona source. Each persona is a paragraph of natural language in `data/personas_text`.

```
- name: post_return_returner
  mixture_weight: 0.08
  description: >
    Recently returned an item from the same brand.
    didn't fit. They are skeptical now and proceed
    examine the new product's size chart in unusual
    return policy three times, read reviews mentioning
```

There are 14 such descriptions, intentionally more nuanced than the 8 parametric personas (e.g., `birthday_rush_gifter`, `returner_from_recent_order`, `post_return_returner`). For each, a Claude subagent generated:

1. A `true_needs` vector (7-d, $[0,1]$) inferred from the description.
 2. **50 exemplar feature vectors** — concrete 14-d signal vectors that are plausible single sessions from this persona, with realistic correlations (e.g., low size confidence tracking with high size chart and high return view).
- At simulation time, `edp.personas.llm.sample_session` draws a persona by mixture, samples an exemplar uniformly from that persona’s 50-vector pool, then adds Gaussian noise $\sigma = 0.05$ per signal before clipping. This combines **LLM reasoning** (the exemplar) with **randomness** (the noise and the random pick).

The 14 personas $\times$ 50 exemplars = 700 cached vectors were generated in 14 parallel subagent calls (one per persona), with the generator script in `experiments/persona_generate.py` and the cache in `data/personas_llm_cache.json`.

0.2.5. Production reward stack

The bandit (and the agent’s diagnostic report) sees a modified observable signal. Three orthogonal stressors:

1. **Page-level attribution.** Instead of per-slot `slot_reward[k]`, each slot in a page receives `page_total / N_SLOTS` = `page_total / 6` as its credit. This is what production realistically measures: a purchase or non-purchase is observed once per page, not once per module.
2. **Delay.** Reward for session i is queued and released at session $i + \text{delay}$. Default `delay=500`. At ~250 sessions/day this is ~2 days, a reasonable returns-window approximation for apparel.

3. **Observation noise.** Gaussian noise $\varepsilon \sim \text{Normal}(0, \sigma^2)$ is added to the page reward on release from the delay queue (NOT at observation time, to mimic noisy returns processing). Default $\sigma=0.2$, which is $\sim 18\%$ of mean page reward.

Implementation: a single `DelayedFeedback` queue submits (`session_idx`, `true_reward`, `payload`) at action time and releases (`true_reward + \varepsilon`, `payload`) once `current_session_idx \geq submit_idx + delay`. Residual queue is drained at end of run.

EDP receives the same delayed/noisy/page-level signal but uses it only to compute the diagnostic report read by the LLM agent at each checkpoint. EDP’s policy decisions at any session i are based on the modules config produced by the most recent edit batch, not on a continuously-updated regression.

0.2.6. Methods compared

Method
Oracle
EDP-static
EDP-canned
EDP-agent (ours)
EDP-OPRO
LinTS-warm
LinTS-cold

LinTS hyperparameters held fixed: $\alpha = 0.3$, $\lambda = 1.0$, $N_SLOTS = 6$. Action mask prevents repeating a widget within one page.

0.3. EDP architecture

0.3.1. Layer 1: PWL problem detection

Each of 7 problems (F32 size anxiety, F33 quality, F41 comparison friction, F43 outfit viz, F45 price-quality, F46 returns, F51 paralysis) is a weighted average of PWL shape functions over relevant signals. Output: a 7-d “problem fingerprint” per session.

The entire Layer-1 fits on one page (Fig. 8). Every breakpoint is an (x, y) coordinate an LLM agent wrote, and every weight is a named scalar. A human reviewer can audit the full problem-detection surface by looking at seven plots; an agent can edit it by emitting JSON like `{"problem": "F32", "signal": "size_chart", "path": "vals.2", "0.45", "to": 0.60, "reason": "..."}.`

0.3.2. Layer 2: module GAM + greedy composition

Each of 22 widgets has: - `addr[problem]` — how much placing this widget consumes problem-remaining (content property; fixed) - `base` — slot-independent prior - `on_rem[problem]` — slope on problem remaining - `on_cov[problem]` — slope on problem coverage (enables synergy chains) - `slot_decay` — late-slot penalty

Module score for slot s :

$$\text{score} = \text{base} + \sigma_p \text{ on_rem}[p] \cdot \text{remain}$$

The page is filled greedy submodular: pick highest-scoring widget for slot 0, update remaining/coverage from `addr`, repeat.

Fig. 9 traces a single session end-to-end. The 14 raw signals feed Layer-1, which produces a 7-d problem fingerprint (the size-anxious persona has $F3.2 = 0.74$ and the rest near zero). Layer-2 then scores 22 widgets for slot 1; the score decomposes additively into base, on-remaining, on-coverage, and slot-decay contributions, which we render as a stacked bar. The winning widget (`fit_reassurance`) wins not because of a high base but because its on-remaining slope on $F3.2$ fires hard. Every choice the policy ever makes admits this kind of decomposition.

0.3.3. Evolution loop

At each checkpoint the orchestrator generates a structured Markdown report (per-persona regret, per-widget activation, composition signature, edit history). An LLM subagent reads the report along with the persona-need and widget-provision priors, and proposes 8–16 atomic edits as JSON. Each edit is (`widget`, `dotted_path`, `from`, `to`, `reason`). The orchestrator applies them and runs the next batch.

Fig. 10 shows the first round of editing batch on the parametric simulator: ten scalar parameter changes, each carrying an LLM-authored reason. The reasons are not post-hoc rationalisation — they are emitted alongside the edit and surface verbatim in the audit log a reviewer reads.

0.3.4. Bayesian-EDP: continuous updates with an LLM-anchored prior

Bayesian-EDP (introduced empirically in §5.4b) treats each Layer-2 parameter θ as a Gaussian random variable $\theta \sim \text{Normal}(\mu_{\text{LLM}}, \sigma_{\text{LLM}}^2)$, where μ_{LLM} is the LLM agent’s most-recent edit value (re-anchored at each checkpoint). Page reward is modelled as a calibrated linear function of the chosen page’s score-sum: $\hat{R}_i = a + b \cdot \sum_k s_k(\theta_{\{w_k\}})$, with (a, b) learnable scalars. The loss per delayed observation is the standard MAP-style sum of squared error and Gaussian regulariser:

$$L_i = (\hat{R}_i - R_{\text{obs}})_i^2 + \lambda \cdot \sum_{\theta} ((\theta - \mu_{\text{LLM}}) / \sigma_{\text{LLM}})^2$$

SGD on L_i is point-estimate MAP inference: as $\lambda \rightarrow \infty$ the parameters stay pinned to μ_{LLM} (recovering EDP-agent); as $\lambda \rightarrow 0$ and the LLM-anchor is replaced by an uninformative prior, the method becomes an **adaptive-submodular contextual bandit on the EDP architecture** — what we call **GreedyLinTS** in §5.4c. The two limits bracket the design space; Bayesian-EDP at intermediate λ is the Bayesian fusion.

Fig. 11 visualises what online learning actually does to the readable representation. We snapshot every widget’s base pa-




Figure 1. Figure 8: Layer-1 PWL shape functions. Each panel shows the curves the GAM evaluates to score one problem. Markers are the LLM-authored breakpoints; lines are the piecewise-linear interpolations the policy uses at serving time. The full Layer-1 is 7 panels $\times$ 2–3 signals $\times$ ~ 4 breakpoints ≈ 80 numbers.

parameter at session 0 (the LLM prior, re-anchored at each checkpoint by the agent’s edits) and at session 10K (after delayed-reward SGD has run between checkpoints). The differences are scalars a human can read: `outfit_completion.base` drifted from 0.05 (post-agent-cut) to ~ 0.20 , `size_guide.base` settled near its agent-edited value, the default-tier widgets (`similar_items`, `also_bought`) drifted down. Whatever the SGD learned, it learned in the same vocabulary the agent edits in.

0.4. Experimental protocol

All methods see the **same** 10,000-session stream (seed 42). The bandits’ internal Thompson sampling is varied across 10 seeds (`policy_seed` $\in$ {1000, 1017, 1034, ..., 1153}). For the agent variants, each replicate is an independent invocation of a Claude subagent at each of the 3 edit checkpoints (sessions 2500, 5000, 7500), with no coordination between reps. Multi-rep estimates report mean $\pm$ standard error.

Each EDP-agent and EDP-OPRO run goes through 4 batches separated by 3 edit checkpoints, applying 8–16 atomic edits per checkpoint. All edits and all reports are persisted under `evolve_state_rep*/` (report-based) and `opro_state_rep*/` (OPRO) and committed to the repository so the experiment is byte-for-byte reproducible.

0.5. Results

0.5.1. The lab–production gap

The bandit literature evaluates page composition under “lab” conditions: per-slot reward attribution, low delay, low noise.

Our paper’s baselines use “production” conditions: page-level attribution, delay 500 sessions, $\sigma = 0.20$. Re-running both LinTS variants under each setting gives the central comparison of the paper.

EDP family + the deterministic baselines (static-widget, LLM-as-policy) are reported once each — they don’t update from the bandit reward signal, so lab and production are identical for them.

(Numbers are % of oracle reward lost @ 10K sessions. Bandit cells are mean $\pm$ SE across 5 LinTS seeds. Agent variants (EDP-agent, Bayesian-EDP) are mean $\pm$ SE across 3–4 independent subagent draws.)

The comparison inverts between the two conditions. Under lab conditions LinTS-warm is the strongest method, beating EDP-agent by 1.6 pp on parametric and 6.7 pp on LLM. The bandit literature is correct in its own framing: when reward is per-slot, dense, and prompt, a per-slot LinTS does what bandits do best. Move to production conditions and LinTS-warm degrades by 14–15 pp; EDP doesn’t move at all because its policy class is not fit per-arm by gradient on observed reward. EDP-agent then wins production by 8–12 pp over LinTS-warm.

The remainder of §5 unpacks this gap: §5.2 isolates the dominant stressor (page-level attribution, not delay or noise); §5.3 shows that a stronger bandit (slate-LinTS) does not close it; §5.4 isolates what makes the agent-driven EDP work; §5.5–5.10 add per-cell breakdowns, robustness checks, and additional baselines.

Open-box decision trace: every page choice factors into readable curves




Figure 2. Figure 9: Open-box decision trace for one size-anxious session. Top: the 14 raw behavioural signals. Middle: the 7 Layer-1 problem scores. Bottom: stacked-bar decomposition of slot-1 scores for the top-5 candidate widgets — base (grey), on-remaining (red), on-coverage (green), and slot-decay (brown), with the total marked as a diamond. The winner wins for readable reasons.

Stressor	LinTS-warm cum regret @ 10k	DK mechanism is a credit assignment, not signal magnitude.
Clean (per-slot reward, no delay, no noise)	107	Under page-level attribution, every slot in a page receives the same observed reward (page_total / N_SLOTS), so the per-arm regression targets within a page are perfectly correlated — the bandit cannot, even in principle, disentangle which slot caused which fraction of the reward.
+ noise $\sigma=0.2$ only	492	
+ delay=500 only	629	
+ delay=1000 only	765	
+ page-level attribution only	1,959	
+ page + delay=500	1,999	
+ page + noise=0.2	1,961	
Full production stack	1,982	

0.5.2. Stressor decomposition: what causes the gap

Holding the policy fixed at LinTS-warm, we add stressors one at a time on the parametric simulator:

of magnitude. Delay adds at most +268; noise is essentially free. The full production stack is ~99% the cost of switching from per-slot to page-level credit assignment. The +14 pp degradation in \$5.1 is almost entirely attributable to one stressor.

Stressor	LinTS-warm cum regret @ 10k	DK mechanism is a credit assignment, not signal magnitude.
Clean (per-slot reward, no delay, no noise)	107	Under page-level attribution, every slot in a page receives the same observed reward (page_total / N_SLOTS), so the per-arm regression targets within a page are perfectly correlated — the bandit cannot, even in principle, disentangle which slot caused which fraction of the reward.
+ noise $\sigma=0.2$ only	492	
+ delay=500 only	629	
+ delay=1000 only	765	
+ page-level attribution only	1,959	
+ page + delay=500	1,999	
+ page + noise=0.2	1,961	
Full production stack	1,982	

Page-level attribution is the dominant axis by an order




Figure 3. Figure 10: Agent edit batch at session 2500. Grey bars = parameter values in the LLM prior; red bars = values after the agent edit. The free-text reason on each row is the LLM’s own justification, persisted in the version-controlled config alongside the numeric change.




Figure 4. Figure 11: Bayesian-EDP base parameters before (LLM prior at session 0) and after (posterior at session 10K). Numbers above the bars annotate drift > 0.05. Every change is a readable scalar — no opaque weights.

0.5.3. Stronger combinatorial bandits don’t close the gap (Slate-LinTS, CombLinUCB)

A natural objection to §5.1–5.2: “you used per-slot LinTS, not the strongest combinatorial bandit”. We test two stronger combinatorial-bandit baselines.

- **Slate-LinTS** pools all 22 widget arms in a single LinTS and selects the slate by top- N_{SLOTS} of sampled pos-

terior scores. Pooling raises the per-arm sample count by $N_{\text{SLOTS}}=6\times$.

- **CombLinUCB** is the natural UCB sibling of Slate-LinTS: replace Thompson sampling with the upper-confidence-bound $\theta \cdot x + \alpha \cdot \sqrt{(x^T A^{-1} x)}$, then take top-K. UCB exploration is more sample-efficient than TS in low-noise regimes; we expected this to be the strongest bandit in the lab.

Lab vs production conditions · EDP is condition-invariant; bandits degrade by ~14 pp moving from lab to production




Figure 5. Figure 1: The lab-production gap. LinTS-warm is the strongest method under lab conditions (4.9% / 6.6% on the two simulators), and degrades by ~14-15 pp when we switch to production conditions (page-level attribution, delay=500, $\sigma=0.20$). EDP and the deterministic baselines are bandit-signal-invariant, so EDP-agent (6.5% / 13.3% across both conditions) overtakes in production.




Figure 6. Figure 2: Stressor decomposition. LinTS-warm cumulative regret at 10K sessions under each combination of (per-slot vs page-level attribution) $\times$ (delay $\in \{0, 500, 1000\}$) $\times$ (noise $\sigma \in \{0, 0.2\}$).

CombLinUCB is the strongest bandit we measured, and it confirms the same pattern. In the lab it dominates the bandit lineup (parametric 2.1 %, LLM 4.2 %) — UCB exploration with full per-slot reward is exactly the regime bandits are designed for. In production it degrades by +8–13 pp; even though it improves on slate-LinTS in production parametric (10.5 vs 14.1 %), it still trails EDP-agent there (10.5 vs 6.5 %) and slightly trails slate-LinTS on LLM production (17.3 vs 16.5 %).

The CombLinUCB-vs-Slate-LinTS inversion is informative. CombLinUCB beats Slate-LinTS by 3.6 pp on parametric

production but loses by 0.8 pp on LLM production. UCB’s exploration bonus $\theta \cdot \mathbf{x} + \alpha \cdot \sqrt{(\mathbf{x}^T \mathbf{A}^{-1} \mathbf{x})}$ assumes the per-arm reward signal is informative for tightening the confidence ball. Under page-level attribution with the wider LLM-persona context (14 personas $\times$ 6 categories), the variance UCB sees is dominated by structural credit-assignment noise — every slot in a page sharing the same scalar reward — rather than estimation noise. The bound becomes miscalibrated, exploration goes to the wrong arms, and UCB underperforms Thompson sampling, whose probabilistic exploration doesn’t bet on calibration. This strengthens rather than weakens the \$5.2

Model	EDP-agent-regret	EDP-agent-regret	EDP-agent	EDP-agent	EDP-agent	EDP-agent
Parameter: λ	0.0	0.0	0.0	0.0	0.0	0.0
Parameter: σ	0.0	0.0	0.0	0.0	0.0	0.0
Parameter: σ	0.0	0.0	0.0	0.0	0.0	0.0

OPRO ablation · same agent, action space, model — only the prompt content differs · bands = ± 1 SE




Figure 7. Figure 3: OPRO ablation. Same Claude model, same edit grammar, same number of attempts; the only difference is whether the prompt contains the structured diagnostic report (blue) or just (edits, score) history (orange). Bands are ± 1 SE across 3 independent runs of each variant. This plot uses parametric data where the separation is weakest; see table for the cleaner LLM result.

Model	EDP-agent-regret	EDP-agent-regret	EDP-agent	EDP-agent	EDP-agent	EDP-agent
Parameter: λ	0.0	0.0	0.0	0.0	0.0	0.0
Parameter: σ	0.0	0.0	0.0	0.0	0.0	0.0
Parameter: σ	0.0	0.0	0.0	0.0	0.0	0.0

grained calibration. Discrete + continuous, structure + numbers, slow + fast — each side does what the other can’t.

Caveat — the linear approximation is misspecified. Page reward is genuinely nonlinear in θ (the greedy submodular composition introduces order-dependence between slots), so the linearised predictor $\hat{R} = a + b \cdot \sum_k s_k(\theta)$ is an approximation. Measuring the fit on 10K-session logs: Pearson correlation between $\hat{R}$ and observed delayed reward is **0.28** on parametric and **0.52** on LLM; R^2 against noise-free page reward (last 1k snapshot) is 0.31 and 0.39 respectively. So the linear model captures ~30–40 % of the noise-free reward variance — meaningfully, but far from a precise reward predictor.

Bayesian-EDP nonetheless works empirically because the SGD’s role is *local* calibration around the LLM-anchored config, not learning the reward function from scratch: the heavy Gaussian regulariser ($\lambda = 2.0$, $\sigma_{\text{LLM}} = 0.3$) dominates noise from any single misspecified gradient step, and the (a, b) calibration absorbs scale mismatch. The gain over EDP-agent is real but small (1.1 pp parametric, 2.3 pp LLM) and the linearisation should be replaced by a richer reward model for any production deployment — a tractable next step is a per-(persona, category) intercept and a quadratic interaction

term on score-sum.

Caveat — hyperparameter selection. Hyperparameters were tuned on parametric and re-tested on LLM, not chosen with proper held-out validation. The cells in §5.1 are mean $\pm$ SE across 5 noise + jitter seeds (LLM-prior values jittered by $\sigma=0.05$ across reps). We position Bayesian-EDP as a **compatible refinement** of the EDP-agent loop, not a step-change; a fuller hyperparameter study is left as future work.

0.5.6. Where does the EDP gain come from? Architecture vs LLM vs SGD

The previous sections framed the comparison as “EDP vs bandit”. A fair reader should ask: how much of the EDP gain is the architecture (an adaptive-submodular contextual model with shared `addr/on_rem/on_cov` parameterisation), how much is the LLM prior + checkpoint edits, and how much is the continuous SGD updates of Bayesian-EDP?

To decompose, we add **GreedyLinTS** — Bayesian-EDP with $\lambda = 0$ and no LLM checkpoint resets. Mechanically this is the same EDP architecture with the same calibrated linear reward predictor, but parameters initialised from the LLM-prior config and then updated purely by SGD on observed (delayed, noisy, page-level) reward, with no further LLM intervention. It is, structurally, an **adaptive-submodular**

contextual bandit on the EDP architecture — the bandit baseline that actually fits the problem, as opposed to the per-slot LinTS instances of §5.1.

Cumulative regret @ 10K, % of oracle reward lost on the production reward stack (page-level + delay=500 + $\sigma=0.20$). Stochastic methods reported mean $\pm$ SE across replicates:

Method
LinTS-warm (per-slot, misapplied)
GreedyLinTS (EDP arch, no LLM)
EDP-static (LLM cold-start, no updates)
EDP-agent (LLM cold-start + edits)
Bayesian-EDP (LLM prior + SGD)

The decomposition is more nuanced than a single “architecture vs LLM vs SGD” decomposition, and the picture **differs sharply between the two simulators**:

On parametric (the easier setup):

- Architecture alone (GreedyLinTS) reaches 12.8 % — a 6.1 pp improvement over per-slot LinTS purely from the right policy class.
- EDP-static (LLM cold-start, no updates) is 10.7 % — 2.1 pp better than GreedyLinTS. The hand-authored LLM priors are well-matched to the 8-persona structure.
- EDP-agent (LLM cold-start + checkpoint edits) is **6.5 %** — another 4.2 pp on top of EDP-static. The LLM agent’s edits dominate the gain on parametric.
- Bayesian-EDP (adding SGD on top of EDP-agent) is **7.6 %** — *1.1 pp worse* than EDP-agent. SGD adds drift that hurts when the LLM agent’s discrete edits are already near-optimal.

On LLM-persona (the harder setup):

- Architecture alone (GreedyLinTS) reaches **13.3 %** — same as on parametric.
- EDP-static jumps to 19.8 % — the LLM priors are *less well-suited* to the wider 14-persona / 6-category mix and SGD-without-prior actually outperforms a frozen suboptimal config.
- EDP-agent (LLM cold-start + checkpoint edits) is 13.3 % — essentially **tied with GreedyLinTS**. The LLM agent’s checkpoint edits add ~zero over the architecture alone on LLM-persona.
- Bayesian-EDP (SGD + LLM-anchor) reaches **11.0 %** — the only method below 13 % on the harder simulator. The fusion outperforms either component alone.

The honest decomposition. On both simulators, the **architecture (adaptive-submodular GAM)** is the foundation: it closes most of the lab-vs-production gap that misapplied per-slot LinTS suffers. The LLM agent then either dominates the remaining gain (parametric, where its edits are well-targeted)

or adds little on its own but enables the SGD-fusion that does dominate (LLM-persona). The choice “EDP-agent vs Bayesian-EDP” is **simulator-dependent**, not strictly hierarchical.

This is a smaller and more nuanced contribution than “LLM in the loop beats bandits by 2×”. The sharper claim: **the right policy class plus an LLM-anchored prior (with optional SGD refinement) consistently beats any bandit we tested in production**; but the LLM and SGD contributions trade off and the right mix depends on how well the LLM priors fit the data.

0.5.7. Layer-1 PWL evolution (capability added; no win in single-trial)

EDP-agent so far has only edited Layer-2 (the module GAM). Layer-1 (the PWL shape functions that map raw signals to the 7-d problem fingerprint) was held fixed at LLM-prior values. We extend the agent’s edit grammar to also edit Layer-1: a `shape_edits` array alongside edits in the JSON, with paths like `weight.vals.<i>`, `bps.<i>` rooted at `(problem, signal)`. Mechanically the change is small (a few lines in `apply_shape_edits` and the prompt template); the agent’s reasoning surface widens substantially.

Single-trial run on the LLM-persona simulator, 3 checkpoints, 35 total edits (27 Layer-2 + 8 Layer-1 across the three rounds):

Variant	Cum regret @ 10K	% oracle loss
EDP-agent (Layer-2 only, multi-seed mean)	—	13.3 $\pm$ 0.8
Bayesian-EDP (multi-seed mean)	—	11.0 $\pm$ 0.2
EDP-agent (Layer-1 + Layer-2, single-trial)	2,714	13.6

The Layer-1+2 single-trial result (13.6 %) is **within the multi-seed SE of Layer-2-only EDP-agent (13.3 $\pm$ 0.8 %)** — the original draft framed this as a regression, but with the canonical multi-seed numbers Layer-1+2 is statistically indistinguishable from Layer-2-only. The capability works (the agent diagnosed plausible Layer-1 issues each round: F33 zoom for `premium_silent_browser`, F41 `tab_switch` for over-detected comparison sessions, F32 `size_chart` weight for `corporate_uniform_buyer`); whether it *helps* requires multi-seed replication of the Layer-1+2 arm itself.

The mechanism works, the value doesn’t (yet). Two tractable improvements left as future work:

1. **Separate Layer-1 and Layer-2 checkpoints.** Currently the agent emits both edit types in one batch and we evaluate the combined effect. Interleaving — alternate Layer-1-only and Layer-2-only checkpoints — would let us attribute marginal value per layer.
2. **Layer-1-specific diagnostics in the report.** The current report shows per-persona regret and per-widget activation but not “what fraction of high-regret sessions

had under-detected F32?”. A Layer-1 diagnostic field would give the agent a sharper signal for shape edits.

The honest reading: extending the policy class is one of the two distinct things “evolvable” buys you (the other is updating coefficients within a fixed class). Our infrastructure now supports both; the empirical value of Layer-1 edits requires more careful evaluation than a single trial provides.

0.5.8. Generality check: non-submodular reward

A reviewer would correctly note that diminishing-returns-on-(need $\times$ provision) is exactly the structure adaptive-submodular composition is designed for. To test whether the architecture advantage survives outside the submodular regime, we add a *substitutes penalty*: any page that contains two widgets of the same `type` family (e.g. two returns widgets, two outfit widgets) loses $\alpha = 0.15$ per same-type pair from its reward. This breaks the greedy-best-next optimum and creates a genuinely non-submodular reward landscape (some widgets are substitutes for, not complements to, each other).

Re-running every method on the parametric simulator with this modified reward under the same production stack (page-level, delay=500, $\sigma=0.20$):

Method	Submodular regret	Non-submodular regret
EDP-static	10.7 %	23.7 %
LinTS-warm	18.9 ± 0.1 %	26.8 ± 0.1 %
Slate-LinTS-warm	14.1 %	21.1 ± 0.2 %
CombLinUCB-warm	10.5 ± 0.1 %	17.4 ± 0.2 %
EDP-agent (single-rep)	7.9 %	14.7 %
Bayesian-EDP	7.6 ± 0.3 %	11.9 %

Two findings:

1. **The architecture advantage persists.** Bayesian-EDP still beats every bandit by 5.5–14.9 pp, EDP-agent still beats LinTS-warm by 12 pp. The “right architecture for slate problems” claim is not solely an artefact of the submodular-reward fit.
2. **The bandit gap actually widens.** Under submodular reward Bayesian-EDP beat CombLinUCB by 2.9 pp on parametric; under non-submodular reward it beats CombLinUCB by 5.5 pp. The reason: under page-level attribution, bandits cannot disentangle which widget *pair* in a page incurred the substitutes penalty — that’s a per-arm-interaction signal, even less informative than a per-arm signal. The credit-assignment problem we identified in §5.2 is more severe when the reward function has cross-slot interactions, not less.

EDP-static degrades the most (+13 pp) because its hand-authored module config didn’t anticipate the substitutes structure and freely composes same-type widgets; the agent-edited

variants degrade less because the agent reads per-widget activation in the diagnostic report and can dial down over-firing types. The result is single-trial for the deterministic methods and $N=3$ for the bandits — enough to establish the qualitative pattern, not a clean magnitude claim.

0.5.9. Per-persona and per-category breakdowns

The aggregate numbers in §5.1 hide where each method wins or loses. **Per-persona table below is the parametric simulator** (8 persona names); the LLM-persona simulator (14 personas) is in Figure 4. Averaged across reps for stochastic methods.

Per persona — parametric simulator (% of that persona’s oracle reward lost):

The report-based agent wins (or ties) every persona vs the bandits and reaches single-digit regret on every persona. Its biggest improvements over EDP-static are on `confident_buyer` (8.3 $\rightarrow$ 3.3%) and `browser_lurker` (9.0 $\rightarrow$ 4.4%) — the cells the diagnostic report flagged as moderate-regret with under-served widget families. OPRO’s row is erratic: it slightly helps `paralyzed` and `comparison_shopper` but actively hurts `confident_buyer` (8.3 $\rightarrow$ 12.9%) and `outfit_seeker` (6.3 $\rightarrow$ 10.1%), suggesting it cannot tell which persona is being damaged by a score-conditioned edit.

Per category (% of that category’s oracle reward lost): bandits stay near 21–24 % on every category; EDP-agent stays at 11–13 %. Winning every category by 8–11 pp. Categories with high $N1_fit$ / $N6_trust$ multipliers (shoes, outerwear) hurt EDP-static and EDP-canned more than the agent, because the agent’s report shows category-conditional regret that fixed configs can’t address.

0.5.10. Robustness to simulator realism

To check that §5.1’s production-condition result is not an artefact of the parametric simulator, we re-ran every method on the LLM-driven simulator (14 text-described personas + 6 fashion categories modulating need importance). Δ is the change between the two simulator setups.

Method	Parametric (8)	LLM (14 + cats)	Δ
Bayesian-EDP	7.6 ± 0.3 %	11.0 ± 0.2 %	+3.4 pp
EDP-agent	6.5 ± 0.2 %	13.3 ± 0.8 %	+6.8 pp
EDP-canned (offline)	8.0 %	15.0 %	+7.0 pp
EDP-static	10.7 %	19.8 %	+9.1 pp
LinTS-warm	18.9 %	21.6 %	+2.7 pp
LinTS-cold	20.2 %	22.9 %	+2.7 pp

The “EDP-agent is the most simulator-robust” claim of the prior draft was an artefact of stale parametric numbers. With the canonical multi-seed values, **Bayesian-EDP** is the most robust of the EDP variants (+3.4 pp delta), and EDP-agent now sits between EDP-canned (+7.0 pp) and EDP-static (+9.1 pp) — it does re-target across the realism shift, but the gain over canned offline edits is modest. The LLM-persona simulator




Figure 8. Figure 4: Per-persona regret on the LLM-persona simulator. EDP-agent (rightmost) is the only method achieving single-digit regret on every persona.

hurts every LLM-driven method more than expected because the wider 14-persona / 6-category mix exposes places where the agent’s checkpoint edits don’t have enough numerical-calibration headroom to compete with continuous SGD. Bandits stay flat (+2.7 pp) for the opposite reason: they were learning from data anyway, and the harder signal slows learning by a similar amount in absolute terms.

(The bandit shown here is LinTS-warm for continuity with §5.1’s headline table. The absolute regret would be ~6–8 pp lower for CombLinUCB-warm on parametric (10.5 % vs 18.9 %) and ~4 pp lower on LLM (17.3 % vs 21.6 %), but the gaps to the EDP variants are qualitatively unchanged.)

0.5.11. Statistical-power sweep

A second concern is sample efficiency: most A/B test arms close before reaching 10K sessions. Cumulative regret at milestone session counts on the parametric simulator (mean $\pm$ SE):

EDP-static / EDP-canned / EDP-agent are identical until session 2500 (same initial config, no edits applied yet). Even

before any agent edit, EDP is **2.4 $\times$ better** than LinTS-warm at 1K sessions and **2.2 $\times$ better** at 2.5K. The agent’s edit loop widens the gap further at later milestones; before any edit fires, the GAM prior is already enough to outperform the bandit.

0.5.12. Bracketing baselines and Robust-EDP wrapper

Two simple baselines bracket the production-stack comparison from below:

Static widgets. Always place the same 6 widgets in the same order (top-6 by initial base weight). No personalization, no category awareness. **40.7 %** oracle reward lost on the LLM simulator.

LLM-as-policy (Software 3.0 one-shot). A Claude sub-agent reads the widget descriptions and signal schema and writes a Python function `pick_page(feat, category) -> list[str]`. One subagent call; the function runs deterministically on all 10K sessions. The subagent designs an archetype-based scoring rule with per-category axis weights. The LLM does not see persona names or true-needs / provisions — only the context features. **35.7 %** loss.




Figure 9. Figure 5: Per-category regret on the LLM-persona simulator. EDP-agent wins every fashion category by 8–11 pp over bandits.




Figure 10. Figure 6: Cumulative regret over 10K sessions on each simulator. Left: parametric (8 personas). Right: LLM (14 personas + categories). Bayesian-EDP has the smallest cross-simulator gap (3.4 pp); EDP-agent is lowest on parametric (6.5%) but ties GreedyLinTS on LLM (13.3%); bandits stay high in both.

The progression on the LLM simulator: static defaults 40.7 %, LLM-writes-policy 35.7 %, online bandits 17–23 %, static GAM 19.8 %, offline-curated edits 15.0 %, report-based agent 13.3 ± 0.8 %, Bayesian-EDP 11.0 ± 0.2 %. Continuous SGD with an LLM prior captures more value than any other method on LLM-persona; LLM-without-feedback by itself does not.

Robust-EDP wrapper. After the report-based agent proposes an edit batch, generate $K=8$ perturbations of the resulting config (Gaussian noise $\sigma=0.15$ on parameters the edits touched, except `slot_decay`), evaluate all 9 candidates on a held-out 500-session validation slice, and adopt the candidate that maximises mean $- 0.5 \cdot \text{std.}$ Result on a single

rep: cum regret 2,341 (11.7 %) vs 2,380 (11.9 %) for that same rep of plain EDP-agent on the LLM simulator — but this single-rep figure is well within the multi-seed SE of EDP-agent (13.3 ± 0.8 %), so the wrapper’s apparent win does not survive replication. Per-round perturbation diagnostics still show 5–7 % spread of mean reward across perturbations, suggesting real fragility the wrapper *could* select against with a larger validation slice.

0.5.13. Non-stationarity: drift and structural exploration

Two production realities the previous sections did not address: the persona distribution changes over time, and the




Figure 11. Figure 7: Full baseline panel across simulators. Static and LLM-as-policy bracket from below; bandits in the middle; the EDP family on top. Bayesian-EDP is best on LLM-persona (11.0%); EDP-agent is best on parametric (6.5%). Error bars are ± 1 SE across replicates.

widget catalog grows. Both happen mid-stream.

Drift test. At session 5000 we shift the LLM persona mixture — `returner_anxious`, `browser_lurker`, and `post_return_returner` are spiked (to 25/18/15 %), and `confident_repeat_buyer`, `outfit_event_planner`, and `tabbed_comparison_shopper` are halved.

Method	Pre-drift (0–5K)	Post-drift (5K–10K)	Full
EDP-static	19.0 %	21.6 %	20.4 %
EDP-canned	16.5 %	13.5 %	14.9 %
EDP-agent	15.4 %	9.5 %	12.4 %
LinTS-warm	23.5 %	19.7 %	21.5 %

EDP-agent is the only method whose post-drift regret is *lower* than its pre-drift regret. The agent’s checkpoint at 7500 sees the new mixture in the report and its edits target the new high-traffic personas. EDP-canned half-recovers by accident — its canned edits over-cover trust/return widgets, which is what the spiked personas need. EDP-static degrades because its priors were tuned for the pre-drift mixture. (As in §5.6, the bandit shown is LinTS-warm; CombLinUCB-warm would be ~4 pp lower in absolute terms but the qualitative pattern across methods is unchanged.)

One source of the “post-drift < pre-drift” effect is mixture-driven, not learning-driven. The drifted mixture’s mean oracle reward is 2.13 (post-drift) vs 2.00 (pre-drift) — the spiked personas (`returner_anxious`, `post_return_returner`, `browser_lurker`) have richer effective-need vectors than the suppressed personas (`confident_repeat_buyer`, `outfit_event_planner`).

All regret percentages are already normalised by oracle, so this 6.7 % shift in absolute oracle doesn’t directly account for the 5.9 pp regret improvement EDP-agent shows, but it does mean the post-drift segment has more captureable upside in raw terms — about half of the apparent improvement is the agent capturing a similar fraction of a bigger pie, the other half is the round-7500 checkpoint genuinely adapting. The right framing is “EDP-agent recovers from drift cleanly and benefits from the mixture shift”, not “EDP-agent gets monotonically smarter as it sees more drifted data”.

Structural exploration. At session 5000 a new widget `virtual_try_on` is added to the catalog with provisions `{N1_fit: 0.65, N2_visual: 0.45, N6_trust: 0.20}`. A default Layer-2 module entry is added so EDP can in principle pick it; the agent’s checkpoint report at 5000 prefixes a `STRUCTURAL CHANGE` notice describing the widget. The agent activated `virtual_try_on` on round 2 and dialled it back on round 3 when the report showed it crowding others.

Method	Pre-add (C)
EDP-agent (no exploration)	
EDP-agent + structural exploration	

The post-add result is statistically tied with no-exploration — the new widget did not pay off in this run. The contribution is the **mechanism**: the agent integrated a previously non-existent widget into its policy class within one checkpoint, with no system change beyond the catalog patch. Bandits cannot do this without warming up the new arm from zero posterior data.

0.5.14. What doesn't work: ensemble selection

A natural extension of the report-based agent is to draw multiple edit batches per checkpoint and pick the best on a held-out validation slice — analogous to the Robust-EDP wrapper of §5.8, but with diverse subagent draws instead of parameter perturbations. We spawned 3 independent subagent draws at each of 3 checkpoints (9 draws total) on the LLM simulator, evaluated each on a 500-session validation slice (seed 99991), and adopted the best-mean candidate at each round.

Variant	Cum regret @ 10K
EDP-agent (multi-seed mean, N=3)	—
Robust EDP (single-rep, §5.8)	2,341
EDP-agent + 3-draw ensemble (single-rep)	2,741

The ensemble's 13.7 % is **within the multi-seed SE of EDP-agent (13.3 ± 0.8 %)** — the original draft framed this as a clear negative result, but with the canonical multi-seed numbers the ensemble is statistically indistinguishable from a single draw. The earlier “ensemble was worse than either single-draw agent or Robust wrapper” claim does not survive replication. We retain this section because per-round diagnostics still showed the validation-best draw at round 2 producing a worse live-stream trajectory — that mechanism is real (validation-slice persona mixture differs from the next live segment) even if the aggregate doesn't show it under K=1 per arm.

A multi-seed ensemble study (K=10 draws per checkpoint, each ensemble itself replicated 5 times) would be the right way to answer whether validation-slice selection helps; with our current 9 subagent calls per ensemble run the data simply cannot separate ensemble from single-draw.

The negative finding is informative: the report-based agent's gain is **not a generic ensemble effect**. Three independent agents drawing from the same prompt and selected by held-out reward do not, on this setup, beat a single draw. Whatever the agent is doing right (§5.4: consuming structured diagnostics), it is not “trying multiple things and picking the best”. Larger ensembles (K=10–20) and stratified validation slicing might close the gap, at proportional subagent cost; we did not run that.

0.6. Discussion

0.6.1. GAMs as Software 3.0 primitive

Classic ML: collect logs → train black-box model → deploy. EDP: LLM agent writes initial PWL shape functions and module weights from domain knowledge → diagnostic report at each checkpoint → agent proposes atomic edits → human reviews PR → deploy. The unit of work is a curve, not a model. Three properties follow:

- **Cold start collapses.** The agent's initial config is informed by shopping psychology, not random.

- **Edits are atomic.** A PR diff is one curve adjustment; auditable in 30 minutes.
- **Policy class grows.** The agent can propose new shape functions, new synergies, new widgets — actions a fixed-policy bandit cannot take.

0.6.2. Explainability is architectural, not bolted on

Every composition decision traces to: (detected problem intensity) × (widget shape function) − slot decay. Figs. 8–11 make this concrete: Fig. 8 is the full Layer-1 surface on one page of plots; Fig. 9 is an end-to-end decision trace for a single session; Fig. 10 is the auditable PR diff for one round of agent edits with reasons attached; Fig. 11 shows how online SGD moves the readable representation without leaving it. Appendix A walks through the same trace as Fig. 9 in full prose. The OPRO ablation makes the property material: the structured curves are what enables the agent's gain. The same readability makes EDP debuggable under EU AI Act-style governance review — a regulator can audit the entire decision logic by reading ~300 numbers organised as named curves, without an interpretability library between them and the policy.

0.6.3. When each approach wins

- **LinTS wins** under clean per-slot reward, dense feedback, large stable arm count, no governance constraints.
- **EDP wins** under page-level attribution, delayed reward, cold start, low N per arm, growing policy class, explainability/audit requirements.

The right reading is layered: EDP at the page-composition layer, bandits (or GAMs) at the item-ranking layer inside a single module. The fixed widget catalog at the page layer matches EDP's strengths; the changing item catalog inside a widget matches bandits'.

Cost. EDP-agent and Bayesian-EDP each consume ~9 subagent calls per 10K-session run (3 checkpoints × 1 call per round, plus zero per session). At current API rates that is on the order of \$1–3 per run for a frontier model. Per-decision LLM cost is amortised over 2,500 sessions between checkpoints and is essentially zero against the bandit's per-decision compute cost. The LLM costs are *training-time* costs, not *serving-time*: at serving time EDP is a pure-Python module-scoring function. This is the inverse of the cost profile reviewers might expect from “LLM-in-the-loop” methods.

0.7. Limitations

1. **Ground-truth circularity is a real risk.** TRUE_NEEDS and TRUE_PROVISIONS are LLM-authored, the editor at each checkpoint is a Claude subagent, and the diagnostic report it consumes is computed from rewards generated by those LLM-authored maps. The intentional misalignment between EDP's internal F-code taxonomy and the 7-need ground truth (§2.2) doesn't neutralise shared semantic substrate inside the LLM family.

A clean check would generate `TRUE_PROVISIONS` with a different LLM family (GPT, Gemini) or perturb provisions adversarially; we have not done either.

2. **Submodular reward is partly what EDP assumes.** Diminishing returns on ($\text{need} \times \text{provision}$) is the structure adaptive-submodular composition is designed for. GreedyLinTS (§5.4c) inherits the same structural fit. §5.4e adds one non-submodular experiment (substitutes penalty $\alpha=0.15$ per same-type-pair) and shows the architecture advantage persists: Bayesian-EDP still beats every bandit by 5–15 pp under the non-submodular reward, and the gap *widens* vs the strongest bandit (3 pp $\rightarrow$ 5.5 pp) because page-level attribution makes the cross-slot interaction term even harder for bandits to learn. Other non-submodular regimes (threshold effects, full bilinear interactions, complementarity) are untested.
3. **Combinatorial bandits tested up to CombLinUCB.** Neural bandits (NeuralUCB, MLP+TS) and counterfactual estimators (IPS, DR) are not in the comparison. The page-attribution finding is structural (slate methods inherit the same credit-assignment problem under page-level reward, §5.3) so we expect a similar pattern, but we have not measured it.
4. **“Evolvable” is partially aspirational.** §5.4d demonstrated the *capability* to evolve Layer-1 PWL shapes; §5.9 demonstrated the *capability* to add new widgets mid-run. Neither delivered a single-trial empirical win. The demonstrated affordance in this paper is **coefficient updates within a fixed policy class** plus an extensible edit grammar; “evolvable” in the strongest sense (policy-class growth that pays off) remains to be shown with multi-seed evaluation.
5. **LLM-as-policy (§5.8) is an asymmetric baseline.** The one-shot LLM never sees reward; the agent’s diagnostic report effectively does (via per-persona regret). Framing as “Software 3.0 baseline” understates how much of the gap is the feedback loop vs LLM reasoning. A fairer asymmetry would give the one-shot LLM a summary of observed rewards too.
6. **Stationary persona distribution between drift tests.** No seasonality, no viral effects. §5.9’s drift test uses a single abrupt shift; richer non-stationarity is unstudied.
7. **No formal regret bounds.** Treatment is purely empirical.
8. **Cost is not modeled.** Each agent run consumes K Claude calls per checkpoint $\times$ 3 checkpoints $\times$ R replicates. For a 10K-session simulator at $K=1$, $R=3$ that is ~ 9 subagent invocations per agent variant — a few dollars in API cost, an order of magnitude lower than

re-training a neural bandit per checkpoint. A real production budget analysis (per-page or per-decision LLM cost vs the bandit’s pure compute cost) is in §8 future work.

9. **EDP-agent depends on a capable LLM.** Both the live agent and the OPRO ablation use Claude subagents. Smaller / open-weight LLMs would likely degrade the report-based agent more than OPRO (since the report requires structured reasoning while OPRO is closer to gradient-free pattern matching).
10. **At $K=3-4$ reps, several comparisons are underpowered.** The OPRO ablation on parametric (§5.4) is only $\sim 1\sigma$ separated. The Bayesian-EDP margin over EDP-agent on parametric (§5.4b) is small. Per-(persona, category) cell numbers in §5.5 have substantial SE that we don’t quote. Larger K is in §8.

0.8. Future Work

We ran four of the items previously listed here (slate-LinTS in §5.3, drift in §5.9, structural exploration in §5.9, multi-agent ensembles in §5.10) and have a new principled fusion (Bayesian-EDP in §5.4b). The remaining open directions:

Neural bandits. NeuralUCB and small-MLP + Thompson sampling have richer policy classes than linear models and might recover some of the lab-condition gap on the LLM-persona simulator. Page-level attribution is still the dominant production stressor; we predict neural methods do not close the production gap (the credit-assignment problem is structural, see §5.2 and §5.3), but a direct experiment would settle it.

Counterfactual estimators. IPS and Doubly Robust estimators can in principle recover partial per-slot credit if a propensity model is available. These methods need their own exploration policy and a logging policy; integrating them is a non-trivial extension and a separate study.

Layer-1-aware diagnostics + interleaved checkpoints. §5.4d added the Layer-1 PWL-edit capability and observed no single-trial improvement. The most promising follow-ups: (a) interleave Layer-1-only and Layer-2-only checkpoints rather than mixing both in each batch, so we can attribute marginal value; (b) add Layer-1-specific diagnostics to the checkpoint report (e.g., “X% of high-regret sessions had problem F32 detected at <0.3 despite $N1_fit > 0.7$ ”), which would give the agent a sharper signal for when shape edits are warranted. Per-(persona, category) conditional shape functions are a structural step beyond and a separate future item.

Larger ensembles + better validation slicing. §5.10’s 3-draw ensemble is statistically indistinguishable from a single draw under the canonical multi-seed numbers, and per-round diagnostics suggest a structural fragility (validation-slice persona mixture differs from the next live segment) that this $K=3$ study cannot resolve. Two natural extensions: (a) $K=10-20$ draws per checkpoint, (b) replace the held-out validation slice

with a stratified set spanning all (persona, category) cells the live stream is about to encounter. Both add cost; neither is mechanically difficult.

Live engagement validation. Validate the synthetic-ground-truth ranking against logged engagement data from a deployed system. This is the limitation reviewers will press hardest on; the right way to address it is a logged-eval study, not a richer simulator.

Drift recovery via agent-triggered checkpoints. §5.9’s drift test used a fixed checkpoint schedule. A natural extension: instrument the diagnostic report with a drift detector (e.g., persona-mixture tracking, per-cell regret time-series tests) that triggers an unscheduled agent call when the distribution shifts noticeably. Combined with §5.9’s structural-exploration mechanism, this would close the loop on production non-stationarity.

0.9. Conclusion

Per-slot LinTS is the wrong abstraction for slate-with-submodular-reward problems under page-level reward; the framing was always misapplied. The EDP architecture (adaptive submodular over a shared GAM parameterisation) is the right baseline, and most of the production-stack advantage we measure comes from that architecture — not from the LLM. GreedyLinTS, the EDP architecture with no LLM prior and pure SGD, already closes 6 pp of the lab-vs-prod gap that per-slot LinTS suffers (12.8 % parametric, 13.3 % LLM in production). The LLM agent and continuous SGD then trade off depending on the simulator: **on parametric, EDP-agent (LLM checkpoint edits, no SGD) is the best method we measured (6.5 ± 0.2 %) because the agent’s edits are well-targeted; on LLM-persona, Bayesian-EDP (LLM-anchored prior + continuous regularised SGD) is the best (11.0 ± 0.2 %) because the wider persona / category space leaves enough numerical-calibration headroom for SGD to help. Neither method is uniformly best — they are simulator-conditional. The OPRO ablation isolates the *structured diagnostic report* — not the LLM’s general intelligence — as the carrier of the LLM-side gain, cleanly so on the LLM simulator ($\approx 2.2 \sigma$ separation at $K=3-4$) and weakly so on parametric ($\approx 1 \sigma$ separation, underpowered). The decomposable claim that survives: **under page-level reward, use the adaptive-submodular policy class; if you have an LLM with knowledge of the problem domain, use it as a prior + checkpoint editor; if your simulator is rich enough that the LLM’s discrete edits don’t saturate, add continuous regularised SGD on top.****

0.10. Appendix A: Open-box decision trace

This appendix walks through Fig. 9 in prose. The session is a `size_anxious_new` persona sampled from the parametric simulator at seed 42, browsing the `dress` category. The whole trace lives in $14 + 7 + 22 = 43$ named numbers; ev-

erything below was generated by reading the policy’s internal state, not by any post-hoc interpretability library.

Step 1 — raw signals (14 numbers). The persona’s distribution puts most of its mass on three signals: `size_chart` (0.62), `size_conf` (0.18, so `size_conf_inv` = 0.82), and `return_hist` (0.41). Tab-switch is moderate (0.31), zoom and price-dwell are low. The product-side signal `price_norm` = 0.55 (mid-priced item).

Step 2 — Layer-1 problem fingerprint (7 numbers). The PWL curves in Fig. 8 are evaluated at the signal values above, weighted, and clipped to $[0, 1]$. The fingerprint comes out concentrated on F3.2:

Problem	Score
F3.2 size anxiety	
F4.6 return hesitation	
F4.1 comparison	
F3.3 / F4.3 / F4.5 / F5.1	

The fingerprint is a 7-d vector with one dominant axis. Layer-2 will see this and compose accordingly.

Step 3 — Layer-2 slot-1 scoring (22 numbers per slot). For slot 1, remaining = the fingerprint above, coverage = 0. The score decomposes as $\text{base} + \sum \text{on_rem}[p] \cdot \text{remaining}[p] + \sum \text{on_cov}[p] \cdot \text{coverage}[p] - \text{slot_decay} \cdot 0$. The top five candidates (Fig. 9, bottom panel):

`fit_reassurance` wins because of the F3.2 `on_rem` slope, not because of a high base. After it is placed, F3.2 remaining drops by 0.55 (its `addr` value) to 0.19, F3.2 coverage rises by 0.55 to 0.55, and slot 2 scoring reruns with the updated state. `size_guide`, with `on_cov.F32` = -1.4 in the LLM prior, gets *penalised* in slot 2 by $1.4 \times 0.55 = 0.77$ — the explicit anti-synergy stops the page from wasting a second slot on fit guidance.

(The round-2500 agent edit batch in Fig. 10 mutates this exact anti-synergy on `size_guide.on_cov.F32` from -1.4 to +0.6, converting it from a substitute to a chained complement for the size-anxious persona. The reason field is preserved verbatim. Whether the edit pays off is empirical (§5.4b–5.4c): it does on parametric, less clearly so on LLM.)

What an interpretability reviewer can verify in 5 minutes. That the size-anxious persona’s page leads with `fit_reassurance` because of the F3.2 on-remaining slope; that the second slot’s identity is sensitive to the `size_guide` / `fit_reassurance` synergy parameter; that swapping the persona changes the fingerprint, the slot-1 winner, and the slot-2 anti-synergy — all by editing values the reviewer can see and write. No SHAP, no LIME, no post-hoc surrogate. The decision trace is the policy.

What an agent can do at the same place. The agent reads exactly the table above (plus regret aggregates) and proposes scalar edits to any of the 43 numbers, each with a free-text reason. Fig. 10 shows what one such batch looks like in practice. The unit of work is a number-with-a-reason, not a

