





					Manufacturer		Supplier Bart		
Description	Designator	Footprint	Quantity	Manufacturer	Part Number	Supplier 1	Supplier Part Number 1	Comment	Case/Package
CERAMIC CAPACITOR, 10UF, 16V, X5R, 20%, 0805, FULL REEL: Product Rangie: Cseries; Capacitance: 10 F: Capacitance: 20%; Dielectric Characteristic:X5R; Voltage Rating:16V; Ceramic Capacitor Case:0805 [2012 Metric]; MSL:-:RoHS Compliant: Yes	C1	CAP_0805	1	TDK	C2012X5R1C106M 125AC	Digi-Key	445-4115-1-ND	10uF	0805
C Series 1206 100 uF 10 V ±20 % Tolerance JB SMT Multilayer Ceramic Capacitor	C2	CAP3216	1	TDK	C3216JB1A107M1 60AC	Arrow Electronics	C3216JB1A107M1 60AC	100uF 10V	1206
C Series 0805 0.1 uF 50 V ±10 % Tolerance X7R SMT Multilayer Ceramic Capacitor	C3, C4	CAP_0805	2	TDK	C2012X7R1H104K0 85AA	Avnet	87R4037	100nF	0805
C Series 0805 0.1 uF 250 V ±20 % Tolerance X7T SMT Multilayer Ceramic Capacitor	C5	CAP_0805	1					CAP 100 nF 250V	
VR=30V IF=200mA 10pF P=200mW	D1, D2, D3	SOD323	3	ON Semiconductor / Fairchild	BAT54HT1G	Newark	83H6419	BAT54HT1G	
Conn Unshrouded Header HDR 2 POS 2.54mm Solder ST Thru-Hole Poly Bag 2~24 Poles, Screw	J1, J2, J7	HDR 1x2	3	Amphenol ICC / FCI	75160-327-02LF	Avnet	75160-327-02LF	75160-327-02LF	
Type, Horizontal, 5.08 Pitch, 26~12 (AWG), Terminal Block Connector	J3	CUI_TB010-508-02BE	1	CUI Devices	TB010-508-02BE	Arrow Electronics	TB010-508-02BE	TB010-508-02BE	
Phoenix Contact 5441540, BC-500X10- 3 BK PCB terminal blo	J4	Screw 5mm 3 Terminal	1	Phoenix Contact	5441540	Mouser	651-5441540	400 V 13.5 A	
Conn Unshrouded Header HDR 3 POS 2.54mm Solder ST Top Entry Thru-Hole BergStik® Bulk	JP1, JP2	HDR 1x3	2	Amphenol ICC / FCI	68797-403HLF	Mouser	649-68797-403HLF	HDR 1x3	
Conn Unshrouded Header HDR 4 POS 2.54mm Solder ST Thru-Hole Bag	JP3	HDR 1X4	1	Amphenol ICC	68001-204HLF	Allied Electronics	70302499	HDR 1X4	
Transistor Bipolar (BJT) NPN 60V 100mA 225mW Surface Mount SOT-23-3	Q3	SOT23-3	1	ON Semiconductor	MMBT2484LT1G	RSComponents	7916126P	MMBT2484LT1G	SOT-23-3
三极管 2NPN Vceo=40V Ic=200mA Pd=225mW	Q, Q1, Q2	SOT-363	3	Pan Jit	MMDT3904_R1_00 001	Digi-Key	3757- MMDT3904_R1_00 001CT-ND	NPN	
贴片电阻 1000Ω ± 1.00% 0.125W ± 100ppm/°C 0805	R1, R2, R4, R5, R6, R7, R9, R13, R15, R16, R19, R21	R_0805	12	Yageo	RC0805FR-071KL	Future Electronics	8126013	1K	0805
贴片电阻 560Ω ± 1.00% 0.125W ± 100ppm/°C 0805	R3, R10, R11, R12, R14, R17, R18, R20, R23, R24, R25	R_0805	11	Yageo	RC0805FR- 07560RL	Avnet	RC0805FR- 07560RL	560 R	0805
贴片电阻 100000Ω± 1.00% 0.125W± 100ppm/°C 0805	R8	R_0805	1	Yageo	RC0805FR- 07100KL	Avnet	RC0805FR- 07100KL	100K	0805
贴片电阻 10000Ω± 1.00% 0.125W± 100ppm/°C 0805	R22	R_0805	1	Yageo	RC0805FR-0710KL	Avnet	RC0805FR-0710KL	10K	0805
6-ch, 4.5-V to 5.5-V inverters with Schmitt-Trigger inputs 14-TSSOP -40 to 85	U1	14-TSSOP	1	Texas Instruments	SN74ACT14PWR	Digi-Key	296-4369-1-ND	Inverter	TSSOP
Single 2-input, 4.5-V to 5.5-V AND gate with TTL-compatible CMOS inputs 5-SOT- 23-40 to 125	U2	SOT-23-5	1	Texas Instruments	SN74AHCT1G08DB V3	Digi-Key	296- SN74AHCT1G08DB V3CT-ND	SN74AHCT1G08DB V3	
AND Gate IC 2	U3	SOIC 14	1	Texas	SN74HC21DR	Arrow Electronics	SN74HC21DR	SN74HC21DR	SOIC
Channel 14-SOIC CMOS Presettable Binary Up/Down Counter 16-SO -55 to 125	U4	SOIC 16	1	Texas Instruments	CD4516BNSR	Digi-Key	296-29362-1-ND	CD4516BNSR	SOP
Flip Flop JK-Type Pos- Edge 1-Element 8-Pin TSSOP T/R	U5	8-TSSOP	1	ON Semiconductor	MC10EP35DTR2G	Mouser	863- MC10EP35DTR2G	MC10EP35DTR2G	TSSOP
TRIAC Standard 600V 16A Through Hole TO- 220AB	U6	BAT16	1					BTA16-600BRG	
DC-IN 1-CH Transistor With Base DC-OUT 6- Pin PDIP SMD	U7	SMD 6	1	Isocom	4N26XSM	RSComponents	1712953	4N26XSM	SMD/SMT