

All eight candidate rows were attempted

A numerical score was retained only when the receptor pocket and alternate definition supported it.

	1. FYN · saracatinib validated + pocket absent	Canonical redocking validated; 115-aa alternate lacks the kinase domain.	HIGH
	2. KIT · masitinib attempted; alternate unresolved	Ser715 lies in the unresolved 1T46 segment; predicted-model docking showed clashes and was rejected.	LIMITED
	3. GABRA2 · AZD7325 canonical cross-dock + pocket absent	9CSB alpha2/gamma2 pocket passed transfer checks; 73-aa alternate cannot form the receptor.	EXPLORATORY
	4. CACNA1D · isradipine shared-pocket control	The deposited human pocket ends before the alternate C-terminal truncation.	EXPLORATORY
	5. BACE1-476 · verubecestat modeled comparative docking	Canonical cognate redocking validated; alternate pocket has high local pLDDT.	MODERATE
	6. BACE1-457 · verubecestat modeled comparative docking	Deletion removes 5 of 28 experimental pocket-contact residues; model passed local quality checks.	MODERATE
	7. CHRNA7/CHRFAM7A · encenicline two topology hypotheses	Canonical redocking validated, but sample stoichiometry/genotype support is absent.	HYPOTHESIS ONLY
	8. PDE9A · BI 409306 canonical cross-dock only	The candidate file does not name the coding-altered PDE9A transcript.	INCOMPLETE PAIR