Virtual Memory

Jin-Soo Kim
(*jinsoo.kim@snu.ac.kr*)

Systems Software &
Architecture Lab.


Seoul National University


Spring 2026



Physical Memory Management

- Contiguous allocation with variable-sized segments
- Internal/external fragmentation
- Sharing
- Protection and isolation
- Limited capacity






Source: https://semiconductor.samsung.com/news-events/news/samsung-starts-mass-production-of-most-advanced-14nm-euv-ddr5-dram/
https://news.skhynix.com/sk-hynix-obtains-industrys-first-validation-for-1anm-ddr5-dram-on-the-4th-gen-intel-xeon-scalable-processor/

Virtual Memory: Goals

- Transparency
  - Processes should not be aware that memory is shared
  - Provide a convenient abstraction for programming (i.e., a large, contiguous memory space)
- Efficiency
  - Minimize fragmentation due to variable-sized requests (space)
  - Get some hardware support (time)
- Protection
  - Protect processes and the OS from another process
  - Isolation: a process can fail without affecting other processes
  - Cooperating processes can share portions of memory


(Virtual) Address Space

- Process' abstract view of memory
  - OS provides illusion of private address space to each process
  - Contains all of the memory state of the process
  - Static area
    - Allocated on exec()
    - Code & Data
  - Dynamic area
    - Allocated at runtime
    - Can grow or shrink
    - Heap & Stack




Virtual Memory

- Each process has its own virtual address space
  - Large and contiguous
  - Use virtual addresses for memory references
  - Virtual addresses are private to each process
- Address translation is performed at run time
  - From a virtual address to the corresponding physical address
- Supports lazy allocation
  - Physical memory is dynamically allocated or released on demand
  - Programs execute without requiring their entire address space to be resident in physical memory




Virtual Memory



Static Relocation (1)

- Software-based relocation
  - OS rewrites each program before loading it into memory
  - Changes addresses of static data and functions



Static Relocation (2)


- Pros
  - No hardware support is required
- Cons
  - No protection enforced
    - A process can destroy memory regions of the OS or other processes
    - No privacy: can read any memory address
  - Cannot move address space after it has been placed
    - May not be able to allocate a new process due to external fragmentation

→ 거의 안 쓴다.

Dynamic Relocation


- Hardware-based relocation
  - Hardware performs address translation on every memory reference instructions
  - Protection is enforced by hardware: if the virtual address is invalid, the hardware raises an exception
  - OS passes the information about the valid address space of the current process to the hardware

- Implementations
  - Fixed or variable partitions
  - Segmentation
  - Paging



Fixed Partitions (1)

- Physical memory is broken up into fixed partitions
  - Size of each partition is the same and fixed
  - The number of partitions = degree of multiprogramming




Fixed Partitions (2)

- Hardware requirements: base register
  - Physical address = virtual address + base register
  - Base register loaded by OS on context switch

- Pros
  - Easy to implement
  - Fast context switch
- Cons
  - Internal fragmentation: unused area in a partition is wasted
  - Partition size: one size does not fit all


Fixed Partitions (3)

- Improvement
  - Partition size needs not be equal
  - Allocation strategies
    - A separate queue for each partition size
    - A single queue + first fit
    - A single queue + best fit
  - Used in IBM OS/MFT (Multiprogramming with a Fixed number of Tasks)



Variable Partitions (1)

- Physical memory is broken up into variable-sized partitions
  - Used in IBM OS/MVT



Variable Partitions (2)

- Hardware requirements: base register + limit register
  - The role of limit register: protection
- Pros
  - Simple, inexpensive implementation
  - No internal fragmentation
- Cons
  - Each process must be allocated contiguously in physical memory
  - External fragmentation:
    - Holes are left scattered throughout physical memory
    - Compaction can be used to reduce external fragmentation
  - No partial sharing: cannot share parts of address space




이런 예제

e.g. 코드의 공유.


Segmentation

- Divide address space into logical segments
  - Each segment corresponds to logical entity in address space
    - Code, data, stack, heap, etc.
  - Users view memory as a collection of variable-sized segments, with no necessary ordering among them
    - Virtual address: <Segment #, Offset>
  - Each segment can independently
    - be placed in physical memory
    - grow or shrink
    - be protected (separate read/write/execute protection bits)
  - Natural extension of variable partitions
    - Variable partitions: 1 segment / process
    - Segmentation: many segments / process



Segmentation: Addressing


- Explicit approach
  - Use a part of virtual address as a segment number
  - The remaining bits mean the offset within the segment
  - e.g., VAX/VMS system



- Implicit approach
  - Determines the segment by the type of memory reference
    - PC-based addressing: code segment
    - SP- or BP-based addressing: stack segment

Segmentation: Implementation

- Segment registers or table (per process)




Segmentation: Pros

- Enables sparse allocation of address space
  - Stack and heap can grow independently
- Easy to protect segments
  - Valid bit
  - Different protection bits for different segments
    - e.g., Read-only status for code, Kernel-mode-only for system segment
- Easy to share segments
  - Put the same translation into base/limit pair
  - Code/data sharing at segment level (e.g., shared libraries)
- Supports dynamic relocation of each segment

Segmentation: Cons

- Each segment must be allocated contiguously
  - External fragmentation
  - May not have sufficient physical memory for large segments
- Large segment table
  - Keep in main memory
  - Use hardware cache for speed
- Cross-segment addresses
  - Segments need to have same segment number for pointers to them to be shared among processes
  - Otherwise, use indirect addressing only



Summary

- Separates user's virtual memory from physical memory
  - Abstracts main memory into a large, uniform array of bytes
  - Frees programmers from the concerns of memory limitations
  - Physical memory locations can be moved transparently
- The virtual address space is overcommitted
  - Allows the execution of processes that may not be completely in memory
  - Physical memory is allocated on demand
  - Views the physical memory as a cache for the disk
- Easy to protect and share memory regions among processes