

Reviewer Appendix: Label Difference Review

This appendix summarizes the reviewed differences between the original human annotations and the current annotations.

Scope: the review file covers label differences between the original human annotation and the current annotation.

Interpretation of difference types

- Objective: marked when the original annotated method is not shown in the execution trace, and we revise the annotation to match the current methods in this version as closely as possible.
- Subjective: marked when the authors disagree with the original label.
- The previous human annotations do not include execution IDs and therefore do not distinguish between different executions. This can be especially problematic in cases such as gson::1174 and gson::1175, where both tests share the same source-code location but execute on different classes: JsonTreeReader in one case and JsonReader in the other.
- Paper scoring note: the score reported in the paper is based on the objective modifications. The subjective annotations are used in the updated set of 500 annotations.

Summary

- Test cases with different annotations between the updated and original human annotations: 39
- Objective difference labels: 31
- Subjective difference labels: 49
- Cases containing at least one objective difference: 15
- Cases containing at least one subjective difference: 27
- Cases containing both objective and subjective differences: 3

Project: commons-io

1. Test commons-io::1485

Original human annotation

- Not available from the matched comparison source.

Current annotation

- Not available from the matched comparison source.

Reason category: version drift behavior change

Explanation: org.apache.commons.io.IOCase.values() does not get invoked in the call graph.

Classified differences

- OBJECTIVE | Only in original human annotation | org.apache.commons.io.IOCase.values()

2. Test commons-io::999

Test name: testCancel

Current Test Name and Execution ID: org.apache.commons.io.DirectoryWalkerTest_testCancel_233c73ad

Old Test Name: org.apache.commons.io.DirectoryWalkerTestCase.testCancel()

Original human annotation

- org.apache.commons.io.DirectoryWalker.handleCancelled(File, Collection, CancelException)
- org.apache.commons.io.DirectoryWalker.walk(java.io.File, java.util.Collection<T>)

Current annotation

- org.apache.commons.io.DirectoryWalker.walk(java.io.File, java.util.Collection<T>)

Reason category: old label irrelevant

Explanation: handleCancel is defined and overwritten in the test suite.

Classified differences

- OBJECTIVE | Only in original human annotation |
org.apache.commons.io.DirectoryWalker.handleCancelled(File, Collection, CancelException)
- OBJECTIVE | Only in original human annotation |
org.apache.commons.io.DirectoryWalker.handleCancelled(java.io.File,
java.util.Collection<T>, org.apache.commons.io.DirectoryWalker.CancelException)

3. Test commons-io::5825

Test name: testLargeUTF8WithSingleByteWrite

Current Test Name and Execution ID:

org.apache.commons.io.output.WriterOutputStreamTest_testLargeUTF8WithSingleByteWrite_1ae648b0

Old Test Name: org.apache.commons.io.output.WriterOutputStreamTest.testLargeUTF8WithSingleByteWrite()

Original human annotation

- org.apache.commons.io.output.WriterOutputStream.WriterOutputStream(Writer, String)
- org.apache.commons.io.output.WriterOutputStream.write(int)

Current annotation

- org.apache.commons.io.output.WriterOutputStream.write(int)

Reason category: old label contains setup method

Explanation: org.apache.commons.io.output.WriterOutputStream.WriterOutputStream(Writer, String) is just a setup method. write itself is the focal method.

Classified differences

- SUBJECTIVE | Only in original human annotation |
org.apache.commons.io.output.WriterOutputStream(java.io.Writer, java.lang.String)
- SUBJECTIVE | Only in original human annotation |
org.apache.commons.io.output.WriterOutputStream.WriterOutputStream(Writer, String)

4. Test commons-io::5844

Test name: testLatin7Encoding

Current Test Name and Execution ID:

org.apache.commons.io.output.XmlStreamWriterTest_testLatin7Encoding_c8ef8459

Old Test Name: org.apache.commons.io.output.XmlStreamWriterTest.testLatin7Encoding()

Original human annotation

- org.apache.commons.io.output.XmlStreamWriter.detectEncoding(char[], int, int)

Current annotation

- org.apache.commons.io.output.XmlStreamWriter.detectEncoding(char[], int, int)
- org.apache.commons.io.output.XmlStreamWriter.write(char[], int, int)

Reason category: old label missing core behavior

Explanation: Write is the core behavior with detection as well.

Classified differences

- SUBJECTIVE | Only in current annotation |
org.apache.commons.io.output.XmlStreamWriter.write(char[], int, int)

5. Test commons-io::5847

Test name: testUTF16BEEncoding

Current Test Name and Execution ID:

org.apache.commons.io.output.XmlStreamWriterTest_testUTF16BEEncoding_ee528fd1

Old Test Name: org.apache.commons.io.output.XmlStreamWriterTest.testUTF16BEEncoding()

Original human annotation

- org.apache.commons.io.output.XmlStreamWriter.detectEncoding(char[], int, int)

Current annotation

- org.apache.commons.io.output.XmlStreamWriter.detectEncoding(char[], int, int)
- org.apache.commons.io.output.XmlStreamWriter.write(char[], int, int)

Reason category: old label missing core behavior

Explanation: Write is the core behavior with detection as well.

Classified differences

- SUBJECTIVE | Only in current annotation |
org.apache.commons.io.output.XmlStreamWriter.write(char[], int, int)

6. Test commons-io::1390

Test name: testWriteLines_3argsWithAppendOptionTrue_ShouldNotDeletePreviousFileLines

Current Test Name and Execution ID:

org.apache.commons.io.FileUtilsTest_testWriteLines_3argsWithAppendOptionTrue_ShouldNotDeletePreviousFileLines_1b5c853b

Old Test Name:

org.apache.commons.io.FileUtilsTestCase.testWriteLines_3argsWithAppendOptionTrue_ShouldNotDeletePreviousFileLines()

Original human annotation

- org.apache.commons.io.FileUtils.readFileToString(java.io.File)
- org.apache.commons.io.FileUtils.writeLines(java.io.File, java.util.Collection<?>, boolean)
- org.apache.commons.io.FileUtils.writeStringToFile(java.io.File, java.lang.String, java.nio.charset.Charset)

Current annotation

- org.apache.commons.io.FileUtils.writeLines(java.io.File, java.util.Collection<?>, boolean)

Reason category: old label contains setup method

Explanation: org.apache.commons.io.FileUtils.readFileToString(java.io.File)

org.apache.commons.io.FileUtils.writeStringToFile(java.io.File, java.lang.String, java.nio.charset.Charset)

are setup method. testWriteLines should be the focus as suggested by testname.

Classified differences

- SUBJECTIVE | Only in original human annotation |
org.apache.commons.io.FileUtils.readFileToString(java.io.File)
- SUBJECTIVE | Only in original human annotation |
org.apache.commons.io.FileUtils.writeStringToFile(java.io.File, java.lang.String, java.nio.charset.Charset)

7. Test commons-io::1395

Test name: testWriteLines_4argsWithAppendOptionTrue_ShouldNotDeletePreviousFileLines

Current Test Name and Execution ID:

org.apache.commons.io.FileUtilsTest_testWriteLines_4argsWithAppendOptionTrue_ShouldNotDeletePreviousFileLines_2160509a

Old Test Name:

org.apache.commons.io.FileUtilsTestCase.testWriteLines_4argsWithAppendOptionTrue_ShouldNotDeletePreviousFileLines()

Original human annotation

- org.apache.commons.io.FileUtils.readFileToString(java.io.File)

- org.apache.commons.io.FileUtils.writeLines(java.io.File, java.util.Collection<?>, java.lang.String, boolean)
- org.apache.commons.io.FileUtils.writeStringToFile(java.io.File, java.lang.String)

Current annotation

- org.apache.commons.io.FileUtils.writeLines(java.io.File, java.util.Collection<?>, java.lang.String, boolean)

Reason category: old label contains setup method

Explanation: org.apache.commons.io.FileUtils.readFileToString(java.io.File)

org.apache.commons.io.FileUtils.writeStringToFile(java.io.File, java.lang.String, java.nio.charset.Charset)

are setup method. testWriteLines should be the focus as suggested by testname.

Classified differences

- SUBJECTIVE | Only in original human annotation | org.apache.commons.io.FileUtils.readFileToString(java.io.File)
- SUBJECTIVE | Only in original human annotation | org.apache.commons.io.FileUtils.writeStringToFile(java.io.File, java.lang.String)

8. Test commons-io::1396

Test name: testWriteLines_5argsWithAppendOptionFalse_ShouldDeletePreviousFileLines

Current Test Name and Execution ID:

org.apache.commons.io.FileUtilsTest_testWriteLines_5argsWithAppendOptionFalse_ShouldDeletePreviousFileLines_54d19b99

Old Test Name:

org.apache.commons.io.FileUtilsTestCase.testWriteLines_5argsWithAppendOptionFalse_ShouldDeletePreviousFileLines()

Original human annotation

- org.apache.commons.io.FileUtils.readFileToString(java.io.File)
- org.apache.commons.io.FileUtils.writeLines(java.io.File, java.lang.String, java.util.Collection<?>, java.lang.String, boolean)
- org.apache.commons.io.FileUtils.writeStringToFile(java.io.File, java.lang.String)

Current annotation

- org.apache.commons.io.FileUtils.writeLines(java.io.File, java.lang.String, java.util.Collection<?>, java.lang.String, boolean)

Reason category: old label contains setup method

Explanation: org.apache.commons.io.FileUtils.readFileToString(java.io.File)

org.apache.commons.io.FileUtils.writeStringToFile(java.io.File, java.lang.String, java.nio.charset.Charset)

are setup method. testWriteLines should be the focus as suggested by testname.

Classified differences

- SUBJECTIVE | Only in original human annotation | org.apache.commons.io.FileUtils.readFileToString(java.io.File)
- SUBJECTIVE | Only in original human annotation | org.apache.commons.io.FileUtils.writeStringToFile(java.io.File, java.lang.String)

9. Test commons-io::5195

Test name: testWriteStringBuilder

Current Test Name and Execution ID:

org.apache.commons.io.output.AppendableOutputStreamTest_testWriteStringBuilder_5384fe9e

Old Test Name: org.apache.commons.io.output.AppendableOutputStreamTest.testWriteStringBuilder()

Original human annotation

- org.apache.commons.io.output.AppendableOutputStream.getAppendable()
- org.apache.commons.io.output.AppendableOutputStream.write(int)

Current annotation

- org.apache.commons.io.output.AppendableOutputStream.write(int)

Reason category: old label contains probe

Explanation: getAppendable is just a probe to check the output. write is the focal method.

Classified differences

- SUBJECTIVE | Only in original human annotation |
org.apache.commons.io.output.AppendableOutputStream.getAppendable()

Project: commons-lang

10. Test commons-lang::5238

Test name: testFloatArray

Current Test Name and Execution ID:

org.apache.commons.lang3.builder.ToStringBuilderTest_testFloatArray_81f8e8d0

Old Test Name: org.apache.commons.lang3.builder.ToStringBuilderTest.testFloatArray()

Original human annotation

- org.apache.commons.lang3.builder.ToStringBuilder.toString()

Current annotation

- org.apache.commons.lang3.builder.ToStringBuilder.append(java.lang.Object)
- org.apache.commons.lang3.builder.ToStringBuilder.append(float[])
- org.apache.commons.lang3.builder.ToStringBuilder.toString()

Reason category: Unspecified

Classified differences

- OBJECTIVE | Only in current annotation |
org.apache.commons.lang3.builder.ToStringBuilder.append(java.lang.Object)

11. Test commons-lang::3865

Test name: testRandomPrintRange

Current Test Name and Execution ID:

org.apache.commons.lang3.RandomStringUtilsTest_testRandomPrintRange_493e302c

Old Test Name: org.apache.commons.lang3.RandomStringUtilsTest.testRandomPrintRange()

Original human annotation

- org.apache.commons.lang3.RandomStringUtils.randomPrint(int, int)

Current annotation

- org.apache.commons.lang3.RandomStringUtils.nextPrint(int, int)

Reason category: version drift behavior change

Classified differences

- OBJECTIVE | Only in current annotation |
org.apache.commons.lang3.RandomStringUtils.nextPrint(int, int)
- OBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.RandomStringUtils.randomPrint(int, int)

12. Test commons-lang::128

Test name: testRemoveAllNullObjectArray

Current Test Name and Execution ID:

org.apache.commons.lang3.ArrayUtilsRemoveMultipleTest_testRemoveAllNullObjectArray_85570fc9

Old Test Name: org.apache.commons.lang3.ArrayUtilsRemoveMultipleTest.testRemoveAllNullObjectArray()

Original human annotation

- org.apache.commons.lang3.ArrayUtils.remove(T[], int)

Current annotation

- org.apache.commons.lang3.ArrayUtils.removeAll(T[], int[])

Reason category: Unspecified

Classified differences

- OBJECTIVE | Only in current annotation |
org.apache.commons.lang3.ArrayUtils.removeAll(T[], int[])
- OBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.ArrayUtils.remove(T[], int)

13. Test commons-lang::1141

Test name: test_getName_Object

Current Test Name and Execution ID: org.apache.commons.lang3.ClassUtilsTest_test_getName_Object_75d0ec2b

Old Test Name: org.apache.commons.lang3.ClassUtilsTest.test_getName_Object()

Original human annotation

- org.apache.commons.lang3.ClassUtils.getName(Class, String)
- org.apache.commons.lang3.ClassUtils.getName(Object, String)

Current annotation

- org.apache.commons.lang3.ClassUtils.getName(java.lang.Object, java.lang.String)

Reason category: Unspecified

Classified differences

- OBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.ClassUtils.getName(java.lang.Class<?>, java.lang.String)

14. Test commons-lang::7094

Test name: testCapacityAndLength

Current Test Name and Execution ID:

org.apache.commons.lang3.text.StrBuilderTest_testCapacityAndLength_a284b652

Old Test Name: org.apache.commons.lang3.text.StrBuilderTest.testCapacityAndLength()

Original human annotation

- org.apache.commons.lang3.text.StrBuilder.capacity()
- org.apache.commons.lang3.text.StrBuilder.ensureCapacity(int)
- org.apache.commons.lang3.text.StrBuilder.isEmpty()
- org.apache.commons.lang3.text.StrBuilder.length()
- org.apache.commons.lang3.text.StrBuilder.minimizeCapacity()
- org.apache.commons.lang3.text.StrBuilder.size()

Current annotation

- org.apache.commons.lang3.text.StrBuilder.length()
- org.apache.commons.lang3.text.StrBuilder.capacity()
- org.apache.commons.lang3.text.StrBuilder.append(java.lang.String)
- org.apache.commons.lang3.text.StrBuilder.isEmpty()
- org.apache.commons.lang3.text.StrBuilder.ensureCapacity(int)
- org.apache.commons.lang3.text.StrBuilder.minimizeCapacity()
- org.apache.commons.lang3.text.StrBuilder.setLength(int)
- org.apache.commons.lang3.text.StrBuilder.size()
- org.apache.commons.lang3.text.StrBuilder.clear()

Reason category: old label missing core behavior

Explanation: This method clearly targeting all methods.

Classified differences

- SUBJECTIVE | Only in current annotation |
org.apache.commons.lang3.text.StrBuilder.append(java.lang.String)
- SUBJECTIVE | Only in current annotation |
org.apache.commons.lang3.text.StrBuilder.clear()

- SUBJECTIVE | Only in current annotation |
org.apache.commons.lang3.text.StrBuilder.setLength(int)

15. Test commons-lang::5548

Test name: testChangeEvent

Current Test Name and Execution ID:

org.apache.commons.lang3.concurrent.EventCountCircuitBreakerTest_testChangeEvent_b4e774dc

Old Test Name: org.apache.commons.lang3.concurrent.EventCountCircuitBreakerTest.testChangeEvent()

Original human annotation

- org.apache.commons.lang3.concurrent.AbstractCircuitBreaker.addChangeListener(java.beans.PropertyChangeListenersCollection)
- org.apache.commons.lang3.concurrent.EventCountCircuitBreaker.close()
- org.apache.commons.lang3.concurrent.EventCountCircuitBreaker.open()

Current annotation

- org.apache.commons.lang3.concurrent.EventCountCircuitBreaker.close()
- org.apache.commons.lang3.concurrent.EventCountCircuitBreaker.open()

Reason category: old label contains probe

Explanation: addChangeListener is just a probe to listen to changes.

Classified differences

- SUBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.concurrent.AbstractCircuitBreaker.addChangeListener(java.beans.PropertyChangeListenersCollection)

16. Test commons-lang::5642

Test name: testInitializeResultsIsSuccessfulFalse

Current Test Name and Execution ID:

org.apache.commons.lang3.concurrent.MultiBackgroundInitializerTest_testInitializeResultsIsSuccessfulFalse_629890ec

Old Test Name:

org.apache.commons.lang3.concurrent.MultiBackgroundInitializerTest.testInitializeResultsIsSuccessfulFalse()

Original human annotation

- org.apache.commons.lang3.concurrent.BackgroundInitializer.start()
- org.apache.commons.lang3.concurrent.MultiBackgroundInitializer.addInitializer(java.lang.String, org.apache.commons.lang3.concurrent.BackgroundInitializer<?>)
- org.apache.commons.lang3.concurrent.MultiBackgroundInitializer.initialize()

Current annotation

- org.apache.commons.lang3.concurrent.MultiBackgroundInitializer\$MultiBackgroundInitializerResults.isSuccessful()

Reason category: old label missing core behavior

Explanation: as suggested by name, this test is targetting isSuccessful.

Classified differences

- SUBJECTIVE | Only in current annotation |
org.apache.commons.lang3.concurrent.MultiBackgroundInitializer\$MultiBackgroundInitializerResults.isSuccessful()
- SUBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.concurrent.BackgroundInitializer.start()
- SUBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.concurrent.MultiBackgroundInitializer.addInitializer(java.lang.String, org.apache.commons.lang3.concurrent.BackgroundInitializer<?>)
- SUBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.concurrent.MultiBackgroundInitializer.initialize()

17. Test commons-lang::7129

Test name: testLang295

Current Test Name and Execution ID: org.apache.commons.lang3.text.StrBuilderTest_testLang295_7ea79eaf

Old Test Name: org.apache.commons.lang3.text.StrBuilderTest.testLang295()

Original human annotation

- org.apache.commons.lang3.text.StrBuilder.StrBuilder(String)
- org.apache.commons.lang3.text.StrBuilder.contains(char)
- org.apache.commons.lang3.text.StrBuilder.deleteFirst(java.lang.String)
- org.apache.commons.lang3.text.StrBuilder.indexOf(char)

Current annotation

- org.apache.commons.lang3.text.StrBuilder.contains(char)
- org.apache.commons.lang3.text.StrBuilder.indexOf(char)

Reason category: old label contains setup method

Explanation: org.apache.commons.lang3.text.StrBuilder(java.lang.String) and org.apache.commons.lang3.text.StrBuilder.deleteFirst(java.lang.String) are just a setup method in this test case.

Classified differences

- SUBJECTIVE | Only in original human annotation | org.apache.commons.lang3.text.StrBuilder(java.lang.String)
- SUBJECTIVE | Only in original human annotation | org.apache.commons.lang3.text.StrBuilder.StrBuilder(String)
- SUBJECTIVE | Only in original human annotation | org.apache.commons.lang3.text.StrBuilder.deleteFirst(java.lang.String)

18. Test commons-lang::4807

Test name: testObjectComparator

Current Test Name and Execution ID:

org.apache.commons.lang3.builder.CompareToBuilderTest_testObjectComparator_06d24568

Old Test Name: org.apache.commons.lang3.builder.CompareToBuilderTest.testObjectComparator()

Original human annotation

- org.apache.commons.lang3.builder.CompareToBuilder.toComparison()

Current annotation

- org.apache.commons.lang3.builder.CompareToBuilder.toComparison()
- org.apache.commons.lang3.builder.CompareToBuilder.append(java.lang.Object, java.lang.Object, java.util.Comparator<?>)

Reason category: old label missing core behavior

Explanation: Append is also the core behavior here.

Classified differences

- SUBJECTIVE | Only in current annotation | org.apache.commons.lang3.builder.CompareToBuilder.append(java.lang.Object, java.lang.Object, java.util.Comparator<?>)

19. Test commons-lang::4929

Test name: testObjectRecursiveCycleSelfreference

Current Test Name and Execution ID:

org.apache.commons.lang3.builder.EqualsBuilderTest_testObjectRecursiveCycleSelfreference_e142db5b

Old Test Name: org.apache.commons.lang3.builder.EqualsBuilderTest.testObjectRecursiveCycleSelfreference()

Original human annotation

- org.apache.commons.lang3.builder.EqualsBuilder.isEquals()
- org.apache.commons.lang3.builder.EqualsBuilder.setTestRecursive(boolean)

Current annotation

- org.apache.commons.lang3.builder.EqualsBuilder.append(java.lang.Object, java.lang.Object)

Reason category: old label contains setup method

Explanation: append() performs the comparison.

(this test was also discussed heavily as one author also mark setTestRecursive) However, after the discussion, we think the setTestRecursive is merely a setup call, the append is the actual function that carries out the behavior under test.

Classified differences

- SUBJECTIVE | Only in current annotation |
org.apache.commons.lang3.builder.EqualsBuilder.append(java.lang.Object, java.lang.Object)
- SUBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.builder.EqualsBuilder.isEquals()
- SUBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.builder.EqualsBuilder.setTestRecursive(boolean)

20. Test commons-lang::5304

Test name: testSetSizeStartText

Current Test Name and Execution ID:

org.apache.commons.lang3.builder.ToStringStyleTest_testSetSizeStartText_5ef7aa9f

Old Test Name: org.apache.commons.lang3.builder.ToStringStyleTest.testSetSizeStartText()

Original human annotation

- org.apache.commons.lang3.builder.ToStringStyle.getSizeStartText()
- org.apache.commons.lang3.builder.ToStringStyle.setSizeStartText(java.lang.String)

Current annotation

- org.apache.commons.lang3.builder.ToStringStyle.setSizeStartText(java.lang.String)

Reason category: Unspecified

Classified differences

- SUBJECTIVE | Only in original human annotation |
org.apache.commons.lang3.builder.ToStringStyle.getSizeStartText()

Project: gson

21. Test gson::1174

Test name: path

Current Test Name and Execution ID: com.google.gson.stream.JsonReaderPathTest_path_37d311cc

Old Test Name: com.google.gson.stream.JsonReaderPathTest.path()

Original human annotation

- com.google.gson.internal.bind.JsonTreeReader.getPath()

Current annotation

- com.google.gson.internal.bind.JsonTreeReader.getPreviousPath()
- com.google.gson.internal.bind.JsonTreeReader.getPath()

Reason category: old label missing core behavior

Explanation: the original dataset did not account for execution differences.

Classified differences

- OBJECTIVE | Only in current annotation |
com.google.gson.internal.bind.JsonTreeReader.getPath()
- OBJECTIVE | Only in original human annotation |
com.google.gson.stream.JsonReader.getPath()

- SUBJECTIVE | Only in current annotation |
com.google.gson.internal.bind.JsonTreeReader.getPreviousPath()

22. Test gson::105

Test name: testEqualsAndHashCode

Current Test Name and Execution ID: com.google.gson.JsonNullTest_testEqualsAndHashCode_c0614b86

Old Test Name: com.google.gson.JsonNullTest.testEqualsAndHashCode()

Original human annotation

- com.google.gson.common.MoreAsserts.assertEqualsAndHashCode(Object, Object)

Current annotation

- com.google.gson.JsonNull.hashCode()
- com.google.gson.JsonNull.equals(java.lang.Object)

Reason category: Unspecified

Classified differences

- OBJECTIVE | Only in current annotation |
com.google.gson.JsonNull.equals(java.lang.Object)
- OBJECTIVE | Only in current annotation | com.google.gson.JsonNull.hashCode()
- OBJECTIVE | Only in original human annotation |
com.google.gson.common.MoreAsserts.assertEqualsAndHashCode(Object, Object)

23. Test gson::15

Test name: testName

Current Test Name and Execution ID: com.google.gson.FieldAttributesTest_testName_77c09c2c

Old Test Name: com.google.gson.FieldAttributesTest.testName()

Original human annotation

- com.google.gson.FieldAttributes(java.lang.reflect.Field)

Current annotation

- com.google.gson.FieldAttributes.getName()

Reason category: Unspecified

Classified differences

- OBJECTIVE | Only in current annotation | com.google.gson.FieldAttributes.getName()
- OBJECTIVE | Only in original human annotation |
com.google.gson.FieldAttributes(java.lang.reflect.Field)

24. Test gson::56

Test name: testOverridesDefaultExcluder

Current Test Name and Execution ID: com.google.gson.GsonTest_testOverridesDefaultExcluder_7a31aa8d

Old Test Name: com.google.gson.GsonTest.testOverridesDefaultExcluder()

Original human annotation

- com.google.gson.Gson(com.google.gson.GsonBuilder)

Current annotation

- com.google.gson.Gson(com.google.gson.GsonBuilder)
- com.google.gson.GsonBuilder.create()

Reason category: old label missing core behavior

Explanation: both Gson constructor and the GsonBuilder are equally important under this test (this test was heavily discussed and were initially labeled differently by two authors. we later decide to keep both to recognize GsonBuilders' importance in this test)

Classified differences

- OBJECTIVE | Only in current annotation |
com.google.gson.Gson(com.google.gson.GsonBuilder)

- OBJECTIVE | Only in original human annotation | `com.google.gson.Gson.Gson(Excluder, FieldNamingStrategy, Map, boolean, boolean, boolean, boolean, boolean, boolean, boolean, LongSerializationPolicy, List)`
- SUBJECTIVE | Only in current annotation | `com.google.gson.GsonBuilder.create()`

25. Test gson::203

Test name: `testReadClosed`

Current Test Name and Execution ID: `com.google.gson.MixedStreamTest_testReadClosed_03b3b04b`

Old Test Name: `com.google.gson.MixedStreamTest.testReadClosed()`

Original human annotation

- `com.google.gson.Gson.fromJson(com.google.gson.stream.JsonReader, java.lang.reflect.Type)`
- `com.google.gson.stream.JsonReader.close()`

Current annotation

- `com.google.gson.Gson.fromJson(com.google.gson.stream.JsonReader, java.lang.reflect.Type)`

Reason category: old label contains setup method

Explanation: close is just to prepare the state to test if the fromJson would throw an error.

Classified differences

- OBJECTIVE | Only in original human annotation | `com.google.gson.Gson.fromJson(com.google.gson.stream.JsonReader, java.lang.reflect.Class)`
- SUBJECTIVE | Only in original human annotation | `com.google.gson.stream.JsonReader.close()`

26. Test gson::1175

Test name: `path`

Current Test Name and Execution ID: `com.google.gson.stream.JsonReaderPathTest_path_548b77ba`

Old Test Name: `com.google.gson.stream.JsonReaderPathTest.path()`

Original human annotation

- `com.google.gson.stream.JsonReader.getPath()`

Current annotation

- `com.google.gson.stream.JsonReader.getPreviousPath()`
- `com.google.gson.stream.JsonReader.getPath()`

Reason category: old label missing core behavior

Explanation: `getPreviousPath` is also heavily tested.

Classified differences

- SUBJECTIVE | Only in current annotation | `com.google.gson.stream.JsonReader.getPreviousPath()`

27. Test gson::966

Test name: `testEscapingQuotesInStringSerialization`

Current Test Name and Execution ID:

`com.google.gson.functional.StringTest_testEscapingQuotesInStringSerialization_bb2eff6b`

Old Test Name: `com.google.gson.functional.StringTest.testEscapingQuotesInStringSerialization()`

Original human annotation

- `com.google.gson.Gson.toJson(java.lang.Object)`

Current annotation

- `com.google.gson.Gson.toJson(java.lang.Object)`
- `com.google.gson.Gson.fromJson(java.lang.String, java.lang.Class<T>)`

Reason category: old label missing core behavior

Explanation: serialization is testing both write and read.

Classified differences

- SUBJECTIVE | Only in current annotation |
com.google.gson.Gson.fromJson(java.lang.String, java.lang.Class<T>)

28. Test gson::21

Test name: testNotEquals

Current Test Name and Execution ID: com.google.gson.GenericArrayTypeTest_testNotEquals_489df098

Old Test Name: com.google.gson.GenericArrayTypeTest.testNotEquals()

Original human annotation

- com.google.gson.reflect.TypeToken.getType()

Current annotation

- com.google.gson.internal.GsonTypes\$GenericArrayTypeImpl.equals(java.lang.Object)

Reason category: old label contains setup method

Explanation: getType is just a setup, this test is clearly testing the equal functionality.

Classified differences

- SUBJECTIVE | Only in current annotation |
com.google.gson.internal.GsonTypes\$GenericArrayTypeImpl.equals(java.lang.Object)
- SUBJECTIVE | Only in original human annotation |
com.google.gson.reflect.TypeToken.getType()

29. Test gson::22

Test name: testOurTypeFunctionality

Current Test Name and Execution ID: com.google.gson.GenericArrayTypeTest_testOurTypeFunctionality_f10b1bcf

Old Test Name: com.google.gson.GenericArrayTypeTest.testOurTypeFunctionality()

Original human annotation

- com.google.gson.reflect.TypeToken.getType()

Current annotation

- com.google.gson.internal.GsonTypes\$GenericArrayTypeImpl.getGenericComponentType()
- com.google.gson.internal.GsonTypes\$GenericArrayTypeImpl.hashCode()
- com.google.gson.internal.GsonTypes\$GenericArrayTypeImpl.equals(java.lang.Object)

Reason category: old label irrelevant

Explanation: Get type is just a setup call to retrieve the type. the test is to test the functionality underneath the type class.

Classified differences

- SUBJECTIVE | Only in current annotation |
com.google.gson.internal.GsonTypes\$GenericArrayTypeImpl.equals(java.lang.Object)
- SUBJECTIVE | Only in current annotation |
com.google.gson.internal.GsonTypes\$GenericArrayTypeImpl.getGenericComponentType()
- SUBJECTIVE | Only in current annotation |
com.google.gson.internal.GsonTypes\$GenericArrayTypeImpl.hashCode()
- SUBJECTIVE | Only in original human annotation |
com.google.gson.reflect.TypeToken.getType()

30. Test gson::232

Test name: testOverrideStringAdapter

Current Test Name and Execution ID:

com.google.gson.OverrideCoreTypeAdaptersTest_testOverrideStringAdapter_a3b3ef6b

Old Test Name: com.google.gson.OverrideCoreTypeAdaptersTest.testOverrideStringAdapter()

Original human annotation

- com.google.gson.GsonBuilder.registerTypeAdapter(java.lang.reflect.Type, java.lang.Object)

Current annotation

- `com.google.gson.Gson.toJson(java.lang.Object, java.lang.reflect.Type)`
- `com.google.gson.Gson.fromJson(java.lang.String, java.lang.Class<T>)`

Reason category: old label missing core behavior

Explanation: while `registerTypeAdaptor` is mentioned in the test name, it is just a setup call. the core behavior can only be expressed in `toJson` and `fromJson`.

Classified differences

- SUBJECTIVE | Only in current annotation |
`com.google.gson.Gson.fromJson(java.lang.String, java.lang.Class<T>)`
- SUBJECTIVE | Only in current annotation | `com.google.gson.Gson.toJson(java.lang.Object, java.lang.reflect.Type)`
- SUBJECTIVE | Only in original human annotation |
`com.google.gson.GsonBuilder.registerTypeAdapter(java.lang.reflect.Type, java.lang.Object)`

Project: jfreechart

31. Test jfreechart::795

Test name: `testBug1126_c`

Current Test Name and Execution ID: `org.jfree.chart.plot.pie.PiePlotTest_testBug1126_c_7ff9d8cb`

Old Test Name: `org.jfree.chart.plot.PiePlotTest.testBug1126_c()`

Original human annotation

- `org.jfree.chart.plot.PiePlot.clone()`
- `org.jfree.chart.plot.PiePlot.getSectionOutlineStroke(Comparable)`
- `org.jfree.chart.plot.PiePlot.setSectionOutlineStroke(Comparable, Stroke)`

Current annotation

- `org.jfree.chart.plot.pie.PiePlot.clone()`
- `org.jfree.chart.plot.pie.PiePlot.setSectionOutlineStroke(K, java.awt.Stroke)`
- `org.jfree.chart.plot.pie.PiePlot.getSectionOutlineStroke(K)`

Reason category: version drift behavior change

Explanation: the API name updated.

Classified differences

- OBJECTIVE | Only in current annotation | `org.jfree.chart.plot.pie.PiePlot.clone()`
- OBJECTIVE | Only in current annotation |
`org.jfree.chart.plot.pie.PiePlot.getSectionOutlineStroke(K)`
- OBJECTIVE | Only in current annotation |
`org.jfree.chart.plot.pie.PiePlot.setSectionOutlineStroke(K, java.awt.Stroke)`
- OBJECTIVE | Only in original human annotation | `org.jfree.chart.plot.PiePlot.clone()`
- OBJECTIVE | Only in original human annotation |
`org.jfree.chart.plot.PiePlot.getSectionOutlineStroke(Comparable)`
- OBJECTIVE | Only in original human annotation |
`org.jfree.chart.plot.PiePlot.setSectionOutlineStroke(Comparable, Stroke)`

32. Test jfreechart::452

Test name: `testCloning`

Current Test Name and Execution ID:

`org.jfree.chart.labels.StandardCategoryToolTipGeneratorTest_testCloning_02e4ace9`

Old Test Name: `org.jfree.chart.labels.StandardCategoryToolTipGeneratorTest.testCloning()`

Original human annotation

- `org.jfree.chart.labels.AbstractCategoryItemLabelGenerator.clone()`

Current annotation

- `org.jfree.chart.labels.StandardCategoryToolTipGenerator.clone()`

Reason category: Unspecified

Explanation: as suggested by test name, this test is targetted `StandardCategoryToolTipGenerator` instead of the `abstractcategoryitemlabelgenerator`.

Classified differences

- OBJECTIVE | Only in current annotation |
`org.jfree.chart.labels.StandardCategoryToolTipGenerator.clone()`
- OBJECTIVE | Only in original human annotation |
`org.jfree.chart.labels.AbstractCategoryItemLabelGenerator.clone()`

33. Test `jfreechart::707`

Test name: `testCloning`

Current Test Name and Execution ID: `org.jfree.chart.plot.compass.PlumNeedleTest_testCloning_02e4ace9`

Old Test Name: `org.jfree.chart.needle.PlumNeedleTest.testCloning()`

Original human annotation

- `org.jfree.chart.needle.PlumNeedle.clone()`

Current annotation

- `org.jfree.chart.plot.compass.PlumNeedle.clone()`

Reason category: version drift behavior change

Explanation: the API function name updated.

Classified differences

- OBJECTIVE | Only in current annotation | `org.jfree.chart.plot.compass.PlumNeedle.clone()`
- OBJECTIVE | Only in original human annotation |
`org.jfree.chart.needle.PlumNeedle.clone()`

34. Test `jfreechart::1129`

Test name: `testHashCode`

Current Test Name and Execution ID: `org.jfree.chart.renderer.xy.XYBubbleRendererTest_testHashCode_181f3c6e`

Old Test Name: `org.jfree.chart.renderer.xy.XYBubbleRendererTest.testHashCode()`

Original human annotation

- `org.jfree.chart.renderer.AbstractRenderer.hashCode()`

Current annotation

- `org.jfree.chart.renderer.xy.AbstractXYItemRenderer.hashCode()`

Reason category: version drift behavior change

Classified differences

- OBJECTIVE | Only in current annotation |
`org.jfree.chart.renderer.xy.AbstractXYItemRenderer.hashCode()`
- OBJECTIVE | Only in original human annotation |
`org.jfree.chart.renderer.AbstractRenderer.hashCode()`

35. Test `jfreechart::2104`

Test name: `test788597`

Current Test Name and Execution ID: `org.jfree.data.xy.TableXYDatasetTest_test788597_6d0c29cf`

Old Test Name: `org.jfree.data.xy.TableXYDatasetTest.test788597()`

Original human annotation

- `org.jfree.data.xy.DefaultTableXYDataset.addSeries(org.jfree.data.xy.XYSeries<S>)`
- `org.jfree.data.xy.DefaultTableXYDataset.getItemCount()`
- `org.jfree.data.xy.DefaultTableXYDataset.removeAllSeries()`

Current annotation

- `org.jfree.data.xy.DefaultTableXYDataset.removeAllSeries()`

Reason category: old label contains probe

Explanation: the old label contains both probe and the setup. the test is to verify if the `removeAllSeries` can actually remove all the item in the dataset.

Classified differences

- SUBJECTIVE | Only in original human annotation |
`org.jfree.data.xy.DefaultTableXYDataset.addSeries(org.jfree.data.xy.XYSeries<S>)`
- SUBJECTIVE | Only in original human annotation |
`org.jfree.data.xy.DefaultTableXYDataset.getItemCount()`

36. Test `jfreechart::832`

Test name: `testCloning`

Current Test Name and Execution ID: `org.jfree.chart.renderer.LookupPaintScaleTest.testCloning_02e4ace9`

Old Test Name: `org.jfree.chart.renderer.LookupPaintScaleTest.testCloning()`

Original human annotation

- `org.jfree.chart.renderer.LookupPaintScale.add(double, java.awt.Paint)`
- `org.jfree.chart.renderer.LookupPaintScale.clone()`

Current annotation

- `org.jfree.chart.renderer.LookupPaintScale.clone()`

Reason category: old label contains setup method

Explanation: `add` is just use to check if the state mutation would affect the clone.

Classified differences

- SUBJECTIVE | Only in original human annotation |
`org.jfree.chart.renderer.LookupPaintScale.add(double, java.awt.Paint)`

37. Test `jfreechart::913`

Test name: `testDrawWithNullInfo`

Current Test Name and Execution ID:

`org.jfree.chart.renderer.category.GroupedStackedBarRendererTest.testDrawWithNullInfo_f39d2692`

Old Test Name: `org.jfree.chart.renderer.category.GroupedStackedBarRendererTest.testDrawWithNullInfo()`

Original human annotation

- `org.jfree.chart.JFreeChart.createBufferedImage(int, int, org.jfree.chart.ChartRenderingInfo)`

Current annotation

- `org.jfree.chart.renderer.category.GroupedStackedBarRenderer.drawItem(java.awt.Graphics2D, org.jfree.chart.renderer.category.CategoryItemRendererState, java.awt.geom.Rectangle2D, org.jfree.chart.plot.CategoryPlot, org.jfree.chart.axis.CategoryAxis, org.jfree.chart.axis.ValueAxis, org.jfree.data.category.CategoryDataset, int, int, int)`

Reason category: old label too shallow

Explanation: as suggested by the test case class name this test is used to test

`GroupedStackedBarRenderer` draw item functionality.

Classified differences

- SUBJECTIVE | Only in current annotation |
`org.jfree.chart.renderer.category.GroupedStackedBarRenderer.drawItem(java.awt.Graphics2D, org.jfree.chart.renderer.category.CategoryItemRendererState, java.awt.geom.Rectangle2D, org.jfree.chart.plot.CategoryPlot, org.jfree.chart.axis.CategoryAxis, org.jfree.chart.axis.ValueAxis, org.jfree.data.category.CategoryDataset, int, int, int)`
- SUBJECTIVE | Only in original human annotation |
`org.jfree.chart.JFreeChart.createBufferedImage(int, int, org.jfree.chart.ChartRenderingInfo)`

38. Test jfreechart::316

Test name: testNF

Current Test Name and Execution ID: org.jfree.chart.block.GridArrangementTest_testNF_bba22c4b

Old Test Name: org.jfree.chart.block.GridArrangementTest.testNF()

Original human annotation

- org.jfree.chart.block.BlockContainer.arrange(java.awt.Graphics2D, org.jfree.chart.block.RectangleConstraint)

Current annotation

- org.jfree.chart.block.GridArrangement.arrangeNF(org.jfree.chart.block.BlockContainer, java.awt.Graphics2D, org.jfree.chart.block.RectangleConstraint)

Reason category: old label too shallow

Explanation: as suggested by name this is to test arrangeNF not just arrange.

Classified differences

- SUBJECTIVE | Only in current annotation |
org.jfree.chart.block.GridArrangement.arrangeNF(org.jfree.chart.block.BlockContainer, java.awt.Graphics2D, org.jfree.chart.block.RectangleConstraint)
- SUBJECTIVE | Only in original human annotation |
org.jfree.chart.block.BlockContainer.arrange(java.awt.Graphics2D, org.jfree.chart.block.RectangleConstraint)

39. Test jfreechart::68

Test name: testSetSeriesToolTipGenerator

Current Test Name and Execution ID: org.jfree.chart.XYBarChartTest_testSetSeriesToolTipGenerator_8ab92898

Old Test Name: org.jfree.chart.XYBarChartTest.testSetSeriesToolTipGenerator()

Original human annotation

- org.jfree.chart.renderer.xy.AbstractXYItemRenderer.getToolTipGenerator(int, int)
- org.jfree.chart.renderer.xy.AbstractXYItemRenderer.setSeriesToolTipGenerator(int, org.jfree.chart.labels.XYToolTipGenerator)

Current annotation

- org.jfree.chart.renderer.xy.AbstractXYItemRenderer.setSeriesToolTipGenerator(int, org.jfree.chart.labels.XYToolTipGenerator)

Reason category: old label contains probe

Explanation: as suggested by test name, this is targeting setSeriesToolTipGenerator not the getter.

Classified differences

- SUBJECTIVE | Only in original human annotation |
org.jfree.chart.renderer.xy.AbstractXYItemRenderer.getToolTipGenerator(int, int)