STANDARD OPERATING PROCEDURE · BY ROLE

Admin

For: Admin (the site's owner of the app) · Full Harvest Inventory

This procedure is for the one or two people who own the app at the site: who set it up, keep it running, make the logins, and are called when nothing else works. It is the only role that opens **Settings**. The counting itself, the floor and the numbers are other roles' procedures; this one is about everything those roles need to be in place.

Printed October 20, 2026

Contents

1 — What only an admin can do 3

2 — Deploying and keeping the server 4

3 — Logins and profiles 5

4 — The site: name, logo, look, Teams, pallet system 7

5 — Scanners 8

6 — Lists, racking and the inventory report 10

7 — The count session and its settings 11

8 — Count day: what the admin does 12

9 — Closing, the ERP file, backups and the log 13

10 — A year of housekeeping 14

11 — When something goes wrong 15

1 — What only an admin can do

Everything on the **Settings** page, which no other profile opens. It has six sections: **Count setup** (the count-day check, the setup checklist, the count session), **Lists & racking**, **Scanners**, **Integrations** (ERP file, adjustment reasons, pallet system, Teams), **Backups & log** (with the OneDrive copy) and **Logins & site**. From there you:

- create, rename and delete **supervisor logins**, choose what each may do, **invite** a new one by email, and lift a **sign-in lock**;
- switch the parts of the app nobody needs yet **off for the whole site** (cycle counts, front bins, the map…) and back on;
- the **site name**, the **logo**, the **Teams channel**, the **pallet system** address;
- register and reset **scanners**; choose which **jobs** the scanners offer;
- upload the **bin list**, pair the **racking blocks**, upload the **inventory report**;
- create the **count session**, set its options and thresholds, run and end a **trial**, **close** and **delete** counts;
- the **ERP layouts** and the ERP file; **backups** and the **Google Drive** or **OneDrive** copy; the **adjustment reasons**; **the log**;
- run the **Ready for count day** check before every wall-to-wall.

A *supervisor* login does everything else. Keep the admin logins to the few who need them: an admin can delete a count.

The cards you set once — the counting-screen layout, the barcode test book, the comment, override, SOS and Report a problem lists, the adjustment reasons, the pallet system, Teams, OneDrive, What is switched on, Systems, site name, logo and look — are **folded** to their headings (a ▸ in front). Click a heading to open it; each computer remembers what you keep open, and a *Ready for count day* link or a search hit opens the card it points at.

2 — Deploying and keeping the server

- The app runs from one Docker image on **Railway** (or on a PC in the warehouse with `docker compose`). The manual's Step 1 and 2 have the exact steps; the short version: attach a **volume**, point `DB_PATH` at it, set `SUPERADMIN_USER`, `SUPERADMIN_NAME` and `SUPERADMIN_PASSWORD`, and `SITE_TIMEZONE`.
- The **superadmin** is made from those variables the first time the app starts. If every admin login is ever lost, set `SUPERADMIN_USER` to a new name and restart: a fresh admin appears.
- A **domain of your own** goes on under Railway → the service → Settings → Networking → Custom Domain; a subdomain takes a CNAME, the bare name needs a DNS host with CNAME flattening. After the change, re-open each scanner's link on the new address: an installed app is tied to the address it came from.
- One instance carries the site: the load test put twenty teams and twenty thousand bins through it with the dashboard under a second a refresh. Scale the instance up before thinking about more of them; the database is on the instance's volume.
- The **bare address** opens the supervisor sign-in. Scanners open their own links.

3 — Logins and profiles

Settings → Logins & site → Supervisor logins.

1. **Add a login**: username, full name and, best, their **email** — then **Email the invite** sends them a one-time link (good for three days) on which they choose their own password, from your own mail, with no password in the message. Without an email, a starter password (typed, or generated if left blank) is shown once; the first sign-in makes them replace it. **Invite again** makes a new link; the old one stops working.
2. Pick a **profile**, or tick pages and functions by hand:

PROFILE	PAGES	FUNCTIONS	FOR
Admin	everything, Settings included	all	you
Supervisor	everything but Settings	all	a senior supervisor
Inventory control	Dashboard, Testing Suite	approve adjustments, downloads	the inventory controller
Count supervisor	Dashboard, Teams & crew, Testing Suite	message the floor, answer SOS, queue aisles and raise second counts, downloads	whoever runs the floor
Warehouse jobs	Front bins, Not in Location, Cycle counts, Testing Suite	downloads	the day-to-day warehouse jobs
Cycle counter	Cycle counts, Testing Suite	—	a cycle counter at a desk
Custom	ticked by hand, down to a tab	ticked by hand	anything else

The **User guide** is open to every login whatever else it has.

1. Each login's **picker** shows only the kinds of count it may work: no *Cycle counts* page, no cycle counts in it; a cycle counter sees no full count.
2. Nobody but **the site admin** (the login the site started with) can change the site admin's account: another admin cannot reset its password, take its pages or switch it off.
3. A login's **tabs** can be narrower than its pages: *Dashboard → Progress and Reports* only, say. The checklist under each login shows every tab.

4. **Untick Active** to stop a login; its sign-ins end at once. **Reset password** gives a new starter password. Changing either ends every sign-in that login holds.
5. **Locked out?** Five wrong passwords from one place lock that login there for 15 minutes (twenty from one place lock the place). The row shows *locked*; **Unlock** lifts it, and so does a password reset.
6. Sign-ins last 30 days from last use and survive a restart. **Log out** ends one, and the next person to sign in on that computer starts fresh on the dashboard, not where the last one left off.

What is switched on — the card above the logins. A team with a few days to learn the count does not need cycle counts, front bins or the map in front of it. **Full counts and second counts only** hides Cycle counts, Front bins, Not in Location, the Map, Adjustments and Reports for every login, admins included — the sidebar, the dashboard tabs, the search box and the scanners' sign-on screen all follow — and keeps Alerts (an SOS needs an answer) and the Testing Suite (where the count is practiced). Tick by hand and **Save** for anything in between; **Everything on** brings it all back. Hidden is not forbidden: roles still apply, nothing is deleted, a bookmark to a hidden page says so, and the job ticks under Scanners are kept, grayed, for when their part comes back. Always on: Progress, Team plan, Second counts, Full Counts, Teams & crew, Settings, the guide.

Each role has a procedure of its own in `docs/roles/`; hand a new login the right one.

4 — The site: name, logo, look, Teams, pallet system

Site name, logo and look under **Settings → Logins & site**; Teams and the pallet system under **Settings → Integrations**. On a phone, *Add to Home Screen* on any office page installs the office side as its own app (*FH Office*), with a Menu button in place of the side panel.

- **Site name**: the app's name and the location under it. A change lands at once on every sidebar, the sign-in screen, the window titles, the scanner app's header, the office board and the installed app's manifest. Blank name = back to *Full Harvest Inventory*.
- **Logo**: PNG, JPEG, WebP, GIF or SVG under about 400 KB; across the top of the sidebar, and on the scanners if ticked.
- **Appearance**: themes, accents, text size, density, corners, sidebar width, contrast. Per computer, not per login.
- **Microsoft Teams channel**: a Workflows webhook address. SOS and stopped-scanning alerts post a card there as well as on the dashboard. **Send a test card** before count day; Microsoft is retiring the old *Incoming Webhook* connectors.
- **Pallet system**: the web address of the system the pallets live in, with `{pallet}`, `{from}`, `{to}` in it so each pallet opens on its own record, and **how it opens**: framed under the desks, **through this app** (framed too, but fetched by this server and shown as part of this site, so a sign-in that will not stick in a plain frame sticks — the usual choice for an ASP.NET or in-house system the server can reach), or in its own window (when it cannot). **Check the address** reads the system's headers and says which it needs.

5 — Scanners

Settings → Scanners.

- **Scanner setup**: add a scanner by name; open its link (`/?d=…`) on the device once, then install the app from Chrome's menu or the button on the sign-on screen. The link is a key: **Reset link** issues a new one and kills the old; removing a scanner stops it. **Print setup cards** gives one QR card per scanner for the cradles. A link used more than once is flagged, which is normal after a wipe and worth a look otherwise.
- **Jobs on the sign-on screen** (in *What the scanners offer*): the scanners show exactly what is ticked: full count, cycle count, Front2Back, Not in Location (NIL). Day to day tick the last three; on the morning of a wall-to-wall untick them and tick the full count alone; swap back after. At least one stays on. The practice gun has its own ticks in the Testing Suite's sandbox, all four to start with.
- **The picker opens on the right count.** An open full count first (the one the scanners land on, else the newest), else an open cycle count; and it lists only the kinds the site has switched on.
- **Systems** (Settings → Logins & site → Systems): LIVE is the home; add TEST with its address, tick who may use it, and whether the scanners may switch. TEST is the app deployed again with its own database and three variables (`SYSTEM_NAME`, `SYSTEM_HOME_URL`, `SYSTEM_LINK_KEY`) — the steps are on the card. People switch from the sidebar; scanners from the sign-on screen. Tick who may use TEST in the **Systems** column of Supervisor logins; logins are made on LIVE only and go with the person when they switch. If **Back to LIVE** says *this system's own address*, TEST's `SYSTEM_HOME_URL` holds TEST's address: set it to LIVE's and redeploy TEST.
- **Report a problem** (Settings → Scanners → What the scanners offer): the kinds of problem the gun offers, their reasons, and what each makes the counter scan to confirm — the bin, the pallet, either, or nothing. Add your own, take any off, or restore the shipped list.
- **Practice counts stay out of the picker.** Nobody's practice count from the Testing Suite is in a dashboard's picker, yours included. **Learn → Practice data** — admins only — lists every login's practice in one place: who has practiced, each run with what was tried and how far it got, an export of one person's lot, and Delete to start them fresh.
- **How the counting screen is put together**: the order of the questions (pallet, quantity, lot, expiry, bin, comments), text size, language, the Keyboard button, *Keep it upright*, *Update itself after a deploy*, *Show the next bin in the aisle*. The preview is the real screen size.
- **What the scanners offer**: one section with one Save: the jobs, the comments (ask or not, required or not, the wait before the step moves on, the one-tap reasons), the override reasons and the SOS list.
- **DataWedge** on each Zebra sends ENTER (or TAB) after a scan; without it a scan does nothing. The manual's DataWedge section has the profile.

Settings reach a running gun within about half a minute, between pallets. A new version of the app needs a reload: with *Update itself after a deploy* on it does that by itself.

6 — Lists, racking and the inventory report

Settings → Lists & racking.

1. **Bin list**: one column of bin codes, or the site's own export, uploaded by you — no bin list ships with the app, so a new installation starts empty. The aisles come from it.
2. **Aisles & racking blocks**: pair the aisles that share a rack. The guided setup marks blocks as wanted; without them two teams can meet on one rack.
3. **Inventory report**: the site's export as it comes, one upload per system, naming the **System**. Read the upload summary: merged rows, duplicates, open bins, zero and negative quantities. Hand it to inventory control; it is theirs to accept. *Replace what is there* re-uploads a fresh report over the old.

Both uploads are per count. The guided setup card says what the count still lacks.

7 — The count session and its settings

Settings → Count setup → Count session.

- **New count**: from **Full Counts → New count** (a full count) or *Cycle counts → Program* (the year's cycle session); the Count session card does both too. **Full Counts** also lists every wall-to-wall with its progress, **Scanners land here**, **Close** / **Reopen**, and a **Set-up** tab for what a count still needs.
- **Options**: pallet check (*off*, *warn*, *strict*), guided bins, comments, the **map drawing**, auto second counts with **Recount over N units / or over N %** and a **cap**, **Adjustments need approval** with its own threshold, **Show on the scanners**, and the **default** count the guns land on.
- **Trial run**: counts for real on the dashboard, exports nothing to the ERP; **End the trial** wipes it so the real count starts from zero on the same setup.
- **Counting plan**: on Teams & crew. The count supervisor usually owns it.
- **Close session** when inventory control says so. **Delete** is separate, needs the count closed and its name typed, and takes a backup first.

Agree the thresholds and the approval setting with inventory control before the count starts. Their procedure says what they will ask for.

8 — Count day: what the admin does

The afternoon before, and first thing: open **Settings → Count setup → Ready for count day** and clear every red line, and every amber one you can. It checks the jobs on the scanners (the full count alone), the scanners, the crew list, the alerts, the backups and the OneDrive copy, and a default password. Each line's button opens the card that fixes it.

Then, usually little. Be reachable for:

- a scanner that needs its link reset or re-registered;
- a setting that turns out wrong: thresholds at 0 flooding the second-count list, approvals that should have been on, a job that should be hidden on the guns;
- a login that needs a function it was not given;
- the Teams channel, if cards stop arriving.

The count supervisor runs the floor; inventory control reads the numbers. Both procedures say when they will come to you.

9 — Closing, the ERP file, backups and the log

Settings → Integrations (the ERP file, adjustment reasons) and **Settings → Backups & log**.

- **Send to the ERP**: pick the layout and the system, **Preview**, **Download CSV**. The preview says how many adjustments it held back for approval; inventory control reads it with you. A trial refuses to export.
- **Adjustment reasons**: the list inventory control picks from when approving; match it to the ERP's own codes.
- **ERP layouts**: column names and which rows go in; add a layout rather than editing a file afterwards.
- **Filed as the count goes** (Dashboard → Reports) writes every handed-back aisle to an `exports` folder beside the backups, and the **final report** every sheet of Export everything once the count is whole. Copy that folder off the server with the backup.
- **Back up now** before and after anything large; the app also keeps a daily backup and the last fourteen on its volume. A volume is not an archive: connect **Off-site copy: Google Drive** (an Apps Script in your own Google account — nothing for IT) or **OneDrive** (needs an Azure app registration) once — the steps are on each card — and every backup is copied there too — with each daily backup, or every 12, 6, 2 hours or every hour during a count. Without it, **Download** one after every count.
- **Export the log** for an auditor: every supervisor action, who and when.

10 — A year of housekeeping

- After each count: close it, export everything with inventory control, download a backup.
- Each quarter: review the logins (leavers off, profiles still right), the SOS reasons and the adjustment reasons, the Teams channel with a test card.
- Before each wall-to-wall: a trial run with the crew, the bin list refreshed, the scanners charged and up to date, *Jobs on the scanners* set to the full count alone.
- The cycle-count session runs all year; do not replace it.
- Keep `docs/SOP.pdf` and the role procedures where the supervisors can find them, and the **User guide** in the sidebar is the same text inside the app.

11 — When something goes wrong

WHAT YOU SEE	WHAT IT MEANS	WHAT TO DO
Nobody can sign in	The admin logins were lost	Set `SUPERADMIN_USER` to a new name in the server variables and restart
Everyone was signed out	A normal restart does not do this; a lost database volume does	Check the volume on the host
Gun: *this scanner is no longer authorized*	Its link was reset or it was removed	Reset link, open the new link on it
Gun: *this scanner link is not registered*	A link that was never created here, or the server was reset	Add the scanner again
A scan does nothing on a handheld	DataWedge is not sending ENTER	DataWedge → Basic data formatting → send ENTER
An SOS did not reach Teams	Address wrong, expired, or Teams down	The dashboard still has it; send a test card; make a Workflows webhook
A pallet system will not show under the move desk	It refuses to be framed	Nothing to fix: the desk offers Open in a new tab
The second-count list is enormous	Thresholds at 0	Count session → Recount over, or over %, and a cap
A gun does not offer a job	It is unticked under Jobs on the scanners	Tick it back on
The app still shows the old name somewhere	A scanner or the board has not refreshed	They pick it up on their next refresh; an installed icon's name updates on reinstall
A count was deleted by mistake	A backup was taken before the delete	Restore it under Backups & log
You do not know what a message means	—	Paste it into **User guide → Ask the guide**