SIV



${f S}$ ysteme ${f I}$ ntegration ${f V}$ ertrieb Elektronische Bauteile

Ferritringe

Material 43

| Тур | Σℓ/A(cm ⁻¹) | ℓ _e (cm) | A _e (cm ²) | V _e (cm ³) | A _∟ (nH)±25% |
|-----------|-------------------------|---------------------|-----------------------------------|-----------------------------------|-------------------------|
| FT-23-43 | 63.8 | 1.30 | 0.020 | 0.027 | 158 |
| FT-37-43 | 28.6 | 2.07 | 0.072 | 0.15 | 350 |
| FT-50-43 | 22.9 | 2.95 | 0.129 | 0.38 | 440 |
| FT-82-43 | 21.3 | 5.2 | 0.243 | 1.26 | 470 |
| FT-114-43 | 19.8 | 7.3 | 0.37 | 2.70 | 510 |
| FT-140-43 | 11.2 | 8.9 | 0.79 | 7.0 | 885 |
| FT-240-43 | 9.2 | 14.5 | 1.58 | 22.8 | 1075 |

Material 61

| Тур | Σℓ/A(cm ⁻¹) | ℓ _e (cm) | A _e (cm ²) | V _e (cm ³) | A _∟ (nH)±25% |
|-----------|-------------------------|---------------------|-----------------------------------|-----------------------------------|-------------------------|
| FT-23-61 | 63.8 | 1.30 | 0.020 | 0.027 | 25 |
| FT-37-61 | 28.6 | 2.07 | 0.072 | 0.15 | 55 |
| FT-50-61 | 22.9 | 2.95 | 0.129 | 0.38 | 69 |
| FT-82-61 | 21.3 | 5.2 | 0.243 | 1.26 | 75 |
| FT-114-61 | 19.8 | 7.3 | 0.37 | 2.70 | 80 |
| FT-140-61 | 11.2 | 8.9 | 0.79 | 7.0 | 140 |
| FT-240-61 | 9.2 | 14.5 | 1.58 | 22.8 | 170 |

Material 77

| Тур | Σℓ/A(cm ⁻¹) | ℓ _e (cm) | A _e (cm ²) | V _e (cm ³) | A _∟ (nH)±25% |
|-----------|-------------------------|---------------------|-----------------------------------|-----------------------------------|-------------------------|
| FT-23-77 | 63.8 | 1.30 | 0.020 | 0.027 | 390 |
| FT-37-77 | 28.6 | 2.07 | 0.072 | 0.15 | 880 |
| FT-50-77 | 22.9 | 2.95 | 0.129 | 0.38 | 1100 |
| FT-82-77 | 21.3 | 5.2 | 0.243 | 1.26 | 1175 |
| FT-114-77 | 19.8 | 7.3 | 0.37 | 2.70 | 1275 |
| FT-140-77 | 11.2 | 8.9 | 0.79 | 7.0 | 2250 |
| FT-240-77 | 9.2 | 14.5 | 1.58 | 22.8 | 2725 |

16.08.2006