

Activity No. 4.2 Strings	
Course Code: CPE 103	Program: Computer Engineering
Course Title: Object Oriented Programming	Date Performed: April 12, 2025
Section: 1-A	Date Submitted: April 17, 2025
Name: Directo, Hannah Thea B.	Instructor: Engr. Maria Rizette Sayo
1. Objective(s)	
This activity aims to demonstrate the students' understanding of strings implementation in solving problems.	
2. Intended Learning Outcomes (ILOs)	
After this module, the students should be: <ul style="list-style-type: none"> Demonstrate the implementation of strings in different use cases and acquire skills in solving difficult problems using strings. 	
3. Discussion	
<p>A string is a sequence</p> <p>A string is a <i>sequence</i> of characters. You can access the characters one at a time with the bracket operator:</p> <pre>>>> fruit = 'banana' >>> letter = fruit[1]</pre> <p>The second statement extracts the character at index position 1 from the fruit variable and assigns it to the letter variable.</p> <p>The expression in brackets is called an <i>index</i>. The index indicates which character in the sequence you want (hence the name).</p> <p>But you might not get what you expect:</p> <pre>>>> print(letter) a</pre> <p>For most people, the first letter of “banana” is “b”, not “a”. But in Python, the index is an offset from the beginning of the string, and the offset of the first letter is zero.</p> <pre>>>> letter = fruit[0] >>> print(letter) b</pre> <p>So “b” is the 0th letter (“zero-th”) of “banana”, “a” is the 1th letter (“one-th”), and “n” is the 2th (“two-th”) letter.</p> <p>String Indexes</p> <p>You can use any expression, including variables and operators, as an index, but the value of the index has to be an integer. Otherwise you get:</p> <pre>>>> letter = fruit[1.5] TypeError: string indices must be integers</pre> <p>Getting the length of a string using len</p> <p>len is a built-in function that returns the number of characters in a string:</p> <pre>>>> fruit = 'banana' >>> len(fruit) 6</pre> <p>To get the last letter of a string, you might be tempted to try something like this:</p> <pre>>>> length = len(fruit)</pre>	

```
>>> last = fruit[length]
```

IndexError: string index out of range

The reason for the IndexError is that there is no letter in “banana” with the index 6. Since we started counting at zero, the six letters are numbered 0 to 5. To get the last character, you have to subtract 1 from length:

```
>>> last = fruit[length-1]
```

```
>>> print(last)
```

a

Alternatively, you can use negative indices, which count backward from the end of the string. The expression `fruit[-1]` yields the last letter, `fruit[-2]` yields the second to last, and so on.

Traversal through a string with a loop

A lot of computations involve processing a string one character at a time. Often they start at the beginning, select each character in turn, do something to it, and continue until the end. This pattern of processing is called a *traversal*. One way to write a traversal is with a while loop:

```
index = 0
```

```
while index < len(fruit):
```

```
    letter = fruit[index]
```

```
    print(letter)
```

```
    index = index + 1
```

This loop traverses the string and displays each letter on a line by itself. The loop condition is `index < len(fruit)`, so when `index` is equal to the length of the string, the condition is false, and the body of the loop is not executed. The last character accessed is the one with the index `len(fruit)-1`, which is the last character in the string.

Another way to write a traversal is with a for loop:

```
for char in fruit:
```

```
    print(char)
```

Each time through the loop, the next character in the string is assigned to the variable `char`. The loop continues until no characters are left.

String slices

A segment of a string is called a *slice*. Selecting a slice is similar to selecting a character:

```
>>> s = 'Monty Python'
```

```
>>> print(s[0:5])
```

Monty

```
>>> print(s[6:12])
```

Python

The operator `[n:m]` returns the part of the string from the “n-th” character to the “m-th” character, including the first but excluding the last.

If you omit the first index (before the colon), the slice starts at the beginning of the string. If you omit the second index, the slice goes to the end of the string:

```
>>> fruit = 'banana'
```

```
>>> fruit[:3]
```

'ban'

```
>>> fruit[3:]
```

'ana'

If the first index is greater than or equal to the second the result is an *empty string*, represented by two quotation marks:

```
>>> fruit = 'banana'
>>> fruit[3:3]
''
```

An empty string contains no characters and has length 0, but other than that, it is the same as any other string.

Strings are immutable

It is tempting to use the operator on the left side of an assignment, with the intention of changing a character in a string. For example:

```
>>> greeting = 'Hello, world!'
>>> greeting[0] = 'J'
```

TypeError: 'str' object does not support item assignment

The “object” in this case is the string and the “item” is the character you tried to assign. For now, an *object* is the same thing as a value, but we will refine that definition later. An *item* is one of the values in a sequence.

The reason for the error is that strings are *immutable*, which means you can't change an existing string.

The best you can do is create a new string that is a variation on the original:

```
>>> greeting = 'Hello, world!'
>>> new_greeting = 'J' + greeting[1:]
>>> print(new_greeting)
```

Jello, world!

This example concatenates a new first letter onto a slice of greeting. It has no effect on the original string.

Looping and counting

The following program counts the number of times the letter “a” appears in a string:

```
word = 'banana'
count = 0
for letter in word:
    if letter == 'a':
        count = count + 1
print(count)
```

This program demonstrates another pattern of computation called a *counter*. The variable count is initialized to 0 and then incremented each time an “a” is found. When the loop exits, count contains the result: the total number of a's.

The in operator

The word in is a boolean operator that takes two strings and returns True if the first appears as a substring in the second:

```
>>> 'a' in 'banana'
True
>>> 'seed' in 'banana'
False
```

String comparison

The comparison operators work on strings. To see if two strings are equal:

```
if word == 'banana':
```

```
    print('All right, bananas.')
```

Other comparison operations are useful for putting words in alphabetical order:

```
if word < 'banana':
```

```
    print('Your word,' + word + ', comes before banana.')
```

```
elif word > 'banana':
```

```
    print('Your word,' + word + ', comes after banana.')
```

```
else:
```

```
    print('All right, bananas.')
```

Python does not handle uppercase and lowercase letters the same way that people do. All the uppercase letters come before all the lowercase letters, so:

Your word, Pineapple, comes before banana.

A common way to address this problem is to convert strings to a standard format, such as all lowercase, before performing the comparison. Keep that in mind in case you have to defend yourself against a man armed with a Pineapple.

String methods

Strings are an example of Python *objects*. An object contains both data (the actual string itself) and *methods*, which are effectively functions that are built into the object and are available to any *instance* of the object.

Python has a function called `dir` which lists the methods available for an object. The `type` function shows the type of an object and the `dir` function shows the available methods.

```
>>> stuff = 'Hello world'
```

```
>>> type(stuff)
```

```
<class 'str'>
```

```
>>> dir(stuff)
```

```
[... 'capitalize', 'casefold', 'center', 'count', 'encode',  
'endswith', 'expandtabs', 'find', 'format', 'format_map',  
'index', 'isalnum', 'isalpha', 'isdecimal', 'isdigit',  
'isidentifier', 'islower', 'isnumeric', 'isprintable',  
'isspace', 'istitle', 'isupper', 'join', 'ljust', 'lower',  
'lstrip', 'maketrans', 'partition', 'replace', 'rfind',  
'rindex', 'rjust', 'rpartition', 'rsplit', 'rstrip',  
'split', 'splitlines', 'startswith', 'strip', 'swapcase',  
'title', 'translate', 'upper', 'zfill']
```

```
>>> help(str.capitalize)
```

Help on method_descriptor:

```
capitalize(self, /)
```

Return a capitalized version of the string.

More specifically, make the first character have upper case and the rest lower case.

```
>>>
```

While the `dir` function lists the methods, and you can use `help` to get some simple documentation on a method.

Calling a *method* is similar to calling a function (it takes arguments and returns a value) but the syntax is different. We call a method by appending the method name to the variable name using the period as a delimiter.

For example, the method `upper` takes a string and returns a new string with all uppercase letters: Instead of the function syntax `upper(word)`, it uses the method syntax `word.upper()`.

```
>>> word = 'banana'
>>> new_word = word.upper()
>>> print(new_word)
```

BANANA

This form of dot notation specifies the name of the method, `upper`, and the name of the string to apply the method to, `word`. The empty parentheses indicate that this method takes no argument.

A method call is called an *invocation*; in this case, we would say that we are invoking `upper` on the `word`. For example, there is a string method named `find` that searches for the position of one string within another:

```
>>> word = 'banana'
>>> index = word.find('a')
>>> print(index)
1
```

In this example, we invoke `find` on `word` and pass the letter we are looking for as a parameter.

The `find` method can find substrings as well as characters:

```
>>> word.find('na')
2
```

It can take as a second argument the index where it should start:

```
>>> word.find('na', 3)
4
```

One common task is to remove white space (spaces, tabs, or newlines) from the beginning and end of a string using the `strip` method:

```
>>> line = ' Here we go '
>>> line.strip()
'Here we go'
```

Some methods such as *startswith* return boolean values.

```
>>> line = 'Have a nice day'
>>> line.startswith('Have')
True
```

```
>>> line.startswith('h')
False
```

You will note that `startswith` requires case to match, so sometimes we take a line and map it all to lowercase before we do any checking using the `lower` method.

```
>>> line = 'Have a nice day'
>>> line.startswith('h')
False
```

```
>>> line.lower()
'have a nice day'
```

```
>>> line.lower().startswith('h')
```

```
True
```

In the last example, the method `lower` is called and then we use `startswith` to see if the resulting lowercase string starts with the letter “h”. As long as we are careful with the order, we can make multiple method calls in a single expression.

Parsing strings

Often, we want to look into a string and find a substring. For example if we were presented a series of lines formatted as follows:

```
From stephen.marquard@uct.ac.za Sat Jan  5 09:14:16 2008
```

and we wanted to pull out only the second half of the address (i.e., `uct.ac.za`) from each line, we can do this by using the `find` method and string slicing.

First, we will find the position of the at-sign in the string. Then we will find the position of the first space *after* the at-sign. And then we will use string slicing to extract the portion of the string which we are looking for.

```
>>> data = 'From stephen.marquard@uct.ac.za Sat Jan  5 09:14:16 2008'
```

```
>>> atpos = data.find('@')
```

```
>>> print(atpos)
```

```
21
```

```
>>> spos = data.find(' ',atpos)
```

```
>>> print(spos)
```

```
31
```

```
>>> host = data[atpos+1:spos]
```

```
>>> print(host)
```

```
uct.ac.za
```

```
>>>
```

We use a version of the `find` method which allows us to specify a position in the string where we want find to start looking. When we slice, we extract the characters from “one beyond the at-sign through up to *but not including* the space character”.

Formatted String Literals

A formatted string literal (often referred to simply as an f-string) allows Python expressions to be used within string literals. This is accomplished by prepending an `f` to the string literal and enclosing expressions in curly braces `{}`.

For example, wrapping a variable name in curly braces inside an f-string will cause it to be replaced by its value:

```
>>> camels = 42
```

```
>>> f'{camels}'
```

```
'42'
```

The result is the string `'42'`, which is not to be confused with the integer value `42`.

An expression can appear anywhere in the string, so you can embed a value in a sentence:

```
>>> camels = 42
```

```
>>> f'I have spotted {camels} camels.'
```

```
'I have spotted 42 camels.'
```

Several expressions can be included within a single string literal in order to create more complex strings.

```
>>> years = 3
```

```
>>> count = .1
>>> species = 'camels'
>>> f'In {years} years I have spotted {count} {species}.'
'In 3 years I have spotted 0.1 camels.'
```

Reference:

PY4E - Python for everybody. (n.d.). <https://www.py4e.com/html3/06-strings>

4. Materials and Equipment

To properly perform this activity, the student must have:

- Python
- Spyder IDE
- Jupyter Notebook

5. Procedure

1. Open the Anaconda.
2. Use the jupyter notebook and follow the instructions below.
3. Provide a screenshot for every test case in each code and insert in the Output section with a corresponding description and observation.

A string is a sequence

```
[ ] fruit = 'banana'
    letter = fruit[1]
```

```
[ ] print(letter)
```

```
[ ] letter = fruit[0]
    print(letter)
```

```
[ ] letter = fruit[1.5]
```

Getting the length of a string using len

```
[ ] fruit = 'banana'
    len(fruit)
```

```
[ ] length = len(fruit)
    last = fruit[length]
```

```
[ ] last = fruit[length-1]
    print(last)
```

Traversal through a string with a loop

```
[ ] index = 0
    while index < len(fruit):
        letter = fruit[index]
        print(letter)
        index = index + 1
```

```
[ ] for char in fruit:
    print(char)
```

String slices

```
[ ] s = 'Monty Python'
    print(s[0:5])
```

```
[ ] print(s[6:12])
```

```
[ ] fruit = 'banana'
    fruit[:3]
```

```
[ ] fruit[3:]
```

```
[ ] fruit = 'banana'
    fruit[3:3]
```


Strings are immutable

```
[ ] greeting = 'Hello, world!'
    greeting[0] = 'J'
```

```
[ ] greeting = 'Hello, world!'
    new_greeting = 'J' + greeting[1:]
    print(new_greeting)
```

Looping and counting

```
[ ] word = 'banana'
    count = 0
    for letter in word:
        if letter == 'a':
            count = count + 1
    print(count)
```

6. Output

Refer to this link: [LAB 4.2.ipynb - Colab](#)

Provide an output of your work here. (include an analyzation for every screenshot or output)

A string is a sequence

```
fruit = 'banana'
letter = fruit[1]

[ ] print(letter)

↵ a

[ ] letter = fruit[0]
print(letter)

↵ b

letter = fruit[1.5]

↵ -----
TypeError                                 Traceback (most recent call last)
<ipython-input-6-bb89ba6efbbd> in <cell line: 0>()
----> 1 letter = fruit[1.5]

TypeError: string indices must be integers, not 'float'
```

Analysis: In Python, strings are indexed starting from 0. For example, `fruit = 'banana'` assigns the string to `fruit`. `fruit[1]` accesses the second character, 'a', and `fruit[0]` accesses the first character, 'b'. However, using a non-integer index, like `fruit[1.5]`, causes a `TypeError` because string indices must be integers.

Getting the length of a string using len

```
[ ] fruit = 'banana'
len(fruit)

↵ 6

[ ] length = len(fruit)
last = fruit[length]

↵ -----
IndexError                                 Traceback (most recent call last)
<ipython-input-8-4dd85e09c2d1> in <cell line: 0>()
      1 length = len(fruit)
----> 2 last = fruit[length]

IndexError: string index out of range

[ ] last = fruit[length-1]
print(last)

↵ a
```

Analysis: This code shows how to get the length of a string in Python. `len("banana")` gives 6, which is the number of letters. Trying to use 6 as an index gives an error because Python counts from 0. To get the last letter, use `fruit[length - 1]`, so for "banana", it's `fruit[5]`, which gives 'a'.

Traversal through a string with a loop

```
[ ] index = 0
    while index < len(fruit):
        letter = fruit[index]
        print(letter)
        index = index + 1
```

⇒
b
a
n
a
n
a

```
[ ] for char in fruit:
    print(char)
```

⇒
b
a
n
a
n
a

Analysis: This code shows two ways to print each letter in a string: The first way uses a while loop, which goes through each letter one by one, starting from 0 and printing each letter of "banana". The second way uses a for loop, which automatically goes through each letter in "banana" and prints it.

String Slices

```
[ ] s = 'Monty Python'
    print(s[0:5])
```

⇒ Monty

```
[ ] print(s[6:12])
```

⇒ Python

```
[ ] fruit = 'banana'
    fruit[:3]
```

⇒ 'ban'

```
[ ] fruit[3:]
```

⇒ 'ana'

```
[ ] fruit = 'banana'
    fruit[3:3]
```

⇒ ''

Analysis: This code shows how to slice strings in Python, which access parts of a string by specifying start and end positions.

String immutable

```
[ ] greeting = 'Hello, World!'
greeting[0] = 'J'
```



```
-----
TypeError                                 Traceback (most recent call last)
<ipython-input-18-7271656728c4> in <cell line: 0>()
      1 greeting = 'Hello, World'
----> 2 greeting[0] = 'J'

TypeError: 'str' object does not support item assignment
```

```
[ ] greeting = 'Hello, World!'
new_greeting = 'J' + greeting [1:]
print(new_greeting)
```



```
Jello, World!
```

Analysis: This code shows that strings in Python can't be changed directly. If you try to change a character, it will cause an error. Instead, you need to create a new string with the changes you want.

Looping and Counting

```
word = 'banana'
count = 0
for letter in word:
    if letter == 'a':
        count = count + 1
print(count)
```



```
3
```

Analysis: This code shows how to count how many times a letter appears in a string. After checking all the letters, it prints the final count

7. Supplementary Activity

Solve the following problems:

1. Take the following Python code that stores a string:

```
str = 'CPE-CPE009A-2025: 0.8475'
```

Use find and string slicing to extract the portion of the string after the colon character and then use the float function to convert the extracted string into a floating point number.

*Insert the code and the output here with the corresponding analyzation.

```
str = 'CPE_CPE009A-2025: 0.8475'
print(float(str[19:]))
```

0.8475

Analyzation: This code shows how to get a number from a string and turn it into a float. It uses slicing to pick out the number from the string, then converts it to a float using the float() function. The code assumes the number is always in the same place, so if the string format changes, the code would need to be updated to work correctly.

2. Write a python program that asks the user for their first name and convert it in to as a string. Print out the 3 words middle of the name using slice.

*Insert the code and the output here with the corresponding analyzation.

```
name = input("Enter your first name: ")
middle = len(name) // 2

middle = name[middle - 1 : middle + 2]
print(f"The middle 3 letters of '{name}' are '{middle}'.")
```

Enter your first name: Hannah
The middle 3 letters of 'Hannah' are 'nna'.

Analyzation: This code shows how to get the middle three letters from a name using string slicing. It finds the middle position, then takes one letter before and two after that point.

8. Conclusions/Observations

In this activity, we learned basic string operations in Python, like accessing characters, slicing, and using loops. We discovered that strings start at index 0, and trying to use non-integer indices causes errors. Since strings can't be changed directly, we create new ones instead. We also used methods like upper() and find() to work with strings, and learned how to compare them. Overall, this activity helped us understand how to manipulate and analyze strings in Python.

9. Assessment Rubric

