

Dissertation

[TODO: create cover, add boilerplate stuff]

Acknowledgements

[TODO: write; may be added after uploading dissertation to MyPhD]

Table of contents

Acknowledgements	2
Samenvatting	5
Glossary	6
Introduction	6
Why this dissertation?	6
What is this dissertation about?	6
What is MI?	7
What is FCS?	8
Building and evaluating imputation models	11
Evaluating imputations	11
What is computational evaluation?	13
Why should we care about computational evaluation of imputation methodology?	14
What is the scope of this dissertation?	15
Chapters	16
Introducing chapter 1: evaluation	16
Introducing chapter 2: convergence	16
Introducing chapter 3: ggmice	17
Indicators for adoption: how is the software already used?	17
Design principles	17
Limitations	18
What does ggmice aim to solve?	18
Existing solutions	18
Software development	19
Future research & development	19
Chapter 1: evaluation	21
Chapter 2: convergence	22
Chapter 3: ggmice	23
Discussion	24
Conclusion	24
Limitations	24
Outlook	25
References	27

[TODO: fix which sections are included]

Samenvatting

[TODO: write; may be added after uploading dissertation to MyPhD]

Glossary

- complete
- imputed
- missing
- observed
- synthetic

Introduction

Why this dissertation?

[Idea by Hidde: personal relevance to draw the reader in. Not just scientific and societal relevance of research, but also: why me?]

- My motivation is to contribute to trust in science. How? By showing uncertainty in data analysis efforts/inferences/graphs
- Methodology and statistics as a tool for expressing/quantifying uncertainty.
- While it is also a research discipline in itself, we develop tools that are domain-agnostic.
- I want to contribute methodology that facilitates social and biomedical scientists in drawing valid inferences.

What is this dissertation about?

[TODO: add take-home message in 1-2 sentences without jargon]

- Algorithms are everywhere.
- How can we know when to trust the output of algorithms?
 - Theoretical properties: analytically (often impossible)
 - Empirical performance: via simulation studies ('in silico'; the standard, but not standardized)
 - In practice/applied use: evaluate output, sensitivity analyses, ...? (very ad hoc, not systematic)
- In this dissertation, I investigate how the quality of the output of *imputation* algorithms can be evaluated: algorithms with the purpose of generating plausible values that may replace missing values in incomplete data.

Missing data problems are timeless, but technological advances have made treating missingness easier than ever. A single line of code can seem to solve your missing data problem nowadays. But is that solution really what you expect? That is what my dissertation is about.

This practice of drawing inference by replacing missing values with synthetic substitutes is called ‘multiple imputation’. Multiple imputation is a popular and flexible procedure that separates the missing data problem from the analysis of scientific interest. Imputation allows data analysts to first solve for the missingness, to then be able to analyze the completed data as if they were completely observed.

Although imputation is widely supported with software, and many implementations of the method have convenient defaults, generating *good* imputations is not a trivial task. Evaluating whether these imputations should be trusted remains challenging. In this dissertation, I set out to investigate what is needed to develop, apply, and evaluate data-generating algorithms. I thereby focus on the imputation procedure ‘MICE’ as implemented in the R package *mice*.

TODO: add image for missingness/imputation?

[TODO: add aim of bridging inferential evaluation and data-/algorithm-level diagnostics for imputation methods. current evaluation practices (simulation design, convergence diagnostics, visual diagnostics) are fragmented and insufficient.]

What is MI?

- MI = replace each missing value with a synthetic substitute multiple times.
- For each missing datapoint, we draw samples from a distribution of values that *might have* been (posterior predictive distribution).
- this generates several imputations: *completed* datasets.
- completed data can be analyzed as if the data were complete to begin with.
- obtain estimates of the analysis of scientific interest on each imputation.
- estimates are then combined to obtain one pooled estimate [TODO: add SI?].
- the variance of the estimate incorporates not just the sampling variance (within each imputation) but also added variance due to non-response (between imputation variance and simulation error).
- the variability between imputations reflects uncertainty due to the missingness.
- [TODO: why single imputation may yield implausible inference]

TODO: add image MI workflow

What is FCS?

[TODO: reframe as ‘Why MI in the flavor of mice?’ I.e., FCS is a flexible and agnostic way to specify conditionals to arrive at a joint. MICE also allows JOMO: a direct and inflexible way to arrive at a joint. With MICE, it’s easy to generate synthetic values. mice is not just imputation software, but rather an ‘information generating machine’. Describe imputation models, analysis models, non-response model and SMC.]


- In general, imputation methods are developed to solve missing data problems.
- What types of missing data problems are we considering in this dissertation? Incomplete samples where some—but not all—entries are missing per row or per column. Entirely missing rows would be ‘unit non-response’; entirely missing columns would be unobserved variables. We are interested in data with incomplete cases/variables, or ‘item non-response’.
- Missing observations in incomplete cases/variables can be filled in using an imputation model
- In the FCS framework (Van Buuren et al., 2006), we need an imputation model for each incomplete variable
- fcs is substantive model agnostic, and does not assume any specific joint distribution.
- while “Rubin (Ch. 5) distinguished three tasks for creating imputations under an explicit model: the *modeling* task the *imputation* task and the *estimation* task.” (van Buuren, 2007, p. 221), FCS does not require these explicit tasks. Instead, FCS only requires an *imputation model* to describe how synthetic values may be generated, without explicit specification of the joint model.
- imputation models consist of the functional form of the model (e.g., stochastic regression) and imputation model predictors (i.e., other variables in the data)
- recurring questions: how do we choose an appropriate imputation model? and how do we know whether we have chosen an appropriate imputation model?
- “Imputation models bypass the need to specify $P(Y, X, R)$, though their use creates new responsibilities for substantiating its correctness for a given statistical analysis.” (van Buuren, 2007, p. 222).
- That’s where computational evaluation comes in!

FCS $\neq$ SMC

- the quality of the imputation model can only be determined/assessed based on the complete data model $\rightarrow$ TODO: specify terminology!! $\rightarrow$ comp eval also possible without analysis model vs statistical evaluation relies on known analysis model (prangender vandaag want imputation gebruikt voor meer analyses) fcs is substantive model agnostic
- what if that model is not (yet) available? then take the most complex possible model and check that, because if you would take the simplest model, then that would im-

plcitly mean you are holding/constraining parameters (forcing $b=0$), systematically suppressing relations.

- another option would be like smc-fcs: we assume a complete data model and derive the imputations from there.



TODO: verwerken in flow chart

- misfit en non-conv next to each other? = do the imputation models fit the data?
- Computational evaluation is in every trapezoid: processes that require human intervention. Statistical evaluation is mainly focused on the relation between the pooled estimates and
- Paragraph after this: convince reviewers that this is the right choice. Giswerk/gebrek aan controle leidt to suboptimale estimates
- missing: draw inference after pooled est; use external info after inspect miss to involve all stakeholders (CRISP-DM step)
- in simulation studies, focus is often just on incomplete data and pooled estimates

Building and evaluating imputation models

- Model building: how do we know which functional form to choose?
 - rely on defaults, tested in simulation studies
 - assess the distribution of the incomplete variable (e.g., visual inspection)
 - ...? (maybe ad transformations?)
- Model building: how do we know which imputation model predictors to select?
 - association of incomplete variable with other variables in the data (“include an auxiliary variable if its correlation with the main variable is 0.5 (in absolute value) [25]” Nguyen et al., 2021)
 - association of missingness indicator with other variables in the data
 - external input (e.g., branching patterns, or expert knowledge to correct for MNAR)
 - Take the analysis model (if available) as starting point for imputation workflow, for congeniality
 - ...?
- Model evaluation: how do we assess imputation model misfit?
 - fit of the model to the observed data
 - non-convergence in the algorithm
 - mismatch between observed and imputed data distributions (e.g., visual inspection)
 - ...?

Evaluating imputations

- FCS has no analytical proof → rely on evidence from simulation studies
- has been shown that it works under many conditions

- but how to know in practice? we need assumptions
- like assumptions for GLM, we look at the data to evaluate the appropriateness of our chosen model
- some assumption checks are visual inspection, some are quantitative, some need external info
- similarly, we need to evaluate the choice of imputation models
- ideally: evaluate inferential validity, but only available in simulation studies
- in practice, the thing we need is not available by definition
- some assumptions are impossible to definitively determine (e.g. MNAR), some we can evaluate by looking at the data
- this is what this dissertation is about: computational evaluation
- In practice, you cannot validate whether the imputation model was appropriate (???), because what you would need to do so is exactly the thing you don't have: the missing part of the incomplete data, while you only have the observed part.
- The best thing we can do is to rely on a combination of assumptions/theoretical justifications/substantive expertise and indirect evidence of imputation model fit: check the observed versus imputed data distributions, and inspect the imputations for signs of non-convergence. This dissertation offers insight and tools to do so.
- The only setting where we do have the comparative truth (the true but missing values) is simulation studies. Imputers have to rely on simulation study results in order to choose the best imputation method for their incomplete variables. That's why simulation studies for imputation methodology should be comparable with one another, so imputers can make a 'grounded' assessment which imputation methods may be applicable, and choose the most appropriate one. → example: NRI search for lower bound, so impute as 'positive behavior', but per definition wrong statistical inf, because we intentionally bias in one direction
- [in simulation study kun je waarheid maken, maar in de praktijk moet je aannames doen. die aannames zijn belangrijk, juist omdat ze niet/ten dele te bewijzen zijn]
- [what is a simulation study? add a brief methodological background section on simulation studies in statistics]

What is computational evaluation?

- Computational evaluation is not equal to statistical evaluation. Statistical evaluation is important, e.g. to quantify bias and variance of estimators/procedures, but not the focus of this dissertation.
- Computational evaluation is something to check *conditional on* acceptable statistical properties, and does not replace statistical evaluation.
- Computational evaluation is originally from information retrieval research (see e.g. “Evaluation Measures (Information Retrieval),” 2025)
- The practice of computational evaluation combines *effectiveness* (i.e., did the process yield the correct result, e.g., accuracy, precision, recall, etc.), *system quality* (e.g., speed, coverage of all possible results, etc.) and, importantly, *user utility* (e.g., happiness, productivity, etc.) (Manning et al., 2008)
- The term ‘computational evaluation’ is not specifically defined for the field of statistics, but it could be useful.
- One definition of computational evaluation is “to determine the quality of solutions attainable” (Dudek, 2004)
- Translated to statistics, a model may be statistically valid, but not fit for purpose. For example, computations that take too long to converge for use in a production pipeline/real-time use in patient care.
- Another definition of computational evaluation is “the process of ensuring an algorithmic solution is a good one: that it is fit for purpose” (Curzon et al., 2014).
- We can use this when a statistical process has different purposes and thus different usability/requirements. For example, calculating uncertainty at the level of a single case, a sample, or inferring to a population.
- Since the term is not defined for statistics, there is no definition to use for the computational evaluation of imputation methodology.
- In this dissertation, I want to plant a flag: how can we define ‘computational evaluation’ in the context of imputation methodology?
- Working definition: *systematic assessment of the algorithmic behavior and data-level outputs of imputation procedures*, focused on: algorithmic stability (convergence, failure modes), sensitivity to modeling choices, plausibility and coherence of imputed values, and usability for applied researchers.
- These aspects are often already taken into account by imputers, but I try to systematize and operationalize these aspects that are often informal or *ad hoc*.

Dimensions of computational evaluation: e.g. inferential validity, algorithmic behavior, data-level plausibility, user utility, ...

Why should we care about computational evaluation of imputation methodology?

- What do we care about? bias/coverage/variance, empirical relevance/plausibility, software-engineering nitpicks like speed/convergence/fault rate.
- Computational evaluation goes beyond statistical evaluation.
- In this dissertation I will use computational evaluation as a suite of tools to investigate the domains of algorithmic stability, data plausibility, and user burden, next to inferential validity.
- Even if we know the process yields correct inferences, we can evaluate the usability/appropriateness/plausibility of the solution. For example, one question to consider is: do the imputed values lie within the range of the observed values?
- Imputation theory does not require the imputed values to be plausible.
- Rubin (1976, 1987) developed the methodology to get correct population-level inferences from incomplete samples, not at the individual case-level within the sample. [TODO: consider adding that since then, data analysis has changed]
- Bluntly stated: imputation pragmatists/purists don't care for the imputed values themselves, as long as they result in statistically valid inferences.
- But what are the limitations of purely inferential metrics (bias, coverage)? e.g. imputing negative values for age, using PMM for a variable with a sparse region (yielding 'unrealistic' imputed values), or evaluating imputed values of non-converged chain (?), or not knowing the analysis model up front so congeniality is at risk (???) -> PPC would show problem with sparse region
- And vice versa: when might the plausibility of imputed values mislead a data analyst into believing the imputations are statistically valid? when 'looking reasonable' is confused with 'being consistent with the data-generating process', such as single imputation (stoch reg), or imputing under MCAR assumption when there is a MAR mechanism, or destroying the joint distribution of the data while preserving the marginals. [TODO: figure out the difference with Gerko's interpretation of joint occurrence (cross tabs) within conditional distribution; should we make an algorithm to show user which combinations of bivariate obs only occur in imp? Not now!]
- Statistical evaluation of bias and coverage is not possible in practice, only in simulation studies.
- Stat evaluation may not possible IRL? Bias and confidence interval coverage are impossible to determine without a comparative truth (although PPC and bootstrapping allows us to compare with respect to observed values).
- [TODO: rephrase as ability to explain differences between observed and imputed data (e.g., lower means in boys data), not as reverse engineering but as statistical evaluation of the data -> then computational eval may be needed to explain differences?] Computational evaluation means not just taking the answer as-is, but tracing back the solution of an algorithm to its origin/back-tracing the procedure: you should *always* be able to retrieve the chain of the imputation procedure. E.g., implausible or impossible imputed values can yield valid statistical inference, but are we satisfied with the way that the imputation

were obtained?

Examples of stat but not comp

- polynomials (ignoring the U in imps could still get stat val)
- example: psych study with baseline, some of which are missing; baseline, intervention, follow-up → mice would inflate baseline and follow-up if both are incomplete; statistical evaluation will not show this (unbiased, cov ok, etc.); over-imputation or postpred check would show diff distr for obs and imp; circularity should be removed: follow-up should not predict baseline
- fcs iterations not stable, but estimand ok (in simulation study true value) → conv at cell level??
- PMM with part of sample space with too little donors

What is the scope of this dissertation?

RQ: what tools are required to assess the quality of data-generating algorithms? in the development, evaluation, and application.

- is the status quo sufficient? no, statistical evaluation is required, but not sufficient.
- how Rubin developed the methodology works in theory, but is not enough for contemporary practitioners
- can we use existing tools or do we need more? and how? no, not all are present in the imputer's toolbox. I contribute to the new status quo ("verleggen" = generalizable scientific contribution of this dissertation)
- unifying how imputations are generated and evaluated (??)
- lifecycle of imputation methods: method is theorized, method is implemented in software, method is evaluated in simulation study, method is put to scrutiny by scientific community, method is applied in practice, method is evaluated in real-world data.
- two types of evaluation: statistical properties of the method in simulation (e.g., bias and confidence-validity; statistical evaluation) & practical application (computational evaluation).

[TODO: remove what I will not address! Maybe add a sentence 'You might expect me to go into...' In the category non-response: just item, and M(C)AR mech. In the category imputation algo: just FCS. In the category substantive models: just GLM for stat inference.] In this dissertation, we will focus on missing data problems with item non-response and MCAR/MAR missingness mechanisms. Unit non-response and MNAR missingness mechanisms are outside of the scope of this dissertation. The missing data method under consideration is primarily multiple imputation by chained equations (MICE), but some results may generalize to other iterative (FCS) imputation algorithms. We do not cover joint modeling (JOMO) imputation or non-imputation missing data methods. Although MICE is not SMC-FCS, we will restrict the

analysis of scientific interest mostly to GLM family of models. The applications are aimed at statistical inference (not prediction or causal inference).

Chapters

1. Evaluation paper: evaluating (new) imputation methods via simulation studies/how we know FCS works
2. Convergence paper: evaluating imputation algorithm quantitatively
3. Software: choosing/evaluating imputation models in practice

Introducing chapter 1: evaluation

- **RQ: what to look out for when designing simulation studies for the evaluation of imputation methodology?**/How can computational evaluation criteria be systematically incorporated into simulation studies for imputation methodology?
- published as Oberman & Vink (2024), cited 27x according to Google Scholar (of which 11x CrossRef)
- based on literature review Liu et al. (2023)
- How can we trust simulation studies for imputation methods?
- How can we make them compatible & fair?

REF: Morris ADEMP: Using simulation studies to evaluate statistical methods, pre-registration template, FIMD, Introduction to statistical simulations in health research?, Pitfalls and Potentials in Simulation Studies?

Introducing chapter 2: convergence

- **RQ: FSC is iterative, so convergence *should* be a requirement for valid inference, or is it?**/How does non-convergence in iterative imputation affect inferential validity, and how can non-convergence be diagnosed?
- simulation study, published as pre-print (11x cited according to Google Scholar), presented at ICML
- even without convergence, we can get valid inference at sample/population level, but not at individual cell level
- imputation stays a custom job: convergence of imputation is conditional on imputation model

- today, imputation are not generated for 1 analysis prob, but all analyses that may be fitted on the data -> all imputation models should be compatible and congenial -> more ‘omvattende’ imputation models required
- liefst wil je analysemodel parameters tracken, daarom is computational evaluation zo belangrijk
- Can we quantify the convergence of the MICE algorithm?

REFs: Graphical and numerical diagnostic tools to assess suitability of multiple imputations and imputation models, Diagnostic checking of multiple imputation models, Convergence Properties of a Sequential Regression Multiple Imputation Algorithm, FIMD, Diagnostics for multivariate imputations

Introducing chapter 3: `ggmice`

[TODO: add poster and ‘age old adage’ picture vs 1000w.]

This chapter introduces the software `ggmice`: an R package for building and evaluating imputation models. The `ggmice` package offers tools for the visualization of incomplete data, imputation models, and imputed data.

Indicators for adoption: how is the software already used?

- software published on Zenodo (Oberman, 2022), with open code and bug reporting via GitHub
- peer-review not formal via journal, but via Issues and Pull Requests on GitHub (10x external Issue, 13x external PR)
- impact: citations (5x according to Google Scholar), CRAN downloads (852x/month; 21k total) and conda downloads (100+/month; <https://anaconda.org/channels/conda-forge/packages/r-ggmice/overview>)

Design principles

- `ggmice` is compatible with the popular R packages `mice` (for imputation) and `ggplot2` (for flexible data visualizations based on the ‘grammar of graphics’ framework).
- `mice` imputation models are substantive model agnostic: flexible, var-by-var definition of imputation model. `ggmice` supports this.
- Grammar of Graphics = layered plots (Wilkinson, 2012) -> `ggmice` produces `ggplot` objects: layered, easily adjustable

- Assumptions: imputation model should fit the observed part, imputation model should be congenial → providing tools to see observed and imputation side-by-side/evaluation of the distribution of observed and imputed data

Limitations

- make explicit what these plots/analyses can and cannot tell us: imputation models should fit the observed part of the data, but no way to determinately state miss mech.
- visualization $\neq$ objective truth → good imputation model fit/plausible values is not a guarantee for statistical validity
- visualization is not a replacement of evaluation but support, also check metrics such as FMI
- interpretation remains subjective (e.g. convergence, MAR assumption, etc.)

What does **ggmice** aim to solve?

The **ggmice** package aims to solve the following problems:

- no direct graphical comparisons between incomplete and imputed data; side-by-side presentation of the data before and after imputation; Visualizations with **ggmice** can be made to inspect marginal and joint distributions of incomplete variables side-to-side to compare incomplete and imputed data
- no previously existing methods for visualizing **mice** imputation models; complex imputation models are easier to review through visualization (as opposed to console prints/excel exports of predictor matrix)
- existing plotting tools for **mids** objects not easily editable/publication-ready; Visualizations with **ggmice** can be extended and adapted with tidyverse functions to create publication-ready graphs of imputed data (reflecting the uncertainty due to missingness).
- unified toolbox for the development and evaluation of imputation models

Existing solutions

The **ggmice** package fills a hiatus in the software landscape, with other packages generally supporting either **mice** or **ggplot2**, but not both. Table REF provides an overview of R packages that offer visualization tools for incomplete and imputed data. In short: with **mice** you cannot plot incomplete data distributions, all other packages lack support for **mice**-imputed data, and visualization of **mice** imputation models did not exist at all prior to **ggmice**.

	ggmice	mice	naniar	VIM
Incomplete data (e.g., <code>data.frame</code> object)				

	ggmice	mice	naniar	VIM
– joint & marginal distributions	+	–	+	+
– missing data patterns	+	+	±	+
– imputation models	+	–	–	–
Imputed data (e.g., <code>mids</code> object)				
– joint & marginal distributions	+	+	–	–
– imputation models	+	–	–	–
– trace plot of the imputation algorithm	+	+	–	–
User utility (e.g., <code>ggplot</code> object)				
– flexibility/extensibility of visualization types	+	–	±	–
– adaptability/publication readiness of visualizations	+	–	+	–

TODO

- write table footnote to explain all aspects of the table. i.e., these are only diffs. the table does not include things that all packages can → maybe as appendix?
- explain the purpose of the table: I'm both player and referee. I've got skin in the game, but I made the rubric. Someone else might evaluate/value different aspects.
- also add number of downloads: `ggmice` has 800 monthly compared to `VIM` 13k and `naniar` 22k
- make 'Imputation models' a separate section?

Software development

- Open Source Software development/FAIR → R, GitHub, CRAN, Zenodo, ...
- CRAN downloads
- GitHub stars and issues
- StackOverflow mentions/questions
- feedback at conferences
- citations of the package (Zenodo reference)

Future research & development

- visualizing `mira` objects
- add posterior predictive check plots & over-imputation
- quantifying uncertainty at pattern/cell level
- tools for sensitivity analyses: inducing MNAR in observed part of the data and evaluating effects on the imputations/inference

- What data-level diagnostics are informative for assessing imputation model adequacy in practice (i.e., when inferential validity cannot be evaluated)?
- pre vs post imputation facilitator functions om te checken of er nieuwe verbanden in zitten (kruistabel)

Chapter 1: evaluation

[TODO: link/insert]

Chapter 2: convergence

[TODO: link/insert]

Chapter 3: ggmmice

[TODO: link/insert]

Discussion

Conclusion

- Computational evaluation of imputation methodology is never finished.
- The main findings in this thesis are...
 - Defining and testing new imputation methods through simulation studies requires careful consideration of the simulation design and evaluation to make imputation methods comparable across studies. We need simulation studies to know imputation methods work. But we cannot be certain they actually *did* work whenever we apply them. The missing part of the data is by definition not available, so we cannot definitively state anything about the imputation model fit to the unobserved part of the data. Moreover, there's untestable assumptions (e.g., MNAR) and lack of clear diagnostic cut offs (e.g., convergence).
 - Non-convergence is hard to diagnose, and typical thresholds to evaluate non-convergence may not be applicable to FCS algorithms: MICE reaches stable output before non-convergence metrics would indicate so. There is a mismatch between theoretical convergence criteria and practical algorithmic behavior. That's why we still have to rely on visual inspection.
 - Visual inspection aids imputers in developing and evaluating imputation models, because formal tests are not available. The R package `ggmice` offers tools for the computational evaluation of the imputations models that were previously unavailable.
- Recommendations for fellow missing data methodologists:
 - design simulation studies structured and reproducible (e.g., report design choices, publish code)
 - talk to your intended audience (i.e., applied researchers), or at least check what they are struggling with (e.g., StackOverflow)
 - ...?
- Recommendations for fellow imputers:
 - think before you code
 - look at the data, plot the data
 - ...?

Limitations

- Computational evaluation is not a substitute for thinking. It may give a false sense of certainty, e.g. against MNAR mechanism (untestable assumption).

- Instead, use computational evaluation as complement to (not a replacement for) substantive knowledge and sensitivity analyses. Use expert insight
- This entire dissertation relies on the R language and centers the `mice` package [TODO rephrase as not a flaw: I focus on a dominant ecosystem, and concepts generalize beyond].
 - While this set-up is very popular, the data science landscape has expanded and is ever evolving
 - Many machine learning and deep learning methods are not (yet) implemented as imputation models in `mice`. These might be able to better approximate the posterior predictive distribution of the missing values than `mice` methods, but research should show that still.
- ~~I haven't tested whether the tools I developed actually improve the imputations of `mice` users~~ This dissertation evaluates tools and diagnostics at the methodological level; assessing their causal impact on user behavior and imputation quality is not feasible to systematically test.
 - GitHub issues and StackOverflow are indication
 - Onmogelijk om evidence-based conclusies te trekken, maar misschien wel evidence-informed?
- The visualizations implemented in `ggmice` are generally better suited for numeric data, as opposed to categorical variables (or even open text field data, which is not supported by `mice` currently). Future research on: associations of cat vars with miss indicators, and convergence parameter other than SD of imputed values.

- TODO: rephrase 'haven't's into future research (positive phrasing: reframe as scope conditions, not shortcomings)
- maybe future: computational evaluation of variable importance within imputation models

Outlook

- This chapter ends with a future perspective...
- Missing data remains a problem indefinitely. I expect imputation methodology to be developed and applied for the foreseeable future. But the way we deal with data might change.
- With the rise of machine learning and deep learning methods (or “AI”), evaluation will become ever more important. Novel methods are being developed under a prediction framework, not statistical inference framework: ignoring the uncertainty in the estimates,

and thus not incorporating between-imputation variance. This leads to too narrow CIs, and too low p-values. Which, in turn, causes spurious results.

- AI models should propagate uncertainty!
- trust in science requires honest reflection of uncertainty in our analyses
- be open about uncertainty, and limitations of scientific studies
- publish null results (e.g., registered reports or pre-registrations)
- share data and code with other scientists, and the public
- publish open access, educational materials too!
- change the way we evaluate science: this dissertation is an example of the new recognition and rewards vision. it includes software as an actual chapter, not something extra.
- I hope to inspire others to reflect on their own view of what scientific output is. And most of all, I hope to set an example for other PhD candidates to do the same
- imputation is not always the way to go: missingness can tell you about mismatch between data collection method and lived experience → positionality??

References

- Curzon, P., Dorling, M., Ng, T., Selby, C., & Woollard, J. (2014). *Developing computational thinking in the classroom: A framework*. Computing at School.
- Dudek, G. (2004). Computational Evaluation. In G. Dudek (Ed.), *Collaborative Planning in Supply Chains: A Negotiation-Based Approach* (pp. 165–213). Springer. https://doi.org/10.1007/978-3-662-05443-7_7
- Evaluation measures (information retrieval). (2025). In *Wikipedia*. [https://en.wikipedia.org/w/index.php?title=Evaluation_measures_\(information_retrieval\)&oldid=1329650960](https://en.wikipedia.org/w/index.php?title=Evaluation_measures_(information_retrieval)&oldid=1329650960)
- Liu, D., Oberman, H. I., Muñoz, J., Hoogland, J., & Debray, T. P. A. (2023). Quality Control, Data Cleaning, Imputation. In F. W. Asselbergs, S. Denaxas, D. L. Oberski, & J. H. Moore (Eds.), *Clinical Applications of Artificial Intelligence in Real-World Data* (pp. 7–36). Springer International Publishing. https://doi.org/10.1007/978-3-031-36678-9_2
- Manning, C. D., Raghavan, P., & Schütze, H. (2008). *Introduction to Information Retrieval*. Cambridge University Press. <https://doi.org/10.1017/CBO9780511809071>
- Nguyen, C. D., Carlin, J. B., & Lee, K. J. (2021). Practical strategies for handling breakdown of multiple imputation procedures. *Emerging Themes in Epidemiology*, 18, 5. <https://doi.org/10.1186/s12982-021-00095-3>
- Oberman, H. I. (2022). *Ggmice: Visualizations for 'mice' with 'Ggplot2'* [Computer software]. Zenodo. <https://doi.org/10.5281/zenodo.6532702>
- Oberman, H. I., & Vink, G. (2024). Toward a standardized evaluation of imputation methodology. *Biometrical Journal*, 66(1), 2200107. <https://doi.org/10.1002/bimj.202200107>
- Rubin, D. B. (1976). Inference and Missing Data. *Biometrika*, 63(3), 581–592. <https://doi.org/10.2307/2335739>
- Rubin, D. B. (1987). *Multiple Imputation for nonresponse in surveys*. Wiley.
- van Buuren, S. (2007). Multiple imputation of discrete and continuous data by fully conditional specification. *Statistical Methods in Medical Research*, 16(3), 219–242. <https://doi.org/10.1177/0962280206074463>
- Van Buuren, S., Brand, J. P. L., Groothuis-Oudshoorn, C. G. M., & Rubin, D. B. (2006). Fully conditional specification in multivariate imputation. *Journal of Statistical Computation and Simulation*, 76(12), 1049–1064. <https://doi.org/10.1080/10629360600810434>
- Wilkinson, L. (2012). The Grammar of Graphics. In *Handbook of Computational Statistics* (pp. 375–414). Springer, Berlin, Heidelberg. https://doi.org/10.1007/978-3-642-21551-3_13

CV

[TODO: write]