

Happy Key: HPKE implementation (draft-irtf-cfrg-hpke)

<https://github.com/sftcd/happykey>

Generated by Doxygen 1.8.18



<b>1 Data Structure Index</b>	<b>1</b>
1.1 Data Structures	1
<b>2 File Index</b>	<b>3</b>
2.1 File List	3
<b>3 Data Structure Documentation</b>	<b>5</b>
3.1 hpke_aead_info_t Struct Reference	5
3.1.1 Detailed Description	5
3.2 hpke_kdf_info_t Struct Reference	5
3.2.1 Detailed Description	6
3.3 hpke_kem_info_t Struct Reference	6
3.3.1 Detailed Description	6
3.4 hpke_suite_t Struct Reference	7
3.4.1 Detailed Description	7
3.5 hpke_tv_encs_t Struct Reference	7
3.5.1 Detailed Description	7
3.6 hpke_tv_s Struct Reference	8
3.6.1 Detailed Description	9
<b>4 File Documentation</b>	<b>11</b>
4.1 hpke.c File Reference	11
4.1.1 Detailed Description	13
4.1.2 Function Documentation	14
4.1.2.1 hpke_aead_dec()	14
4.1.2.2 hpke_aead_enc()	14
4.1.2.3 hpke_ah_decode()	15
4.1.2.4 hpke_dec()	16
4.1.2.5 hpke_do_kem()	17
4.1.2.6 hpke_enc()	18
4.1.2.7 hpke_EVP_PKEY_new_raw_nist_private_key()	19
4.1.2.8 hpke_EVP_PKEY_new_raw_nist_public_key()	19
4.1.2.9 hpke_expand()	20
4.1.2.10 hpke_extract()	21
4.1.2.11 hpke_extract_and_expand()	22
4.1.2.12 hpke_kem_id_check()	22
4.1.2.13 hpke_kem_id_nist_curve()	23
4.1.2.14 hpke_kg()	23
4.1.2.15 hpke_mode_check()	23
4.1.2.16 hpke_psk_check()	24
4.1.2.17 hpke_suite_check()	24
4.1.3 Variable Documentation	25
4.1.3.1 hpke_aead_strtab	25

4.1.3.2 hpke_aead_tab . . . . .	25
4.1.3.3 hpke_kdf_strtab . . . . .	25
4.1.3.4 hpke_kdf_tab . . . . .	25
4.1.3.5 hpke_kem_strtab . . . . .	26
4.1.3.6 hpke_kem_tab . . . . .	26
4.1.3.7 hpke_mode_strtab . . . . .	26
4.2 hpke.h File Reference . . . . .	26
4.2.1 Detailed Description . . . . .	29
4.2.2 Macro Definition Documentation . . . . .	29
4.2.2.1 HPKE_A2B . . . . .	29
4.2.2.2 HPKE_SUITE_DEFAULT . . . . .	29
4.2.3 Function Documentation . . . . .	30
4.2.3.1 hpke_ah_decode() . . . . .	30
4.2.3.2 hpke_dec() . . . . .	31
4.2.3.3 hpke_enc() . . . . .	32
4.2.3.4 hpke_kg() . . . . .	33
4.2.3.5 hpke_suite_check() . . . . .	34
4.3 hpketv.c File Reference . . . . .	34
4.3.1 Detailed Description . . . . .	35
4.3.2 Macro Definition Documentation . . . . .	35
4.3.2.1 FAIL2BUILD . . . . .	35
4.3.3 Function Documentation . . . . .	35
4.3.3.1 hpke_tv_free() . . . . .	35
4.3.3.2 hpke_tv_load() . . . . .	36
4.3.3.3 hpke_tv_pick() . . . . .	36
4.3.3.4 hpke_tv_print() . . . . .	37
4.4 hpketv.h File Reference . . . . .	37
4.4.1 Detailed Description . . . . .	38
4.4.2 Typedef Documentation . . . . .	38
4.4.2.1 hpke_tv_t . . . . .	38
4.4.3 Function Documentation . . . . .	39
4.4.3.1 hpke_tv_free() . . . . .	39
4.4.3.2 hpke_tv_load() . . . . .	39
4.4.3.3 hpke_tv_pick() . . . . .	39
4.4.3.4 hpke_tv_print() . . . . .	40

# Chapter 1

## Data Structure Index

### 1.1 Data Structures

Here are the data structures with brief descriptions:

<a href="#">hpke_aead_info_t</a>	Info about an AEAD . . . . .	5
<a href="#">hpke_kdf_info_t</a>	Info about a KDF . . . . .	5
<a href="#">hpke_kem_info_t</a>	Info about a KEM . . . . .	6
<a href="#">hpke_suite_t</a>	Ciphersuite combination . . . . .	7
<a href="#">hpke_tv_encs_t</a>	Encryption(s) Test Vector structure using field names from published JSON file . . . . .	7
<a href="#">hpke_tv_s</a>	HKPE Test Vector structure using field names from published JSON file . . . . .	8



## Chapter 2

# File Index

### 2.1 File List

Here is a list of all documented files with brief descriptions:

<a href="#">hpke.c</a>	11
<a href="#">hpke.h</a>	26
<a href="#">hpketv.c</a>	34
<a href="#">hpketv.h</a>	37





## Chapter 3

# Data Structure Documentation

### 3.1 hpke\_aead\_info\_t Struct Reference

info about an AEAD

#### Data Fields

- uint16\_t [aead\\_id](#)  
*code point for aead alg*
- const EVP\_CIPHER \*(\* [aead\\_init\\_func](#) )(void)  
*the aead we're using*
- size\_t [taglen](#)  
*aead tag len*
- size\_t [Nk](#)  
*size of a key for this aead*
- size\_t [Nn](#)  
*length of a nonce for this aead*

#### 3.1.1 Detailed Description

info about an AEAD

The documentation for this struct was generated from the following file:

- [hpke.c](#)

### 3.2 hpke\_kdf\_info\_t Struct Reference

info about a KDF

## Data Fields

- `uint16_t kdf_id`  
*code point for KDF*
- `const EVP_MD *(* hash_init_func )(void)`  
*the hash alg we're using*
- `size_t Nh`  
*length of hash/extract output*

### 3.2.1 Detailed Description

info about a KDF

The documentation for this struct was generated from the following file:

- [hpke.c](#)

## 3.3 hpke\_kem\_info\_t Struct Reference

info about a KEM

## Data Fields

- `uint16_t kem_id`  
*code point for key encipherment method*
- `int groupid`  
*NID of KEM.*
- `const EVP_MD *(* hash_init_func )(void)`  
*the hash alg we're using for the HKDF*
- `size_t Nsecret`  
*size of secrets*
- `size_t Nenc`  
*length of encapsulated key*
- `size_t Npk`  
*length of public key*
- `size_t Npriv`  
*length of raw private key*

### 3.3.1 Detailed Description

info about a KEM

The documentation for this struct was generated from the following file:

- [hpke.c](#)

## 3.4 hpke\_suite\_t Struct Reference

ciphersuite combination

```
#include <hpke.h>
```

### Data Fields

- uint16\_t [kem\\_id](#)  
*Key Encryption Method id.*
- uint16\_t [kdf\\_id](#)  
*Key Derivation Function id.*
- uint16\_t [aead\\_id](#)  
*Authenticated Encryption with Associated Data id.*

### 3.4.1 Detailed Description

ciphersuite combination

The documentation for this struct was generated from the following file:

- [hpke.h](#)

## 3.5 hpke\_tv\_encs\_t Struct Reference

Encryption(s) Test Vector structure using field names from published JSON file.

```
#include <hpketv.h>
```

### Data Fields

- const char \* [aad](#)  
*ascii-hex encoded additional authenticated data*
- const char \* [nonce](#)  
*aascii-hex encoded nonce*
- const char \* [plaintext](#)  
*aascii-hex encoded plaintext*
- const char \* [ciphertext](#)  
*ascii-hex encoded ciphertext*

### 3.5.1 Detailed Description

Encryption(s) Test Vector structure using field names from published JSON file.

The documentation for this struct was generated from the following file:


- [hpketv.h](#)

### 3.6 hpke\_tv\_s Struct Reference

HKPE Test Vector structure using field names from published JSON file.

```
#include <hpketv.h>
```

Collaboration diagram for hpke\_tv\_s:



#### Data Fields

- `uint8_t mode`
- `uint16_t kdf_id`
- `uint16_t aead_id`
- `uint16_t kem_id`
- `const char * info`
- `const char * exporter_secret`
- `const char * enc`
- `const char * key_schedule_context`
- `const char * nonce`
- `const char * secret`
- `const char * shared_secret`
- `const char * skEm`
- `const char * skRm`
- `const char * skSm`
- `const char * pkEm`
- `const char * pkRm`
- `const char * pkSm`
- `const char * seedE`
- `const char * seedR`
- `const char * seedS`
- `const char * psk_id`
- `const char * psk`
- `int nencs`
- `hpke_tv_encs_t * encs`
- `void * jobj`

*pointer to json-c object into which the char\* pointers above point*

### 3.6.1 Detailed Description

HKPE Test Vector structure using field names from published JSON file.

The jobj field (at the end) is the json-c object from which all these are derived and into which most of the char \* pointers point. When we make an array of [hpke\\_tv\\_s](#) then the same jobj will be pointed at by all, so when it's time to call hpke\_tv\_free then we'll just free one of those using the json-c API.

The documentation for this struct was generated from the following file:

- [hpketv.h](#)




## Chapter 4

# File Documentation

### 4.1 hpke.c File Reference

```
#include <stddef.h>
#include <stdint.h>
#include <string.h>
#include <openssl/ssl.h>
#include <openssl/rand.h>
#include <openssl/kdf.h>
#include <openssl/evp.h>
#include <openssl/params.h>
#include <crypto/hpke.h>
```

Include dependency graph for hpke.c:



### Data Structures

- struct [hpke\\_aead\\_info\\_t](#)  
*info about an AEAD*
- struct [hpke\\_kem\\_info\\_t](#)  
*info about a KEM*
- struct [hpke\\_kdf\\_info\\_t](#)  
*info about a KDF*

### Macros

- #define **DRAFT\_05**
- #define [HPKE\\_5869\\_MODE\\_PURE](#) 0  
*Do "pure" RFC5869.*
- #define [HPKE\\_5869\\_MODE\\_KEM](#) 1

- Abide by HPKE section 4.1.*
  - #define [HPKE\\_5869\\_MODE\\_FULL](#) 2
- Abide by HPKE section 5.1.*
  - #define [HPKE\\_VERLABEL](#) "HPKE-05 "
- The version string label.*
  - #define [HPKE\\_SEC41LABEL](#) "KEM"
- The "suite\_id" label for 4.1.*
  - #define [HPKE\\_SEC51LABEL](#) "HPKE"
- The "suite\_id" label for 5.1.*
  - #define [HPKE\\_EAE\\_PRK\\_LABEL](#) "eae\_prk"
- The label within ExtractAndExpand.*
  - #define [HPKE\\_PSKIDHASH\\_LABEL](#) "psk\_id\_hash"
- A label within key\_schedule\_context.*
  - #define [HPKE\\_INFOHASH\\_LABEL](#) "info\_hash"
- A label within key\_schedule\_context.*
  - #define [HPKE\\_SS\\_LABEL](#) "shared\_secret"
- Yet another label.*
  - #define [HPKE\\_NONCE\\_LABEL](#) "nonce"
- guess?*
  - #define [HPKE\\_EXP\\_LABEL](#) "exp"
- guess again?*
  - #define [HPKE\\_KEY\\_LABEL](#) "key"
- guess again?*
  - #define [HPKE\\_PSK\\_HASH\\_LABEL](#) "psk\_hash"
- guess again?*
  - #define [HPKE\\_SECRET\\_LABEL](#) "secret"
- guess again?*

## Functions

- int [hpke\\_ah\\_decode](#) (size\_t ahlen, const char \*ah, size\_t \*bolen, unsigned char \*\*buf)  
*decode ascii hex to a binary buffer*
- static int [hpke\\_kem\\_id\\_check](#) (uint16\_t kem\_id)  
*Check if kem\_id is ok/known to us.*
- static int [hpke\\_kem\\_id\\_nist\\_curve](#) (uint16\_t kem\_id)  
*check if KEM uses NIST curve or not*
- static EVP\_PKEY \* [hpke\\_EVP\\_PKEY\\_new\\_raw\\_nist\\_public\\_key](#) (int curve, unsigned char \*buf, size\_t buflen)  
*hpke wrapper to import NIST curve public key as easily as x25519/x448*
- static int [hpke\\_aead\\_dec](#) ([hpke\\_suite\\_t](#) suite, unsigned char \*key, size\_t keylen, unsigned char \*iv, size\_t ivlen, unsigned char \*aad, size\_t aadlen, unsigned char \*cipher, size\_t cipherlen, unsigned char \*plain, size\_t \*plainlen)  
*do the AEAD decryption*
- static int [hpke\\_aead\\_enc](#) ([hpke\\_suite\\_t](#) suite, unsigned char \*key, size\_t keylen, unsigned char \*iv, size\_t ivlen, unsigned char \*aad, size\_t aadlen, unsigned char \*plain, size\_t plainlen, unsigned char \*cipher, size\_t \*cipherlen)  
*do the AEAD encryption as per the I-D*
- static int [hpke\\_extract](#) ([hpke\\_suite\\_t](#) suite, int mode5869, const unsigned char \*salt, const size\_t saltlen, const unsigned char \*label, const size\_t labellen, unsigned char \*ikm, const size\_t ikmlen, unsigned char \*secret, size\_t \*secretlen)



- static int [hpke\\_expand](#) ([hpke\\_suite\\_t](#) suite, int mode5869, unsigned char \*prk, size\_t prklen, unsigned char \*label, size\_t labellen, unsigned char \*info, size\_t infolen, uint32\_t L, unsigned char \*out, size\_t \*outlen)
- static int [hpke\\_extract\\_and\\_expand](#) ([hpke\\_suite\\_t](#) suite, int mode5869, unsigned char \*shared\_secret, size\_t shared\_secretlen, unsigned char \*context, size\_t contextlen, unsigned char \*secret, size\_t \*secretlen)  
*ExtractAndExpand.*
- static int [hpke\\_do\\_kem](#) (int encrypting, [hpke\\_suite\\_t](#) suite, EVP\_PKEY \*key1, size\_t key1enclen, unsigned char \*key1enc, EVP\_PKEY \*key2, size\_t key2enclen, unsigned char \*key2enc, EVP\_PKEY \*akey, size\_t apublen, unsigned char \*apub, unsigned char \*\*ss, size\_t \*sslen)  
*run the KEM with two keys as per draft-05*
- static int [hpke\\_mode\\_check](#) (unsigned int mode)  
*check mode is in-range and supported*
- static int [hpke\\_psk\\_check](#) (unsigned int mode, char \*pskid, size\_t psklen, unsigned char \*psk)  
*check psk params are as per spec*
- static EVP\_PKEY \* [hpke\\_EVP\\_PKEY\\_new\\_raw\\_nist\\_private\\_key](#) (int curve, unsigned char \*buf, size\_t buflen)  
*hpke wrapper to import NIST curve private key as easily as x25519/x448*
- int [hpke\\_enc](#) (unsigned int mode, [hpke\\_suite\\_t](#) suite, char \*pskid, size\_t psklen, unsigned char \*psk, size\_t publen, unsigned char \*pub, size\_t privlen, unsigned char \*priv, size\_t clearlen, unsigned char \*clear, size\_t aadlen, unsigned char \*aad, size\_t infolen, unsigned char \*info, size\_t \*senderpublen, unsigned char \*senderpub, size\_t \*cipherlen, unsigned char \*cipher)  
*HPKE single-shot encryption function.*
- int [hpke\\_dec](#) (unsigned int mode, [hpke\\_suite\\_t](#) suite, char \*pskid, size\_t psklen, unsigned char \*psk, size\_t publen, unsigned char \*pub, size\_t privlen, unsigned char \*priv, EVP\_PKEY \*evppriv, size\_t enclen, unsigned char \*enc, size\_t cipherlen, unsigned char \*cipher, size\_t aadlen, unsigned char \*aad, size\_t infolen, unsigned char \*info, size\_t \*clearlen, unsigned char \*clear)  
*HPKE single-shot decryption function.*
- int [hpke\\_kg](#) (unsigned int mode, [hpke\\_suite\\_t](#) suite, size\_t \*publen, unsigned char \*pub, size\_t \*privlen, unsigned char \*priv)  
*generate a key pair*
- int [hpke\\_suite\\_check](#) ([hpke\\_suite\\_t](#) suite)  
*check if a suite is supported locally*

## Variables

- const char \* [hpke\\_mode\\_strtab](#) []
- [hpke\\_aead\\_info\\_t](#) [hpke\\_aead\\_tab](#) []  
*table of AEADs*
- const char \* [hpke\\_aead\\_strtab](#) []
- [hpke\\_kem\\_info\\_t](#) [hpke\\_kem\\_tab](#) []  
*table of KEMs*
- const char \* [hpke\\_kem\\_strtab](#) []
- [hpke\\_kdf\\_info\\_t](#) [hpke\\_kdf\\_tab](#) []  
*table of KDFs*
- const char \* [hpke\\_kdf\\_strtab](#) []

### 4.1.1 Detailed Description

An OpenSSL-based HPKE implementation following draft-irtf-cfrg-hpke

I plan to use this for my ESNI-enabled OpenSSL build ( <https://github.com/sftcd/openssl> ) when the time is right.

## 4.1.2 Function Documentation

### 4.1.2.1 hpke\_aead\_dec()

```
static int hpke_aead_dec (
    hpke_suite_t suite,
    unsigned char * key,
    size_t keylen,
    unsigned char * iv,
    size_t ivlen,
    unsigned char * aad,
    size_t aadlen,
    unsigned char * cipher,
    size_t cipherlen,
    unsigned char * plain,
    size_t * plainlen ) [static]
```

do the AEAD decryption

#### Parameters

<i>suite</i>	is the ciphersuite
<i>key</i>	is the secret
<i>keylen</i>	is the length of the secret
<i>iv</i>	is the initialisation vector
<i>ivlen</i>	is the length of the iv
<i>aad</i>	is the additional authenticated data
<i>aadlen</i>	is the length of the aad
<i>cipher</i>	is obvious
<i>cipherlen</i>	is the ciphertext length
<i>plain</i>	is an output
<i>plainlen</i>	is an input/output, better be big enough on input, exact on output

#### Returns

1 for good otherwise bad

### 4.1.2.2 hpke\_aead\_enc()

```
static int hpke_aead_enc (
    hpke_suite_t suite,
    unsigned char * key,
    size_t keylen,
    unsigned char * iv,
    size_t ivlen,
    unsigned char * aad,
```

```
size_t aadlen,  
unsigned char * plain,  
size_t plainlen,  
unsigned char * cipher,  
size_t * cipherlen ) [static]
```

do the AEAD encryption as per the I-D

#### Parameters

<i>suite</i>	is the ciphersuite
<i>key</i>	is the secret
<i>keylen</i>	is the length of the secret
<i>iv</i>	is the initialisation vector
<i>ivlen</i>	is the length of the iv
<i>aad</i>	is the additional authenticated data
<i>aadlen</i>	is the length of the aad
<i>plain</i>	is an output
<i>plainlen</i>	is the length of plain
<i>cipher</i>	is an output
<i>cipherlen</i>	is an input/output, better be big enough on input, exact on output

#### Returns

1 for good otherwise bad

#### 4.1.2.3 hpke\_ah\_decode()

```
int hpke_ah_decode (  
    size_t ahlen,  
    const char * ah,  
    size_t * blen,  
    unsigned char ** buf )
```

decode ascii hex to a binary buffer

Since I always have to reconstruct this again in my head...  
Bash command line hashing starting from ascii hex example:

```
$ echo -e "4f6465206f6e2061204772656369616e2055726e" | xxd -r -p | openssl sha256  
(stdin)= 55c4040629c64c5efec2f7230407d612d16289d7c5d7afcf9340280abd2de1ab
```

The above generates the Hash(info) used in Appendix A.2

```

If you'd like to regenerate the zero_sha256 value above, feel free
$ echo -n "" | openssl sha256
echo -n "" | openssl sha256
(stdin)= e3b0c44298fclc149afb4c8996fb92427ae41e4649b934ca495991b7852b855
Or if you'd like to re-caclulate the sha256 of nothing...
SHA256_CTX sha256;
SHA256_Init(&sha256);
char* buffer = NULL;
int bytesRead = 0;
SHA256_Update(&sha256, buffer, bytesRead);
SHA256_Final(zero_sha256, &sha256);
...but I've done it for you, so no need:-)
static const unsigned char zero_sha256[SHA256_DIGEST_LENGTH] = {
    0xe3, 0xb0, 0xc4, 0x42, 0x98, 0xfc, 0x1c, 0x14,
    0x9a, 0xfb, 0xf4, 0xc8, 0x99, 0x6f, 0xb9, 0x24,
    0x27, 0xae, 0x41, 0xe4, 0x64, 0x9b, 0x93, 0x4c,
    0xa4, 0x95, 0x99, 0x1b, 0x78, 0x52, 0xb8, 0x55};

```

#### Parameters

<i>ahlen</i>	is the ascii hex string length
<i>ah</i>	is the ascii hex string
<i>blen</i>	is a pointer to the returned binary length
<i>buf</i>	is a pointer to the internally allocated binary buffer

#### Returns

1 for good otherwise bad

#### 4.1.2.4 hpke\_dec()

```

int hpke_dec (
    unsigned int mode,
    hpke_suite_t suite,
    char * pskid,
    size_t psklen,
    unsigned char * psk,
    size_t publen,
    unsigned char * pub,
    size_t privlen,
    unsigned char * priv,
    EVP_PKEY * evppriv,
    size_t enclen,
    unsigned char * enc,
    size_t cipherlen,
    unsigned char * cipher,
    size_t aadlen,
    unsigned char * aad,
    size_t infolen,
    unsigned char * info,
    size_t * clearlen,
    unsigned char * clear )

```

HPKE single-shot decryption function.

## Parameters

<i>mode</i>	is the HPKE mode
<i>suite</i>	is the ciphersuite
<i>pskid</i>	is the pskid string for a PSK mode (can be NULL)
<i>psklen</i>	is the psk length
<i>psk</i>	is the psk
<i>publen</i>	is the length of the public (authentication) key
<i>pub</i>	is the encoded public (authentication) key
<i>privlen</i>	is the length of the private key
<i>priv</i>	is the encoded private key
<i>evppriv</i>	is a pointer to an internal form of private key
<i>enclen</i>	is the length of the peer's public value
<i>enc</i>	is the peer's public value
<i>cipherlen</i>	is the length of the ciphertext
<i>cipher</i>	is the ciphertext
<i>aadlen</i>	is the length of the additional data
<i>aad</i>	is the encoded additional data
<i>infolen</i>	is the length of the info data (can be zero)
<i>info</i>	is the encoded info data (can be NULL)
<i>clearlen</i>	is the length of the input buffer for cleartext (octets used on output)
<i>clear</i>	is the encoded cleartext

## Returns

1 for good (OpenSSL style), not-1 for error

## 4.1.2.5 hpke\_do\_kem()

```
static int hpke_do_kem (
    int encrypting,
    hpke_suite_t suite,
    EVP_PKEY * key1,
    size_t keylenclen,
    unsigned char * keylenc,
    EVP_PKEY * key2,
    size_t key2enclen,
    unsigned char * key2enc,
    EVP_PKEY * akey,
    size_t apublen,
    unsigned char * apub,
    unsigned char ** ss,
    size_t * sslen ) [static]
```

run the KEM with two keys as per draft-05

## Parameters

<i>encrypting</i>	is 1 if we're encrypting, 0 for decrypting
-------------------	--

## Parameters

<i>suite</i>	is the ciphersuite
<i>key1</i>	is the first key, for which we have the private value
<i>key1enclen</i>	is the length of the encoded form of key1
<i>key1en</i>	is the encoded form of key1
<i>key2</i>	is the peer's key
<i>key2enclen</i>	is the length of the encoded form of key1
<i>key2en</i>	is the encoded form of key1
<i>akey</i>	is the authentication private key
<i>apublen</i>	is the length of the encoded the authentication public key
<i>apub</i>	is the encoded form of the authentication public key
<i>ss</i>	is (a pointer to) the buffer for the shared secret result
<i>sslen</i>	is the size of the buffer (octets-used on exit)

## Returns

1 for good, not-1 for not good

## 4.1.2.6 hpke\_enc()

```
int hpke_enc (
    unsigned int mode,
    hpke_suite_t suite,
    char * pskid,
    size_t psklen,
    unsigned char * psk,
    size_t publen,
    unsigned char * pub,
    size_t privlen,
    unsigned char * priv,
    size_t clearlen,
    unsigned char * clear,
    size_t aadlen,
    unsigned char * aad,
    size_t infolen,
    unsigned char * info,
    size_t * senderpublen,
    unsigned char * senderpub,
    size_t * cipherlen,
    unsigned char * cipher )
```

HPKE single-shot encryption function.

## Parameters

<i>mode</i>	is the HPKE mode
<i>suite</i>	is the ciphersuite to use
<i>pskid</i>	is the pskid string fpr a PSK mode (can be NULL)
<i>psklen</i>	is the psk length

## Parameters

<i>psk</i>	is the psk
<i>publen</i>	is the length of the recipient public key
<i>pub</i>	is the encoded recipient public key
<i>privlen</i>	is the length of the private (authentication) key
<i>priv</i>	is the encoded private (authentication) key
<i>clearlen</i>	is the length of the cleartext
<i>clear</i>	is the encoded cleartext
<i>aadlen</i>	is the length of the additional data (can be zero)
<i>aad</i>	is the encoded additional data (can be NULL)
<i>info</i>	is the length of the info data (can be zero)
<i>info</i>	is the encoded info data (can be NULL)
<i>senderpublen</i>	is the length of the input buffer for the sender's public key (length used on output)
<i>senderpub</i>	is the input buffer for ciphertext
<i>cipherlen</i>	is the length of the input buffer for ciphertext (length used on output)
<i>cipher</i>	is the input buffer for ciphertext

## Returns

1 for good (OpenSSL style), not-1 for error

## 4.1.2.7 hpke\_EVP\_PKEY\_new\_raw\_nist\_private\_key()

```
static EVP_PKEY* hpke_EVP_PKEY_new_raw_nist_private_key (
    int curve,
    unsigned char * buf,
    size_t buflen ) [static]
```

hpke wrapper to import NIST curve private key as easily as x25519/x448

## Parameters

<i>curve</i>	is the curve NID
<i>buf</i>	is the binary buffer with the private value
<i>buflen</i>	is the length of the private key buffer

## Returns

a working EVP\_PKEY \* or NULL

Loads a malarkey required as it turns out... You gotta: 1) name group 2) import private 3) then manually re-calc public key before 4) make an EVP\_PKEY

## 4.1.2.8 hpke\_EVP\_PKEY\_new\_raw\_nist\_public\_key()

```
static EVP_PKEY* hpke_EVP_PKEY_new_raw_nist_public_key (
    int curve,
```

```

    unsigned char * buf,
    size_t buflen ) [static]

```

hpke wrapper to import NIST curve public key as easily as x25519/x448

#### Parameters

<i>curve</i>	is the curve NID
<i>buf</i>	is the binary buffer with the (uncompressed) public value
<i>buflen</i>	is the length of the private key buffer

#### Returns

a working EVP\_PKEY \* or NULL

#### 4.1.2.9 hpke\_expand()

```

static int hpke_expand (
    hpke_suite_t suite,
    int mode5869,
    unsigned char * prk,
    size_t prklen,
    unsigned char * label,
    size_t labellen,
    unsigned char * info,
    size_t infolen,
    uint32_t L,
    unsigned char * out,
    size_t * outlen ) [static]

```

brief RFC5869 HKDF-Expand

#### Parameters

<i>suite</i>	is the ciphersuite
<i>mode5869</i>	- controls labelling specifics
<i>prk</i>	- the initial pseudo-random key material
<i>prk</i>	- length of above
<i>label</i>	- label to prepend to info
<i>labellen</i>	- label to prepend to info
<i>context</i>	- the info
<i>contextlen</i>	- length of above
<i>L</i>	- the length of the output desired
<i>out</i>	- the result of expansion (allocated by caller)
<i>outlen</i>	- buf size on input



## Returns

1 for good otherwise bad

## 4.1.2.10 hpke\_extract()

```
static int hpke_extract (
    hpke_suite_t suite,
    int mode5869,
    const unsigned char * salt,
    const size_t saltlen,
    const unsigned char * label,
    const size_t labellen,
    unsigned char * ikm,
    const size_t ikmlen,
    unsigned char * secret,
    size_t * secretlen ) [static]
```

brief RFC5869 HKDF-Extract

## Parameters

<i>suite</i>	is the ciphersuite
<i>mode5869</i>	- controls labelling specifics
<i>salt</i>	- surprisingly this is the salt;-)
<i>saltlen</i>	- length of above
<i>label</i>	- label for separation
<i>labellen</i>	- length of above
<i>zz</i>	- the initial key material (IKM)
<i>zzlen</i>	- length of above
<i>secret</i>	- the result of extraction (allocated inside)
<i>secretlen</i>	- bufsize on input, used size on output

## Returns

1 for good otherwise bad

Mode can be:

- HPKE\_5869\_MODE\_PURE meaning to ignore all the HPKE-specific labelling and produce an output that's RFC5869 compliant (useful for testing and maybe more)
- HPKE\_5869\_MODE\_KEM meaning to follow section 4.1 where the suite\_id is used as: concat("KEM", I2OSP(kem\_id, 2))
- HPKE\_5869\_MODE\_FULL meaning to follow section 5.1 where the suite\_id is used as: concat("HPKE", I2OSP(kem\_id, 2), I2OSP(kdf\_id, 2), I2OSP(aead\_id, 2))

Isn't that a bit of a mess!

#### 4.1.2.11 hpke\_extract\_and\_expand()

```
static int hpke_extract_and_expand (
    hpke_suite_t suite,
    int mode5869,
    unsigned char * shared_secret,
    size_t shared_secretlen,
    unsigned char * context,
    size_t contextlen,
    unsigned char * secret,
    size_t * secretlen ) [static]
```

ExtractAndExpand.

##### Parameters

<i>suite</i>	is the ciphersuite
<i>mode5869</i>	- controls labelling specifics
<i>shared_secret</i>	- the initial DH shared secret
<i>shared_secretlen</i>	- length of above
<i>context</i>	- the info
<i>contextlen</i>	- length of above
<i>secret</i>	- the result of extract&expand
<i>secretlen</i>	- buf size on input

##### Returns

1 for good otherwise bad

#### 4.1.2.12 hpke\_kem\_id\_check()

```
static int hpke_kem_id_check (
    uint16_t kem_id ) [static]
```

Check if kem\_id is ok/known to us.

##### Parameters

<i>kem_id</i>	is the externally supplied kem_id
---------------	-----------------------------------

##### Returns

1 for good, not-1 for error

#### 4.1.2.13 hpke\_kem\_id\_nist\_curve()

```
static int hpke_kem_id_nist_curve (
    uint16_t kem_id ) [static]
```

check if KEM uses NIST curve or not

##### Parameters

<i>kem_id</i>	is the externally supplied kem_id
---------------	-----------------------------------

##### Returns

1 for NIST, 0 otherwise, -1 for error

#### 4.1.2.14 hpke\_kg()

```
int hpke_kg (
    unsigned int mode,
    hpke_suite_t suite,
    size_t * publen,
    unsigned char * pub,
    size_t * privlen,
    unsigned char * priv )
```

generate a key pair

##### Parameters

<i>mode</i>	is the mode (currently unused)
<i>suite</i>	is the ciphersuite (currently unused)
<i>publen</i>	is the size of the public key buffer (exact length on output)
<i>pub</i>	is the public value
<i>privlen</i>	is the size of the private key buffer (exact length on output)
<i>priv</i>	is the private key

##### Returns

1 for good (OpenSSL style), not-1 for error

#### 4.1.2.15 hpke\_mode\_check()

```
static int hpke_mode_check (
    unsigned int mode ) [static]
```

check mode is in-range and supported

**Parameters**

<i>mode</i>	is the caller's chosen mode
-------------	-----------------------------

**Returns**

1 for good (OpenSSL style), not-1 for error

**4.1.2.16 hpke\_psk\_check()**

```
static int hpke_psk_check (
    unsigned int mode,
    char * pskid,
    size_t psklen,
    unsigned char * psk ) [static]
```

check psk params are as per spec

**Parameters**

<i>mode</i>	is the mode in use
<i>pskid</i>	PSK identifier
<i>psklen</i>	length of PSK
<i>psk</i>	the psk itself

**Returns**

1 for good (OpenSSL style), not-1 for error

If a PSK mode is used both pskid and psk must be non-default. Otherwise we ignore the PSK params.

**4.1.2.17 hpke\_suite\_check()**

```
int hpke_suite_check (
    hpke_suite_t suite )
```

check if a suite is supported locally

**Parameters**

<i>suite</i>	is the suite to check
--------------	-----------------------

**Returns**

1 for good/supported, not-1 otherwise

### 4.1.3 Variable Documentation

#### 4.1.3.1 hpke\_aead\_strtab

```
const char* hpke_aead_strtab[]
```

**Initial value:**

```
={  
    NULL,  
    HPKE_AEADSTR_AES128GCM,  
    HPKE_AEADSTR_AES256GCM,  
    HPKE_AEADSTR_CP}
```

#### 4.1.3.2 hpke\_aead\_tab

```
hpke_aead_info_t hpke_aead_tab[]
```

**Initial value:**

```
={  
    { 0, NULL, 0, 0, 0 },  
    { HPKE_AEAD_ID_AES_GCM_128, EVP_aes_128_gcm, 16, 16, 12 },  
    { HPKE_AEAD_ID_AES_GCM_256, EVP_aes_256_gcm, 16, 32, 12 },  
    { HPKE_AEAD_ID_CHACHA_POLY1305, EVP_chacha20_poly1305, 16, 32, 12 }  
}
```

table of AEADs

#### 4.1.3.3 hpke\_kdf\_strtab

```
const char* hpke_kdf_strtab[]
```

**Initial value:**

```
={  
    NULL,  
    HPKE_KDFSTR_256,  
    HPKE_KDFSTR_384,  
    HPKE_KDFSTR_512}
```

#### 4.1.3.4 hpke\_kdf\_tab

```
hpke_kdf_info_t hpke_kdf_tab[]
```

**Initial value:**

```
={  
    { 0, NULL, 0 },  
    { HPKE_KDF_ID_HKDF_SHA256, EVP_sha256, 32 },  
    { HPKE_KDF_ID_HKDF_SHA384, EVP_sha384, 48 },  
    { HPKE_KDF_ID_HKDF_SHA512, EVP_sha512, 64 }  
}
```

table of KDFs

#### 4.1.3.5 hpke\_kem\_strtab

```
const char* hpke_kem_strtab[]
```

##### Initial value:

```
={
    NULL, NULL, NULL, NULL,
    NULL, NULL, NULL, NULL,
    NULL, NULL, NULL, NULL,
    NULL, NULL, NULL, NULL,
    HPKE_KEMSTR_P256,
    HPKE_KEMSTR_P384,
    HPKE_KEMSTR_P521,
    NULL,
    NULL, NULL, NULL, NULL,
    NULL, NULL, NULL, NULL,
    NULL, NULL, NULL, NULL,
    HPKE_KEMSTR_X25519,
    HPKE_KEMSTR_X448,
    NULL}
```

#### 4.1.3.6 hpke\_kem\_tab

```
hpke_kem_info_t hpke_kem_tab[]
```

table of KEMs

Ok we're wasting space here, but not much and it's ok

#### 4.1.3.7 hpke\_mode\_strtab


```
const char* hpke_mode_strtab[]
```

##### Initial value:


```
={
    HPKE_MODESTR_BASE,
    HPKE_MODESTR_PSK,
    HPKE_MODESTR_AUTH,
    HPKE_MODESTR_PSKAUTH}
```

## 4.2 hpke.h File Reference

```
#include <openssl/ssl.h>
Include dependency graph for hpke.h:
```



This graph shows which files directly or indirectly include this file:



## Data Structures

- struct [hpke\\_suite\\_t](#)  
*ciphersuite combination*

## Macros

- #define [HPKE\\_MAXSIZE](#) (40\*1024)  
*40k is more than enough for anyone (using this program:-)*
- #define [HPKE\\_MODE\\_BASE](#) 0  
*Base mode.*
- #define [HPKE\\_MODE\\_PSK](#) 1  
*Pre-shared key mode.*
- #define [HPKE\\_MODE\\_AUTH](#) 2  
*Authenticated mode.*
- #define [HPKE\\_MODE\\_PSKAUTH](#) 3  
*PSK+authenticated mode.*
- #define [HPKE\\_KEM\\_ID\\_RESERVED](#) 0x0000  
*not used*
- #define [HPKE\\_KEM\\_ID\\_P256](#) 0x0010  
*NIST P-256.*
- #define [HPKE\\_KEM\\_ID\\_P384](#) 0x0011  
*NIST P-256.*
- #define [HPKE\\_KEM\\_ID\\_P521](#) 0x0012  
*NIST P-521.*
- #define [HPKE\\_KEM\\_ID\\_25519](#) 0x0020  
*Curve25519.*
- #define [HPKE\\_KEM\\_ID\\_448](#) 0x0021  
*Curve448.*
- #define [HPKE\\_KDF\\_ID\\_RESERVED](#) 0x0000  
*not used*
- #define [HPKE\\_KDF\\_ID\\_HKDF\\_SHA256](#) 0x0001  
*HKDF-SHA256.*
- #define [HPKE\\_KDF\\_ID\\_HKDF\\_SHA384](#) 0x0002

- HKDF-SHA512.*
  - #define [HPKE\\_KDF\\_ID\\_HKDF\\_SHA512](#) 0x0003
    - HKDF-SHA512.*
  - #define [HPKE\\_KDF\\_ID\\_MAX](#) 0x0003
    - HKDF-SHA512.*
  - #define [HPKE\\_AEAD\\_ID\\_RESERVED](#) 0x0000
    - not used*
  - #define [HPKE\\_AEAD\\_ID\\_AES\\_GCM\\_128](#) 0x0001
    - AES-GCM-128.*
  - #define [HPKE\\_AEAD\\_ID\\_AES\\_GCM\\_256](#) 0x0002
    - AES-GCM-256.*
  - #define [HPKE\\_AEAD\\_ID\\_CHACHA\\_POLY1305](#) 0x0003
    - Chacha20-Poly1305.*
  - #define [HPKE\\_AEAD\\_ID\\_MAX](#) 0x0003
    - Chacha20-Poly1305.*
  - #define [HPKE\\_MODESTR\\_BASE](#) "base"
    - base mode (1), no sender auth*
  - #define [HPKE\\_MODESTR\\_PSK](#) "psk"
    - psk mode (2)*
  - #define [HPKE\\_MODESTR\\_AUTH](#) "auth"
    - auth (3), with a sender-key pair*
  - #define [HPKE\\_MODESTR\\_PSKAUTH](#) "pskauth"
    - psk+sender-key pair (4)*
  - #define [HPKE\\_KEMSTR\\_P256](#) "p256"
    - KEM id 0x10.*
  - #define [HPKE\\_KEMSTR\\_P384](#) "p384"
    - KEM id 0x11.*
  - #define [HPKE\\_KEMSTR\\_P521](#) "p521"
    - KEM id 0x12.*
  - #define [HPKE\\_KEMSTR\\_X25519](#) "x25519"
    - KEM id 0x20.*
  - #define [HPKE\\_KEMSTR\\_X448](#) "x448"
    - KEM id 0x21.*
  - #define [HPKE\\_KDFSTR\\_256](#) "hkdf-sha256"
    - KDF id 1.*
  - #define [HPKE\\_KDFSTR\\_384](#) "hkdf-sha384"
    - KDF id 2.*
  - #define [HPKE\\_KDFSTR\\_512](#) "hkdf-sha512"
    - KDF id 3.*
  - #define [HPKE\\_AEADSTR\\_AES128GCM](#) "aes128gcm"
    - AEAD id 1.*
  - #define [HPKE\\_AEADSTR\\_AES256GCM](#) "aes256gcm"
    - AEAD id 2.*
  - #define [HPKE\\_AEADSTR\\_CP](#) "chachapoly1305"
    - AEAD id 3.*
  - #define [HPKE\\_SUITE\\_DEFAULT](#) { [HPKE\\_KEM\\_ID\\_25519](#), [HPKE\\_KDF\\_ID\\_HKDF\\_SHA256](#), [HPKE\\_AEAD\\_ID\\_AES\\_GCM\\_128](#) }
    -
  - #define [HPKE\\_SUITE\\_TURNITUPTO11](#) { [HPKE\\_KEM\\_ID\\_448](#), [HPKE\\_KDF\\_ID\\_HKDF\\_SHA512](#), [HPKE\\_AEAD\\_ID\\_CHACHA\\_POLY1305](#) }
    -
  - #define [HPKE\\_A2B](#)(\_\_c\_\_)
- Map ascii to binary - utility macro used in > 1 place.*



## Functions

- int [hpke\\_enc](#) (unsigned int mode, [hpke\\_suite\\_t](#) suite, char \*pskid, size\_t psklen, unsigned char \*psk, size\_t publen, unsigned char \*pub, size\_t privlen, unsigned char \*priv, size\_t clearlen, unsigned char \*clear, size\_t aadlen, unsigned char \*aad, size\_t infolen, unsigned char \*info, size\_t \*senderpublen, unsigned char \*senderpub, size\_t \*cipherlen, unsigned char \*cipher)  
*HPKE single-shot encryption function.*
- int [hpke\\_dec](#) (unsigned int mode, [hpke\\_suite\\_t](#) suite, char \*pskid, size\_t psklen, unsigned char \*psk, size\_t publen, unsigned char \*pub, size\_t privlen, unsigned char \*priv, EVP\_PKEY \*evppriv, size\_t encen, unsigned char \*enc, size\_t cipherlen, unsigned char \*cipher, size\_t aadlen, unsigned char \*aad, size\_t infolen, unsigned char \*info, size\_t \*clearlen, unsigned char \*clear)  
*HPKE single-shot decryption function.*
- int [hpke\\_kg](#) (unsigned int mode, [hpke\\_suite\\_t](#) suite, size\_t \*publen, unsigned char \*pub, size\_t \*privlen, unsigned char \*priv)  
*generate a key pair*
- int [hpke\\_ah\\_decode](#) (size\_t ahlen, const char \*ah, size\_t \*blen, unsigned char \*\*buf)  
*decode ascii hex to a binary buffer*
- int [hpke\\_suite\\_check](#) ([hpke\\_suite\\_t](#) suite)  
*check if a suite is supported locally*

### 4.2.1 Detailed Description

This has the data structures and prototypes (both internal and external) for an OpenSSL-based HPKE implementation following draft-irtf-cfrg-hpke

I plan to use this for my ESNI-enabled OpenSSL build when the time is right, that's: <https://github.com/sftcd/openssl>

### 4.2.2 Macro Definition Documentation

#### 4.2.2.1 HPKE\_A2B

```
#define HPKE_A2B(
    __c__ )
```

**Value:**

```
(__c__>='0' && __c__<='9' ? (__c__-'0') : \
 (__c__>='A' && __c__<='F' ? (__c__-'A'+10) : \
 (__c__>='a' && __c__<='f' ? (__c__-'a'+10) : 0))
```

Map ascii to binary - utility macro used in >1 place.

#### 4.2.2.2 HPKE\_SUITE\_DEFAULT

```
#define HPKE_SUITE_DEFAULT { HPKE\_KEM\_ID\_25519, HPKE\_KDF\_ID\_HKDF\_SHA256, HPKE\_AEAD\_ID\_AES\_GCM\_128 }
```

Two suite constants, use this like:

```
hpke_suite_t myvar = HPKE_SUITE_DEFAULT;
```

## 4.2.3 Function Documentation

### 4.2.3.1 hpke\_ah\_decode()

```
int hpke_ah_decode (
    size_t ahlen,
    const char * ah,
    size_t * blen,
    unsigned char ** buf )
```

decode ascii hex to a binary buffer

#### Parameters

<i>ahlen</i>	is the ascii hex string length
<i>ah</i>	is the ascii hex string
<i>blen</i>	is a pointer to the returned binary length
<i>buf</i>	is a pointer to the internally allocated binary buffer

#### Returns

1 for good (OpenSSL style), not-1 for error

Since I always have to reconstruct this again in my head...  
Bash command line hashing starting from ascii hex example:

```
$ echo -e "4f6465206f6e2061204772656369616e2055726e" | xxd -r -p | openssl sha256
(stdin)= 55c4040629c64c5efec2f7230407d612d16289d7c5d7afcf9340280abd2de1ab
```

The above generates the Hash(info) used in Appendix A.2

If you'd like to regenerate the zero\_sha256 value above, feel free

```
$ echo -n "" | openssl sha256
echo -n "" | openssl sha256
(stdin)= e3b0c44298fclcl49afbf4c8996fb92427ae41e4649b934ca495991b7852b855
Or if you'd like to re-caclulate the sha256 of nothing...
SHA256_CTX sha256;
SHA256_Init(&sha256);
char* buffer = NULL;
int bytesRead = 0;
SHA256_Update(&sha256, buffer, bytesRead);
SHA256_Final(zero_sha256, &sha256);
...but I've done it for you, so no need:-)
static const unsigned char zero_sha256[SHA256_DIGEST_LENGTH] = {
    0xe3, 0xb0, 0xc4, 0x42, 0x98, 0xfc, 0x1c, 0x14,
    0x9a, 0xfb, 0xf4, 0xc8, 0x99, 0x6f, 0xb9, 0x24,
    0x27, 0xae, 0x41, 0xe4, 0x64, 0x9b, 0x93, 0x4c,
    0xa4, 0x95, 0x99, 0x1b, 0x78, 0x52, 0xb8, 0x55};
```

## Parameters

<i>ahlen</i>	is the ascii hex string length
<i>ah</i>	is the ascii hex string
<i>blen</i>	is a pointer to the returned binary length
<i>buf</i>	is a pointer to the internally allocated binary buffer

## Returns

1 for good otherwise bad

## 4.2.3.2 hpke\_dec()

```
int hpke_dec (
    unsigned int mode,
    hpke_suite_t suite,
    char * pskid,
    size_t psklen,
    unsigned char * psk,
    size_t publen,
    unsigned char * pub,
    size_t privlen,
    unsigned char * priv,
    EVP_PKEY * evppriv,
    size_t enclen,
    unsigned char * enc,
    size_t cipherlen,
    unsigned char * cipher,
    size_t aadlen,
    unsigned char * aad,
    size_t infolen,
    unsigned char * info,
    size_t * clearlen,
    unsigned char * clear )
```

HPKE single-shot decryption function.

## Parameters

<i>mode</i>	is the HPKE mode
<i>suite</i>	is the ciphersuite
<i>pskid</i>	is the pskid string fpr a PSK mode (can be NULL)
<i>psklen</i>	is the psk length
<i>psk</i>	is the psk
<i>publen</i>	is the length of the public (authentication) key
<i>pub</i>	is the encoded public (authentication) key
<i>privlen</i>	is the length of the private key
<i>priv</i>	is the encoded private key
<i>evppriv</i>	is a pointer to an internal form of private key
<i>enclen</i>	is the length of the peer's public value

**Parameters**

<i>enc</i>	is the peer's public value
<i>cipherlen</i>	is the length of the ciphertext
<i>cipher</i>	is the ciphertext
<i>aadlen</i>	is the lenght of the additional data
<i>aad</i>	is the encoded additional data
<i>infolen</i>	is the lenght of the info data (can be zero)
<i>info</i>	is the encoded info data (can be NULL)
<i>clearlen</i>	is the length of the input buffer for cleartext (octets used on output)
<i>clear</i>	is the encoded cleartext

**Returns**

1 for good (OpenSSL style), not-1 for error

**4.2.3.3 hpke\_enc()**

```
int hpke_enc (
    unsigned int mode,
    hpke_suite_t suite,
    char * pskid,
    size_t psklen,
    unsigned char * psk,
    size_t publen,
    unsigned char * pub,
    size_t privlen,
    unsigned char * priv,
    size_t clearlen,
    unsigned char * clear,
    size_t aadlen,
    unsigned char * aad,
    size_t infolen,
    unsigned char * info,
    size_t * senderpublen,
    unsigned char * senderpub,
    size_t * cipherlen,
    unsigned char * cipher )
```

HPKE single-shot encryption function.

**Parameters**

<i>mode</i>	is the HPKE mode
<i>suite</i>	is the ciphersuite to use
<i>pskid</i>	is the pskid string fpr a PSK mode (can be NULL)
<i>psklen</i>	is the psk length
<i>psk</i>	is the psk
<i>publen</i>	is the length of the recipient public key
<i>pub</i>	is the encoded recipient public key

## Parameters

<i>privlen</i>	is the length of the private (authentication) key
<i>priv</i>	is the encoded private (authentication) key
<i>clearlen</i>	is the length of the cleartext
<i>clear</i>	is the encoded cleartext
<i>aadlen</i>	is the lenght of the additional data (can be zero)
<i>aad</i>	is the encoded additional data (can be NULL)
<i>info</i>	is the lenght of the info data (can be zero)
<i>info</i>	is the encoded info data (can be NULL)
<i>senderpublen</i>	is the length of the input buffer for the sender's public key (length used on output)
<i>senderpub</i>	is the input buffer for ciphertext
<i>cipherlen</i>	is the length of the input buffer for ciphertext (length used on output)
<i>cipher</i>	is the input buffer for ciphertext

## Returns

1 for good (OpenSSL style), not-1 for error

## 4.2.3.4 hpke\_kg()

```
int hpke_kg (
    unsigned int mode,
    hpke_suite_t suite,
    size_t * publen,
    unsigned char * pub,
    size_t * privlen,
    unsigned char * priv )
```

generate a key pair

## Parameters

<i>mode</i>	is the mode (currently unused)
<i>suite</i>	is the ciphersuite (currently unused)
<i>publen</i>	is the size of the public key buffer (exact length on output)
<i>pub</i>	is the public value
<i>privlen</i>	is the size of the private key buffer (exact length on output)
<i>priv</i>	is the private key

## Returns

1 for good (OpenSSL style), not-1 for error

#### 4.2.3.5 hpke\_suite\_check()

```
int hpke_suite_check (
    hpke_suite_t suite )
```

check if a suite is supported locally

##### Parameters

<i>suite</i>	is the suite to check
--------------	-----------------------


##### Returns

1 for good/supported, not-1 otherwise

### 4.3 hpketv.c File Reference

```
#include <stddef.h>
#include <stdint.h>
#include <string.h>
#include <ctype.h>
#include <stdio.h>
#include "hpke.h"
#include "hpketv.h"
#include <json.h>
#include <json_tokener.h>
```

Include dependency graph for hpketv.c:



### Macros

- #define **FAIL2BUILD**(x) int x;
- #define **grabnum**(\_xx) if (!strcmp(key,"##\_xx")) { thearr[i].\_xx=json\_object\_get\_int(val); }  
*copy typed/named field from json-c to hpke\_tv\_t*
- #define **grabstr**(\_xx) if (!strcmp(key,"##\_xx")) { thearr[i].\_xx=json\_object\_get\_string(val); }  
*copy typed/named field from json-c to hpke\_tv\_t*
- #define **grabestr**(\_xx) if (!strcmp(key,"##\_xx")) { encs[j].\_xx=json\_object\_get\_string(val); }  
*copy typed/named field from json-c to hpke\_tv\_t*
- #define **PRINTIT**(\_xx) printf("\t"##\_xx": %s\n",a->\_xx);  
*print the name of a field and the value of that field*

## Functions

- static char \* **u2c\_transform** (const char \*uncomp)
- int **hpke\_tv\_load** (char \*fname, int \*nelems, [hpke\\_tv\\_t](#) \*\*array)  
*load test vectors from json file to array*
- void **hpke\_tv\_free** (int nelems, [hpke\\_tv\\_t](#) \*array)  
*free up test vector array*
- void **hpke\_tv\_print** (int nelems, [hpke\\_tv\\_t](#) \*array)  
*print test vectors*
- static int **hpke\_tv\_match** (unsigned int mode, [hpke\\_suite\\_t](#) suite, [hpke\\_tv\\_t](#) \*a)
- int **hpke\_tv\_pick** (unsigned int mode, [hpke\\_suite\\_t](#) suite, int nelems, [hpke\\_tv\\_t](#) \*arr, [hpke\\_tv\\_t](#) \*\*tv)  
*select a test vector to use based on mode and suite*

### 4.3.1 Detailed Description

Implementation related to test vectors for HPKE.

This is compiled in if TESTVECTORS is #define'd, otherwise not.

The overall plan with test vectors is to:

- define data structures here to store the test vectors
- have global variables with the actual data
- have a #ifdef'd command line argument to generate/check a test vector
- have #ifdef'd additional parameters to \_enc/\_dec functions for doing generation/checking

Source for test vectors is: <https://raw.githubusercontent.com/cfrg/draft-irtf-cfrg-hpke/master/test-vectors.json> A copy from 20191126 is also in this repo in test-vectors.json

### 4.3.2 Macro Definition Documentation

#### 4.3.2.1 FAIL2BUILD

```
#define FAIL2BUILD(  
    x ) int x;
```

Crap out if this isn't defined.

### 4.3.3 Function Documentation

#### 4.3.3.1 hpke\_tv\_free()

```
void hpke_tv_free (  
    int nelems,  
    hpke\_tv\_t * array )
```

free up test vector array

**Parameters**

<i>nelems</i>	is the number of array elements
<i>array</i>	is a guess what?

Caller doesn't need to free "parent" array

**4.3.3.2 hpke\_tv\_load()**

```
int hpke_tv_load (
    char * fname,
    int * nelems,
    hpke_tv_t ** array )
```

load test vectors from json file to array

**Parameters**

<i>fname</i>	is the json file
<i>nelems</i>	returns with the number of array elements
<i>array</i>	returns with the elements

**Returns**

1 for good, other for bad

**4.3.3.3 hpke\_tv\_pick()**

```
int hpke_tv_pick (
    unsigned int mode,
    hpke_suite_t suite,
    int nelems,
    hpke_tv_t * arr,
    hpke_tv_t ** tv )
```

select a test vector to use based on mode and suite

**Parameters**

<i>mode</i>	is the selected mode
<i>suite</i>	is the ciphersuite
<i>nelems</i>	is the number of array elements
<i>arr</i>	is the elements
<i>tv</i>	is the chosen test vector (doesn't need to be freed)



**Returns**

1 for good, other for bad

This function will randomly pick a matching test vector that matches the specified criteria.

The string to use is like "0,1,1,2" specifying the mode and suite in the (sorta:-) obvious manner. < array of pointers to matching vectors

**4.3.3.4 hpke\_tv\_print()**

```
void hpke_tv_print (
    int nelems,
    hpke_tv_t * array )
```

print test vectors

**Parameters**


<i>nelems</i>	is the number of array elements
<i>array</i>	is the elements

**Returns**

1 for good, other for bad

**4.4 hpketv.h File Reference**

This graph shows which files directly or indirectly include this file:

**Data Structures**

- struct [hpke\\_tv\\_encs\\_t](#)  
*Encryption(s) Test Vector structure using field names from published JSON file.*
- struct [hpke\\_tv\\_s](#)  
*HKPE Test Vector structure using field names from published JSON file.*

## Typedefs

- typedef struct `hpke_tv_s` `hpke_tv_t`  
*HKPE Test Vector structure using field names from published JSON file.*

## Functions

- int `hpke_tv_load` (char \*fname, int \*nelems, `hpke_tv_t` \*\*array)  
*load test vectors from json file to array*
- int `hpke_tv_pick` (unsigned int mode, `hpke_suite_t` suite, int nelems, `hpke_tv_t` \*arr, `hpke_tv_t` \*\*tv)  
*select a test vector to use based on mode and suite*
- void `hpke_tv_free` (int nelems, `hpke_tv_t` \*array)  
*free up test vector array*
- void `hpke_tv_print` (int nelems, `hpke_tv_t` \*array)  
*print test vectors*

### 4.4.1 Detailed Description

Header file related to test vectors for HPKE.

This is compiled in if TESTVECTORS is #define'd, otherwise not.

The overall plan with test vectors is to:

- define data structures here to store the test vectors
- have global variables with the actual data
- have a #ifdef'd command line argument to generate/check a test vector
- have #ifdef'd additional parameters to \_enc/\_dec functions for doing generation/checking

Source for test vectors is: [https://raw.githubusercontent.com/cfrg/draft-irtf-cfrg-hpke/master/test\\_vectors.json](https://raw.githubusercontent.com/cfrg/draft-irtf-cfrg-hpke/master/test_vectors.json) A copy from 20191126 is also in this repo in test-vectors.json

This should only be included if TESTVECTORS is #define'd.

### 4.4.2 Typedef Documentation

#### 4.4.2.1 hpke\_tv\_t

```
typedef struct hpke_tv_s hpke_tv_t
```

HKPE Test Vector structure using field names from published JSON file.

The jobj field (at the end) is the json-c object from which all these are derived and into which most of the char \* pointers point. When we make an array of `hpke_tv_s` then the same jobj will be pointed at by all, so when it's time to call `hpke_tv_free` then we'll just free one of those using the json-c API.

### 4.4.3 Function Documentation

#### 4.4.3.1 hpke\_tv\_free()

```
void hpke_tv_free (
    int nelems,
    hpke_tv_t * array )
```

free up test vector array

##### Parameters

<i>nelems</i>	is the number of array elements
<i>array</i>	is a guess what?

Caller doesn't need to free "parent" array

#### 4.4.3.2 hpke\_tv\_load()

```
int hpke_tv_load (
    char * fname,
    int * nelems,
    hpke_tv_t ** array )
```

load test vectors from json file to array

##### Parameters

<i>fname</i>	is the json file
<i>nelems</i>	returns with the number of array elements
<i>array</i>	returns with the elements

##### Returns

1 for good, other for bad

#### 4.4.3.3 hpke\_tv\_pick()

```
int hpke_tv_pick (
    unsigned int mode,
    hpke_suite_t suite,
    int nelems,
    hpke_tv_t * arr,
    hpke_tv_t ** tv )
```

select a test vector to use based on mode and suite

**Parameters**

<i>mode</i>	is the selected mode
<i>suite</i>	is the ciphersuite
<i>nelems</i>	is the number of array elements
<i>arr</i>	is the elements
<i>tv</i>	is the chosen test vector (doesn't need to be freed)

**Returns**

1 for good, other for bad

This function will randomly pick a matching test vector that matches the specified criteria.

The string to use is like "0,1,1,2" specifying the mode and suite in the (sorta:-) obvious manner. < array of pointers to matching vectors

**4.4.3.4 hpke\_tv\_print()**

```
void hpke_tv_print (
    int nelems,
    hpke_tv_t * array )
```

print test vectors

**Parameters**

<i>nelems</i>	is the number of array elements
<i>array</i>	is the elements

**Returns**

1 for good, other for bad

# Index

## FAIL2BUILD

hpketv.c, [35](#)

## hpke.c, [11](#)

hpke\_aead\_dec, [14](#)  
hpke\_aead\_enc, [14](#)  
hpke\_aead\_strtab, [25](#)  
hpke\_aead\_tab, [25](#)  
hpke\_ah\_decode, [15](#)  
hpke\_dec, [16](#)  
hpke\_do\_kem, [17](#)  
hpke\_enc, [18](#)  
hpke\_EVP\_PKEY\_new\_raw\_nist\_private\_key, [19](#)  
hpke\_EVP\_PKEY\_new\_raw\_nist\_public\_key, [19](#)  
hpke\_expand, [20](#)  
hpke\_extract, [21](#)  
hpke\_extract\_and\_expand, [21](#)  
hpke\_kdf\_strtab, [25](#)  
hpke\_kdf\_tab, [25](#)  
hpke\_kem\_id\_check, [22](#)  
hpke\_kem\_id\_nist\_curve, [22](#)  
hpke\_kem\_strtab, [25](#)  
hpke\_kem\_tab, [26](#)  
hpke\_kg, [23](#)  
hpke\_mode\_check, [23](#)  
hpke\_mode\_strtab, [26](#)  
hpke\_psk\_check, [24](#)  
hpke\_suite\_check, [24](#)

## hpke.h, [26](#)

HPKE\_A2B, [29](#)  
hpke\_ah\_decode, [30](#)  
hpke\_dec, [31](#)  
hpke\_enc, [32](#)  
hpke\_kg, [33](#)  
hpke\_suite\_check, [33](#)  
HPKE\_SUITE\_DEFAULT, [29](#)

## HPKE\_A2B

hpke.h, [29](#)

## hpke\_aead\_dec

hpke.c, [14](#)

## hpke\_aead\_enc

hpke.c, [14](#)

## hpke\_aead\_info\_t, [5](#)

## hpke\_aead\_strtab

hpke.c, [25](#)

## hpke\_aead\_tab

hpke.c, [25](#)

## hpke\_ah\_decode

hpke.c, [15](#)

hpke.h, [30](#)

## hpke\_dec

hpke.c, [16](#)

hpke.h, [31](#)

## hpke\_do\_kem

hpke.c, [17](#)

## hpke\_enc

hpke.c, [18](#)

hpke.h, [32](#)

## hpke\_EVP\_PKEY\_new\_raw\_nist\_private\_key

hpke.c, [19](#)

## hpke\_EVP\_PKEY\_new\_raw\_nist\_public\_key

hpke.c, [19](#)

## hpke\_expand

hpke.c, [20](#)

## hpke\_extract

hpke.c, [21](#)

## hpke\_extract\_and\_expand

hpke.c, [21](#)

## hpke\_kdf\_info\_t, [5](#)

## hpke\_kdf\_strtab

hpke.c, [25](#)

## hpke\_kdf\_tab

hpke.c, [25](#)

## hpke\_kem\_id\_check

hpke.c, [22](#)

## hpke\_kem\_id\_nist\_curve

hpke.c, [22](#)

## hpke\_kem\_info\_t, [6](#)

## hpke\_kem\_strtab

hpke.c, [25](#)

## hpke\_kem\_tab

hpke.c, [26](#)

## hpke\_kg

hpke.c, [23](#)

hpke.h, [33](#)

## hpke\_mode\_check

hpke.c, [23](#)

## hpke\_mode\_strtab

hpke.c, [26](#)

## hpke\_psk\_check

hpke.c, [24](#)

## hpke\_suite\_check

hpke.c, [24](#)

hpke.h, [33](#)

## HPKE\_SUITE\_DEFAULT

hpke.h, [29](#)

## hpke\_suite\_t, [7](#)

## hpke\_tv\_encs\_t, [7](#)

## hpke\_tv\_free

- hpke\_tv.c, [35](#)
  - hpke\_tv.h, [39](#)
- hpke\_tv\_load
  - hpke\_tv.c, [36](#)
  - hpke\_tv.h, [39](#)
- hpke\_tv\_pick
  - hpke\_tv.c, [36](#)
  - hpke\_tv.h, [39](#)
- hpke\_tv\_print
  - hpke\_tv.c, [37](#)
  - hpke\_tv.h, [40](#)
- hpke\_tv\_s, [8](#)
- hpke\_tv\_t
  - hpke\_tv.h, [38](#)
- hpke\_tv.c, [34](#)
  - FAIL2BUILD, [35](#)
  - hpke\_tv\_free, [35](#)
  - hpke\_tv\_load, [36](#)
  - hpke\_tv\_pick, [36](#)
  - hpke\_tv\_print, [37](#)
- hpke\_tv.h, [37](#)
  - hpke\_tv\_free, [39](#)
  - hpke\_tv\_load, [39](#)
  - hpke\_tv\_pick, [39](#)
  - hpke\_tv\_print, [40](#)
  - hpke\_tv\_t, [38](#)