

Use of Python functions

```
# We used some simple builtin functions before, like:
F1001 >>> min(9, 4, 6, 8) # return the smallest value from a list
==> 4
F1002 >>> drinks = ["whiskey", "beer", "wine", "juice", "water"] # define a list
F1003 >>> sorted(drinks) # returns a new list
==> ['beer', 'juice', 'water', 'whiskey', 'wine']
F1004 >>> print("hello world")
p() hello world
F1005 >>> round(5.53703, 2)
==> 5.54
F1006 >>> bool(2+4==6)
==> True
```

Create our own function

```
# let's create a function with the name 'foo'. Does it already exist?
F1007 >>> foo
err! NameError("name 'foo' is not defined",)
# to create our own functions, we use the 'def' statement (=define)
F1008 >>> def foo():
...     print('this is the foo-function')
# the code inside the function is indented one level
# the function is now defined, python knows its name:
F1009 >>> foo
==> <function foo at 0x0000000033B9F28>
# now we call the function - using the name with parenthesis
F1010 >>> foo()
p() this is the foo-function
# we see: calling a function means to execute the statements inside
```

Functions can take arguments

```
F1011 >>> def foo(text):  
...         print("foo was called with '{}'.format(text))  
...         # we just used the same name for new function. Now call it:  
F1012 >>> foo('stars')  
p()      foo was called with 'stars'  
  
...         # several arguments can be used:  
F1013 >>> def foo(arg1, arg2):  
...         print("called with arguments: {}, {}".format(arg1, arg2))  
F1014 >>> foo(987, 38)  
p()      called with arguments: 987, 38
```

Functions can return results

```
# calculate and return a value
F1015 >>> def square(arg1):
...         prod = arg1 * arg1
...         return prod
F1016 >>> square(16)
==> 256

F1017 >>> def multiply(fact1, fact2):
...         return fact1 * fact2
F1018 >>> multiply(7, 13)
==> 91

# try a special function:
F1019 >>> def python_is_cool():
...         return True
F1020 >>> python_is_cool() # no further argument is needed :-)
==> True
```

Return multiple values

```
F1021 >>> drinks = ["whiskey", "beer", "wine", "juice", "water"] # define a list

F1022 >>> def first_and_last(sequ): # take a sequence (like a list)
...     first = sequ[0] # get the first element
...     last = sequ[-1] # and the last
...     return first, last # return more than one value
F1023 >>> first_and_last(drinks) # this returns a tuple
==> ('whiskey', 'water')

F1024 >>> df, dl = first_and_last(drinks) # 'unpack' the tuple
F1025 >>> dl
==> 'water'

F1026 >>> both = first_and_last("LISBOA") # yes, a string can be used like a list
F1027 >>> both # the tuple was assigned to a variable
==> ('L', 'A')

# In the Collection-OOTS there is a section about tuples,
# which explains the handling of tuples more detailed
```

Return from a function

```
# A function does not need a return statement
F1028 >>> def noreturn(text):
...         print("called with:", text)
F1029 >>> result = noreturn('some text')
p() called with: some text
F1030 >>> str(result) # Show the 'None' result
==> 'None'

# A function can have more than one return statement
F1031 >>> def decide(p1, p2):
...         if p2 == True:
...             return p1
...         print('no', p1)
...         return False
F1032 >>> decide("success", True)
==> 'success'
F1033 >>> decide("success", False)
p() no success
==> False
```

Function arguments with defaults (1)

```
# An argument can have a default (predefined) value
F1034 >>> def decide(p1, p2=False):
...         if p2 == True:
...             return p1
...         print('no', p1)
...         return False
F1035 >>> decide("success") # argument p2 is not specified on call
p() no success
==> False
F1036 >>> decide("success", True)
==> 'success'
```

Function arguments with defaults (2)

```
# Arguments without a default value must be specified at the function call
F1037 >>> def manyargs(name, number, third="3rd", fourth=None, fifth="5th"):
...         print("name:{}, number:{}, third:{}, fourth:{}, fifth:{}".format(name, number, third, fourth, fifth))
...
F1038 >>> manyargs('Tom', 17)
p() name:Tom, number:17, third:3rd, fourth:None, fifth:5th
F1039 >>> manyargs('Tom', 17, 'drei') # specify arguments by position
p() name:Tom, number:17, third:drei, fourth:None, fifth:5th
F1040 >>> manyargs('Tom', 17, fourth='vier') # specify an argument by name
p() name:Tom, number:17, third:3rd, fourth:vier, fifth:5th
F1041 >>> manyargs('Tom', number=17, fifth='fünf') # specify by name also for args without default
p() name:Tom, number:17, third:3rd, fourth:None, fifth:fünf

# On a function definition:
#     First arguments without defaults, then arguments with defaults
# On a function call:
#     First arguments without names (positional) then args with names (keyword)
```


Functions used for a general program structure

Most of the code of a program should be enclosed in functions,
starting with a 'main()' function, followed by other function definitions
The last statement in the program is then the call of the main function.

```
F1042 >>> # python3 #  
... """ This is a sample for the general form  
...       of a python program  
...       """  
... import random # import statements  
...  
... def main():  
...     print("start of main function")  
...     result = sample('test')  
...     print("result:", result)  
...  
... def sample(arg1):  
...     print("start of sample function")  
...     return arg1 + ' ' + str(random.random() * 999)  
...  
... print("call of the main function")  
... main()  
p() call of the main function  
p() start of main function  
p() start of sample function  
p() result: test 884.3919664433572
```

Functions as objects

Everything in Python is an object, ==> functions are objects

```
F1043 >>> def foo():      # the def creates a name (foo) and connects it to a function object
...         print('this is foo()')
...         return True
F1044 >>> foo      # show the name of a function
==> <function foo at 0x00000000033BDB70>
F1045 >>> foo()    # execute the function
p()    this is foo()
==> True
F1046 >>> other = foo # a new name for the same object
F1047 >>> other()   # can be used to call the function as well - wow!
p()    this is foo()
==> True
```

Functions as arguments

```
F1048 >>> limit = 4
F1049 >>> def check_limit(arg1):
...         if arg1 > limit: # we can access a variable, which is defined 'outside'
...             print("{} is too big".format(arg1))

F1050 >>> check_limit(3)
F1051 >>> check_limit(8) # to call the function works as expected
p() 8 is too big

# but what goes on here:
F1052 >>> def repeater(count, func):
...         limit = 6 # this does not overwrite the 'limit' defined outside
...         for val in range(count):
...             func(val) # what does happen here?

F1053 >>> repeater(8, check_limit)
p() 5 is too big
p() 6 is too big
p() 7 is too big

# We call the repeater() with a function object, which is then executed inside.
# The repeater can use any function, that is called with one numeric argument.
# check_limit() is defined locally and is later called from 'outside'. A function, handed
# over to someone else, who calls the function later, is a 'call-back' function.
```