

Network Analysis

Stepan Kuznetsov

Computer Science Department, Higher School of Economics

Outline

Watts – Strogatz Random Graphs

Clustering Coefficient

- Our experiment comparing graph from the Facebook dataset and an Erdős – Rényi graph shows that the average clustering coefficient (ACC) is much bigger on real data.

Clustering Coefficient

- Our experiment comparing graph from the Facebook dataset and an Erdős – Rényi graph shows that the average clustering coefficient (ACC) is much bigger on real data.
- Edge probability, however, is the same.

Clustering Coefficient

- The difference of the ACC comes from the fact that in the social network graph the edges are not independent.

Clustering Coefficient

- The difference of the ACC comes from the fact that in the social network graph the edges are not independent.
- Indeed, the existence of edges $A - B$ and $A - C$ increases the probability of $B - C$.

Clustering Coefficient

- The difference of the ACC comes from the fact that in the social network graph the edges are not independent.
- Indeed, the existence of edges $A - B$ and $A - C$ increases the probability of $B - C$.
- This is called the *small-world property*.

Clustering Coefficient

- The difference of the ACC comes from the fact that in the social network graph the edges are not independent.
- Indeed, the existence of edges $A - B$ and $A - C$ increases the probability of $B - C$.
- This is called the *small-world property*.
- Thus, we need better models for social network graphs, than Erdős – Rényi.

Watts – Strogatz Model

- The Watts – Strogatz model was invented for better modelling of graphs with the small-world property: good clustering, small average distance.

Watts – Strogatz Model

- The Watts – Strogatz model was invented for better modelling of graphs with the small-world property: good clustering, small average distance.
- Published in *Nature*, 1998.

Watts – Strogatz Model

- Parameters:

Watts – Strogatz Model

- Parameters:
 - n , number of vertices

Watts – Strogatz Model

- Parameters:
 - n , number of vertices
 - k , average degree; k should be even


Watts – Strogatz Model

- Parameters:
 - n , number of vertices
 - k , average degree; k should be even
 - $\beta \in [0, 1]$ (constant)

Watts – Strogatz Model

- Parameters:
 - n , number of vertices
 - k , average degree; k should be even
 - $\beta \in [0, 1]$ (constant)
- Step 1: regular ring lattice. Put n vertices in a circle and connect each vertex with $k/2$ neighbours on the left and $k/2$ neighbours on the right.

Regular Ring Lattice Example



$$n = 8, k = 4$$

Watts – Strogatz Model

Step 2: rewiring.

- The regular ring lattice is deterministic (just a concrete graph).

Watts – Strogatz Model

Step 2: rewiring.

- The regular ring lattice is deterministic (just a concrete graph).
- Now we add some randomness.

Watts – Strogatz Model

Step 2: rewiring.


- The regular ring lattice is deterministic (just a concrete graph).
- Now we add some randomness.
- Each edge going to the right from a vertex gets *rewired* with probability β to another random point, while avoiding loops and parallel edges.

Watts – Strogatz Model


Step 2: rewiring.

- The regular ring lattice is deterministic (just a concrete graph).
- Now we add some randomness.
- Each edge going to the right from a vertex gets *rewired* with probability β to another random point, while avoiding loops and parallel edges.
- This gives the random graph $WS(n, k, \beta)$.


Rewiring Example



Rewiring Example



Rewiring Example



Properties of $WS(n, k, \beta)$

- The Watts – Strogatz random graph is controlled by the β parameter.

Properties of $WS(n, k, \beta)$

- The Watts – Strogatz random graph is controlled by the β parameter.
- If β is close to zero, then the graph is close to the regular ring lattice.

Properties of $WS(n, k, \beta)$

- The Watts – Strogatz random graph is controlled by the β parameter.
- If β is close to zero, then the graph is close to the regular ring lattice.
- Such a graph shows good clustering ($\frac{3}{4}$ for the lattice itself; $\approx \frac{3}{4}(1 - \beta)^3$ for WS).

Properties of $WS(n, k, \beta)$

- The Watts – Strogatz random graph is controlled by the β parameter.
- If β is close to zero, than the graph is close to the regular ring lattice.
- Such a graph shows good clustering ($\frac{3}{4}$ for the lattice itself; $\approx \frac{3}{4}(1 - \beta)^3$ for WS).
- If β is close to one, the graph is like Erdős – Rényi (but not exactly, since each vertex still should have a high degree, $\geq k/2$).

Properties of $WS(n, k, \beta)$

- The Watts – Strogatz random graph is controlled by the β parameter.
- If β is close to zero, than the graph is close to the regular ring lattice.
- Such a graph shows good clustering ($\frac{3}{4}$ for the lattice itself; $\approx \frac{3}{4}(1 - \beta)^3$ for WS).
- If β is close to one, the graph is like Erdős – Rényi (but not exactly, since each vertex still should have a high degree, $\geq k/2$).
- Average distance falls rapidly when $\beta \rightarrow 1$.

Conclusion

- Thus, Watts – Strogatz is a better model for “small-world” graphs.

Conclusion

- Thus, Watts – Strogatz is a better model for “small-world” graphs.
- There are also other, more sophisticated models, like Barabási – Albert, for example.

Conclusion

- Thus, Watts – Strogatz is a better model for “small-world” graphs.
- There are also other, more sophisticated models, like Barabási – Albert, for example.
- Watts – Strogatz is implemented in NetworkX (just invoke `watts_strogatz_graph`).