

Geodata models and core concepts for analysis

Spatial Data Analysis and Simulation modelling,
2020, Simon Scheider




Outline

- Principles of spatial data transformation
 - Layer principle and overlay in GIS
 - Analysis process
 - Different types of overlay
 - Different methods for point data
- Geometric data models
 - Geometric layer models
 - Vector geometry models
 - Basic geometric manipulations
- Core concept data types
 - Core concepts
 - Core concept data types (CCD)
 - Examples
 - Constraints for possible transformations

Principles of spatial data transformation


Layer principle of GIS

- Fundamental principle
- Layers (vector, raster) are overlaid
 - To derive new layers
 - To spatially analyse landscape
 - To aggregate and summarize data
- Overlay methods for vector and raster data differ, however (and are not always called overlay)



Vector overlay analysis in GIS


- Development suitability analysis
- Steep slopes, soil, and vegetation type given as polygons



	FID	Shape*	FID_soils	CODE	CLASS	FID_sl	SLOPE	FID_veg	DET_TYPE
	3039	Polygon	508	38F	6	0	60	117	A
	3040	Polygon	508	38F	6	0	60	119	SS
	3041	Polygon	508	38F	6	0	60	157	U
	3042	Polygon	508	38F	6	0	60	158	A
	3043	Polygon	508	38F	6	0	60	160	FC

Raster overlay

- Three raster layers (steep slopes, soils, and vegetation) are ranked for development suitability on a scale of 1 to 7.
- Sum = suitability for development




Analysis as a process

The five steps in the analysis process are:

- Frame the question
- Explore and prepare data
- Choose analysis methods and tools
- Perform the analysis
- Examine and refine results


How to decide on each step?



Breaking down an analytic question

What is the proportion of green space in Amsterdam?

What is the amount of elderly people living in PC4 areas in Amsterdam?



Landuse map (Grondgebruik) of the Amsterdam Municipality


Aantal inwoners van 65 jaar en ouder - (2016)



① Informatie over de kaartlaag

Het aantal inwoners dat op 1 januari 65 jaar of ouder is. Een percentage wordt uitgedrukt in gehele procenten van het totaal aantal inwoners in een gebied.


[Verberg legenda >](#)




CBS Buurt (neighborhood) statistics

Selecting overlay methods for analysis

- Which overlay method could be used for assessing the amount of elderly people living in PC4 areas?



(a) Vector overlay method.




(b) Simple areal interpolation method. Image by kind permission of Michael Goodchild.

Methods for spatially combining polygon data. Which one is applicable for analysing a given polygon data set?

How much polluted is Germany?

CO₂ emissions of power plants




```
> co2cleaned[1:5, c("latitude",  
+ "longitude", "carbon_2007")]  
  latitude longitude carbon_2007  
1 51.83248 14.453050    27400000  
2 51.05470  6.575827    24100000  
3 50.99228  6.668831    30400000  
4 51.03780  6.615766    22200000  
5 50.83805  6.313576    22000000
```

Given: some point datasets in R with pollution measurements.

How to assess pollution intensity of Germany?

By interpolation? Aggregation?

PM₁₀ measurements



```
> pm10points[1:5, c("PM10")]  
coordinates      PM10  
52 (9.58591, 53.6706) 16.042  
53 (9.68503, 53.5242) 15.792  
54 (11.2202, 47.9688) 16.833  
55 (13.647, 52.4478) 15.750  
56 (13.2259, 52.4731) 12.375
```


Interpolated CO₂ emissions



Sum of CO₂ emissions



Interpolated PM₁₀ measurements




Sum of PM₁₀ measurements



Aggregation or interpolation?


- ... which GIS methods are appropriate?



Zonal
statistics?



Spatial join?




Point
Interpolation?



Geometric data models

Tessellations

- Regular (Raster) and irregular (Vector)




Point and Line datasets




Generalized geometric layer model

- *Region*: dataset where the geometric primitives are regions (polygons or cells)
- *Tessellation*: A specific form of *Region*. Regions are non-overlapping, and fill the entire extent of the dataset without gaps
- *Raster*: A special kind of *Tessellation*, where the regions are all squares (cells)
- *VectorTessellation*: Irregular tessellation



Vector geometry model (Simple Features)

(WKT standard)



Geometry primitives (2D)



Type	Examples	
Point	POINT (30 10)	
LineString	LINESTRING (30 10, 10 30, 40 40)	
Polygon	POLYGON ((30 10, 10 20, 20 40, 40 40, 30 10))	
	POLYGON ((35 10, 10 20, 15 40, 45 45, 35 10), (20 30, 35 35, 30 20, 20 30))	

Multipart geometries (2D)

Type	Examples	
MultiPoint	MULTIPOINT ((10 40), (40 30), (20 20), (30 10))	
	MULTIPOINT (10 40, 40 30, 20 20, 30 10)	
MultiLineString	MULTILINESTRING ((10 10, 20 20, 10 40), (40 40, 30 30, 40 20, 30 10))	
MultiPolygon	MULTIPOLYGON (((30 20, 10 40, 45 40, 30 20)), ((15 5, 40 10, 10 20, 5 10, 15 5)))	
	MULTIPOLYGON (((40 40, 20 45, 45 30, 40 40)), ((20 35, 45 20, 30 5, 10 10, 10 30, 20 35), (30 20, 20 25, 20 15, 30 20)))	


Vector data model (Geometry + attributes)

- The association of attributes and spatial geometries makes geodata special. Captured by OGC's notion of a *feature* (here: *GeoSPARQL*)




Vector data model (Geometry + attributes)

- GDAL/OGR is a universal library for dealing with vector (and raster) formats <https://gdal.org/>



OGR class structure



Basic geometric operations: Point in Polygon and Centroid

- To find out whether a point is located inside a polygon
- To find out the center of gravity




Figure 7.7 Illustration of the half-line theorem (point-in-polygon rule).

Laurini/Thompson 1996




Figure 7.8 Definition of centroids. (a) Examples of centroids. (b) Examples of centroids defined as centres of gravity. (c) Moving an outside centroid.

Basic geometric operations: Geometric intersections

- Compute the difference, union and intersection of polygons




Figure 7.10 Union and intersection of polygons. (a) Two intersecting polygons. (b) Union of A and B. (c) Intersection of A and B.




Figure 7.11 Splitting two polygons into slabs.


Core concept data types

Core concepts of spatial information (Kuhn 2012)

Cognitive lenses through which the environment can be studied
(... like “cell” in biology or “value” in economics)


Provides constraints for...

1. Analysing geodatasets with tools
2. Posing analytical questions
3. Finding answers with GIS workflows



Core concepts (= what geodata represents)

Field



- continuous phenomenon
- Space -> Quality (value field)
- boundaries are irrelevant

Object



- discrete phenomenon with qualities
- Object -> Space (projected in space, not time)
- boundaries are relevant
- Object -> Quality

Event



- like objects, but...
- Event -> Time, Space (projected in time and space)
















Network




- Quantified relations between objects
- Object x Object -> Quality

Raster/vector data model (= how geodata represents)

- Concept != data model
- Raster – Vector data model
- Can both represent fields, and objects, and networks ...
- So why do we use one over the other?
- Concept is “added” by human interpreter of data
- Concept is needed to understand analysis and possible transformations

The raster view of the world	Happy Valley spatial entities	The vector view of the world
	 Points: hotels	
	 Lines: ski lifts	
	 Areas: forest	
	 Network: roads	
	 Surface: elevation	

How geodata models represent core concepts




Core concept data types (CCD) ontology


The ontology combines three dimensions:

1. Layer types
2. Core concepts
field, object,
event, network
3. Levels of
measurement

(see lab for examples)



In which ways can geodata be transformed?




CCD Ontology

The ontology
can be used to
annotate geodata
resources.
(Scheider et al. 2020)

Examples
from the Amsterdam
data portal


https://maps.amsterdam.nl/open_geodata/



ObjectPoint




EventPoint




PointMeasures



Coverage



Contour




Lattice

The difference between Coverages and Lattices

Tessellations are regions that fully cover space without overlap. For three polygons A, B, and C, land cover type and average elevation values are given in the table. At an arbitrary location inside a polygon, for example, the location marked with a +, a *coverage* yields the quality for that location, such as its land cover type. For a *lattice*, such as average elevation, the elevation value at this particular location (+) is not available.

Coverage: self-similar
(the attribute value of the whole applies also to parts)


Lattice: not self-similar




	Coverage	Lattice
	land cover type	average elevation (m)
A	Forest	631
B	Urban	220
C	Water	42
+	Urban	

Which overlay method could be used for assessing the amount of elderly people living in PC4 areas?


Answer:



(a) CBS Buurt statistics, showing the percentage of persons over 65 in neighborhoods.




Lattices are not self-similar, thus overlay needs to account for this



(b) Simple areal interpolation method. Image by kind permission of Michael Goodchild.

In which ways can geodata be transformed?



The difference between ObjectPoints, PointMeasures, LineMeasures and Contours

ObjectPoints are point representations of objects


PointMeasures are pointwise measurements of fields

LineMeasures are linewise measurements of fields

Contours are tessellated regions of field intervals




Trees: ObjectPoint



Temperature:
PointMeasures




Coast: LineMeasures



Noise: Contours


How much polluted is Germany?

CO₂ emissions of power plants




ObjectPoints


PM₁₀ measurements



PointMeasures



In which ways can geodata be transformed?



Questions?
(Q&A session)

References

- Mandatory readings:
 - Chapter 2 “Measurement frameworks” in Chrisman 2002: Exploring geographic information systems, 2nd edition)
 - Chapter 7: Manipulations (interpolations, geometric operations, transformations) in Laurini and Thompson 1992: Fundamentals of Spatial Information Systems
- <https://www.ogc.org/standards/sfa>
- Kuhn, W. (2012). Core concepts of spatial information for transdisciplinary research. International Journal of Geographical Information Science, 26(12), 2267-2276.
- Scheider, S., Meerlo, R., Kasalica, V., & Lamprecht, A. L. (2020). Ontology of core concept data types for answering geo-analytical questions. Journal of Spatial Information Science, 2020(20), 167-201 (<http://www.josis.org/index.php/josis/article/viewArticle/555>)