Ex.No: 13 13. IMPLEMENT OWN PING PROGRAM
08.10.24

Aim:

To implement a python program to check the connectivity b/w the local system and a specified host using the ping command.

Ping program:

```
import os
import platform
import subprocess
def ping(host="gmail.com", count=4):
    param="-n" if platform.system().lower()=="windows"
                                        else "-c"
    command=["ping", param, str(count), host]
    try:
        output=subprocess.check_output(
            command,
            universal_newlines=True
        )
        print(output)
    except Exception as e:
        print(f"Ping failed: {e}")
if __name__=="__main__":
    ping("8.8.8.8")
```

O/P:

```
Pinging 8.8.8.8 with 32 bytes of data:
Reply from 8.8.8.8: bytes=32 time=6ms TTL=119
Reply from 8.8.8.8: bytes=32 time=10ms TTL=119
Reply from 8.8.8.8: bytes=32 time=12ms TTL=119
Reply from 8.8.8.8: bytes=32 time=5ms TTL=119
```

Ping statistics for 8.8.8.8:

Packets: Sent = 4, Received = 4, Lost = 0 (0% Loss),
Approximate round trip times in milli-seconds.
Minimum = 5ms, Maximum = 12 ms, Average = 8ms.

Result:

Thus, the python program was successfully implemented to ping the specified host 8.8.8.8 and display the connectivity response.