

OSS SKILL

Name: P.Dhanasri

RollNo:2520030115

Sec: 9

Week 1-SKILL

```
dhanu@dhnpc: ~  
GNU nano 7.2 skill1.c  
#include <stdio.h>  
#include <unistd.h>  
#include <sys/wait.h>  
  
int main()  
{  
    pid_t pid;  
  
    pid = fork();  
  
    if (pid == 0)  
    {  
        printf("Child Process\n");  
        printf("Child PID: %d\n", getpid());  
        printf("Parent PID: %d\n", getppid());  
  
        execl("/bin/ls", "ls", NULL);  
    }  
    else if (pid > 0)  
    {  
        printf("Parent Process\n");  
        printf("Parent PID: %d\n", getpid());  
  
        wait(NULL);  
  
        printf("Child process completed.\n");  
    }  
    else  
    {  
        perror("fork failed");  
    }  
  
    return 0;  
}
```

```

dhanu@dhnpc:~$ nano skill1.c
dhanu@dhnpc:~$ gcc skill1.c -o skill1
dhanu@dhnpc:~$ ./skill1
Parent Process
Parent PID: 619
Child Process
Child PID: 620
Parent PID: 619
6.1.6          command_exec.c  command_vxdc  read.c  t2.txt  week3.c
a.out          command_vx.c    dhanu.cyyyyy  sample.c  week1
addition.c.save command_vxc    dirl        skill1    week1.c
command_exec   command_vxd    exeworking.c.save skill1.c  week10000
'command_exec. linux' command_vxd.c  open.c      t1.txt    week3
Child process completed.
dhanu@dhnpc:~$

```

Week 2 –skill

```

dhanu@dhnpc: ~
GNU nano 7.2 skill2.c
#include <stdio.h>
#include <string.h>

int main()
{
    char command[100];

    while (1)
    {
        printf("myshell> ");
        fgets(command, sizeof(command), stdin);

        command[strcspn(command, "\n")] = '\0';

        if (strcmp(command, "exit") == 0)
        {
            printf("Exiting shell...\n");
            break;
        }

        printf("You entered: %s\n", command);
    }

    return 0;
}

```

```
dhanu@dhnpc: ~  
dhanu@dhnpc:~$ nano skill2.c  
dhanu@dhnpc:~$ gcc skill2.c -o skill2  
dhanu@dhnpc:~$ ./skill2  
myshell> hello world  
You entered: hello world  
myshell> ls -l  
You entered: ls -l  
myshell> exit  
Exiting shell...  
dhanu@dhnpc:~$
```

Week 3 – SKILL

```
dhanu@dhnpc: ~  
GNU nano 7.2 skill3.c  
#include <stdio.h>  
#include <string.h>  
  
int main()  
{  
    char history[5][100];  
    char command[100];  
    int count = 0;  
    int i;  
  
    printf("Simple Shell History\n");  
  
    while (count < 5)  
    {  
        printf("myshell> ");  
        fgets(command, sizeof(command), stdin);  
  
        command[strcspn(command, "\n")] = '\0';  
  
        if (strcmp(command, "history") == 0)  
        {  
            printf("\nCommand History:\n");  
  
            for (i = 0; i < count; i++)  
            {  
                printf("%d %s\n", i + 1, history[i]);  
            }  
  
            continue;  
        }  
  
        if (strcmp(command, "exit") == 0)  
        {  
            break;  
        }  
  
        strcpy(history[count], command);  
        count++;  
    }  
  
    return 0;  
}
```



Select dhanu@dhnpc: ~

```
dhanu@dhnpc:~$ nano skill3.c
dhanu@dhnpc:~$ gcc skill3.c -o skill3
dhanu@dhnpc:~$ ./skill3
```

Simple Shell History

```
myshell> ls
myshell> pwd
myshell> date
myshell> history
```

Command History:

```
1  ls
2  pwd
3  date
myshell> █
```