

HiCEnterprise

Documentation

HANIA KRANAS, IRINA TUSZYŃSKA, BARTEK WILCZYŃSKI

January 3, 2018

Contents

1	Introduction	2
1.1	What is in the package?	2
1.1.1	Types of analyses	2
1.2	Dependencies	2
1.3	Basic usage	2
1.3.1	Installation	3
1.3.2	Examples	3
2	HiCEnterprise regions	4
2.1	Input files	4
2.2	Usage	4
2.2.1	Basics	4
2.3	Output files	6
2.3.1	stats folder	6
2.3.2	figures folder	7
2.3.3	pickles folder	7
2.4	All arguments listed alphabetically	7
3	HiCEnterprise tads	9
3.1	Input files	9
3.2	Output files	10
3.2.1	stats folder	10
3.2.2	figures folder	10
3.3	All arguments listed alphabetically	10

Chapter 1

Introduction

HiCEnterprise predicts long-range interactions between regions/domains based on Hi-C maps.
Establish contact!

1.1 What is in the package?

HiCEnterprise takes a list of regions/domains and searches for their significant interactions on given Hi-C maps. Package consists of two types of analyses: regions and domains.

1.1.1 Types of analyses

1.1.1.1 Regions

This part of the package is an implementation of the method for identification of long-range interacting regions and creating interaction profiles based on Hi-C data as introduced by (Won et al. 2016).

More in 2.

1.1.1.2 Domains

In the domain part of the package we implemented the method for prediction of long-range interactions between TADs (Topologically Associating Domains) as presented by (Niskanen et al. n.d.).

More in 3.

1.2 Dependencies

- Python version 2.7 or 3.5/6
- required python packages are provided in requirements.txt file.
- if you want to plot through R, you need have R installed with needed packages.

1.3 Basic usage

HiCEnterprise type options

'type' can be either regions or domains. Other options are type dependent.

If you want to see the list of available arguments with short explanations type either `HiCEnterprise regions --help` or `HiCEnterprise domains --help`. Full specifications for each argument can be found in the documentation (2 and 3)

1.3.1 Installation

```
python setup.py install
```

You may need administrative privileges to do this.

1.3.1.1 Testing the installation

To test if the scripts behave in a way they should be find the main HiCEnterprise directory and run:

```
python setup.py test
```

pytest package is needed for running the test framework.

1.3.2 Examples

We provided some example files (used for testing too) with which you can learn to use the program. Here you can see two example runs:

1.3.2.1 Regions

```
HiCEnterprise regions regions_options
```

1.3.2.2 Domains

```
HiCEnterprise domains domains_options
```

Additional examples and specifications for each argument can be found in the documentation for a specific type (2 and 3).

Chapter 2

HiCEnterprise regions

Regions part of package can be used to identify long-range interacting regions and creating interaction profiles based on Hi-C data. It is based on the method described by (Won, 2016). The significance of the individual pairwise interaction between bins is calculated as the probability of observing a stronger contact under the fitted Weibull distribution matched by chromosome and distance. FDR (False Discovery Rate) is used for correcting for multiple testing.

2.1 Input files

To run the point interactions analysis you need:

- at least one Hi-C map in numpy format for an N chromosome (named `mtx-N-N.npy`)
- BED file with coordinates of regions to extract interaction profiles for (or Enhancer Atlas FASTA file - it has positions of the enhancer region in fasta header of each sequence).

All coordinates should be provided in bp. Analysis results will be more reliable if you provide multiple Hi-C maps that are biological replicates.

2.1.0.1 Example files

Example files are provided in `HiCEnterprise/HiCEnterprise/tests/test_files` directory in `maps` and `enhseq`.

2.2 Usage

2.2.1 Basics

Overall, the usage looks like this:

```
HiCEnterprise regions regions_options
```

To see the available options:

```
HiCEnterprise regions -h
```

2.2.1.1 Example runs

There are a few required arguments for the analysis.

- Path to folders with Hi-C maps in a numpy format:
`--hic_folders ./map40kb_replicate1 ./map40kb_replicate2 \ldots`
- File with coordinates of regions to extract interaction profiles for:
`--region_file regions.bed`
- Name of the chromosome to run the analysis for: `--chr 22`
- Resolution (bin size) of Hi-C maps in bp (all maps provided should be of the same resolution): `--bin_res 40000`

For information on formats of files see 2.1.

Run with only required arguments:

```
HiCEnterprise regions --hic_folders ./map40kb_replicate1
./map40kb_replicate2 --region_file ./regions.bed --chr 22
--bin_res 40000
```

2.2.1.2 Visualisation

If you want to plot the results, add `-plotting` argument to the command. It is possible to choose if you want to plot with matplotlib (mpl) or rpy2 and R (rpy2). Resulting figures can be found in directory provided by `-figures_folder` option.

Example plotting with matplotlib:

```
HiCEnterprise regions --hic_folders ./map40kb_replicate1
./map40kb_replicate2 --region_file ./regions.bed --chr 22 --bin_res
40000 --plotting mpl --figures_folder ./my_folder_for_figures
```

If you don not provide the `-figures_folder` argument, `./figures` directory will be created and the plots will be put there.

2.2.1.2.1 Example usage files There are also some files with example usage files provided in `HiCEnterprise/example_usage` directory i.e.:

- TSS enrichment analysis for found predictions of interactions
- generating random bins
- extracting unique bins and adjusting statistics for comparison between two analyses

Those additional scripts may generate new directories and results. For now, as they are not an official part of the package they are not discussed in this documentation.

2.3 Output files

2.3.1 stats folder

This folder contains the results from the analysis. Result filenames consist of regions file name, map folders names, either 'stats' or 'significant', chromosome name, number of bins considered, resolution and statistical cutoff threshold. Example: regions-map40kb_replicate1-map40kb_replicate2-stats22-200x40000bp-0_01.txt.

2.3.1.1 'stats' files

Stats files are text files that contain statistics derived from analysis. They provide the number of regions (bin regions) in the analysis, how many had predictions and some simple statistics.

2.3.1.2 'significant' files

Files with 'significant' in name contain the statistically significant (with given FDR threshold) interactions derived from the analysis. They can be created in three formats (see 2.4):

2.3.1.2.1 custom txt format Txt contains bin and regions coordinates and corresponding predictions of interactions with q-values.

2.3.1.2.2 modified BED format 3 first columns are coordinates of the predicted interaction, 4th column encodes coordinates of region that interacts, 5th column is score (-log10 q-value).

2.3.1.2.3 modified GFF format Modified GFF contains columns as follows:

- chromosome name
- program name
- type: group (group of regions and their predictions), region, prediction
- start coordinate
- end coordinate
- score (-log10 q-value) for predictions
- strand (none, '?')
- frame (none, '?')
- ID of Parent (group of regions and their predictions) with chromosome name and bin from original assembly

Results in GFF files can be remapped from the original assembly to another one with argument `-remap` (see 2.4). GFF files are suitable for a representation in Jbrowse with modified CSS (thanks to Karolina Sienkiewicz).

2.3.2 figures folder

In this folder you will find the plotted figures if the `-plotting` argument was used. Interaction profiles are extracted to PDF files. Files are named by the regions file name and additional plotting arguments (`-num_regs`, `-section`). Each interaction profile is composited of weighted log Intensity, $-\log_{10}$ p-values and $-\log_{10}$ q-values.

2.3.3 pickles folder

Pickles folder contains pickle files (generated by pickle python library) with saved parts of results that may be useful for running new analyses on the same data (i.e. same Hi-C maps but other regions). Weibull fitting takes a while, so saving the parameters of the distribution for a given map, chromosome and distance can save a lot of time in future calculations.

2.4 All arguments listed alphabetically

- Python version 2.7 or 3.5/6
- required python packages are provided in requirements.txt file.
- if you want to plot through R, you need have R installed with needed packages.
- `-a`, `-section` : Section of bp for the plot
- `-b`, `-bin_res` : REQUIRED Resolution (size of the bins on the Hi-C maps) in bp i.e. 10000 for 10kb resolution. All maps should be of same resolution.
- `-c`, `-chr` : REQUIRED Name of the chromosome for which to extract domain interactions.
- `-f`, `-figures_folder` : Folder to save the figures (plots) in. Default is `'./figures/'`.
- `-m`, `-hic_folders` : REQUIRED Folder/folders in which the Hi-C data is stored with file names in format `mtx-N-N.npy`, where N = chromosome name
- `-n`, `-num_bins` : Number of bins left and right to be considered when extracting the interaction profile.
- `-num_regs` : Number of regions to plot
- `-p`, `-pickled_folder` : Folder with pickled files (to load from/save in). Default is `'./pickles/'`.
- `-plotting` : If there should be plotting, and if so should it be with rpy2 or matplotlib. Options: `mpl`, `rpy2`. Default is `TODO`
- `-r`, `-region_file` : REQUIRED Any tab-delimited BED file or FASTA File from Enhancer-Atlas with regions and their positions.
- `-regs_algorithm` : Algorithm for sorting regions to bins. Options: `all`, `one`. Default is `all`. `TODO` more info
- `-remap` : Assembly that maps and regions are currently in, and assembly in which to save the stats in. Format: `assembly:new_assembly` i.e. `hg_19:hg_38`. Currently only available for GFF files.

- `-s, -stats_folder` : Folder to save the statistics and significant points in. Default is `'../stats/'`.
- `-single_sig` : If the single map significant points should be saved or not.
- `-stat_formats` : In which file formats to save statistics. It is possible to provide multiple formats. Available: `txt`, `bed`, `gff`. Default is only `txt`.
- `-t, -threshold` : Statistical cutoff threshold. Default is `0.01`.

Chapter 3

HiCEnterprise tads

In the domain part of the package the significance of interaction between domains A and B is calculated as the probability of observing a stronger contact under the fitted Hypergeometric distribution, where N (population size) is the sum of all frequencies in the Hi-C map, a is the sum from the column of domain A and b is the sum from the row of domain B (number of success states in the population and number of draws). This idea and original code was developed by Irina Tuszynska and presented in (Niskanen et al. n.d.).

3.1 Input files

To run the point interactions analysis you need:

- one Hi-C map in numpy format for an N chromosome (named `mtx-N-N.npy`)
- file with domains definition in the format: domain id, chromosome name, start coordinate, end coordinate. Optionally fifth column may contain sherpa level.

All coordinates should be provided in bp.

3.1.0.1 Example files

Example files are provided in `HiCEnterprise/HiCEnterprise/tests/test_files` directory in `maps` and `doms`.

Overall, the usage looks like this:

```
HiCEnterprise domains domains_options
```

To see the available options:

```
HiCEnterprise domains -h
```

3.1.0.2 Example runs

There are a few required arguments for the analysis.

- Path to folder with Hi-C map in a numpy format: `--hic_folder ./map40kb`
- File with domain definition: `--domain_file domains.txt`
- Name of the chromosome to run the analysis for: `--chr 22`

- Resolution (bin size) of Hi-C maps in bp (all maps provided should be of the same resolution): `--bin_res 40000`

For information on formats of files see 3.1.

Run with only required arguments:

```
HiCEnterprise domains --hic_folder ./map40kb --domain_file
./domains.txt --chr 22 --bin_res 40000
```

3.1.0.3 Visualisation

If you want to plot the results with matplotlib, add `-plotting` argument to the command. Resulting figures can be found in directory provided by `-figures_folder` option.

In example:

```
HiCEnterprise domains --hic_folder ./map40kb --domain_file
./domains.txt --chr 22 --bin_res 40000 --plotting
--figures_folder ./my_folder_for_figures
```

If you don not provide the `-figures_folder` argument, `./figures` directory will be created and the plots will be put there.

3.2 Output files

3.2.1 stats folder

This folder contains the results from the analysis. Result filenames consist of domains file name, map folder names, 'stats', chromosome name and statistical cutoff. threshold. Example: `domains-map40kb-stats22-0_01.txt`.

3.2.2 figures folder

In this folder you will find the plotted figures if the `-plotting` argument was used. Interaction maps are extracted to PNG files. Files are named by the regions file name, maps name and other arguments.

3.3 All arguments listed alphabetically

- `-b, --bin_res` : REQUIRED Resolution (size of the bins on the Hi-C maps) in bp i.e. 10000 for 10kb resolution. All maps should be of same resolution.
- `-c, --chr` : REQUIRED Name of the chromosome for which to extract domain interactions.
- `-d, --domain_file` : REQUIRED Text file with domain definition in the format: `dom_id(int) chromosome(int) dom_start(bp) dom_end(bp) sherpa-lvl(optional)`.
- `-f, --figures_folder` : Folder to save the figures (plots) in. Default is `./figures/`.
- `-m, --hic_folder` : REQUIRED Folder in which the Hi-C data is stored with file names in format `mtx-N-N.npy`, where N = chromosome name.
- `-plotting` : If results should be plotted. matplotlib library is required.

- -s, -stats_folder : Folder to save the statistics and significant points in. Default is '../stats/'.
- -sherpa_lvl : If there are sherpa levels in the file and which one to use.
- -t, -threshold : Statistical cutoff threshold. Default is 0.01.