




Philipp Hanslovsky

imglyb Bridging The Chasm Between ImageJ and NumPy

imglyb July 10, 201







What is Python?

- ► Interpreted language with dynamic typing.
- ► Access to native memory.
- ► Efficient software through C/C++ extensions.
- ► Interactive shell and notebooks.

What is Java?

- ► Statically typed language that compiles into byte code.
- ▶ Byte code is executed within a virtual machine (JVM).
- ► No access to native memory through Java language API, but:
 - ► Java Native Interface (JNI)
 - ► Internal methods of the Java Runtime Environment

Why are they hard to combine?

- ► Native vs JVM
- ► Java Array \neq C-Array

► Inter-process communication:

- ► Inter-process communication:
 - ✓ Comparatively easy.
 - ✓ Can be extended to any language.
 - No shared memory.

- ► Inter-process communication:
 - ✓ Comparatively easy.
 - ✓ Can be extended to any language.
 - No shared memory.
- ▶ Python and JVM in the same process:

- ► Inter-process communication:
 - ✓ Comparatively easy.
 - ✓ Can be extended to any language.
 - No shared memory.
- Python and JVM in the same process:
 - ✓ Shared memory possible.
 - ✓ Avoids unnecessary copies of data.

► Java implementation of Python: Jython

- ► Java implementation of Python: Jython
 - ✓ Access native CPython extensions through Jython Native Interface

- ► Java implementation of Python: Jython
 - ✓ Access native CPython extensions through Jython Native Interface
 - Only Jython 2.7 is available

- ► Java implementation of Python: Jython
 - ✓ Access native CPython extensions through Jython Native Interface
 - Only Jython 2.7 is available
- Start Java within a CPython process

✓ Start JVM from Python process.

https://github.com/kivy/pyjnius

✓ Start JVM from Python process.

https://github.com/kivy/pyjnius

Make ImgLib2 and NumPy understand each other.

✓ Start JVM from Python process.

https://github.com/kivy/pyjnius

Make ImgLib2 and NumPy understand each other.

https://github.com/imglib/imglib2-unsafe

✓ Start JVM from Python process.

https://github.com/kivy/pyjnius

Make ImgLib2 and NumPy understand each other.

https://github.com/imglib/imglib2-unsafe https://github.com/imglib/imglib2-imglyb

✓ Start JVM from Python process.

https://github.com/kivy/pyjnius

✓ Make ImgLib2 and NumPy understand each other.


https://github.com/imglib/imglib2-unsafe https://github.com/imglib/imglib2-imglyb

https://github.com/imglib/imglyb




My contribution

imglyb



imglyb



Installation & Usage

► Install imglyb from conda conda install -c conda-forge imglyb

Installation & Usage

- ► Install imglyb from conda conda install -c conda-forge imglyb
- ► Install examples from PyPI pip install imglyb-examples

Installation & Usage

- ► Install imglyb from conda conda install -c conda-forge imglyb
- ► Install examples from PyPI pip install imglyb-examples
- ► Notebooks available on https://github.com/hanslovsky/imglyb-learnathon

How to use?

Import imglyb

```
# import imglyb before jnius
import imglyb
from imglyb import util
# import from jnius what you need
from jnius import autoclass, cast, PythonJavaClass, java_method
```

Wrap NumPy arrays in ImgLib2

```
import imglyb
from imglyb import util
import numpy as np

img = np.random.rand( 300, 200, 100 ) * 2**16
wrapped = util.to_imglib( img )
util.BdvFunctions.show( wrapped, "wrapped image" )

rgba = np.random.randint(
    2**32, size = ( 300, 200, 100 ),
    dtype=np.uint32 )
wrapped_rgba = util.to_imglib_argb( rgba )
util.BdvFunctions.show( wrapped_rgba, "wrapped rgba image" )
```

Examples

Available in the imglyb-examples package:

```
imglyb-examples.bdv-hello-world
imglyb-examples.bdv-painter
imglyb-examples.butterfly
imglyb-examples.qt-awt
imglyb-examples.views-stack
```

Known Issues

- ► Java awt and Swing require wrapper script on macOS
- ▶ Dask Arrays cannot be wrapped as ImgLib2 data structures yet

Example 1 — BigDataViewer



BigDataViewer (BDV) is a Java viewer for arbitrarily large multi-view 3D images and 3D image sequences developed by Tobias Pietzsch.

https://imagej.net/BigDataViewer https://github.com/hanslovsky/imglyb-learnathon/blob/master/ notebooks/bdv/show-numpy-array-in-bdv.ipynb

Example 2 — BigDataViewer



BigDataViewer (BDV) is a Java viewer for arbitrarily large multi-view 3D images and 3D image sequences developed by Tobias Pietzsch.

https://imagej.net/BigDataViewer
https://github.com/hanslovsky/imglyb-learnathon/blob/master/
notebooks/bdv/write-into-numpy-array-in-bdv.ipynb

Example 3 — BigWarp



BigWarp is a tool for interactive manual alignment of 2D or 3D images developed by John Bogovic.

https://imagej.net/BigWarp https://github.com/hanslovsky/imglyb-learnathon/blob/master/ notebooks/bigwarp/bigwarp.ipynb

Example 4 — Paintera

Paintera is a tool for the efficient generation of dense ground truth annotations and proof-reading 3D EM connectomics with 3D visualization and mesh generation on the fly.

https://github.com/saalfeldlab/paintera https://github.com/hanslovsky/imglyb-learnathon/blob/master/ notebooks/paintera/paintera-mesh-generation-on-the-fly.ipynb

Resources



Thank You!



https://github.com/hanslovsky/scipy-2019

conda install -c conda-forge imglyb
pip install imglyb-examples

https://github.com/imglib/imglib2-unsafe https://github.com/imglib/imglib2-imglyb https://github.com/imglib/imglyb https://github.com/hanslovsky/imglyb-examples https://github.com/hanslovsky/imglyb-learnathon

https://github.com/imagej/pyimagej