



Open Table InSpector

Database Browser & Library

for HMG Extended (minigui)

© Hans Marc

Belgium

2020...20xx

(Last update : 22-07-2020)

(Written while the world was fighting the Corona virus.)



Status :

FreeWare

Notice :

This program may not be sold or resold, distributed as a part any commercial package, used in a commercial environment, used or distributed in support of a commercial service, or used or distributed to support any kind of profit-generating activity, even if it is being distributed freely. If you would like to distribute this program as part of a commercial distribution, magazine, Internet book, CD ROM, etc. please contact us for permission.

Disclaimer :

This program is FreeWare and is provided "AS IS" without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose. In no event shall the author be liable for any damages whatsoever including direct, indirect, incidental, consequential, loss of business profits or special damages, even if the author has been advised of the possibility of such damages.

Contents

1. What is Otis.
2. What can you do with Otis.
3. How to use Otis.
4. Main screen.
5. Table Inspector screen.
6. Plugin mode.
7. LetoDbf
8. Settings.
9. Files used & created by Otis.
10. Some screens previews.



What is OTIS

Otis stands for 'Open Table InSpector' and is a database table inspection tool for Dbase, Clipper, Harbour, xHarbour, FoxPro, ..., files.

Otis has a integrated **DATASET manager**. This need some explanations.

A **DATASET** is a set of ONE or MORE tables and index files. You can save this SET of files with a name and load it back again later on with only one click. You can whenever you want add or delete tables and index files to a existing dataset and save it again with the same or another name.

The dataset manager permits you to inspect tables when you are developing and testing a program without cycling through the classic operations like :

- open table, open index file, inspect, modify, update, close
- open another table, open index file, inspect, close
- ...etc.

Create simply a **dataset** with tables and index files that you want to inspect on a regular base, save it, and reload all tables and index files with only one click. I can assure you, you will save a lot of clicks and time.

Why did i create this tool (or rather rewrote)

This is in reality a implementation of a old clipper tool that i wrote, i think, more than 20 years ago. But with far fewer possibilities as this new tool that i called Otis. We integrated this module (the old tool) in all our programs and protect it, if necessary, with a password.

Otis() helped me a lot of times for many many years already because it permits me, on site, to inspect, modify or repair data in a table at runtime on the fly in a simple and fast way. This without the necessity to install other external dbf viewer programs.

In 'Plugin mode', you can use it also for runtime debugging inspection of a table. Thus see 'almost' life updates from the running program. No 'modal' windows are used. By using this method, it permits you to switch between the running program and this tool when you want. You can even open multiple tables at the same time. Each table has its own dbfviewer, called 'Inspector' and all tools. Special precautions are taken for this mode to prevent data corruption when you try to modify a table at the same time as the running program. More details for the 'Plugin mode' in another chapter.

You ask me "Why rewrite yet another dbfviewer" ?

My answer, i found that there was always a thing missing in all other, very known, existing programs like dbu, dba, dbfview, mgdbu, ...etc. So i had to use one or more of them to view and or manipulate a dbf file. I don't want to say that those programs were bad, rather the contrary. I used them often, but i tried to regroup and integrate all possibilities of all those separated tools in a single program. It is certainly not perfect for everybody but i am open for suggestions.

I borrowed some code from other dbfviewer programs that are in the sample folders of hmgextended. All concerned parts of the program contains a remark and reference to the original source and author.

Another reason.

I wanted to update / upgrade the visual design to a new level, like the win10 flat design. I don't like toolbars with a lot of pull-down menus. You have to click, click and click endless everywhere to discover what is possible. My opinion is that a userinterface should be clear and eye-catching. At first look all "bells and whistles" should be visible and my experience (>30 years) showed me that the first user experience is very important for a program to be succesfull.

And not to forget, i could always count on the clipper harbour community if i had a question.

So this is my way to contribute. It would be a pleasure if you dogive me some feedback.

ENJOY, i hope OTIS is of any use for you. Let me know ...



What can you do with Otis :

Support all Codepages known in Harbour.

Support for the following RDD drivers :

You can use a mix of rdd drivers in the same dataset.

```
DBFCDX
DBFNTX
DBFNSX
SIXCDX
LETODBF
```

Dataset manager (main screen) :

- Open tables, multiselect and AutoOpen (cdx) support.
- Attach index files to a table, multiselect support.
- Save multiple tables and index files in a Dataset.
- Load a Dataset.

Table and index properties viewer :

- Export structure to a .csv file.
- Export structure to a .prg file. This prg can be used to create a table and all order index files.
- Export structure to the clipboard.
- View table info : filename, date, reccount, used rdd, used codepage, ...etc.
- View index info : list of all index files, tags, filenames, **KEY**, **FOR** and **WHILE** expressions.

Table structure editor :

- Create a new structure.
- Modify a existing structure.
- Import a table to use the structure for a new table.

Table viewer tool called the 'Inspector' :

- Set a filter.
- Show / Hide deleted() records.
- Set / Clear a filelock.
- Lock (freeze) columns on screen.
- Show / Hide columns.
- Search and replace data, file wide or fields only, with **SCOPE**, **FOR** and **WHILE** expressions.
- Seek wizard :
Presents a form with all fields used in the index KEY expression and auto fills the seek expression.
Seek first, Seek last and Set Exact on/off.
Copy the 'seek expression' to the 'filter expression' textbox so that you can use the same expression to filter a table. Example, seek the first record and then show only records with the same field contents.
- Copy / paste a record :
Paste a record to another record in the same table or
Paste to another table.
All fields or a selection of fields.
- Clear / Duplicate a record.
- Add / Insert records.



- Up / Down, moves a record physically.
- Delete / Recall records with **SCOPE**, **FOR** and **WHILE** expressions.
- Pack / Zap a table.
- Append a file.
- Save a table to another table with the possibility to create a sub table.

Index manager :

- Create a new index, tag.
- Delete a index, tag.
- Reindex all orders.
- View index info.

3. How to use Otis :

You can use it in two different ways :

1. Compile it as a STANDALONE executable.

(The executable of Otis is available for download.)

The most simple method to use this program. Start Otis and add tables, indexes, load and save datasets, inspect tables, ...etc.

2. As a PLUGIN in your project.

That's where the magic happens.

Include OTIS.PRG or OTIS.LIB in your project.

First thing to do, attach function **Otis()** to a hotkey or assign it to, by example, a control "ACTION" property.

When you call this function, Otis() scans 'ALL CURRENTLY OPEN TABLES AND INDEX FILES' opened by your program and creates and present them in a new DATASET.

You can save this dataset. Later on, when you reload this dataset in the Otis standalone version. You will find the same situation as if you where in your program to inspect and or modify data.

More specific information for how to use this mode in another chapter.

4. Main screen of Otis

OTIS - DataSet Manager

Freeware - V1.1 B01 - 17/07/2020

Table Inspector

Recent

mixed rdds cdx and leto

Changed

Exclusive

AutoOpen

FRWIN

DBFCDX

?

Table Properties

Struct. Editor

Load DataSet

Save DataSet

Close DataSet

Add Table(s)

Add Index(es)

Remove Table

Remove Index

Settings

Quit

Alias	Area	S	L	Recno	Reccount	Act.Ind.	Nbr.Ind.	Rdd	Table name
▶ MOVART_1	1	*	F	1	2166236	0	7	LETO	\\tps\MOVART.DBF
CATALOG_2	2	F		1	260276	0	1	LETO	\\tps\catalog.dbf
CAIMHI_3	3	F		1	162867	0	0	LETO	\\tps\CAIMHI.DBF
CAIFHI_4	4	F		1	201113	0	0	LETO	\\tps\CAIFHI.DBF
CAIMDHI_5	5	F		1	120461	0	0	LETO	\\tps\CAIMDHI.DBF
CAIFDHI_6	6	F		1	106729	0	0	LETO	\\tps\CAIFDHI.DBF
CLIENT_7	7	F		1	14729	0	0	LETO	\\tps\CLIENT.DBF
MOVART_8	8	F		1	2166236	0	7	DBFCDX	data\MOVART.DBF
CATALOG_9	9	F		1	260276	0	1	DBFCDX	data\catalog.dbf
CAIMHI_10	10	F		1	162867	0	0	DBFCDX	data\CAIMHI.DBF
CAIFHI_11	11	F		1	201113	0	0	DBFCDX	data\CAIFHI.DBF
CAIMDHI_12	12	F		1	120461	0	0	DBFCDX	data\CAIMDHI.DBF
CAIFAZ_13	13	F		1	0	0	0	DBFCDX	D:\pfwin\Data\tps\CAIFAZ.DBF

Left side menus :

- Table Inspector**

Select one of the tables and click on this menu or double click mouse.

You can open multiple 'Inspectors' at the same time.

- Table Properties**

Opens a screen with the table structure information and menus to export the structure to a prg, a csv file or copy the structure to the clipboard for documentations purposes. The generated prg file can be used immediately in your own program to create a empty dbf file and index files and there orders.

- **Structure Editor**
Create a new table or modify a imported existing structure.
- **Load, Save, Close Dataset**
Does not need further explanation.
- **Add, Remove Table / Index**, idem.
- **Settings**, global program settings.

Top line option menus :

- **Recent**
5 most recent used datasets.
- **Changed**
Read only flag to indicate if a loaded dataset has been modified or created from empty.
- **Exclusive**
Set this checkbox if you want to load tables in exclusive mode. This is necessary for certain functions like, pack, zap, reindex, ...etc. Otis refuses those operations and warns you if a table file is not opened exclusive.
- **AutoOpen**
Open index files automatically if it has the same name as the table. Not supported by the NTX rdd.
- **Codepage**
Sets the default codepage that you want to use to open the tables. All existing codepages in Harbour are loaded in Otis.
- **Default Rdd**
Sets the default rdd driver to use to open tables. You can change this setting when you want. Thus you can load one or more DBFNTX table, then load one or more DBFCDX tables and so on. The rdd used to open a table is saved in the dataset. You can thus mix rdd drivers in one dataset. When you reload a DATASET the proper rdd driver is used for each table.
Supported drivers are :
 - DBFCXD
 - DBFNTX
 - DBFNSX
 - SIXCDX
 - and yes also LETODBF.

Table browse control :

- **Alias name**
Is the same as the table name but suffixed with the area number.
Example, the alias for a table with filename 'MOVART' becomes 'MOVART_1'.
- **Area number**,
 - In Standalone mode assigned automatically.
 - In Plugin mode determined by the running program. Remember we scan all areas from 1...65564.
- **S**
Filled with a '*' if this table the current 'selected' table.
- **L**
Three possibilities :
 - 'F' the file is locked, by a filelock or because the option 'Exclusive' was checked before load.
 - 'R' there is a only one record locked.
 - 'R+' there are more than one records locked.
- **Recno**
Current record number.
- **Reccount**
Total number of records, unfiltered by a index or a filter.

- **Act.Ind.**
Number of the actif order.
- **Nbr.Ind.**
Number of orders (not necessary the number of orderbag files, remember compound cdx files.)
- **Rdd**
Rdd driver used to open the file.
- **Table name**
three possibilites :
 - If LetoDbf Rdd, full data pathname of server.
for others
 - Only the sub path name is saved with the filename if you open a table that is in a sub-folder of the current Otis.exe location. Thus without the drive letter or upper level paths. With this method you can move folder\tables to another location. Otis can reload them from the same location as long as they stay a subfolder of the running program.
 - Full pathname, drive, path and filename if a table is loaded in another folder and or disk.

5. Table Inspector screen :

Select one of the tables and click menu button 'Table Inspector' or simply double click a entry.
As already mentionned, you can open multiple tables each with there own 'Inspector' screen.

OTIS - Open Table InSpector

File: data\MOVART.DBF

Alias: MOVART_8

Area: 8

Orders (7)

01 - JNLFACT+STR(NRFACT,6) for

Hide Deleted

Filelock

Lock columns

On/Off

Allow Edit

Order Scope

Hide Columns

Filter

Seek wizard

Search/Repl.

Goto record

Copy

Paste

Clear

Dupl.

Add

Insert

Up

Down

Delete

Recall

Pack

Zap

Append file

Save as

Index manager

Table properties

Quit

Record	Del	Nrfact	Jnlfact	Link	Status	Repr	Reprcp	Reprcv	Referprod	Denomprod	Refcfou	Date	Decheanc
1		0					0.00	0.00					
2		0					0.00	0.00					
285805		0					0.00	0.00					
2139950		20074	ACH				0.00	0.00		Prestations 01/2020	HMIT	31/01/2020	31/01/20
645012		100001	ACH				0.00	0.00		abonn.019/328204	EUPHONY	01/01/2010	31/01/20
645013		100002	ACH				0.00	0.00		abonn.019/323282	EUPHONY	01/01/2010	31/01/20
645014		100003	ACH				0.00	0.00		Livraison 100002, 05/01/10	INGR	05/01/2010	04/02/20
645015		100003	ACH	BCF900445			0.00	0.00		Backorder 900445, 16/12/09	INGR	05/01/2010	04/02/20
645016		100003	ACH	BCF900445	1 B		0.00	0.00	TOBR_PC301	CARTOUCHE D'IMPRESSION PC-301	INGR	05/01/2010	04/02/20
645017		100004	ACH				0.00	0.00		Livraison 900907, 22/12/09	ABC SOFT	07/01/2010	07/01/20
645018		100004	ACH				0.00	0.00	SOBI_BSEC3UPGRA	BIT DEFENDER BUS. SECURITY 3y upgrade	ABC SOFT	07/01/2010	07/01/20
645019		100004	ACH				0.00	0.00		(upgrade CEP)	ABC SOFT	07/01/2010	07/01/20
645020		100005	ACH				0.00	0.00		Livraison 100013, 08/01/10	TD	07/01/2010	06/02/20
645021		100005	ACH	BCF900455			0.00	0.00		Backorder 900455, 28/12/09	TD	07/01/2010	06/02/20
645022		100005	ACH	BCF900455	14 B		0.00	0.00	PPAS_1005HA-BLS	EeePC 1005HA-BLK0175/10.1" LED anti-Gla	TD	07/01/2010	06/02/20
645023		100005	ACH				0.00	0.00	NRSERIE	Nr s.rie 980AAS195352	TD	07/01/2010	06/02/20
645024		100005	ACH	BCF900455	15 B		0.00	0.00	RECUPEL	TAXE RECYCLAGE RECUPEL : (PPAS_1005HA-BLS)	TD	07/01/2010	06/02/20
645025		100005	ACH	BCF900455	16 B		0.00	0.00	BEBAT	TAXE BEBAT (PPAS_1005HA-BLS)	TD	07/01/2010	06/02/20
645039		100006	ACH				0.00	0.00		Livraison 100014, 08/01/10	TD	07/01/2010	06/02/20
645040		100006	ACH	BCF100004			0.00	0.00	Commande	100004, 08/01/10	TD	07/01/2010	06/02/20
645041		100006	ACH	BCF100004	1 B		0.00	0.00	LCDPH_1905W9FS	TFT PHILIPS 19" TFT, WSVGA,1440x900,SILV	TD	07/01/2010	06/02/20
645042		100006	ACH				0.00	0.00	NRSERIE	Nr s.rie AUSA0943004174	TD	07/01/2010	06/02/20
645043		100006	ACH				0.00	0.00	NRSERIE	Nr s.rie AUSA0943004171	TD	07/01/2010	06/02/20
645044		100006	ACH	BCF100004	2 B		0.00	0.00	RECUPEL	TAXE RECYCLAGE RECUPEL : (LCDPH_1905W9FS)	TD	07/01/2010	06/02/20
645045		100006	ACH	BCF100004	3 B		0.00	0.00	RUKI_DT100/8GB	MEMOIRE USB KINGSTON, 8Gb, Datatraveler	TD	07/01/2010	06/02/20
645046		100006	ACH	BCF100004	4 B		0.00	0.00	RUKI_DT100/16GB	MEMOIRE USB KINGSTON, 16Gb, Datatravele	TD	07/01/2010	06/02/20
645047		100006	ACH	BCF100004	6 B		0.00	0.00	ADSLDLDLS-2640B	Modem Router 4p, ADSL 2640B (1ant), B/G	TD	07/01/2010	06/02/20
645048		100006	ACH	BCF100004	7 B		0.00	0.00	RECUPEL	TAXE RECYCLAGE RECUPEL : (ADSLDLDLS-2640B)	TD	07/01/2010	06/02/20
645049		100006	ACH	BCF100004	8 B		0.00	0.00	MSLO_V100	MOUSE LOGITECH V100 OPTICAL NOTEBOOK	TD	07/01/2010	06/02/20
645050		100006	ACH	BCF100004	10 B		0.00	0.00	MSLO_910-001073	Logitech Wireless Mouse M205 Black WER	TD	07/01/2010	06/02/20
645051		100006	ACH	BCF100004	11 B		0.00	0.00	RECUPEL	TAXE RECYCLAGE RECUPEL : (MSLO_910-001073)	TD	07/01/2010	06/02/20
645052		100006	ACH	BCF100004	12 B		0.00	0.00	BEBAT	TAXE BEBAT (MSLO_910-001073)	TD	07/01/2010	06/02/20
645053		100006	ACH	BCF100004	13 B		0.00	0.00	MSLO_931781	PILOT OPTICAL MOUSE SILVER RET PS2 UBS	TD	07/01/2010	06/02/20
645054		100006	ACH	BCF100004	15 B		0.00	0.00	MSLO_909671	Pilot Optical Mouse Black Retail USB/PS2	TD	07/01/2010	06/02/20
645055		100006	ACH	BCF100004	17 B		0.00	0.00	PPPB_LJ65-DT-02	EasyNote LJ65-DT-0278E/Core2Duo T6600	TD	07/01/2010	06/02/20
645056		100006	ACH				0.00	0.00	NRSERIE	Nr s.rie 94927504516	TD	07/01/2010	06/02/20
2166236		2166236											

This is the real table tool center.

Top menu line :

- **Order (x) and combobox**
Display the number of loaded orders for the table. Use the combobox to select one of the orders.
- **Filter**
Write here a filter expression that you can enable/disable with the checkbox just to the right of it.

- **Hide deleted**
Enable/disable display of 'Deleted' records.



**THIS IS A GLOBAL PROGRAM WIDE SETTING.
BE VERY CAREFULL TO USE THIS OPTION ESPECIALLY IN PLUGIN MODE.
IF YOU CHANGE THIS SETTING YOU CHANGE IT FOR ALL OPENED TABLES
AT THE SAME TIME.**

- **Allow Edit**
Set this checkbox if you want to edit cells in the browse table with a double click.
- **Filelock**
Set a filelock if you want to prevent that other parts of a program can make changes. It is set automatically if you loaded the table exclusive and in consequence can not be unchecked.
- **Order scope**
Opens a window where you can set a order TOP and BOTTOM scope. The checkbox permits to switch between scoped and unscoped display of a table.
Each order can have its own scope.
- **Lock columns**
Spinner and checkbox to freeze 'x' columns.
- **Hide columns**
Permits to select the columns to be displayed. Use the checkbox to switch between the two modes.

Left side menus :

- **Seek wizard**
opens a window wherein you can define a seek expression. The wizard creates a form with all the fields used in the expression. You only need to fill in those fields and the wizard will automatically create the full expression in function of the used index key. This wizard is not perfect and some complex key expressions can not (yet) be treated by the wizard. In that case disable the autofill function and enter the expression manually.
You can seek the first record, the last record, set exact on/off and copy the expression to the filter.
- **Search / Repl.**
Two methods.
The first one to search and / or replace data in a table for only one fields or for all fields at the same time.
The second one to replace data in only one field at the time.
Replace a field with a '**Value**' or with the help of a '**Expression**'.
There are options to **set a scope** and set a **FOR** and / or a **WHILE** expression if needed.
- **Goto record**
Goto top, bottom or goto a specific record.
Don't forget that you can also use ctrl-Home/End to go to the top or bottom of a table.
It is obvious that this is always in function of a actif index and or actif filter.
- **Copy, Paste**
The copie / paste buffer is a **global** program buffer.
You can thus copy/paste contents from **one record to another record in the same table** or to **another table**.

Otis even goes further then what is usually possible.

Sometimes it is necessary to copy/paste only some specific fields and not the whole record.
Otis makes it possible. How to proceed. Hide the columns (fields) in the 'Inspector' that contains the database where you want to copy from. Click, copy. Switch to full columns view, goto another record and click paste. Only the previous visible columns (fields) are pasted.

And as already mentionned, you can even copy fields from one table to another table. Remember, the copy/paste buffer is a global program buffer. How to proceed. The same as if you copy between records in the same table but

before clicking the paste tool, choose another table. Fieldnames that do not exist in the target table or are not of the same type are ignored. Also, only non hidden columns (fields) are copied / pasted.

- **Clear, Duplicate**
Does not need explanations.
- **Add, Insert**
You can add / insert multiple records in one run.
Insert needs some special attention.
Insert is only possible if the table is opened in **exclusive** mode. We use the recently introduced new low level function **DBINSERT()** that is very very fast. The only inconvenience is that dbinsert() ignores actif orders. Otis recreates all orders after it.
- **Up, Down**
Physically moves a record up or down.
One limitation, this function can only be used if there is no order actif.
- **Delete, Recall**
You can delete / recall a single or multiple records, set a SCOPE and if necessary, set a FOR and/or WHILE expression.
You can also use the 'delete' key to delete/recall a single record if the 'Allow edit' box is checked.
- **Pack, Zap**
Does not need explanations only that the table must be opened in **exclusive** mode.
- **Append file**
Does not need explanations.
- **Save as**
Needs some special attention.
If you save a file only the records and fields (columns) that are visible in the browse table are saved.
Option like a filter, hidden columns, scope, index, set deleted, they all defines what is saved.
You can thus easily create a subset of a existing table.
- **Index wizard**
Order management wizard.
Permits to create, delete, modify order tags and files.
There is a menu to reindex all orders for a table.
The filename of the index file is automatically proposed by Otis if you create a new order. Sure, you can modify the proposed name.
Single order (ntx) and multi-order, compound cdx files are supported.

I think that almost all tools are there

If you miss one, let me know

6. Plugin mode

As explained you can include Otis in your own program by including the LIB file in your project.

Attach the function **Otis()** to a event like a special key or a control action event. No other functions have to be called to initialize, set, reset or whatever else.

Otis knows when it is in 'plugin mode' or running as a 'standalone' executable. How does Otis know that it is running in 'Standalone' mode. Simply by checking if the word 'OTIS' is found in the executable filename. You can thus create your own executable with your own special SET(...)tings as long as the executable name contains 'OTIS'.

Differences between 'Standalone' and 'Plugin mode' ?

In Plugin mode Otis **inherits** from your application :

- All your program settings SET(...).
- Codepages.
- Rdd drivers.
- Deleted status.
- Exclusive open mode.
- AutoOpen mode.
- All Alias() names.
- All area numbers.
- All table record positions are retrieved.
- All table 'Filter' settings are retrieved.

The corresponding checkbox and or combobox in the main screen reflects these current settings.

There is one thing that needs special attention and that is a very, very important issue in 'plugin' mode :

When you call OTIS() it scan all areas for tables and indexes opened by your program and present them in a new dataset. You can open a table in the 'Inspector' window and this is where a big problem can arise. You will think, why.

An example will speak for itself.

We are running under windows and as you know all forms can be clicked to give them the focus. Remember there are only a few 'Modal' forms in Otis. You can thus at one moment set the focus to a form in your application and then give focus to a form in Otis. What happens if a table is opened in a form in your program and the record pointer is positioned on a specific record. Remember, this table is also shown in the dataset with the consequence that you can open this table in the 'Inspector' at the same time. When you open this table, the 'Inspector' it will be positioned on the same record. What happens if you, in Otis, change the record position, delete / add a record, change order, set a filter, set a scope ? Your application form completely loses control in this table because Otis is working in the same area. This is a dangerous situation and data integrity is not assured. Data could be corrupted or could be lost.

I have found the following solution to prevent these situations :

As said when you call Otis() it scans all areas. Opened tables and indexes are presented in the dataset table with the alias and area number set by your program. I call this area the 'mother' area. What Otis do is reopen the same table with another alias name and another area number (see Settings menu). The default area number for this reopened table is the 'mother' area number plus a offset of 10000. You will see thus each table in what i call a 'Ghost' table with his own alias and area number.

We advise you to open a table opened by your application in this 'Ghost' area because almost all operations like, change order, filter, go to another record, ...etc. are independent of the 'mother' area. Your program form that is positioned on a record will not be influenced by operations in this 'Ghost' area.

Example below :

'Mother' table name is produit.dbf :

The alias name is 'Pro_1' and the area number is '1'.

'Ghost' table :

Alias will be 'Pro_1_1' with area number '10001'.

OTIS - DataSet Manager V1.1 B01 - 17/07/2020

Table Inspector

Recent

Changed

Exclusive

AutoOpen

FRWIN

DBFCDX

Table Properties

Struct. Editor

Load DataSet

Save DataSet

Close Dataset

Add Table(s)

Add Index(es)

Remove Table

Remove Index

Settings

Quit

Alias	Area	S	L	Recno	Reccount	Act.Ind.	Nbr.Ind.	Rdd	Table name
PRO_1	1			1	15182	1	9	DBFCDX	DATA\TPS\PRODUIT.dbf
MOVDOC_1	2			645012	2756312	1	7	DBFCDX	DATA\TPS\MOVART.dbf
LSTFMT_1	3			1	388	0	0	DBFCDX	format\FORMAT.dbf
GEN_1	4			892	1331	1	1	DBFCDX	DATA\TPS\COMPGEN.dbf
CLI_1	5	*		1	14768	1	6	DBFCDX	DATA\TPS\CLIENT.dbf
PRO_1_1	10001			1	15182	1	9	DBFCDX	DATA\TPS\PRODUIT.dbf
MOVDOC_1_2	10002			645012	2756312	1	7	DBFCDX	DATA\TPS\MOVART.dbf
LSTFMT_1_3	10003			1	388	0	0	DBFCDX	format\FORMAT.dbf
GEN_1_4	10004			892	1331	1	1	DBFCDX	DATA\TPS\COMPGEN.dbf
CLI_1_5	10005			1	14768	1	6	DBFCDX	DATA\TPS\CLIENT.dbf



Be carefull, even with this solution, some tools in Otis can have an impact in the 'mother' area and result in loss of data.

This is maybe not the best solution but the only one that came up for the moment.

Last remark, when you are in 'plugin' mode and close a dataset, only the 'Ghost' areas are closed. Otis may not close tables opened by the running program. The difference is made by the area number. All areas > 10000 are closed because they are 'Ghost' areas.

7. Letodbf


Otis contains all the necessary drivers to open and manage LetoDbf tables. LetoDbf is really a excellent client server driver. Thanks to Elch.

The only thing that you have to do is set the servername and port to use for a connexion in the 'Settings' menu.

There is no 'connect' button or whatever else. Otis opens automatically the connexion when it is not yet established when you load a previous saved dataset that contains tables that use the LetoDbf driver or when you want to add a table to a dataset with the LetoDbf rdd driver selected in the combobox. Otis contains special getfile() and putfile() functions to work with the '**Data**' folder (see letodb.ini) of the LetoDbf server.

8. Program settings

There are few program settings, but they need some explanations.



- **Area reserved for OTIS_DS.DBF**
Area number exclusively used for the program dataset table, OTIS_DS.DBF.
Change it if there is a conflict with a area number used by your program when you run in 'plugin' mode.
- **Plugin mode area settings :**
Start and end area range scanned when Otis() is called to fill the dataset with the opened tables by your program.
Ghost area offset, offset added to the 'mother' area number for the 'ghost' areas.
- **LetoDbf settings**
Ip / Hostname of the LetoDbf server.
Can be :
ip address, 192.168.1.253
a hostname LETODBF.DDNS.NET
localhost
...etc.

Port, port number to use.

Don't forget for your firewall that LetoDbf use 2 ports. The one that you specify here and the next one.
Example, 2812 and 2813.



9. Files used and created by Otis :


Otis.exe or Otis.lib creates automatically the following files if they are not found in the folder from where you launch the program :

Otis.ini : contains all program settings.

Otis_ds.dbf : database for dataset storage.

Copy these two files, if you copy Otis.exe from one folder to another folder, if you want to keep the same settings. I choose for this solution because in 'plugin ' mode with the lib file some settings, like by example the Letdbf server settings, could be different per application.

10. Some screen previews :



OTIS - Structure Editor


Structure of: D:\pfwin\Data\tps\catalog.dbf

	Field Name	Type	Len	Dec	#
Append	FOURN	C	8	0	1
Insert	REFFOURN	C	15	0	2
Modify	REFFAB	C	30	0	3
Delete	DESCRIPT	C	100	0	4
	EAN	C	15	0	5
	LP	N	10	2	6
	PA	N	10	2	7
Move Up	RECUPEL	N	8	4	8
	BEBAT	N	8	4	9
Move Down	REPROBEL	N	8	4	10
	AUVIBEL	N	8	4	11
	BRAND	C	20	0	12
Load structure	CAT1	C	40	0	13
	CAT2	C	40	0	14
Clear structure	CAT3	C	40	0	15
	NEWDATE	D	8	0	16
	IMPDATE	D	8	0	17
	MODATE	D	8	0	18
	STOCKLO	N	10	2	19
	STOCKCE	N	10	2	20
	BODATELO	D	8	0	21
	BOSTOCKLO	N	10	2	22
	BODATECE	D	8	0	23
	BOSTOCKCE	N	10	2	24

Cancel

Save as

Structure Editor.



\tps\MOVART.DBF

Nr	Fieldname	Type	Len	Dec
001	NRFAC	N	6.00	0.00
002	JNLFACT	C	3.00	0.00
003	LINK	C	13.00	0.00
004	STATUS	C	1.00	0.00
005	REPR	C	3.00	0.00
006	REPRCP	N	6.00	2.00
007	REPRCV	N	10.00	2.00
008	REFERPROD	C	15.00	0.00
009	DENOMPROD	C	55.00	0.00
010	REFCLFOU	C	8.00	0.00
011	DATE	D	8.00	0.00
012	DECHEANCE	D	8.00	0.00
013	IMPUT	C	8.00	0.00
014	TTVA	C	5.00	0.00
015	PRIXUNIT	N	15.00	4.00
016	QUANT	N	11.00	3.00
017	QUANT2	N	11.00	3.00
018	QUANTCMD	N	11.00	3.00
019	REMISE	N	6.00	2.00
020	THTVA	N	15.00	4.00
021	ARTEC	C	1.00	0.00
022	VISIB	L	1.00	0.00
023	STOCK	L	1.00	0.00
024	VALOR	L	1.00	0.00
025	REFDOC	C	15.00	0.00
026	PA	N	12.00	4.00
027	PV1	N	12.00	4.00
028	DEVCODE	C	3.00	0.00
029	DEVCOUR	N	16.00	10.00
030	MQ1	N	10.00	4.00
031	MQ2	N	10.00	4.00

Quit


Table properties.

Data file full name & path		: \tps\MOVART.DBF
Alias for this workarea		: MOVART_1
Area select number		: 1
Dbf driver used		:
Locking scheme used by RDD		: 3
Codepage used		: FRWIN
Last modification date		: 0d20200714
Was the file opened shared?		: .F.
Was the file opened readonly?		: .F.
Data file's header size		: 1218
The size of 1 record in the file		: 338
Number of fields in a record		: 37
Number of records		: 2166236
Current Filter setting		:
Is there a file lock active?		: .F.
Number of record locks		: 0
An array of locked records numbers		: { Array of 0 Items }
Number of child relations set		: 0
Same as Found()		: .F.
Same as Bof()		: .F.
Same as Eof()		: .F.
Type of MEMO file: DBT, SMT, FPT		: 2
The memo file's file extension		: .fpt
Memo File's block size		: 64

Table info.

Table : \tps\MOVART.DBF	
Index info :	
Orderbags	: 1
Orders	: 7
1 OrderBag name : tps\MOVART.cdx	
Order nbr	: 1
Order name	: IMOVART
Key	: JNLFACT+STR(NRFACT,6)
For	:
Order nbr	: 2
Order name	: IMOVRPR
Key	: REFERPROD+JNLFACT+DTOS(DATE)
For	:
Order nbr	: 3
Order name	: IMOVBO
Key	: JNLFACT+STR(NRFACT,6)+DTOS(DECHEANCE)+REFCLFOU+REFERPROD
For	: STOCK.AND.JNLFACTS"BCC,BCF".AND.STATUS\$"B".AND.QUANT2<>0.AND.!!DELETED()
Order nbr	: 4
Order name	: IMOVCF
Key	: REFCLFOU+JNLFACT+DTOS(DATE)+STR(NRFACT,6)
For	: !!DELETED()
Order nbr	: 5
Order name	: IMOVPRB
Key	: REFERPROD+JNLFACT+DTOS(DECHEANCE)+REFCLFOU
For	: STOCK.AND.JNLFACTS"BCC,BCF".AND.STATUS\$"B".AND.QUANT2<>0.AND.!!DELETED()
Order nbr	: 6
Order name	: IMOVTI
Key	: REFCLFOU+JNLFACT+STR(NRFACT,6)+DTOS(DECHEANCE)+REFERPROD
For	: STOCK.AND.JNLFACTS"BCC,BCF".AND.STATUS\$"B".AND.QUANT2<>0.AND.!!DELETED()
Order nbr	: 7
Order name	: IMOVCFD
Key	: REFCLFOU+DTOS(DATE)+STR(NRFACT,6)
For	: !!DELETED()

Index info.



OTIS - Seek wizard for alias : MOVART_1

Buttons: Seek First, Seek Last, Exact OFF (=), To Filter, Clear, Quit

Order Key Expr. JNLFACT+STR(NRFACT,6)


Expression by hand ☐ (Disable autofill of seek expression.)

Seek expression

JNLFACT (c)

NRFACT (n)

Seek wizard.



OTIS - Search / Replace wizard for alias : MOVART_1

Buttons: Search Next, Replace..., Quit

Table (alias) MOVART_1

Look for

Direction

Forward

Backward


Entire scope

Search in <all columns>

Match case

Match whole word only

Search / Replace (standard version).



OTIS - Extended replace wizard for alias : MOVART_1

Buttons: Replace, Quit

Table (alias) MOVART_1

Field ARTEC

Scope All Rest Next 1


Value

Expression


For

While


Replace wizard (extended version).




Add / Insert.




Delete / Recall.




Index manager.



Program Settings



Add one or multiple tables with rdd LetoDbf filepicker.



And resulting dataset in Otis.

Remark the first 2 tables, order files are opened automatically.