

# MGAgencia → Salesforce Leads API — Functional Specification

## v1.0 (draft for provider review)

Date: 2026-09-01 Prepared by: Grupo Cóndor

### 1. Overview

**Purpose.** MGAgencia collects advertising leads from marketing platforms and sends them to Grupo Cóndor's CRM (Salesforce) so they can be worked by our sales team, without manual data entry.

**Flow**



**Versioning policy.** The current contract is **v1**. Any breaking change (removed/renamed fields, changed status codes, changed semantics) will be released as a new version (e.g. **v2**) with its own endpoint path. Non-breaking additions (new optional fields, new catalog values) may be introduced within v1.

### 2. Environments

| Environment   | Base URL                                          | Notes                                   |
|---------------|---------------------------------------------------|-----------------------------------------|
| Sandbox (UAT) | https://condorsaci--qas.sandbox.my.salesforce.com | For integration testing before go-live. |
| Production    | To be provided at go-live                         | Will be shared once UAT is signed off.  |

**Important:** the token must always be requested from the org's own domain (`*.my.salesforce.com` format), never from `test.salesforce.com` or `login.salesforce.com` — those generic domains reject this authentication flow.

| Item          | Value                                 |
|---------------|---------------------------------------|
| Endpoint path | /services/apexrest/mgagencia/v1/leads |
| HTTP method   | POST                                  |
| Content-Type  | application/json; charset=UTF-8       |
| Transport     | HTTPS only                            |

### 3. Authentication

**Grant type:** OAuth 2.0 Client Credentials.

| Environment | Token endpoint                                                                                   |
|-------------|--------------------------------------------------------------------------------------------------|
| Sandbox     | https://condorsaci--qas.sandbox.my.salesforce.com/services/oauth2/token                          |
| Production  | https://<production-domain>.my.salesforce.com/services/oauth2/token (to be confirmed at go-live) |

Request parameters ( application/x-www-form-urlencoded ):

| Parameter     | Value                    |
|---------------|--------------------------|
| grant_type    | client_credentials       |
| client_id     | Provided by Grupo C ndor |
| client_secret | Provided by Grupo C ndor |

Credentials ( client\_id / client\_secret ) will be delivered by Grupo C ndor through a secure channel (e.g. a password manager share). **They will never be sent by email or chat in plain text.** Delivery is pending completion of the Connected App provisioning on our side.

Every API request must include the access token:

Authorization: Bearer <access\_token>

**Token expiry and renewal.** Tokens expire according to the org's session policy. MGAgencia should request a new token whenever a request fails with 401 Unauthorized , rather than caching a token indefinitely or assuming a fixed lifetime.

**Example**

```
# 1. Get an access token
curl -s -X POST "https://condorsaci--qas.sandbox.my.salesforce.com/services/oauth2/token" \
  -d "grant_type=client_credentials" \
  -d "client_id=<CLIENT_ID>" \
  -d "client_secret=<CLIENT_SECRET>"

# 2. Send a lead
curl -s -X POST "https://condorsaci--qas.sandbox.my.salesforce.com/services/apexrest/mgagencia/v1/leads" \
  -H "Authorization: Bearer <ACCESS_TOKEN>" \
  -H "Content-Type: application/json" \
  -d '{
    "first_name": "Maria",
    "last_name": "Gonzalez",
    "phone": "0981123456",
    "email": "maria.gonzalez@example.com",
    "branch_code": "ASUNCION"
  }'
```

Credentials are **pending delivery** until the Connected App is provisioned. This section describes the confirmed target mechanism; sandbox client\_id / client\_secret will follow.

## 4. Request specification

One JSON object per request. No batch/array wrapping. Unknown properties sent by MGAgencia are ignored (not rejected).

| Field                         | Type   | Required                | Max length | Format                          | Description                                                                                                                                                                                     | Example                                   |
|-------------------------------|--------|-------------------------|------------|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| <code>first_name</code>       | string | Yes                     | —          | Non-empty after trimming        | Lead's first name.                                                                                                                                                                              | <code>"Maria"</code>                      |
| <code>last_name</code>        | string | Yes                     | —          | Non-empty after trimming        | Lead's last name.                                                                                                                                                                               | <code>"Gonzalez"</code>                   |
| <code>phone</code>            | string | Yes                     | —          | Paraguayan mobile number        | Accepted in local ( <code>0981123456</code> ) or international ( <code>595981123456</code> ) format. Normalized server-side to a single canonical format before storage and duplicate matching. | <code>"0981123456"</code>                 |
| <code>email</code>            | string | No                      | —          | Standard email format           | Optional contact email.                                                                                                                                                                         | <code>"maria.gonzalez@example.com"</code> |
| <code>branch_code</code>      | string | No                      | —          | One of the catalog values below | Preferred C ndor branch. Omitting the field is valid; an unrecognized value is rejected.                                                                                                        | <code>"ASUNCION"</code>                   |
| <code>external_lead_id</code> | string | No (see open questions) | —          | Free text                       | Unique identifier MGAgencia may assign to a lead. Not required today; whether it becomes required and used as an idempotency key is open — see  10.                                             | <code>"neb-2026-0000123"</code>           |

`branch_code` catalog

| Value                        |
|------------------------------|
| <code>ASUNCION</code>        |
| <code>CIUDAD_DEL_ESTE</code> |
| <code>CORONEL_OVIEDO</code>  |
| <code>ENCARNACION</code>     |

### 4.1 Example request

```
{
  "first_name": "Maria",
  "last_name": "Gonzalez",
  "phone": "0981123456",
  "email": "maria.gonzalez@example.com",
  "branch_code": "ASUNCION",
  "external_lead_id": "neb-2026-0000123"
}
```

## 5. Response specification

### 5.1 Success — 201 Created

| Field                       | Type          | Description                                                                                                                           |
|-----------------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------|
| <code>code</code>           | string        | Machine-readable outcome code ( <code>LEAD_CREATED</code> ).                                                                          |
| <code>status</code>         | string        | <code>success</code> .                                                                                                                |
| <code>message</code>        | string        | Human-readable summary.                                                                                                               |
| <code>integration_id</code> | string (UUID) | Reference identifier for this request. <b>MGAgencia must store it</b> for support requests. It is not a Salesforce record identifier. |
| <code>duplicated</code>     | boolean       | <code>true</code> if this lead matched an existing one (see §7).                                                                      |

```
{
  "code": "LEAD_CREATED",
  "status": "success",
  "message": "Lead created successfully.",
  "integration_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "duplicated": false
}
```

### 5.2 Error envelope

All error responses share this shape. When the failure is field-level, `errors[]` reports **every** problem found in a single pass, not just the first.

| Field                | Type   | Description                                                                                                            |
|----------------------|--------|------------------------------------------------------------------------------------------------------------------------|
| <code>code</code>    | string | Machine-readable outcome code.                                                                                         |
| <code>status</code>  | string | <code>error</code> .                                                                                                   |
| <code>message</code> | string | Human-readable, safe-to-log summary. Never a raw internal error.                                                       |
| <code>errors</code>  | array  | Present when the failure is field-level. Each item has <code>field</code> , <code>code</code> , <code>message</code> . |

```
{
  "code": "VALIDATION_ERROR",
  "status": "error",
  "message": "One or more fields failed validation.",
  "errors": [
    { "field": "last_name", "code": "REQUIRED", "message": "last_name is required." },
    { "field": "phone", "code": "REQUIRED", "message": "phone is required." }
  ]
}
```

### 5.3 Error catalog

| HTTP status | Code                                          | Meaning                                                                                        |
|-------------|-----------------------------------------------|------------------------------------------------------------------------------------------------|
| 400         | MALFORMED_REQUEST                             | Body missing, not valid JSON, or not a JSON object. No field validation is attempted.          |
| 401         | (auth error)                                  | Missing or invalid access token.                                                               |
| 403         | (auth error)                                  | Valid token, but not authorized for this operation.                                            |
| 422         | VALIDATION_ERROR with sub-code REQUIRED       | A required field is missing or empty.                                                          |
| 422         | VALIDATION_ERROR with sub-code INVALID_FORMAT | A field does not match the expected format (e.g. <code>email</code> ).                         |
| 422         | VALIDATION_ERROR with sub-code UNKNOWN_VALUE  | A field value is not in its catalog (e.g. an unrecognized <code>branch_code</code> ).          |
| 500         | INTERNAL_ERROR                                | Unexpected processing failure on our side. Never includes stack traces or internal error text. |

#### Example — 400 malformed JSON

```
{
  "code": "MALFORMED_REQUEST",
  "status": "error",
  "message": "Request body is not valid JSON."
}
```

#### Example — 422 unknown branch code

```
{
  "code": "VALIDATION_ERROR",
  "status": "error",
  "message": "One or more fields failed validation.",
  "errors": [
    { "field": "branch_code", "code": "UNKNOWN_VALUE", "message": "branch_code does not match a known branch." }
  ]
}
```

## 6. Duplicate handling

Duplicate leads are **never rejected**. If an incoming lead matches an existing one, it is still created, and the response returns `"duplicated": true`.

**Matching signals:** normalized `phone` , or `email` , or `external_lead_id` when provided.

MGAgenia does not need to take corrective action on a duplicate response — it is flagged internally for reporting. Even so, MGAgenia should avoid blindly retrying an already-successful request, since every accepted request currently creates a new lead record (see the idempotency note in §10, item 1).

## 7. Operational behavior

| Topic                | Guidance                                                                                                                                                                                        |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Timeout              | Configure a reasonable client-side timeout (e.g. 30 seconds) per request.                                                                                                                       |
| Retries              | Retry only on <code>5xx</code> responses, with backoff between attempts. Do <b>not</b> retry <code>4xx</code> responses — they indicate the request itself must be corrected, not resent as-is. |
| Rate limits          | Not yet defined — see open question in §10.                                                                                                                                                     |
| Support traceability | Always log the <code>integration_id</code> returned on success. It is required to look up a request when contacting Grupo Cóndor for support.                                                   |

## 8. UAT plan for MGAgenia

Run the following scenarios against the sandbox environment before go-live:

| # | Scenario                                                                                               | Expected result                                                                                           |
|---|--------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| 1 | Valid lead with all fields                                                                             | <code>201</code> , <code>code: LEAD_CREATED</code> , <code>duplicated: false</code> .                     |
| 2 | Duplicate lead (same phone/email/ <code>external_lead_id</code> as a previous one)                     | <code>201</code> , <code>code: LEAD_CREATED</code> , <code>duplicated: true</code> .                      |
| 3 | Missing required field(s) ( <code>first_name</code> , <code>last_name</code> , or <code>phone</code> ) | <code>422</code> , <code>code: VALIDATION_ERROR</code> , <code>errors[]</code> lists every missing field. |
| 4 | Invalid <code>branch_code</code> (not in catalog)                                                      | <code>422</code> , <code>code: VALIDATION_ERROR</code> , <code>errors[].code: UNKNOWN_VALUE</code> .      |
| 5 | Malformed JSON body                                                                                    | <code>400</code> , <code>code: MALFORMED_REQUEST</code> .                                                 |
| 6 | Request without a valid access token                                                                   | <code>401</code> .                                                                                        |

## 9. Open questions for MGAgenia

| # | Question                                                                             | Why it matters                                                                                                                           | Proposed answer                                                                                                                                                                    |
|---|--------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Can you send a unique <code>external_lead_id</code> per lead?                        | If confirmed, it becomes a <b>required</b> field and the idempotency key for safe retries (avoiding duplicate creation on resubmission). | Yes — MGAgenia assigns and sends a stable, unique <code>external_lead_id</code> per lead.                                                                                          |
| 2 | How do you identify advertising campaigns?                                           | Needed to attribute leads to campaigns for reporting.                                                                                    | MGAgenia sends a <code>campaign_code</code> from a catalog agreed with Grupo C ndor; we resolve it internally.                                                                     |
| 3 | Do you need to send the vehicle model of interest?                                   | Needed to route/report leads by product interest.                                                                                        | MGAgenia sends an <code>interest_model</code> value from a catalog Grupo C ndor provides.                                                                                          |
| 4 | Do you need to query lead status after creation, or is the creation response enough? | Determines whether a <code>GET</code> status endpoint is needed in a future phase.                                                       | The synchronous creation response ( <code>integration_id</code> , <code>duplicated</code> ) is sufficient for v1; no <code>GET</code> endpoint planned unless confirmed otherwise. |
| 5 | What request volume do you expect (leads/day, peak rate)?                            | Needed to size the endpoint and define rate limits.                                                                                      | Please share expected average and peak volumes.                                                                                                                                    |

## 10. Support & change management

| Item                 | Detail                                                                                                                                                                                                                                                                         |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Contact              | <i>[Grupo C ndor integration contact — to be provided]</i>                                                                                                                                                                                                                     |
| Change communication | Any change to this contract (new/changed fields, status codes, or behavior) will be communicated to MGAgenia in writing before deployment. Breaking changes are released under a new API version (§1); non-breaking changes are documented as an update to this specification. |

End of document.