

Deep Neural Network for Speech Emotion Recognition

—A Study of Deep Learning—



Zhuowei Han


Institut für Signalverarbeitung
und Systemtheorie

Universität Stuttgart

05.06.2014

Why speech emotion recognition

- Most current work focuses on speech processing based on linguistic information, e.g.: Skype Translator
- More natural human-machine interaction requires paralinguistic information such as age, gender, emotion.
- Speech Recognition / Speaker Identification / Emotion




Deep Network Applications

- Handwriting Digit Recognition
- Image Recognition

Why speech emotion recognition

- Most current work focuses on speech processing based on linguistic information, e.g.: Skype Translator
- More natural human-machine interaction requires paralinguistic information such as age, gender, emotion.
- Speech Recognition / Speaker Identification / Emotion



Deep Network Applications

- Handwriting Digit Recognition
- Image Recognition

Foundations

- Mel Frequency Cepstral Features
- Emotion Recognition Approaches

Conditional Restricted Boltzmann Machine

- Concept

Deep Neural Networks

- Concept
- Problems and Solutions

Long Short Term Memory

- Recurrent Neural Network

Experiments

Conclusion and Outlook

Foundations

- Mel Frequency Cepstral Features

- Emotion Recognition Approaches

Conditional Restricted Boltzmann Machine

- Concept

Deep Neural Networks

- Concept

- Problems and Solutions


Long Short Term Memory

- Recurrent Neural Network

Experiments

Conclusion and Outlook

- short-term power spectrum
- mel-scale approximate human perception
- widely-used in speech recognition tasks
- Transformation between Mel and Hertz scale



$$f_{mel} = 1125 \ln (1 + f_{Hz}/700) \quad (1)$$

$$f_{Hz} = 700 (\exp(f_{mel}/1125) - 1) \quad (2)$$

Traditional Approaches

- pre-selected features
- supervised training
- low-level features not appropriate for classification
- shallow structure of classifiers

Deep Learning Approaches

- learning representations from high-dim data
- extracting appropriate features without hand-crafting
- low-level features are used to build high-level features as network gets deeper
- frame-based classification

Foundations

Mel Frequency Cepstral Features

Emotion Recognition Approaches

Conditional Restricted Boltzmann Machine

Concept

Deep Neural Networks

Concept

Problems and Solutions

Long Short Term Memory

Recurrent Neural Network

Experiments

Conclusion and Outlook

- undirected graphical probabilistic model based on PoE, capable in modeling high-dimension data (speech emotion)
- specifies a joint distribution over input and hidden variables, can either generate data, or with bayesian rule to form conditional distribution.

Desired: $P(x, h)$

Foundations

Mel Frequency Cepstral Features

Emotion Recognition Approaches

Conditional Restricted Boltzmann Machine

Concept

Deep Neural Networks

Concept

Problems and Solutions

Long Short Term Memory

Recurrent Neural Network

Experiments

Conclusion and Outlook

Computing net-activation

$$\underline{z}_k^{(l+1)} = \mathbf{W}^{(l)} \underline{a}_k^{(l)} + \underline{b}^{(l)}$$

$$\underline{a}_k^{(l+1)} = \underline{\Phi} \left(\underline{z}_k^{(l+1)} \right)$$

$$\hat{\underline{y}}_k = \underline{a}_k^{(ol)}$$

- Arbitrary non-linear mapping from \underline{x}_k to $\hat{\underline{y}}_k$ possible
- Relation $N \Leftrightarrow$ Complexity
- Deep Architectures ($l \uparrow$) more efficient than shallow ones ($l \downarrow, N_l \uparrow$)

Training objective

$$J(\mathbf{W}, \underline{b}) = \sum_{\forall k} \frac{1}{2} \|\underline{y}_k - \hat{\underline{y}}_k\|^2 + \frac{\lambda}{2} \sum_{\forall l} \|\mathbf{W}^{(l)}\|_F^2 \quad (3)$$

$$\mathbf{W}, \underline{b} = \arg \min_{\mathbf{W}, \underline{b}} J(\mathbf{W}, \underline{b}) \quad (4)$$

Numerical minimization

- Gradient calculation with Backpropagation
- Stochastic gradient descent
- Limited memory **B**royden-**F**letcher-**G**oldfarb-**S**hanno (L-BFGS)

- Optimization problem non-convex
⇒ getting stuck in poor local minima
- Diffusion of gradients
- Large p small n problem ⇒ overfitting

- Layerwise Pre-training

- Layerwise Pre-training

Foundations

Mel Frequency Cepstral Features

Emotion Recognition Approaches

Conditional Restricted Boltzmann Machine

Concept

Deep Neural Networks

Concept

Problems and Solutions

Long Short Term Memory

Recurrent Neural Network

Experiments

Conclusion and Outlook

Concepts of RNN

- modelling sequential data, emotion in speech .
- Same Structure as MLP but differs from feed-forward network, enabling nonlinear mapping.
- Feedback connection between previous hidden units and current hidden units, enabling memory past hidden state.
- Potentially to model arbitrary dynamic system.
- Trained with backpropagation through time (BPTT)

Concepts of RNN

- modelling sequential data, emotion in speech .
- Same Structure as MLP but differs from feed-forward network, enabling nonlinear mapping.
- Feedback connection between previous hidden units and current hidden units, enabling memory past hidden state.
- Potentially to model arbitrary dynamic system.
- Trained with **backpropagation through time (BPTT)**

Concepts of RNN

- modelling sequential data, emotion in speech .
- Same Structure as MLP but differs from feed-forward network, enabling nonlinear mapping.

$$h_t = \mathcal{H}(W_{xh}x_t + W_{hh}h_{t-1} + b_h)$$
$$y_t = W_{hy}h_t + b_y$$

- Feedback connection between previous hidden units and current hidden units, enabling memory past hidden state.
- Potentially to model arbitrary dynamic system.
- Trained with **backpropagation through time (BPTT)**

Concepts of RNN

- modelling sequential data, emotion in speech .
- Same Structure as MLP but differs from feed-forward network, enabling nonlinear mapping.
- Feedback connection between previous hidden units and current hidden units, enabling memory past hidden state.
- Potentially to model arbitrary dynamic system.
- Trained with **backpropagation through time (BPTT)**


Concepts of RNN

- modelling sequential data, emotion in speech .
- Same Structure as MLP but differs from feed-forward network, enabling nonlinear mapping.
- Feedback connection between previous hidden units and current hidden units, enabling memory past hidden state.
- Potentially to model arbitrary dynamic system.
- Trained with **backpropagation through time (BPTT)**

Concepts of RNN

- modelling sequential data, emotion in speech .
- Same Structure as MLP but differs from feed-forward network, enabling nonlinear mapping.
- Feedback connection between previous hidden units and current hidden units, enabling memory past hidden state.
- Potentially to model arbitrary dynamic system.
- Trained with **backpropagation through time** (BPTT)

Concepts of RNN



Problems with RNN


- gradient vanishing during backpropagation as time steps increases (>100)
- difficult to capture long-time dependency (which is required in emotion recognition)

Solutions



S. Hochreiter and J. Schmidhuber, Lovol. 9, pp. 1735-1780, 1997.

LSTM unit



$$i_t = \sigma(W_{xi}x_t + W_{hi}h_{t-1} + W_{ci}c_{t-1} + b_i)$$


$$f_t = \sigma(W_{xf}x_t + W_{hf}h_{t-1} + W_{cf}c_{t-1} + b_f)$$

$$c_t = f_t c_{t-1} + i_t \tanh(W_{xc}x_t + W_{hc}h_{t-1} + b_c)$$

$$o_t = \sigma(W_{xo}x_t + W_{ho}h_{t-1} + W_{co}c_t + b_o)$$

$$h_t = o_t \tanh(c_t)$$

LSTM unit



$$i_t = \sigma(W_{xi}x_t + W_{hi}h_{t-1} + W_{ci}c_{t-1} + b_i)$$

$$f_t = \sigma(W_{xf}x_t + W_{hf}h_{t-1} + W_{cf}c_{t-1} + b_f)$$


$$c_t = f_t c_{t-1} + i_t \tanh(W_{xc}x_t + W_{hc}h_{t-1} + b_c)$$

$$o_t = \sigma(W_{xo}x_t + W_{ho}h_{t-1} + W_{co}c_t + b_o)$$

$$h_t = o_t \tanh(c_t)$$

Features in LSTM

- gates are trained to learn when it should be open/closed.
- Constant Error Carousel
- preserve long-time dependency by maintaining gradient over time.



Foundations

- Mel Frequency Cepstral Features
- Emotion Recognition Approaches

Conditional Restricted Boltzmann Machine

- Concept

Deep Neural Networks

- Concept
- Problems and Solutions

Long Short Term Memory

- Recurrent Neural Network

Experiments

Conclusion and Outlook

Foundations

Mel Frequency Cepstral Features

Emotion Recognition Approaches

Conditional Restricted Boltzmann Machine

Concept

Deep Neural Networks

Concept

Problems and Solutions

Long Short Term Memory

Recurrent Neural Network

Experiments

Conclusion and Outlook