Zen AI Model Family

Zen-Director

Video Scene Generation, Storyboarding, and Cinematic Direction

Technical Report v2025.01

Hanzo AI Research Team[1] Zoo Labs Foundation[2]

January 2025

Hanzo AI RESEARCH

Zen AI Model Family

Zen-Director

Video Scene Generation, Storyboarding, and Cinematic Direction

Technical Report v2025.01

Hanzo AI Research Team[‡] Zoo Labs Foundation[§]

January 2025

Abstract

We present **Zen-Director**, a 7-billion parameter vision-language model specialized for video scene generation, cinematographic planning, and multi-shot storyboard synthesis. Built on the Zen MoDE (Mixture of Distilled Experts) architecture with a temporal transformer extension, Zen-Director understands and generates structured cinematic descriptions—shot lists, scene compositions, camera movements, and narrative arcs—that downstream video generation models can consume directly. The model achieves BLEU-4 of 0.423 on the VideoCaption benchmark, 81.2% accuracy on CinematicQA (our novel evaluation of cinematographic knowledge), and produces storyboards rated 4.1/5.0 by professional cinematographers in blind evaluation. Zen-Director bridges the gap between natural language creative intent and the precise technical specifications required to direct AI video generation systems at professional quality.

Contents

1 Introduction **4**
1.1 Model Overview 4
1.2 Key Capabilities 4

2 Architecture **4**
2.1 Zen MoDE 7B Language Backbone 4
2.2 Visual Encoder 5
2.3 Temporal Transformer Extension 5
2.4 Shot Plan Generation 5

3 Training **6**
3.1 Dataset 6
3.2 Training Protocol 6

4 Evaluation **6**
4.1 VideoCaption Benchmark 6
4.2 CinematicQA 6
4.3 Professional Storyboard Evaluation 7
4.4 Downstream Video Generation Quality 8

[*]research@hanzo.ai
[†]foundation@zoo.ngo
[‡]research@hanzo.ai
[§]foundation@zoo.ngo

5 Applications **8**
5.1 AI Film Production Pipeline 8
5.2 Film Education 8
5.3 Video Game Cutscene Direction 8

6 Related Work **8**

7 Conclusion **8**

1 Introduction

The rapid maturation of text-to-video generation systems has exposed a critical bottleneck: the gap between a creator's high-level creative intent and the precise technical specifications these systems require to produce coherent, professional-quality video. Current generation workflows demand that users specify camera angles, focal lengths, lighting conditions, shot durations, and scene transitions—knowledge traditionally held by professional cinematographers and directors.

Zen-Director addresses this bottleneck as a **directorial intelligence**: a model that understands narrative intent and translates it into actionable cinematic specifications. Rather than generating video pixels directly, Zen-Director generates structured **shot plans**: hierarchical scene descriptions that video generation systems consume as structured prompts.

1.1 Model Overview

Property	Value
Parameters	7B
Architecture	Zen MoDE 7B + Temporal Transformer
Context Length	32K tokens + 512 video frames
Visual Encoder	ViT-L/14 (336px)
Temporal Depth	12 temporal transformer layers
Shot Plan Format	Structured JSON + prose description
Training Data	8.2M scene-annotation pairs, 1.4M film scripts

Table 1: Zen-Director Model Specifications

1.2 Key Capabilities

- **Scene storyboarding**: Convert natural language scene descriptions into complete shot-by-shot storyboards with camera specifications.
- **Shot composition**: Recommend and generate compositional guidelines (rule of thirds, leading lines, depth of field) for each shot.
- **Narrative arc planning**: Structure multi-scene video narratives with consistent pacing, tension arcs, and visual motifs.
- **Cinematic vocabulary**: Understand and generate industry-standard cinematographic terminology (establishing shot, dolly zoom, rack focus, etc.).
- **Video comprehension**: Analyze existing video clips and generate directorial notes describing their cinematographic techniques.

2 Architecture

2.1 Zen MoDE 7B Language Backbone

The language backbone is Zen MoDE at 7B scale: 28 transformer layers, 28 attention heads with grouped-query attention (4 KV heads), and MoE feed-forward networks (4 experts, top-2 routing). This provides strong natural language understanding for parsing creative briefs and generating rich cinematic descriptions.

2.2 Visual Encoder

A ViT-L/14 vision encoder operating at 336px resolution encodes reference images and video frames into 256 visual tokens per frame. A two-layer MLP projection maps visual tokens into the language model's embedding space.

2.3 Temporal Transformer Extension

The key architectural innovation is a 12-layer temporal transformer that operates *across* frames rather than within them. Given T frames, each encoded to 256 tokens, the temporal transformer attends over the time dimension to build a coherent representation of motion, continuity, and scene evolution:

$$H_{\text{temporal}} = \text{TransformerEncoder}([h_1^{CLS}, h_2^{CLS}, \ldots, h_T^{CLS}]) \tag{1}$$

where h_t^{CLS} is the CLS token representation of frame t from the visual encoder. The temporal representation is concatenated with text tokens before the language model's cross-attention layers.

2.4 Shot Plan Generation

Zen-Director generates shot plans as structured JSON objects:

```
{
  "scene": {
    "id": "s01",
    "location": "rain-soaked rooftop, night",
    "mood": "tense, noir",
    "duration_sec": 45
  },
  "shots": [
    {
      "id": "s01_001",
      "type": "establishing",
      "camera": {"position": "wide", "angle": "high angle", "move": "
          slow push in"},
      "focal_length": "24mm",
      "subject": "city skyline with protagonist silhouette",
      "duration_sec": 8,
      "lighting": "practical neon, rain reflections",
      "notes": "City should feel overwhelming relative to protagonist"
    }
  ]
}
```

Listing 1: Shot Plan Schema

3 Training

3.1 Dataset

Source	Samples	Proportion	Content
Film scripts + frames	2,400,000	29.3%	Script-to-scene alignment
Cinematography textbooks	180,000	2.2%	Technical knowledge
Film criticism corpus	820,000	10.0%	Aesthetic analysis
Video-caption pairs	3,100,000	37.8%	Visual understanding
Storyboard collections	1,700,000	20.7%	Shot plan examples
Total	**8,200,000**	100%	

Table 2: Zen-Director Training Data

3.2 Training Protocol

Stage 1 – Visual encoder alignment (20K steps): The ViT encoder and MLP projection are trained to align visual representations with cinematic language descriptions.

Stage 2 – Temporal pretraining (40K steps): The temporal transformer is pretrained on video sequences with a masked-frame prediction objective.

Stage 3 – Directorial SFT (60K steps): The full model is fine-tuned on storyboard generation, scene description, and cinematographic Q&A tasks jointly.

Stage 4 – RLHF from cinematographers (15K steps): A reward model trained on 50,000 pairwise comparisons from professional cinematographers (recruited via film school partnerships) is used to further refine shot plan quality via PPO.

4 Evaluation

4.1 VideoCaption Benchmark

We evaluate video description quality on a held-out set of 5,000 film clips spanning 20 genres.

Model	BLEU-4	METEOR	CIDEr	ROUGE-L
BLIP-2	0.281	0.314	0.872	0.512
InstructBLIP	0.308	0.341	0.941	0.534
VideoChat2	0.352	0.374	1.021	0.561
Video-LLaMA2	0.387	0.402	1.103	0.584
Zen-Director	**0.423**	**0.441**	**1.187**	**0.612**

Table 3: VideoCaption Benchmark Results (higher is better)

4.2 CinematicQA

CinematicQA is a novel benchmark we introduce comprising 2,000 multiple-choice questions testing cinematographic knowledge: shot types, camera movements, lighting techniques, editing principles, and genre conventions. Questions were authored by five professional cinematographers.

Model	Accuracy (%)
GPT-4o (zero-shot)	68.3
Claude 3.5 Sonnet	71.4
Gemini 1.5 Pro	66.8
Specialist fine-tuned 7B	74.2
Zen-Director 7B	**81.2**

Table 4: CinematicQA Accuracy (%)

4.3 Professional Storyboard Evaluation

Twenty professional cinematographers evaluated storyboards generated from 100 scene descriptions, rating each on a 5-point scale across five dimensions.

Dimension	Mean Score (1–5)
Technical accuracy of shot specifications	4.3
Narrative coherence across shots	4.1
Creative quality / originality	3.9
Pacing appropriateness	4.0
Overall directorial vision	4.1
Overall Mean	**4.1**

Table 5: Professional Cinematographer Evaluation (N=20 evaluators, 100 storyboards)

4.4 Downstream Video Generation Quality

We evaluate whether Zen-Director shot plans improve final video quality when used as structured prompts for a text-to-video generation system. Using the same creative brief:

Prompt Method	Human Preference (%)	FVD ↓
Raw creative brief (baseline)	18.4%	412
Manual cinematographer spec	42.1%	287
Zen-Director shot plan	39.5%	298

Table 6: Downstream Video Quality with Zen-Director Shot Plans

Zen-Director reaches 94% of manual cinematographer performance at a fraction of the cost and time, validating its role as an effective creative intermediary.

5 Applications

5.1 AI Film Production Pipeline

Zen-Director is integrated into the Hanzo AI film production pipeline as the directorial layer between a human creative brief and the Zen-Video generation system. A typical workflow:

1. Human writes a scene description in natural language.
2. Zen-Director generates a shot plan JSON with full cinematographic specs.
3. Human reviews and optionally edits the shot plan (typically 3–5 minutes).
4. Zen-Video consumes the shot plan and generates video clips per shot.
5. Zen-Director evaluates temporal consistency across clips and suggests retakes.

5.2 Film Education

Zen-Director serves as an interactive cinematography tutor: students can submit scene descriptions and receive expert-level directorial notes explaining the reasoning behind each shot choice.

5.3 Video Game Cutscene Direction

Game studios use Zen-Director to generate cinematic specifications for in-engine cutscene directors, reducing the time from narrative script to playable sequence by an estimated 60%.

6 Related Work

Video understanding models (VideoChat, Video-LLaMA) focus primarily on description generation. Text-to-video generation systems (Sora, CogVideo, ModelScope) focus on pixel synthesis. Zen-Director uniquely occupies the directorial planning layer between these two