OpenText™ Service Manager

Invoke auditing for joindefs tables

Version 9.82

PDF Generated on October 12, 2026

© Copyright 2026 Open Text

Table of Contents

Invoke auditing for joindefs tables 3

Invoke auditing for joindefs tables

Applies to User roles: System Administrator

To use the database record auditing functionality, you need to invoke auditing for joindefs tables, as described in the following tasks.

Task 1: Temporarily disable the auditspecs.check Subroutine on the auditspecs Format Control record.

1. Sign in to the Windows client.
2. In Format Control, open the **auditspecs** record (Name: **auditspecs**).
3. Click **Subroutines**, and from the More Actions menu select **Show Expanded Form**.
4. For each of the conditions Add, Update, and Before, append the following expression: **and false**.
   The conditions for each should be: **true and false**.
5. Click **Save**.
   Note: Re-enable the Subroutine after performing Task 2.

Task 2: Add an Audit Specifications record for joinbizservice and each of the other "join" files being used.

1. Click **Tailoring** > **Audit** > **Audit Specifications**.
2. Enter field data as follows:

Field	Value
Filename	joinbizservice
Unique A	logical.name
Field Name	logical.name (and any other fields you want in the list)

3. Click **Add.**
4. Repeat for each additional "join" table desired.

Related topics

Database record auditing
Audit log file
Audit specifications file
Audit processing
Tools to use for promoting customizations
Environment configuration
The Subroutines form

© Copyright 2026 Open Text

For more info, visit https://docs.microfocus.com