

✓ Congratulations! You passed!

Grade received 100% To pass 80% or higher

Go to next item

Optimization Algorithms

Latest Submission Grade 100%

1. Which notation would you use to denote the 3rd layer's activations when the input is the 7th example from the 8th minibatch?

1 / 1 point

- ☒ $a^{[3]}(8)(7)$
- ☐ $a^{[8]}(7)(3)$
- ☐ $a^{[3]}(7)(8)$
- ☐ $a^{[8]}(3)(7)$

✓ Correct

2. Which of these statements about mini-batch gradient descent do you agree with?

1 / 1 point

- ☐ Training one epoch (one pass through the training set) using mini-batch gradient descent is faster than training one epoch using batch gradient descent.
- ☒ One iteration of mini-batch gradient descent (computing on a single mini-batch) is faster than one iteration of batch gradient descent.
- ☐ You should implement mini-batch gradient descent without an explicit for-loop over different mini-batches, so that the algorithm processes all mini-batches at the same time (vectorization).

✓ Correct

3. Why is the best mini-batch size usually not 1 and not m , but instead something in-between?

1 / 1 point

- ☒ If the mini-batch size is 1, you lose the benefits of vectorization across examples in the mini-batch.

✓ Correct


- ☒ If the mini-batch size is m , you end up with batch gradient descent, which has to process the whole training set before making progress.

✓ Correct

- ☐ If the mini-batch size is m , you end up with stochastic gradient descent, which is usually slower than mini-batch gradient descent.
- ☐ If the mini-batch size is 1, you end up having to process the entire training set before making any progress.

4. Suppose your learning algorithm's cost J , plotted as a function of the number of iterations, looks like this:

1 / 1 point



Which of the following do you agree with?

- ☐ If you're using mini-batch gradient descent, something is wrong. But if you're using batch gradient descent, this looks acceptable.
- ☐ Whether you're using batch gradient descent or mini-batch gradient descent, something is wrong.
- ☒ If you're using mini-batch gradient descent, this looks acceptable. But if you're using batch gradient descent, something is wrong.
- ☐ Whether you're using batch gradient descent or mini-batch gradient descent, this looks acceptable.

✓ Correct

5. Suppose the temperature in Casablanca over the first three days of January are the same:

1 / 1 point

Jan 1st: $\theta_1 = 10^\circ C$

Jan 2nd: $\theta_2 10^\circ C$

(We used Fahrenheit in lecture, so will use Celsius here in honor of the metric world.)

Say you use an exponentially weighted average with $\beta = 0.5$ to track the temperature: $v_0 = 0$, $v_t = \beta v_{t-1} + (1 - \beta)\theta_t$. If v_2 is the value computed after day 2 without bias correction, and $v_2^{corrected}$ is the value you compute with bias correction. What are these values? (You might be able to do this without a calculator, but you don't actually need one. Remember what bias correction is doing.)

- ☐ $v_2 = 10$, $v_2^{corrected} = 10$
- ☐ $v_2 = 7.5$, $v_2^{corrected} = 7.5$
- ☐ $v_2 = 10$, $v_2^{corrected} = 7.5$
- ☒ $v_2 = 7.5$, $v_2^{corrected} = 10$

✓ Correct

6. Which of these is NOT a good learning rate decay scheme? Here, t is the epoch number.


1 / 1 point

- ☒ $\alpha = e^t \alpha_0$
- ☐ $\alpha = 0.95^t \alpha_0$
- ☐ $\alpha = \frac{1}{1+2t} \alpha_0$
- ☐ $\alpha = \frac{1}{\sqrt{t}} \alpha_0$

✓ Correct

7. You use an exponentially weighted average on the London temperature dataset. You use the following to track the temperature: $v_t = \beta v_{t-1} + (1 - \beta)\theta_t$. The red line below was computed using $\beta = 0.9$. What would happen to your red curve as you vary β ? (Check the two that apply)

1 / 1 point



- ☐ Decreasing β will shift the red line slightly to the right.
- ☒ Increasing β will shift the red line slightly to the right.

✓ Correct

True, remember that the red line corresponds to $\beta = 0.9$. In lecture we had a green line $\beta = 0.98$ that is slightly shifted to the right.

- ☒ Decreasing β will create more oscillation within the red line.


✓ Correct

True, remember that the red line corresponds to $\beta = 0.9$. In lecture we had a yellow line $\beta = 0.98$ that had a lot of oscillations.

- ☐ Increasing β will create more oscillations within the red line.

8. Consider this figure:

1 / 1 point



These plots were generated with gradient descent; with gradient descent with momentum ($\beta = 0.5$) and gradient descent with momentum ($\beta = 0.9$). Which curve corresponds to which algorithm?

- ☐ (1) is gradient descent. (2) is gradient descent with momentum (large β). (3) is gradient descent with momentum (small β)
- ☐ (1) is gradient descent with momentum (small β). (2) is gradient descent with momentum (small β). (3) is gradient descent
- ☒ (1) is gradient descent. (2) is gradient descent with momentum (small β). (3) is gradient descent with momentum (large β)

momentum (large β)

- ☐ (1) is gradient descent with momentum (small β). (2) is gradient descent. (3) is gradient descent with momentum (large β)

✓ Correct

9. Suppose batch gradient descent in a deep network is taking excessively long to find a value of the parameters that achieves a small value for the cost function $\mathcal{J}(W^{[1]}, b^{[1]}, \dots, W^{[L]}, b^{[L]})$. Which of the following techniques could help find parameter values that attain a small value for \mathcal{J} ? (Check all that apply)

1 / 1 point

☐ Try initializing all the weights to zero

☒ Try mini-batch gradient descent

✓ Correct

☒ Try better random initialization for the weights

✓ Correct

☒ Try tuning the learning rate α

✓ Correct

☒ Try using Adam

✓ Correct

10. Which of the following statements about Adam is False?

1 / 1 point

☐ We usually use "default" values for the hyperparameters β_1 , β_2 and ϵ in Adam ($\beta_1 = 0.9$, $\beta_2 = 0.999$, $\epsilon = 10^{-8}$)

☐ The learning rate hyperparameter α in Adam usually needs to be tuned.

☐ Adam combines the advantages of RMSProp and momentum

☒ Adam should be used with batch gradient computations, not with mini-batches.

✓ Correct