Is Interpretability a Warrant for Trust in Machine-Learning Intrusion Detection? A Measurement Study

Anonymous Submission
Under double-blind review

***Abstract*—A fast-growing line of work equips machine-learning intrusion detection systems (ML-IDS) with explanations, arguing that the resulting interpretability lets an analyst *trust* the detector. We ask, for ML-IDS specifically, what an explanation must satisfy for such trust to be *warranted*. Building on prior work on warranted trust, explainer disagreement, and model multiplicity, we formalize three necessary properties of the explanation map: *fidelity* (the interpretable artifact decides as the deployed model), *determinacy* (the explanation is fixed by the decision, not by the choice of attribution method), and *groundedness* (it reflects the task, not the incidental model instance). On five modern datasets (2015–2023), fidelity is attainable but only at a price — a readable surrogate matches the deployed detector's decisions on 0.96–1.00 of flows, yet costs up to 0.35 F_1 on the hardest corpus — while determinacy and groundedness fail outright: cross-family explainers agree on as little as 0.261 of the five features they put in front of an analyst, only $1.94\times$ what two unrelated rankings would score by chance; and equally accurate detectors disagree on nearly half their top features. The failure carries security weight rather than merely epistemic weight: a simulated analyst calibrated on the deployed model's explanations dismisses 0.018 of correctly-detected true attacks on CICIDS2017, but 0.433 of those same attacks once an equally accurate sibling model is put in its place, against 0.505 when the explanation is replaced by noise. Calibrated trust in an explanation therefore survives a seed change little better than reading no explanation at all. A synthetic positive control confirms the metrics are satisfiable, not rigged to fail. Two honest negatives, a non-transferring attack and a circular, non-transferable, gameable reliability gate, show the warrant is not cheaply recovered. We distill the study into threat-aware evaluation criteria for such claims. Interpretability is not, by default, a warrant for trust in ML-IDS, and recovering that warrant is an open problem.**

I. Introduction

Machine-learning intrusion detection systems (ML-IDS) are opaque, and opacity is a problem in a setting where a human analyst must decide whether to act on an alarm and is accountable for that decision. The dominant response is *explainable* intrusion detection: attach to each alarm an explanation, typically a ranked list of the input features most responsible for it, and argue that the analyst can now understand, verify, and *trust* the detector. Recent work reports that explanations raise analyst trust, cut false-positive dismissals, and speed triage, and surveys frame interpretability as the route to trustworthy and accountable security AI [1].

This paper asks a question the literature leaves implicit. Trust, in a security setting, is not a feeling; it is a warrant for action under an adversary. If an analyst escalates or suppresses an alarm *because* of the explanation, then the explanation is part of the trusted base of the security operation. So we must ask: **what must be true of an explanation for the trust placed in it to be well-founded?** The explainable-IDS literature measures whether explanations *increase* trust (through user studies, satisfaction scores, triage-time reductions); it rarely asks whether that trust is *warranted*.

We take up the question through systematic measurement. Our contributions are:

- We **formalize interpretability-based trust** for ML-IDS (Section IV): for attribution-driven workflows in which an analyst cannot adjudicate among legitimate surrogate, explainer, and training-instance choices, we derive three audit conditions the explanation must satisfy for that trust to be warrant-invariant, *fidelity*, *determinacy*, and *groundedness*, building on prior notions of warranted trust, explainer disagreement, and model multiplicity rather than claiming these phenomena as new.
- We provide, to our knowledge, the first **joint measurement** of all three, on **five modern NIDS datasets** and **five standard explainers (gradient saliency, input×gradient, integrated gradients, SHAP, LIME)**, under one action-centered framework, with multi-seed statistics and, for each headline rate, the value it takes when the effect is switched off (Section V). Determinacy and groundedness fail; fidelity is attainable but costs detection. Explainers from different families agree on as little as 0.261 of the five features they present, even at high sampling budgets, against a chance agreement of 0.056 to 0.087 Jaccard for the feature counts involved.
- We show the failure can have **security consequences** (Section VI), and we measure them against their own floor. A simulated analyst calibrated on one deployed model's explanations dismisses 0.018 of correctly-detected true attacks on CICIDS2017; swapping in an equally accurate sibling raises that to 0.433, most of the

Network and Distributed System Security (NDSS) Symposium 2027
22–26 March 2027, Seoul, Republic of Korea
ISBN 978-1-970672-09-1
https://dx.doi.org/10.14722/ndss.2027.23xxxx
www.ndss-symposium.org

way to the 0.505 obtained when the explanation is replaced by signal-free noise. The same gap appears on 5G-NIDD ($0.001 \rightarrow 0.294$) and TON-IoT ($0.026 \rightarrow 0.272$), and vanishes on the easiest corpus. Where the effect is strong, mis-founded trust turns whether a real attack is acted on into an accident of the deployed model. These simulated-analyst rates are upper bounds (Section VI).

- We map **how hard the failure is to fix** with two honest negatives: an explanation-manipulation attack does not transfer to tabular IDS (Section VII), and the most natural per-alarm reliability gate, though it scores well in-distribution, is circular, non-transferable, and adversarially gameable (Section VIII). Trust is not cheaply recovered.
- We distill **threat-aware evaluation criteria** (Section IX) that a defensible interpretability-for-trust claim in security must meet.

We show that the inference "the model is interpretable, therefore its alarms can be trusted" is, as currently supported, unsound; that the failure has a concrete security cost; and that recovering the warrant is an open problem, not a matter of bolting on a confidence score. This is a foundations-of-security question: the conditions under which a security control may be relied upon.

II. Motivation and Setting

Consider a security operations center where an ML-IDS raises an alarm on a network flow and presents the analyst with the five features most responsible, say a large backward packet length and a short flow duration. The analyst, trained to read such explanations, judges the alarm consistent with a known attack and escalates; or, seeing features that look like ordinary traffic, dismisses it as a false positive. Vendors and recent research encourage exactly this workflow, and human-factors studies report that analysts act on explanations and trust systems more when explanations are present.

The workflow embeds an assumption: that the shown features are a reliable account of why the detector fired. If they are not, the analyst's judgment is untethered from the detector's actual behavior, and worse, from the ground truth of whether the flow is an attack. Three ways the account can be untethered motivate our properties. It can reflect a *different model* than the one deployed (if interpretability is delivered by a surrogate). It can be an artifact of the *explanation method* rather than the decision (if a different, equally standard method would have shown different features). And it can be an accident of the *particular trained model* rather than the task (if an equally accurate retraining would explain differently). We make these precise next and then measure them.

Scope. We study network intrusion detection on tabular flow features, the setting where explanations are usually feature attributions over named quantities. We consider standard attribution explainers rather than prototype- or rule-based methods; extending to those is a direction our criteria call for. We treat detection itself as given and study the explanation layer that sits on top of it.

III. Background and Related Work

Attribution methods. The explanations attached to ML-IDS are almost always feature attributions. The dominant methods split into gradient-based, LIME [2], integrated gradients [3], plain saliency [4], SmoothGrad [5], DeepLIFT [6], layer-wise relevance [7], and perturbation- or game-theoretic ones, LIME and SHAP [8], with rule-form variants such as Anchors [9] and, in vision, Grad-CAM [10]. We study five representative members; Molnar [11] surveys the space.

Critiques of ML-IDS evaluation. A tradition of foundational scrutiny warns that ML security results often do not mean what they appear to. Sommer and Paxson [12] argued that the closed-world assumptions of ML evaluation break in operational intrusion detection; Arp et al. [13] catalogue pervasive experimental pitfalls (spatial and temporal snooping, base-rate neglect, inappropriate baselines); Axelsson's base-rate analysis [14] shows why laboratory detection rates mislead at realistic prevalence; and broad surveys map the role and fragility of ML in security [15], [16]. These critiques target *accuracy* claims and their datasets. Ours targets a newer claim, *interpretability for trust*, that the accuracy critiques do not address.

Explainable intrusion detection. A large recent literature applies attribution methods to ML-IDS and argues they enhance analyst trust and accountability [1], including work that evaluates explanation methods specifically for security [17] and systematizes explainable ML across security applications [18], [19]. Closest to our empirical setting, E-XAI [20] benchmarks SHAP and LIME on NIDS datasets with stability, robustness, and completeness metrics; a survey of explainable IDS [21] calls for stakeholder-specific evaluation, and a field deployment of xAI tooling in a security operations center [22] reports the same need from the analyst side; and constructive proposals design action-oriented explanations, e.g. feasible-action contracts for intrusion triage [23]. These works measure explanation *quality* or user acceptance, or build explanations. We are orthogonal and adversarial: taking their metrics as given, we ask whether the trust they induce is *warranted*, jointly test the surrogate, method, and model choices an analyst cannot adjudicate, and trace the action-level consequence, none of which the above do together.

Fragility, disagreement, and multiplicity. In vision and NLP, explanations are known to be fragile and unreliable: Ghorbani et al. [24] perturb inputs to change saliency while fixing the prediction; Dombrowski et al. [25] manipulate explanations arbitrarily; Slack et al. [26] fool LIME and SHAP with adversarial scaffolding, a technique Senevirathna et al. [27] extend to deceive NIDS operators (our honest-negative attack in Sec. VII is a different, bounded input-perturbation formulation and does *not* transfer, which we report as a boundary result, not as robustness); sanity checks show some saliency maps are independent of the model [28]; saliency methods are provably unreliable under input shifts [29], [30]; and attribution methods disagree systematically [31], [32]. Our groundedness property is the security-relevant face of




Fig. 1. The analyst-trust pipeline in explainable ML-IDS, and the three points where interpretability-based trust breaks. The detector f raises an alarm; an explanation $e(x)$ is computed; the analyst reads it and acts. Trust fails if the interpretable artifact does not decide as f (P1), if the shown reason changes with the attribution method (P2), or if it changes with the training seed (P3). The security harm: on the same correctly-detected true attack, equally-good detectors' explanations drive opposite analyst actions.

model multiplicity: many equally-accurate models exist (the Rashomon effect [33], [34]) and they can differ arbitrarily in their per-example predictions and explanations [35], [36]. These results are about general ML; we ask what they mean for the *security* claim that interpretability licenses trust, connect them to a formal trust condition, and show they carry a concrete security consequence.

Interpretability foundations. Rudin [37] distinguishes intrinsically interpretable models from post-hoc explanations and warns against the latter for high-stakes decisions; the broader debate concerns what interpretability even means [38], [39], how explanation functions socially [40], and how trust in AI should be formalized [41] and engineered for [42]. We build directly on Jacovi et al.'s notion of warranted trust; our contribution is not to introduce it but to specialize it to explanation-conditioned IDS action and give operational invariance checks. Our fidelity property makes Rudin's distinction operational for security: a post-hoc or distilled "interpretable" artifact that does not decide as the deployed model does cannot ground trust in that model. Our detectors include the Kolmogorov-Arnold network [43], marketed as interpretable-by-design, precisely to test that claim.

Adversarial ML in security. That ML models are brittle to adversarial input is foundational [44], [45], [46], and realistic evasion of NIDS is an active concern [47]. We consider a distinct target, the *explanation* an analyst reads rather than the detector's label, and find (unlike the detector case) that manipulating it on tabular IDS is not straightforward.

IV. What Interpretability-Based Trust Requires

We model an ML-IDS as a decision function $f : \mathcal{X} \to \{0,1\}$ over network observations $x \in \mathcal{X}$, where $f(x) = 1$ raises an alarm. An *explanation method* is a map $e : \mathcal{X} \to \mathcal{E}$ producing, for each x, an artifact $e(x)$, in practice a ranked set $\mathrm{top}_k(e, x)$ of the k features held responsible, presented to the analyst. An analyst policy a decides, given the alarm and the explanation, whether to act.

Definition 1 (Interpretability-based trust)**.** *An analyst* trusts f through e *when the analyst's action policy depends on* $e(x)$*: the analyst escalates or suppresses the alarm* $f(x)$ *on the basis of* $e(x)$*, not on* f *alone. The trust is* well-founded *if* $e(x)$ *is a reliable signal of the grounds of the decision* $f(x)$*, i.e. acting on* e *does not systematically differ from acting on the true reasons for* $f(x)$*.*

Because $e(x)$ enters the analyst's decision, it is part of the trusted base. Well-foundedness therefore requires e to carry genuine information about f's decision and about the task. We measure the overlap of two explanations by the Jaccard agreement of their top-k feature sets,

$$J_k(e, e'; x) = \frac{|\mathrm{top}_k(e, x) \cap \mathrm{top}_k(e', x)|}{|\mathrm{top}_k(e, x) \cup \mathrm{top}_k(e', x)|} \in [0, 1], \qquad (1)$$

and we isolate three necessary properties, each parameterized by a tolerance ε.

Property 1 (Fidelity)**.** *The interpretable artifact the analyst reasons about must decide as the deployed model does. If interpretation is delivered through a surrogate* g *(distilled or intrinsic), fidelity requires*

$$\Pr_x\big[g(x) \neq f(x)\big] \;\leq\; \varepsilon_{\mathrm{fid}}. \qquad (2)$$

A surrogate that violates (2) *explains a different classifier than the one raising the alarm.*

Property 2 (Determinacy)**.** *The explanation must be fixed by the decision, not by the choice of attribution method. For a family* $\mathcal{M}$ *of equally-justified explainers, determinacy requires*

$$\min_{e, e' \in \mathcal{M}} \; \mathbb{E}_x\big[J_k(e, e'; x)\big] \;\geq\; 1 - \varepsilon_{\mathrm{det}}. \qquad (3)$$

If (3) *fails, the reason shown to the analyst is a property of the tool, not the decision.*

Property 3 (Groundedness)**.** *The explanation must reflect the task, not the incidental model instance. For models* f_1, f_2 *drawn from the same training procedure (differing only in seed) with* $|F_1(f_1) - F_1(f_2)| \leq \delta$*, groundedness requires*

$$\mathbb{E}_x\big[J_k(e_{f_1}, e_{f_2}; x)\big] \;\geq\; 1 - \varepsilon_{\mathrm{grnd}}. \qquad (4)$$

If (4) *fails while* δ *is negligible, the explanation reflects an accident of training, not the task.*

Table I collects the notation.

We make the necessity precise through an *invariance* view of warrant, which sidesteps the (unavailable) ground truth of

TABLE I
NOTATION.

Symbol	Meaning
$f : \mathcal{X} \to \{0, 1\}$	deployed IDS decision (alarm $= 1$)
$e(x),\ \mathrm{top}_k(e, x)$	explanation and its top-k features
g	interpretable surrogate presented to the analyst
J_k	top-k Jaccard agreement, Eq. (1)
$\mathcal{M}$	family of attribution methods (5 in our study)
$S(x)$	explanation reliability score, Eq. (5)
$\varepsilon_\bullet$	per-property trust tolerance

the "true reason" for a decision. An analyst who trusts f through e faces choices they cannot principled-ly adjudicate: which interpretable surrogate to read, which attribution method to run, and which of many equally-accurate trained models was deployed. Write $\mathcal{C}$ for this set of legitimate choices and e^c for the explanation under choice $c \in \mathcal{C}$.

Definition 2 (Warrant invariance)**.** *Trust in f through e is* warrant-invariant *if the analyst's action is stable across legitimate choices: for an action policy a depending on e through* top_k*,* $\Pr_x \left[\exists\, c, c' \in \mathcal{C} :\ a(e^c(x)) \neq a(e^{c'}(x))\right] \leq \eta$ *for a small η.*

Proposition 1. *If any of fidelity* (2)*, determinacy* (3)*, or groundedness* (4) *is violated by more than its tolerance ε, then trust is not warrant-invariant: there is a positive-measure set of flows on which two legitimate choices induce different top-k explanations, hence different actions for any a that separates those top-k sets.*

Proof sketch. Each property bounds the disagreement between two legitimate choices. If determinacy fails, $\mathbb{E}_x[J_k(e, e'; x)] < 1 - \varepsilon_{\mathrm{det}}$ for two methods $e, e' \in \mathcal{M}$; since $J_k \leq 1$, a positive-measure set has $\mathrm{top}_k(e, x) \neq \mathrm{top}_k(e', x)$, and any a that maps these distinct sets to distinct actions violates Definition 2 with $\eta < \varepsilon_{\mathrm{det}}$. The groundedness case is identical with c, c' two equal-accuracy seeds. For fidelity, a surrogate g with $\Pr[g \neq f] > \varepsilon_{\mathrm{fid}}$ gives, on a positive-measure set, an explanation of a decision the deployed model did not make, so the choice "read g" versus "read f" changes the grounds the analyst acts on. Thus each violation exhibits an unadjudicated choice that flips the action. □

Proposition 1 is deliberately about invariance, not correctness: two methods can agree and both mislead, so agreement is not sufficient for a *correct* explanation. But disagreement is sufficient for an *unwarranted* one, because the analyst has no principled basis to prefer either choice. The necessity is scoped to the policy class, not universal: the proposition shows that *some* action policy sensitive to top_k diverges under unadjudicated choices, and Section VI exhibits two *learned* such policies that do; it does not assert that every conceivable analyst policy would. A policy that ignored the explanation would be trivially invariant, but then interpretability plays no role in the trust it is invoked to support. We now show current practice violates determinacy and groundedness and buys fidelity only at a cost in detection, then that the violation carries a security cost and resists a cheap fix.

TABLE II
WHICH EXPLANATION FAMILIES CAN, IN PRINCIPLE, SATISFY EACH TRUST PROPERTY. ● STRUCTURALLY PROVIDES IT, ◐ CONDITIONALLY, ○ AT RISK AND MUST BE MEASURED. NO FAMILY SATISFIES ALL FOUR FOR FREE.

Explanation family	fidelity	determ.	ground.	faithf.
gradient attribution	●	○	○	○
SHAP / LIME (perturb.)	●	○	○	◐
global surrogate	◐	●	◐	◐
intrinsic / KAN	●	●	○	○
rule / concept	●	◐	◐	◐

A. Which explanation approaches could warrant trust?

Before measuring, we systematize the landscape: which *families* of explanation could, in principle, satisfy each property (Table II)? Post-hoc attributions (gradient [4], [3], perturbation-based SHAP and LIME [8], [2]) are computed *from* a fixed deployed model, so they cannot violate fidelity, but they are method-dependent (determinacy at risk) and model-instance-dependent (groundedness at risk), and faithfulness is not guaranteed. Global surrogates (trees, sparse linear models) can be faithful only up to their approximation of the deployed model, trading fidelity against readability (Section V). Intrinsically interpretable models [37] (and interpretable-by-design networks such as the KAN [43]) escape the surrogate gap by construction, but only if the deployed model *is* the interpretable one, which sacrifices the capacity practitioners deploy for, and, as we show, a KAN's readable symbolic form is not faithful to the trained KAN. Rule- and concept-based methods [9], [48] are more stable but coarser. No family is free of all four risks; the table makes explicit where each must be checked.

V. THE THREE PROPERTIES FAIL

Setup. We evaluate on *five* modern NIDS datasets (Table III), each with named, interpretable flow or connection features so that a feature attribution is a claim about a real network quantity rather than an opaque coordinate. We deliberately span heterogeneous capture settings, attack taxonomies, and class balances so that our negative findings cannot be blamed on a single corpus. Each dataset is cast as binary normal-versus-attack detection with standardized features and stratified $70/30$ train/test splits. Our detectors are a multilayer perceptron (MLP) and a Kolmogorov-Arnold network (KAN, whose learnable univariate edges are explicitly marketed as interpretable); explanations are gradient saliency, input×gradient, integrated gradients, KernelSHAP, and LIME. We further confirm determinacy, groundedness, and faithfulness on the tree ensembles that dominate tabular NIDS, random forests and gradient boosting explained by exact TreeSHAP (Table VII). Results are over three seeds (properties P1, P2) and four seeds (P3); we report mean

and standard deviation. Table IV and Fig. 2 summarize the findings; each property should score 1.0 for trust to hold, and none does on any dataset. Appendix B maps every reported quantity to the script and result file that produce it.

Dataset descriptions. We chose the five corpora to span 2015–2023 of NIDS practice and five distinct deployment regimes, so that any property that held only under one capture pipeline would be exposed. *UNSW-NB15* [49] is generated by the IXIA PerfectStorm tool at ACCS (2015) and mixes normal traffic with nine synthetic attack families (fuzzers, analysis, backdoors, DoS, exploits, generic, reconnaissance, shellcode, worms); we use the 34 numeric/protocol flow features. It is the most balanced corpus (attack rate 0.68) and remains a de facto ML-IDS benchmark. *CICIDS2017* [50] captures five days of a realistic campus network with 80-plus CICFlowMeter statistics; we use the cleaned release of Engelen et al. [51], which repairs the labeling and feature-extraction errors of the original, and keep 52 features. It is the most imbalanced (0.17) and its labeled attack types (DoS/DDoS, web attacks, infiltration, PortScan) let us analyze harm per attack type (Sec. VI). *5G-NIDD* [52] is captured on a live 5G test network (2022) and is the closest to the next-generation settings where ML-IDS is now marketed; its 48 features describe DoS and scanning attacks against 5G services. *TON-IoT* [53] is a telemetry corpus from a medium-scale IoT/IIoT edge testbed (2020); after dropping identifier columns (IP addresses, ports, timestamps) that leak host identity rather than behavior, we keep 38 connection features. Its rich attack taxonomy (scanning, DoS/DDoS, backdoor, ransomware, data injection, XSS, password, MITM) makes it, with CICIDS2017, the second corpus on which we measure per-attack-type harm. *CIC-IoT-2023* [54] is the most recent corpus, captured on a large IoT testbed of 105 real devices (UNB, 2023); we use its 39 named packet and flow features. It is heavily attack-dominated (rate 0.97, DDoS-heavy), so detection is easy and the detector saturates; we add it specifically to test whether the failures persist on current, next-generation data, and the unconfounded ones do (determinacy 0.51, groundedness 0.49; its near-zero faithfulness we read only as consistent, being confounded by saturation, Sec. V).

Fidelity fails (Property 1). We take a KAN-IDS, whose per-edge functions are its interpretability selling point, and extract the interpretable form its proponents invoke, a low-order symbolic surrogate of each edge. Detection F_1 drops by 0.08 ± 0.01 on UNSW-NB15, 0.35 ± 0.03 on CICIDS2017, 0.11 ± 0.01 on 5G-NIDD, and 0.34 ± 0.04 on TON-IoT. On CICIDS2017 the interpretable form collapses from $F_1 = 0.92$ to 0.62 (Fig. 3): the readable model is nearly a different, and far worse, detector. A post-hoc check agrees: keeping only the top-5 attributed features reproduces the 5G-NIDD detector's decision on just 0.63 of flows, so the reason does not even suffice for the decision. The analyst reasons about a model that is not the one guarding the network.

This is not special to the KAN. Fitting standard *global* interpretable surrogates to mimic a deployed MLP-IDS reveals a




Fig. 2. Each necessary property, measured on five modern NIDS datasets. A sound trust signal requires every bar at 1.0; all fall short on every dataset.



Fig. 3. Fidelity fails. The interpretable surrogate of a KAN-IDS detects markedly worse than the deployed model, collapsing on CICIDS2017. The analyst reasons about the lower bar.

fidelity-readability frontier (Table V): a higher-capacity depth-4 tree matches the deployed decisions well (0.98 agreement on CICIDS2017) but is barely more readable than the model, whereas the genuinely readable renderings, a depth-2 tree or a sparse logistic model, lose detection quality (F1 falls from 0.93 to 0.72 and 0.84 on CICIDS2017). Fidelity is thus attainable only by surrendering the readability the trust claim depends on.

Determinacy fails (Property 2). For the same detector and the same flagged-malicious flows, we measure how much the top-5 features agree across explainers. Among the three gradient-family methods, mean agreement is only 0.45 ± 0.017 (UNSW-NB15), 0.36 ± 0.005 (CICIDS2017), 0.53 ± 0.079 (5G-NIDD), and 0.37 ± 0.06 (TON-IoT). This is not an artifact of using only gradient methods, nor of under-sampling: adding the two most deployed model-agnostic explainers, SHAP and LIME, at high sampling budgets, the mean five-explainer agreement stays at 0.32–0.50 (Fig. 4), and *cross-family* agreement is lower still: gradient saliency and SHAP agree on only 0.17–0.31 of the top-5 features. The reason presented to the analyst is largely an artifact of which equally-defensible tool the vendor shipped.

Two clarifications, because a Jaccard is easy to over-read

TABLE III

THE FIVE MODERN NIDS DATASETS. ALL HAVE NAMED, INTERPRETABLE FLOW/CONNECTION FEATURES, SO AN ATTRIBUTION IS A CLAIM ABOUT A REAL NETWORK QUANTITY. "ATTACK RATE" IS THE POSITIVE-CLASS FRACTION AFTER OUR 40K STRATIFIED SUBSAMPLE.

Dataset	Year	Features	Attack rate	Capture setting	Attack families
UNSW-NB15 [49]	2015	34	0.68	IXIA PerfectStorm testbed	9 families: DoS, exploits, reconnaissance, fuzzers, shellcode, worms, backdoors, generic, analysis
CICIDS2017 [50], [51]	2017	52	0.17	campus network flows	DoS/DDoS, web attacks, infiltration, PortScan
5G-NIDD [52]	2022	48	0.61	live 5G core testbed	DoS, port and vulnerability scanning
TON-IoT [53]	2020	38	0.76	IoT/IIoT edge testbed	scanning, DoS/DDoS, backdoor, ransomware, injection, XSS, password, MITM
CIC-IoT-2023 [54]	2023	39	0.97	IoT testbed, 105 devices	DDoS, DoS, Mirai, reconnaissance, spoofing, web, brute force

TABLE IV

EACH NECESSARY PROPERTY OF INTERPRETABILITY-BASED TRUST, ON FIVE MODERN NIDS DATASETS (2015–2023), OVER THREE SEEDS (P1, P2) AND FOUR SEEDS (P3), MEAN±STD. EVERY QUANTITY IS AN AGREEMENT OR RETENTION THAT MUST BE ≈ 1.0 FOR TRUST TO BE WELL-FOUNDED; DETERMINACY AND GROUNDEDNESS FALL SHORT ON EVERY DATASET.

Property	Quantity	UNSW	CICIDS	5G-NIDD	TON-IoT	CIC-IoT23
P1 Fidelity	deployed vs. interpretable-surrogate F_1 drop ↓	0.08±0.01	**0.35±0.03**	0.11±0.01	**0.34±0.04**	0.01±0.01
	top-5 attribution sufficiency (agree w/ decision)	0.92	0.89	0.63	0.87	0.96
P2 Determinacy	mean top-5 agreement, 3 gradient methods	0.45±0.02	0.36±0.01	0.53±0.08	0.37±0.06	0.51±0.01
	mean top-5 agreement, all 5 explainers	0.35	0.34	0.50	0.32	0.36
P3 Groundedness	detection F_1 across 4 seeds	.95±.001	.93±.002	1.0±.000	.99±.000	.99±.000
	cross-seed top-5 explanation agreement	0.53±0.01	0.62±0.03	0.56±0.03	**0.37±0.03**	0.49±0.03

TABLE V

THE FIDELITY-READABILITY FRONTIER: EACH CELL IS DECISION AGREEMENT WITH THE DEPLOYED MLP-IDS (HIGHER IS MORE FAITHFUL) / DETECTION F_1, FOR GLOBAL INTERPRETABLE SURROGATES. READABLE SURROGATES (DEPTH-2 TREE, SPARSE LOGIT) ARE LESS FAITHFUL OR DETECT WORSE.

Surrogate	UNSW	CICIDS	5G	TON	CIC23
tree (d=4)	.96/.94	.98/.94	1.0/1.0	1.0/.99	.99/.99
tree (d=2)	.94/.92	.94/.**72**	.98/.98	.94/.96	.98/.99
sparse logit	.96/.94	.96/.**84**	.99/.99	.96/.97	.99/.99

in either direction. It divides by the union, so an agreement of J at k=5 means the two explanations share $2kJ/(1+J)$ features and the analyst sees $2J/(1+J)$ of the five endorsed by both, not J: our lowest cross-family value, J=0.15 on TON-IoT, is an overlap of 0.261 of what is shown. Earlier drafts stated J itself as that fraction, understating the overlap in the abstract. And J must be read against chance, which depends on the feature count: two independent uniform top-5 rankings score 0.056 (52 features) to 0.087 (34) in expectation, so the observed agreements sit at 1.94×–5.13× chance. They are above chance everywhere, as methods explaining one model should be, and nowhere near the ≈ 1.0 determinacy requires. The claim is not that explainers agree at chance level; it is that they agree far too little for the shown features to be treated as *the* reason.

Groundedness fails (Property 3). We train four detectors that differ only in random seed. Their detection performance is statistically identical (on UNSW-NB15, $F_1 = 0.95\pm0.001$), yet their top-5 explanations for the same inputs agree on only 0.53±0.005 (UNSW-NB15), 0.62±0.029 (CICIDS2017), 0.56±0.027 (5G-NIDD), and 0.37±0.03 (TON-IoT) of features. An analyst handed one detector's explanation is trusting an accident of training that an equally good detector would contradict.

Determinacy and groundedness fail outright across five modern datasets, with tight seed-to-seed variance. Fidelity does not, and the distinction matters: a depth-4 tree reproduces the deployed detector's decisions on .96–1.0 of flows (Table V), so a faithful readable artifact exists. What fails is fidelity *at no cost* — distillation loses up to 0.35 F_1, and the surrogates that stay faithful give up detection on the hardest corpus (.72 and .84 F_1). Fidelity is purchasable; the other two are not. The failures are not artifacts of our choices: determinacy agreement stays low across top-k sizes (k=3, 5, 10; e.g. CICIDS2017 0.35–0.47), and groundedness agreement is flat as the ensemble grows from four to ten models (CICIDS2017 ≈ 0.46, 5G-NIDD ≈ 0.63), so neither failure is rescued by showing more features or averaging more models (Fig. 5). Nor is the disagreement an artifact of the redundancy of flow features: collapsing features into Spearman-correlation clusters, so that an explainer picking a near-duplicate of another's feature is scored as agreeing,




Fig. 4. Determinacy across five explainers (high sampling budgets): top-5 agreement for all ten pairs on each dataset. Only the two input×gradient-based methods (i-ig) agree; every cross-family pair is light (low). The reason shown to the analyst is largely a tool artifact. The underlying numbers for all ten pairs are in Appendix A.

raises agreement by at most 0.14 at a near-duplicate threshold ($|\rho| \geq 0.9$) and never above 0.76 (Table VIII); even at an aggressive $|\rho| \geq 0.8$ the peak is 0.82, on the most redundant dataset, still far from the $\approx$ 1.0 a trust signal needs. The under-determination is thus between genuinely distinct feature clusters, not redundant column pairs. Finally, the metrics are not unsatisfiable by construction: on a synthetic positive control with decorrelated features and a *sparse known* ground-truth, all three properties score 0.92–1.00 and the model's top-5 recover the true informative features exactly, and they fall to the real-NIDS regime ($P2{\approx}0.43$, $P3{\approx}0.44$) only as the sparse, decorrelated structure is removed (Table VI). The metrics are therefore satisfiable *and* calibrated; the failures on real NIDS are a property of real explanations, not of the measurement. This also sets the bar empirically rather than as a strawman: a genuinely grounded task reaches 0.92–1.00 here, so the real-NIDS scores of 0.4–0.6 fall well short of the *achievable* ceiling, not merely of an idealized 1.0. The failures are also not specific to neural detectors: on the tree ensembles that dominate tabular NIDS (random forests and gradient boosting), explained by *exact, deterministic* TreeSHAP, determinacy (across TreeSHAP, LIME, impurity, and permutation attributions), groundedness (across seeds), and faithfulness all fail in the same range as for the MLP and KAN (Table VII). The trust that explainable ML-IDS invites is therefore, as currently produced, not well-founded.

A fourth, deeper property: faithfulness. The three properties above concern the *consistency* of an explanation (across surrogate, method, and seed) and are each necessary for warrant. Faithfulness is stronger: even a perfectly consistent explanation could be wrong about the model. We treat it separately because, unlike the agreement properties, it compares the explanation to the model's actual behavior rather than to another explanation. One might hope the shown features are the ones the model *uses*. They are not. We measure the two standard faithfulness metrics [32], comprehensiveness (the drop in attack-probability when the top-5 features are removed) and sufficiency (how much the top-5 alone retain), on all five datasets. Removing the top-5 attributed features barely moves the decision: comprehensiveness is only 0.18 (UNSW-NB15), 0.16 (5G-NIDD), 0.04 (TON-IoT), and −0.001 on CIC-IoT-2023, and reaches 0.51 only on CICIDS2017. So on four of five datasets the features the analyst is shown (via gradient saliency) are largely not the ones driving the alarm (Table X). The near-zero value on CIC-IoT-2023 is a boundary case we flag rather than lean on: its detector is saturated (attack rate 0.97, attack-probability $\approx$ 1.0 on flagged flows), so no small feature set is comprehensive, and faithfulness here is confounded with task triviality; the unconfounded evidence on this corpus is its determinacy (0.51) and groundedness (0.49) failures, which do not depend on detector confidence. Extending to all five explainers (Table IX) shows faithfulness is real but *unreliable*: it depends on both explainer and dataset. SHAP is the most faithful method but still dataset-dependent, highly faithful on CICIDS2017 (comprehensiveness 0.95) yet only 0.40 on 5G-NIDD and 0.34 on TON-IoT; gradient saliency, the most-deployed explainer, is the least faithful, as low as 0.04 on TON-IoT. No single explainer is faithful across

TABLE VI

POSITIVE CONTROL: THE METRICS ARE SATISFIABLE, NOT RIGGED TO FAIL. ON A SYNTHETIC TASK WITH 32 DECORRELATED FEATURES AND A LINEARLY SEPARABLE LABEL DRIVEN BY ONLY k OF THEM, ALL THREE PROPERTIES REACH ≈ 1.0 WHEN THE GROUND-TRUTH IS SPARSE (k=5), AND THE MODEL'S TOP-5 SALIENCY RECOVERS THE TRUE INFORMATIVE FEATURES EXACTLY (RECOVERY 1.00). SPREADING THE SIGNAL OVER MORE FEATURES (LARGER k), WHICH REMOVES THE SPARSE, DECORRELATED STRUCTURE THAT INTERPRETABILITY IMPLICITLY ASSUMES, DRIVES THE SCORES DOWN TO THE REAL-NIDS REGIME.

Synthetic regime	P1 suff.	P2 determ.	P3 ground.
sparse (k=5, ceiling)	**0.99**	**0.92**	**1.00**
mid (k=12)	0.76	0.56	0.76
diffuse (k=28)	0.67	0.43	0.44

TABLE VII

THE DETERMINACY, GROUNDEDNESS, AND FAITHFULNESS FAILURES ARE NOT SPECIFIC TO NEURAL DETECTORS: THEY HOLD, IN THE SAME RANGE, ON THE TREE ENSEMBLES THAT DOMINATE TABULAR NIDS, EXPLAINED BY *exact, deterministic* TREESHAP. RANGES ARE ACROSS THE FIVE DATASETS. FOR TREES, DETERMINACY IS MEASURED ACROSS EQUALLY-DEFENSIBLE ATTRIBUTIONS (TREESHAP, LIME, IMPURITY, PERMUTATION), SINCE TREESHAP ALONE IS DETERMINISTIC; A READABLE DEPTH-2 SURROGATE ALSO LOSES FIDELITY (E.G. CICIDS2017 F_1 0.99→0.72), AS FOR THE NEURAL DETECTORS.

Detector family	P2 determ.	P3 ground.	Faithful. (comp.)
Neural (MLP, KAN)	0.36–0.53	0.37–0.62	0.00–0.51
Random forest	0.35–0.48	0.52–0.67	0.00–0.59
Gradient boosting	0.21–0.45	0.44–0.76	0.00–1.00




Fig. 5. Robustness of the determinacy and groundedness failures. Agreement stays low as the shown top-k grows (left, k=3, 5, 10) and as the ensemble grows (right, E=4, 6, 10), far below the 1.0 a trust signal needs. The failures are not artifacts of k or ensemble size.

TABLE VIII
THE DETERMINACY (P2) AND GROUNDEDNESS (P3) FAILURES ARE NOT A FEATURE-REDUNDANCY ARTIFACT. "RAW" IS PER-FEATURE TOP-5 JACCARD; THE "$|\rho| \geq \tau$" COLUMNS FIRST COLLAPSE FEATURES INTO SPEARMAN-CORRELATION CLUSTERS, SO AN EXPLAINER THAT PICKS A NEAR-DUPLICATE OF ANOTHER'S FEATURE COUNTS AS AGREEING. EVEN AT AN AGGRESSIVE τ=0.8 NO VALUE REACHES THE ≈ 1.0 A TRUST SIGNAL NEEDS. RAW VALUES ARE SINGLE-SEED AND MATCH TABLE IV WITHIN SEED VARIANCE.

	Grouping	UNSW	CICIDS	5G	TON	CIC23
P2	raw	0.49	0.39	0.61	0.39	0.55
	$\lvert\rho\rvert \geq 0.9$	0.60	0.46	0.71	0.43	0.57
	$\lvert\rho\rvert \geq 0.8$	0.69	0.51	0.79	0.63	0.58
P3	raw	0.56	0.61	0.62	0.39	0.48
	$\lvert\rho\rvert \geq 0.9$	0.68	0.63	0.76	0.51	0.49
	$\lvert\rho\rvert \geq 0.8$	0.75	0.69	**0.82**	0.57	0.50

datasets, so an analyst cannot assume the shown features are the operative ones without measuring it per deployment, which no audited paper does (Section IX-A).

VI. THE FAILURE HAS SECURITY CONSEQUENCES

A skeptic may object that under-determination is generic machine-learning hygiene: rename the datasets to medical or credit and the numbers survive. We answer with a consequence that is specifically about *security decisions* (the harm annotated in Fig. 1). Consider flows that are true attacks and that the IDS *correctly* flags; here the detector is right and, across a seed-ensemble, stable. We model an analyst who reads an explanation and decides to escalate (treat as a real attack) or suppress (dismiss as a false positive) with an auditor classifier trained to read attribution vectors; we use two auditor families (logistic regression and a random forest), so the result is not a linearity artifact. Algorithm 1 states the measurement.

The result is stark on CICIDS2017, the most operationally realistic of the five (a 17% attack rate over many attack types). Detection is stable: the seed-ensemble agrees on 0.88 of these flows that they are attacks. The analyst's action is not. The detector agrees a flow is an attack, but whether the analyst *acts* on it depends on which arbitrary training seed was deployed.

TABLE IX
COMPREHENSIVENESS OF THE TOP-5 EXPLANATION FOR ALL FIVE EXPLAINERS (HIGHER IS MORE FAITHFUL). FAITHFULNESS IS EXPLAINER- AND DATASET-DEPENDENT: NO METHOD IS RELIABLY FAITHFUL ACROSS DATASETS, AND THE MOST-DEPLOYED (SHAP, LIME) SWING WIDELY. †CIC-IOT-2023'S DETECTOR IS SATURATED (ATTACK RATE 0.97), SO NO SMALL FEATURE SET IS COMPREHENSIVE; WE DO NOT READ ITS ZEROS AS AN INDEPENDENT FAITHFULNESS RESULT.

	grad	i×g	int-g	SHAP	LIME
UNSW-NB15	0.17	0.32	0.33	0.35	0.12
CICIDS2017	0.47	0.81	0.74	**0.95**	0.68
5G-NIDD	0.15	0.28	0.30	0.40	0.35
TON-IoT	**0.04**	0.09	0.07	0.34	0.19
CIC-IoT-2023†	0.00	0.00	0.00	0.00	0.00

TABLE X
FAITHFULNESS OF THE TOP-5 EXPLANATION ON FLAGGED ATTACKS, ACROSS FIVE MODERN DATASETS. COMPREHENSIVENESS (DROP IN ATTACK-PROBABILITY WHEN THE TOP-5 ARE REMOVED; HIGHER IS MORE FAITHFUL) IS LOW ON FOUR OF FIVE: THE SHOWN FEATURES ARE LARGELY NOT THE ONES THE MODEL USES. CIC-IOT-2023'S ZERO IS CONFOUNDED BY A SATURATED DETECTOR (SEE TEXT) AND NOT READ AS INDEPENDENT EVIDENCE.

	UNSW	CICIDS	5G	TON	CIC-IoT23
comprehensiveness ↑	0.18	0.51	0.16	0.04	**0.00**
sufficiency gap ↓	0.02	0.37	0.75	0.04	0.00

This is the security harm: mis-founded trust in the explanation converts a grounded detection into an ungrounded response. No adversary is required; it follows from the benign under-determination of Section V. It is largest on the harder corpora and near-zero on the easiest (Fig. 7, Table XI), and it is not an artifact of a linear analyst: both a logistic and a random-forest auditor show it.

What survives control, and what does not. No such rate means anything on its own, so we place each against the value it takes when the effect under study is switched off (Table XI). The auditor is first shown to be competent: it recovers the label from the explanations of the model it was calibrated on with accuracy 0.916 to 0.997, so a suppressed true attack is not simply an incompetent analyst.

The suppression rate survives, and it is the result. On the model it knows, the auditor dismisses only 0.018 of correctly-detected true attacks on CICIDS2017; on the four sibling models it has never seen, 0.433. Feeding it attributions with the flow–explanation link destroyed — same per-feature magnitudes, no signal — gives 0.505. The calibrated analyst is therefore closer to reading noise than to reading the model it was calibrated on, and on 5G-NIDD and TON-IoT the sibling-model rate *exceeds* the noise rate outright. This gap is the paper's security claim, and it is what the controls leave standing.

Action divergence does not survive, and we withdraw it as independent evidence. Divergence is $1 - \Pr[\text{all } E \text{ escalate}] - \Pr[\text{all } E \text{ suppress}]$, so if the E=5 per-model actions were independent at the observed marginal it would already be

Algorithm 1: Explanation-induced action divergence on true attacks

Input: seed-ensemble $\{f_1, \ldots, f_E\}$; auditor g mapping an attribution to escalate/suppress; test set with labels

Output: action-divergence rate on correctly-detected true attacks

$T \leftarrow \{x : y(x){=}1 \wedge f_i(x){=}1 \ \forall i\}$; `// true attacks all models flag`

foreach $x \in T$ **do**

  foreach i **do** $a_i(x) \leftarrow g\big(e_{f_i}(x)\big)$;

  $\mathrm{div}(x) \leftarrow \big[\neg\,(a_1(x){=}\cdots{=}a_E(x))\big]$; `// models split`

return $\frac{1}{|T|}\sum_{x\in T}\mathrm{div}(x)$

$1 - p^5 - (1-p)^5$. Permuting each model's action column across flows — which fixes every per-model marginal exactly and destroys only the flow-level coupling, so it stays valid under flow heterogeneity — gives a null of 0.936 against a measured 0.873 on CICIDS2017. Across all ten dataset–auditor pairs, *not one* measured divergence exceeds this null; five sit within 0.02 of it and the rest fall below. Divergence is thus fully accounted for by the marginal suppression rate and adds no information about explanation instability. We report it for comparison with prior work that quotes disagreement rates without a floor, but rest no claim on it. An earlier version of this paper rested its abstract on it.

The harm is not a coincidence of our auditor; it is a consequence of the groundedness failure, which Proposition 2 states and the measurements below instantiate.

Proposition 2 (Harm from ungroundedness)**.** *Let the analyst action $a(e(x)) \in \{\textit{escalate}, \textit{suppress}\}$ depend on the explanation only through top_k, and let π be the probability that a changes when top_k changes on a flow. For two equally-accurate models f_1, f_2 with cross-seed agreement $\mathbb{E}_x[J_k(e_{f_1}, e_{f_2}; x)] = 1 - \varepsilon_{\mathrm{grnd}}$, the action-divergence rate on their shared true positives is at least $\pi\,\varepsilon'_{\mathrm{grnd}}$, where $\varepsilon'_{\mathrm{grnd}}$ is the fraction of flows with disjoint-enough top-k sets.*

Proof sketch. Groundedness failure means a positive-measure set D of flows has $\mathrm{top}_k(e_{f_1}, x) \neq \mathrm{top}_k(e_{f_2}, x)$. On any $x \in D$ where the differing features flip the analyst's read, the two models induce different actions; the measure of such flows is at least π times $|D|$. Since detection is stable on these true positives (both models flag attack), the divergence is entirely explanation-driven. Larger $\varepsilon_{\mathrm{grnd}}$ forces larger $|D|$, hence a larger lower bound, *holding π and the flow distribution fixed*. □

The predicted cross-dataset trend is not observed, and we withdraw the claim that it is. Ranking the five corpora by seed-agreement P_3 against each harm measure gives Spearman $\rho = +0.4$ for action divergence and $\rho = +0.7$ for the sibling-model dismissal rate (exact permutation $p = 0.233$ at $n{=}5$): five of five tests point *opposite* to the direction the proposition suggests, none significantly. CICIDS2017, where harm is largest, has the *highest* groundedness of the five ($P_3 = 0.618$, against 0.374 on TON-IoT). An earlier version of this paper asserted the reverse as observed fact here; it was wrong against our own Table IV.

This does not refute the proposition, which holds π and the flow distribution fixed and bounds harm from below — neither condition a cross-corpus ranking can honour. It refutes only any reading of our results as empirical support for the mechanism, so we rest no measurement on it. Testing it properly requires varying groundedness with everything else fixed, which only the synthetic control of Table VI does: spreading the ground-truth signal from $k{=}5$ to $k{=}28$ features drives P_3 from 1.00 to 0.44 with the explainer untouched. That also exposes a confound the cross-corpus comparison cannot escape — P_3 tracks how sparse the underlying signal is, so ranking corpora by P_3 partly ranks them by problem structure rather than explanation quality.

In operational cost. The divergence matters because the two actions have very different costs. Write C_{miss} for the cost of suppressing a true attack and C_{fp} for investigating a false positive, with $C_{\mathrm{miss}} \gg C_{\mathrm{fp}}$ in security. On a true attack the correct action is escalate; an explanation that reads benign induces suppress and incurs C_{miss}. Under groundedness failure the suppress event occurs with a seed-dependent probability $s(x)$, so the expected excess cost of trusting the explanation is $\mathbb{E}_x[s(x)]\,C_{\mathrm{miss}}$ over the true attacks, and it concentrates, by Fig. 6, on the high-volume DoS and reconnaissance flows that dominate the attack set. Trusting the explanation therefore does not merely add noise; it adds expected cost weighted toward high-rate threats.

The blind spot is attack-type-dependent. Resolving the harm by attack type on the multiclass datasets (Fig. 6) shows it is far from uniform. On CICIDS2017 the divergence is largest on DoS (0.86) and port scanning (0.62), the high-volume denial and reconnaissance flows an analyst most needs to escalate, and smaller on DDoS (0.20). The pattern differs on TON-IoT, where divergence is high on some flooding and man-in-the-middle traffic but low on several stealthier types, so there is no guarantee that the seed-dependent blind spot spares the serious threats: on the most operationally realistic corpus it clusters precisely on the high-rate DoS and scanning attacks. Mis-founded trust does not spread its risk evenly, and it offers no assurance of sparing the attacks that matter.

VII. Can an Adversary Exploit This?

The failures above are benign: they arise without an adversary. Security demands the adversarial case. Fig. 8 contrasts two routes to get a malicious flow's alarm dismissed: the classical one evades the *detector*; the one this section studies keeps the detector firing but manipulates the *explanation* so the analyst dismisses a true alarm, an evasion by explanation rather than by detection. In vision and NLP the latter is established: explanations can be moved almost arbitrarily while the prediction is fixed [24], [25], [26].




Fig. 6. Action divergence by attack type on correctly-detected true attacks (CICIDS2017). The explanation-induced blind spot is largest on the high-volume DoS and port-scanning flows and smaller on DDoS: mis-founded trust does not spread its risk evenly across attack types.




Fig. 7. The security consequences. On correctly-detected true attacks, detection is stable (the ensemble agrees the flow is an attack), yet the explanation-driven analyst action diverges across equally-good models, most on the realistic CICIDS2017. Whether a real attack is acted on becomes an accident of the deployed seed.

We tested the analogue on our tabular IDS. We model an analyst who reasons from explanations as an auditor classifier trained to map an attribution vector to benign/attack, and we search for a bounded perturbation that keeps the detector's malicious decision while steering the explanation toward the benign prototype. The attack was inconclusive: the detector kept firing on 1.0 of flows, but the manipulated explanations were still read as attack by the auditor almost everywhere, and the fraction of true alarms we could get dismissed never exceeded 0.26, most of which reflects the auditor's baseline error rather than the attack. A second formulation, directly driving attribution mass off the top-k features, also failed to move them.

The tabular result is not evidence that tabular IDS explanations are robust. The gap from the vision result is real and informative: tabular NIDS features are low-dimensional and semantically constrained, so the room to reshape an explanation without either flipping the decision or leaving the data manifold is small, unlike the high-dimensional redundancy of images. Stronger, model-agnostic attacks in the style of adversarial scaffolding [26] remain untested here and are a clear next step. We report the negative result because a security paper should not overstate an attack, and because the benign failures of Section V already void trust without needing an adversary.

TABLE XI

EXPLANATION-INDUCED HARM ON CORRECTLY-DETECTED TRUE ATTACKS, WITH ITS CONTROLS (RANDOM-FOREST AUDITOR; THE LOGISTIC AUDITOR IS WEAKER BUT ORDERED THE SAME). DETECTION IS STABLE. THE RATE AT WHICH A TRUE ATTACK IS DISMISSED RISES SHARPLY WHEN THE AUDITOR READS AN EQUALLY ACCURATE *sibling* MODEL RATHER THAN THE ONE IT WAS CALIBRATED ON — THAT GAP IS THE RESULT. ACTION DIVERGENCE, BY CONTRAST, NEVER EXCEEDS THE PERMUTATION NULL THAT FIXES EACH MODEL'S MARGINAL, AND IS WITHDRAWN AS EVIDENCE.

	UNSW	CICIDS	5G	TON	CIC23
detection agreement	.961	.880	.998	.995	.986
dismissed, own model	.003	0.018	0.001	0.026	.001
dismissed, sibling model	.008	**0.433**	**0.294**	**0.272**	.003
dismissed, signal-free	.000	0.505	0.15	0.179	.000
action divergence	.029	0.873	.682	.813	.009
permutation null	.035	0.936	.816	.821	.013

VIII. Is Trust Cheaply Recoverable? A Negative Result

If interpretability-based trust fails by default, the natural hope is a cheap fix: a per-alarm *reliability gate* that tells the analyst *when* an explanation may be trusted, from the single deployed model, without the expensive machinery of an ensemble. We built the most natural such gate and report an honest negative: it looks good in-distribution but is circular and does not generalize, so trust is not cheaply recovered. We detail it because the way it fails is instructive about why the problem is hard.

What "reliable" means. We call an explanation reliable for a flow if it is *stable*: its top-k features are reproduced both across an ensemble $\{f_1, \ldots, f_E\}$ of equally-good models (groundedness holds locally) and across the attribution family $\mathcal{M}$ (determinacy holds locally). We combine the two into a per-flow reliability score, where $\bar{J}$ denotes the mean pairwise top-k agreement over the indicated set,

$$S(x) = \tfrac{1}{2}\,\bar{J}_{\text{model}}(x) \;+\; \tfrac{1}{2}\,\bar{J}_{\text{method}}(x), \tag{5}$$

with $\bar{J}_{\text{model}}$ taken over the ensemble $\{f_i\}$ (local groundedness, P3) and $\bar{J}_{\text{method}}$ over the family $\mathcal{M}$ (local determinacy, P2). $S(x)$ is the ground truth we want but cannot compute per alarm in deployment, since it needs an ensemble and several explainers. We stress that S measures *stability, not correctness*: a stable explanation is reproducible, not necessarily faithful, so the gate below recovers a necessary component of trust, not all of it (Section X).

The gate. We train a lightweight detector to predict this stability from signals that a single deployed model exposes at alarm time: the decision margin, the concentration (entropy)




Fig. 8. Two routes to suppress a true alarm. Route 1 evades the detector (classical adversarial evasion). Route 2, ours, keeps the detector firing but reshapes the explanation so the analyst dismisses it. On tabular NIDS, Route 2 does not transfer from vision: low-dimensional, manifold-constrained features leave little room to move the explanation without flipping the decision.

Algorithm 2: The reliability gate (which we show does not deploy)

Input: deployed model f; ensemble $\{f_i\}$; method family $\mathcal{M}$; training flows
Output: per-alarm reliability predictor h
`// offline: expensive stability label`
foreach *training flow* x **do**
  $S(x) \leftarrow \frac{1}{2}\bar{J}_{\text{model}}(x) + \frac{1}{2}\bar{J}_{\text{method}}(x)$ (Eq. 5);
`// cheap per-model signals`
$\phi(x) \leftarrow$
  [margin, attr. entropy, local fidelity, OOD dist.];
$h \leftarrow$ classifier fit on $\big(\phi(x), [S(x) > \text{median}]\big)$;
return h ; `// at alarm time:`
  `gate`$(x) = h(\phi(x))$

of the attribution, a local linear-surrogate fidelity, and an out-of-distribution distance (Algorithm 2). If the cheap detector predicts the expensive stability well, the analyst could be told, for free, when not to trust an explanation.

In-distribution, it looks promising. Fit and evaluated on the same dataset, the gate predicts explanation reliability with AUC 0.78 (UNSW-NB15), 0.85 (CICIDS2017), 0.95 (5G-NIDD), and 0.86 (TON-IoT) (Fig. 9), and out-of-distribution distance alone is weak (AUC 0.55 on CICIDS2017, near chance), so the signal is not simply an OOD detector. Taken alone this looks like a working, deployable fix. It is not, for two reasons.

Failure 1: it is circular. The signal that carries the gate is the attribution *concentration*, whose single-signal AUC (0.78 on 5G-NIDD, and 0.87 on TON-IoT, which *exceeds* that dataset's full-gate AUC of 0.86) matches or exceeds the full gate. But concentration is coupled to the label *by construction*: a peaked saliency vector yields a stable top-k set under both re-seeding and method change, so it raises both the reliability label $S(x)$ and the concentration feature (their correlation is ≈ 0.82 in magnitude). The gate is thus, in large part, the same quantity measured twice, not a cheap predictor of an independent property. The "not just OOD" signal is not independent of OOD: it is replaced by a feature entangled with the target. Proposition 3 makes the entanglement precise.

Proposition 3 (Gate circularity)**.** *Let the concentration signal be the negative entropy of the normalized attribution,* $\kappa(x) = \sum_j p_j(x) \log p_j(x)$ *with* $p(x) = |e(x)|/\|e(x)\|_1$ *(so* $\kappa = -H$*, high when peaked). As* $\kappa(x)$ *increases, the attribution mass concentrates on fewer coordinates, so* $\text{top}_k(e, x)$ *is increasingly determined by those coordinates and hence increasingly invariant to small changes of method or seed. Therefore* κ *is monotonically associated with both terms of* $S(x)$ (5)*, and a predictor using* κ *recovers* S *in part by definition, not by learning an independent cue.*

Empirically κ correlates with S at magnitude ≈ 0.82, consistent with the proposition.

Failure 2: it does not generalize. A deployable gate must work without being re-fit on the target dataset's expensive label. It cannot: trained on one dataset and tested on another, its AUC drops to a cross-dataset mean of 0.62, far below its in-distribution 0.78–0.95, and falls *below chance* on several pairs (e.g. 0.47 for UNSW→CICIDS, 0.47 for CICIDS→5G-NIDD, and 0.20 for CICIDS→TON-IoT); the fitted signal weights even flip sign across datasets. So the only way to make the gate work is to compute, per dataset, the very ensemble-and-multi-method reliability label it was meant to spare the operator. The cheap gate is not cheap.

Failure 3: it is adversarially gameable. A security control invites an adversary. Two of the gate's four inputs (decision margin, attribution entropy) are shaped by the input, so an attacker holding a genuinely-unreliable malicious flow can perturb it to make the gate accept its explanation as reliable while keeping the attack decision. This adaptive attack succeeds sharply: the fraction of low-stability true attacks the gate passes as reliable rises from 0.01 to 1.0 on CICIDS2017 (gain




Fig. 9. In-distribution, the gate predicts explanation reliability with high AUC and beats an out-of-distribution baseline. This is misleading: the carrying signal is circular and the gate does not transfer across datasets (Failures 1–2). In-distribution success is necessary but far from sufficient for a deployable gate.

TABLE XII
IN-DISTRIBUTION RELIABILITY-GATE AUC: FULL DETECTOR VERSUS EACH SINGLE SIGNAL. OOD DISTANCE ALONE IS WEAK, BUT THE CONCENTRATION SIGNAL THAT REPLACES IT IS COUPLED TO THE LABEL BY CONSTRUCTION (FAILURE 1), AND NONE OF THIS TRANSFERS ACROSS DATASETS (FAILURE 2).

	UNSW	CICIDS	5G	TON	CIC23
full gate	**0.78**	**0.85**	**0.95**	0.86	0.85
margin only	0.60	0.58	0.70	0.65	0.75
concentration only	0.75	0.51	0.78	**0.87**	0.71
local fidelity only	0.62	0.61	0.69	0.24	0.75
OOD distance only	0.65	0.55	0.91	0.68	0.77

0.99), with the malicious decision preserved throughout. An operator relying on the gate would be handed manipulated "reliable" explanations for real attacks.

Takeaway. The most natural reliability gate recovers a stability signal that is partly tautological, wholly non-transferable, and adversarially gameable. This indicates that recovering interpretability-based trust is a genuine open problem, not a matter of bolting on a confidence score. Whether a gate that predicts *faithfulness* (not mere stability) and generalizes across deployments can recover the warrant is untested and unsolved; we leave it to future work.

IX. THREAT-AWARE EVALUATION CRITERIA

If interpretability is to warrant trust in a security setting, a claim to that effect should be held to checkable conditions. We propose the following, each the operational counterpart of a property or result above, and each currently unmet by typical explainable-IDS papers.

1) **Fidelity budget.** Report the decision agreement between the interpretable artifact the analyst sees and the deployed model, on held-out and on attack traffic. A trust claim below a stated threshold is unsupported.
2) **Method invariance.** Report top-feature agreement across at least two standard attribution methods, including a perturbation-based one (SHAP or LIME). If the shown reason changes with the method, disclose it; do not present one method's output as *the* explanation.
3) **Instance invariance.** Report explanation agreement across performance-equivalent retrainings. Explanations that vary across equally-good models must not be sold as task insight.
4) **Adversarial robustness of the explanation.** State a threat model for the explanation itself and evaluate whether an adversary preserving the malicious decision can alter the shown reason. Absent this, interpretability is a usability feature, not a security one.
5) **Trust as warrant, not satisfaction.** Evaluate whether acting on the explanation agrees with ground truth, not whether analysts *feel* more confident.
6) **Reliability signalling.** Where per-flow reliability varies, provide a gate that tells the analyst when the explanation should not be trusted, and validate it.

These are necessary, not sufficient; but a claim that fails any of them should not be stated as a security benefit. Their cost varies: the method- and surrogate-agreement checks are inexpensive, whereas the model-instance (groundedness) check requires training a small ensemble, the same cost that motivates, but does not rescue, the reliability gate of Section VIII. We release code that computes all six.

A. How current work measures up

To test whether these criteria are already met, we audit a corpus of twelve recent explainable-IDS papers (2020–2026) against the six (Table XIII, all twelve listed). *Selection.* We searched Google Scholar and arXiv for explainable/interpretable network-intrusion detection using SHAP, LIME, or attribution methods, published 2020–2026, and took the twelve most-cited or most-recent that build or evaluate an XAI-IDS; this is a convenience corpus, not an exhaustive survey, so we make no field-prevalence claim beyond it. *Coding.* We score each criterion from each paper's abstract and method only: a criterion is *reported* (1) only when the paper explicitly presents the corresponding evidence, *partial* (0.5) when it is touched but not measured (e.g. two explainers shown without an agreement number), and *not-reported* (0) otherwise; coverage is the mean score over the twelve (e.g. $C_1{=}(0.5{+}0.5)/12{=}8\%$). Scores are thus a lower bound on rigor, and the audit measures *reporting practice*. The full list with DOIs and per-criterion coding is released as `field_audit.csv`.

Table XIII shows the result, and it is stark. No criterion is met by a majority. Fidelity budgets are reported by 8% of papers, instance invariance by 0% (none), an explanation threat model by 12%, warrant-style trust evaluation (versus analyst satisfaction) by 12%, and a reliability signal by 4%. Only method invariance reaches 33%, and even there most papers that use two methods (SHAP and LIME) present them as complementary for *cross-verification* [55], not as a determinacy check, so agreement is assumed rather than measured. The applied papers, which build XAI-IDS systems

TABLE XIII
AUDIT OF RECENT EXPLAINABLE-IDS WORK AGAINST THE SIX CRITERIA (● REPORTED, ◐ PARTIAL, ○ NOT REPORTED; CONSERVATIVE LOWER BOUND FROM ABSTRACT/METHOD). NO CRITERION IS MET BY A MAJORITY; INSTANCE INVARIANCE AND RELIABILITY SIGNALLING BY ALMOST NONE.

Paper	C1 fid	C2 m-inv	C3 i-inv	C4 adv	C5 warr	C6 rely
Warnecke [17] (eval)	◐	●	○	◐	◐	○
Nadeem [18] (SoK)	◐	◐	○	◐	◐	○
Capuano [1]	○	○	○	○	○	○
Le [23]	○	○	○	○	◐	◐
Uccello [57]	○	●	○	○	○	○
Muhammad [55]	○	○	○	○	○	○
Farrukh [56]	○	○	○	○	○	○
Barnard [58]	○	◐	○	◐	○	○
Sharma [59]	○	◐	○	○	○	○
Mohale [60]	○	◐	○	○	○	○
Dong [61]	○	○	○	○	○	○
Faqihi [62]	○	○	○	○	○	○
coverage	8%	33%	0%	12%	12%	4%

and report analyst usefulness [56], [57], report essentially none of the six; the two that engage explanation quality directly are the evaluation and systematization works [17], [18]. In short, the properties whose failure we document are, in current practice, almost never checked, so the failures go unnoticed and the trust claims stand unchallenged.

X. DISCUSSION

Accountability. Operational security increasingly places explanations in the decision loop and, implicitly, in the accountability chain: an analyst who acts "because the system showed feature X" is relying on e. Our results imply this reliance is, today, reliance on an artifact of tool and seed. Accountability regimes that credit "the model is explainable" as a control are mis-specified unless the explanation meets conditions like ours; and, as our negative result shows, one cannot yet discharge that condition with a cheap per-alarm reliability score.

Why recovering trust is hard. A tempting fix is to score, per flow, how much to trust an explanation. Our negative result (Section VIII) shows why the natural version does not work: stability is measurable but partly tautological with its own predictors and does not transfer across deployments, and stability is not faithfulness in any case. A useful gate would have to predict *faithfulness* and generalize, which post-hoc attributions on expressive models may not permit. Selective trust is the right idea; a sound mechanism for it is unsolved.

Scope. The *inference* from interpretability to trust is unlicensed until the properties are checked, and on modern data the check fails by default; this is not specific to the particular methods we test. We report the adversarial manipulation result as inconclusive and the reliability gate as a negative result.

Threats to validity. *Attribution scope*: we study five gradient- and perturbation-family attributions and tree/logistic/KAN surrogates; prototype-, concept-, and rule-based methods [9] may behave differently, which is exactly what our criteria ask authors to check, but the fidelity, faithfulness, and cross-family determinacy failures are method-diverse enough that a single better method is unlikely to rescue trust. *Analyst model*: the analyst is a classifier, not a human; a real analyst uses context beyond the attribution vector and would be swayed less by it, so our simulated divergence is an *upper bound* on a real analyst's explanation-induced divergence, and a human study is essential future work before any operational claim. *Detector scope*: beyond the MLP and KAN detectors, we re-ran determinacy, groundedness, and faithfulness on the tree ensembles that dominate tabular NIDS, random forests and gradient boosting explained by *exact, deterministic* TreeSHAP (Table VII); determinacy and groundedness still fail in the same range, so the result is not an artifact of neural detectors or of Monte-Carlo explainers. A convolutional or transformer NIDS remains future work. *Dataset difficulty, discounted uniformly*: three of the five detectors are effectively saturated (5G-NIDD F_1=1.00, CIC-IoT-2023 and TON-IoT 0.99). We had discounted only CIC-IoT-2023's faithfulness on that ground; the discount is owed wherever saturation can drive a score, so all three should be read as consistent rather than confirming, and the security-harm result rests on CICIDS2017 and TON-IoT — two corpora, not five. *Statistical power*: we report three-seed statistics and, for the gate, expose its true run-to-run instability rather than an over-tight interval. None of these points toward a hidden way that interpretability *does* warrant trust; they bound where our specific numbers apply.

XI. CONCLUSION

Explainable ML-IDS invites analysts to trust detectors through their explanations. We asked what would make that trust well-founded, formalized it as fidelity, determinacy, and groundedness, and showed, on five modern intrusion datasets, that fidelity fails for the interpretable-surrogate route and that determinacy and groundedness fail across five standard explainers including SHAP and LIME. We showed the failure can carry a security cost, measured against its own floor: a simulated analyst calibrated on the deployed model dismisses 0.018 of correctly-detected true attacks on CICIDS2017, and 0.433 of the same attacks when an equally accurate sibling is deployed instead — most of the way to the 0.505 obtained from signal-free attributions (an upper bound), and near-zero on the easiest corpus. The raw action-divergence rate does not exceed its permutation null on any of ten dataset–auditor pairs (Table XI), so we withdraw it: quoting disagreement without a floor is the practice this paper argues against. We then mapped how hard the failure is to fix, reporting two honest negatives, an explanation-manipulation attack that does not transfer to tabular IDS, and a natural reliability gate that is circular, non-transferable, and adversarially gameable. Interpretability, as currently produced and evaluated, is not a sound basis for trust in ML-IDS, and recovering that basis is an open problem.

APPENDIX A
FULL PAIRWISE EXPLANATION AGREEMENT

Table XIV gives the complete top-5 Jaccard agreement for all ten pairs of the five explainers, at the high sampling budgets used throughout (KernelSHAP 1000 samples, LIME 3000). The two variants within the gradient family that share the input×gradient construction (input×gradient vs. integrated gradients) are the only consistently high pair (0.63–0.83); every cross-family pair is low. This is why we anchor the determinacy claim on cross-family disagreement (e.g. gradient vs. SHAP, 0.17–0.33) rather than on the noisier SHAP-vs-LIME comparison: at low sampling budgets SHAP and LIME are not even self-consistent (rerun agreement ≈ 0.43), so part of their mutual disagreement is Monte-Carlo noise, whereas the cross-family gap persists at any budget.

TABLE XIV
TOP-5 JACCARD AGREEMENT FOR ALL EXPLAINER PAIRS (HIGH SAMPLING BUDGET). G=GRADIENT, I=INPUT×GRAD, IG=INTEGRATED GRAD, S=SHAP, L=LIME.

Pair	UNSW	CICIDS	5G	TON	CIC23
g/i	0.36	0.22	0.51	0.30	0.39
g/ig	0.34	0.20	0.51	0.26	0.42
g/s	0.24	0.17	0.31	0.26	0.33
g/l	0.20	0.24	0.50	0.21	0.37
i/ig	0.75	0.78	0.82	0.63	0.83
i/s	0.41	0.55	0.50	0.49	0.21
i/l	0.19	0.20	0.49	0.15	0.22
ig/s	0.40	0.58	0.51	0.51	0.24
ig/l	0.18	0.20	0.50	0.21	0.25
s/l	0.37	0.25	0.36	0.18	0.31

APPENDIX B
REPRODUCIBILITY

We release the complete artifact, the five datasets' preprocessing, every experiment script, and the figure and table generators, so each quantitative claim in the paper can be regenerated from raw data. The anonymized artifact is at https://anonymous.4open.science/r/xai-ids-trust-2826; a permanent, DOI-archived mirror will replace it in the camera-ready. Table XV maps every result to the script that produces it and the file it writes, and each number in the paper is injected at compile time from a one-value-per-file store (`paper/claims/`), so no figure in the text is transcribed by hand.

Environment. Python 3.9.6 with `numpy` 2.0.2, `scipy` 1.13.1, `scikit-learn` 1.6.1, `torch` 2.8.0, `shap` 0.49.1, and `lime` 0.2.0.1, all pinned in `requirements.txt`. Every experiment fixes the `numpy` and `torch` seeds before loading data, so a re-run reproduces the reported numbers exactly; we verified determinism by double-run comparison.

Data. All five datasets are public: UNSW-NB15 [49], the cleaned CICIDS2017 [50], [51], 5G-NIDD [52], TON-IoT [53], and CIC-IoT-2023 [54] (Table III). `data.py` applies the identical pipeline to each: binary normal-versus-attack labels, categorical encoding, standardization, a 40k stratified subsample, and a 70/30 stratified split, dropping identifier columns (IP addresses, ports, timestamps) so an attribution is a claim about behaviour, not host identity.

Running it. After `pip install -r requirements.txt`, running `python <script>.py` for any row of Table XV regenerates that file, and `python plots.py` rebuilds every figure. The full suite completes in well under an hour on a commodity CPU; no GPU is required.

APPENDIX C
ETHICS CONSIDERATIONS

This work studies public network-intrusion datasets (UNSW-NB15, CICIDS2017, 5G-NIDD, TON-IoT, CIC-IoT-2023) and introduces no new data collection or human-subjects experiment; the analyst in our study is modeled by a classifier, not a person, so no IRB approval was required. The paper is a defensive contribution: it warns that a widely promoted security workflow, trusting ML-IDS through explanations, may be unfounded, and offers a mechanism to mitigate the risk. Our inconclusive attack is described at a level sufficient to reproduce the analysis but does not provide an operational tool for evading detectors, and the underlying benign failures are the primary basis of our conclusions. We release code, the data-preparation scripts, and the evaluation criteria to help the community audit interpretability-for-trust claims, which we judge net-beneficial: the same code that could reveal a weak explanation is what a defender needs to avoid over-trusting one. The artifact is available at https://anonymous.4open.science/r/xai-ids-trust-2826 (anonymized for review; a non-anonymous mirror will replace it in the camera-ready). We disclose no specific vulnerable product; the concern is a methodological one affecting the class of explainable ML-IDS.

Use of generative AI. Per the submission policy we disclose that generative AI assistants were used while preparing this work, in two roles: editing and condensing prose, and writing auxiliary tooling (the reference-verification and number-tracing scripts that check the manuscript against the released CSVs). They were not used to generate experimental results, and every number reported here is produced by the released code and mechanically checked back to a result file. The authors take full responsibility for all claims, results and citations.

REFERENCES

[1] N. Capuano, G. Fenza, V. Loia, and C. Stanzione, "Explainable artificial intelligence in CyberSecurity: A survey," *IEEE Access*, vol. 10, pp. 93 575–93 600, 2022.

[2] M. T. Ribeiro, S. Singh, and C. Guestrin, ""why should i trust you?": Explaining the predictions of any classifier," in *ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining (KDD)*, 2016.

[3] M. Sundararajan, A. Taly, and Q. Yan, "Axiomatic attribution for deep networks," in *International Conference on Machine Learning (ICML)*, 2017.

[4] K. Simonyan, A. Vedaldi, and A. Zisserman, "Deep inside convolutional networks: Visualising image classification models and saliency maps," *arXiv preprint arXiv:1312.6034*, 2013.

TABLE XV

EVERY RESULT MAPS TO THE SCRIPT THAT PRODUCES IT AND THE OUTPUT FILE IT WRITES. NUMBERS IN THE PAPER ARE INJECTED FROM `PAPER/CLAIMS/`, ONE VALUE PER FILE. SCRIPT AND FILE NAMES OMIT THE `.PY` AND `.CSV` SUFFIXES.

Result	Script(s)	Output
P1–P3 (Tab. IV, Fig. 2)	`exp_trust`, `exp_multiseed`	`trust`, `multiseed`
Fidelity frontier (Tab. V, Fig. 3)	`exp_fidelity_multi`	`fidelity_multi`
Determinacy, 5 explainers (Fig. 4, Tab. XIV)	`exp_breadth`	`breadth`
Redundancy robustness (Tab. VIII)	`exp_redundancy`	`redundancy`
k/ensemble robustness (Fig. 5)	`exp_ablate_p2p3`	`ablate_p2k`, `ablate_p3E`
Positive control (Tab. VI)	`exp_ceiling`	`ceiling`
Tree ensembles (Tab. VII)	`exp_tree`	`tree`
Faithfulness (Tab. X, IX)	`exp_faithfulness`, `exp_faith_5explainer`	`faithfulness`, `faith_5explainer`
Security harm (Tab. XI, Fig. 7, 6)	`exp_harm`, `exp_harm_bytype`	`harm`, `harm_bytype`
Reliability gate, ablation, transfer (Tab. XII, Fig. 9)	`exp_defense`, `_ablate`, `_transfer`, `_gate_attack`	`defense`, `defense_ablate`, `defense_transfer`, `gate_attack`
Manipulation attack (non-transfer)	`exp_attack`	`attack`
Field audit (Tab. XIII)	`field_audit`	`field_audit`

[5] D. Smilkov, N. Thorat, B. Kim, F. Viégas, and M. Wattenberg, "SmoothGrad: Removing noise by adding noise," *arXiv preprint arXiv:1706.03825*, 2017.

[6] A. Shrikumar, P. Greenside, and A. Kundaje, "Learning important features through propagating activation differences," in *International Conference on Machine Learning (ICML)*, 2017.

[7] S. Bach, A. Binder, G. Montavon, F. Klauschen, K.-R. Müller, and W. Samek, "On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation," *PLOS ONE*, vol. 10, no. 7, p. e0130140, 2015.

[8] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[9] M. T. Ribeiro, S. Singh, and C. Guestrin, "Anchors: High-precision model-agnostic explanations," in *AAAI Conference on Artificial Intelligence*, 2018.

[10] R. R. Selvaraju, M. Cogswell, A. Das, R. Vedantam, D. Parikh, and D. Batra, "Grad-CAM: Visual explanations from deep networks via gradient-based localization," in *IEEE International Conference on Computer Vision (ICCV)*, 2017.

[11] C. Molnar, "Interpretable machine learning: A guide for making black box models explainable," 2022, 2nd ed.

[12] R. Sommer and V. Paxson, "Outside the closed world: On using machine learning for network intrusion detection," in *IEEE Symposium on Security and Privacy (S&P)*, 2010, pp. 305–316.

[13] D. Arp, E. Quiring, F. Pendlebury, A. Warnecke, F. Pierazzi, C. Wressnegger, L. Cavallaro, and K. Rieck, "Dos and don'ts of machine learning in computer security," in *USENIX Security Symposium*, 2022.

[14] S. Axelsson, "The base-rate fallacy and the difficulty of intrusion detection," in *ACM Transactions on Information and System Security (TISSEC)*, vol. 3, no. 3, 2000, pp. 186–205.

[15] G. Apruzzese, P. Laskov, E. Montes de Oca, W. Mallouli, L. Brdalo Rapa, A. V. Grammatopoulos, and F. Di Franco, "The role of machine learning in cybersecurity," *Digital Threats: Research and Practice*, vol. 4, no. 1, pp. 1–38, 2023.

[16] S. Mahdavifar and A. A. Ghorbani, "Application of deep learning to cybersecurity: A survey," in *Neurocomputing*, vol. 347, 2019, pp. 149–176.

[17] A. Warnecke, D. Arp, C. Wressnegger, and K. Rieck, "Evaluating explanation methods for deep learning in security," in *IEEE European Symposium on Security and Privacy (EuroS&P)*, 2020.

[18] A. Nadeem, D. Vos, C. Cao, L. Pajola, S. Dieck, R. Baumgartner, and S. Verwer, "SoK: Explainable machine learning for computer security applications," in *IEEE European Symposium on Security and Privacy (EuroS&P)*, 2023.

[19] T. Ganz, M. Härterich, A. Warnecke, and K. Rieck, "Explaining graph neural networks for vulnerability discovery," in *ACM Workshop on Artificial Intelligence and Security (AISec)*, 2021.

[20] O. Arreche, T. R. Guntur, J. W. Roberts, and M. Abdallah, "E-XAI: Evaluating black-box explainable AI frameworks for network intrusion detection," *IEEE Access*, vol. 12, pp. 23 954–23 988, 2024.

[21] S. Neupane, J. Ables, W. Anderson, S. Mittal, S. Rahimi, I. Banicescu, and M. Seale, "Explainable intrusion detection systems (X-IDS): A survey of current methods, challenges, and opportunities," *IEEE Access*, vol. 10, pp. 112 392–112 415, 2022.

[22] M. Nyre-Yu, E. Morris, M. Smith, B. Moss, and C. Smutz, "Explainable AI in cybersecurity operations: Lessons learned from xAI tool deployment," in *Symposium on Usable Security and Privacy (USEC)*, 2022.

[23] T. D. Le, M. Arifuzzaman, and Y. Bao, "TRACE: Feature-space feasible action contracts for explainable intrusion triage," *Electronics*, vol. 15, no. 15, p. 3291, 2026.

[24] A. Ghorbani, A. Abid, and J. Zou, "Interpretation of neural networks is fragile," in *AAAI Conference on Artificial Intelligence*, 2019.

[25] A.-K. Dombrowski, M. Alber, C. J. Anders, M. Ackermann, K.-R. Müller, and P. Kessel, "Explanations can be manipulated and geometry is to blame," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[26] D. Slack, S. Hilgard, E. Jia, S. Singh, and H. Lakkaraju, "Fooling lime and shap: Adversarial attacks on post hoc explanation methods," in *AAAI/ACM Conference on AI, Ethics, and Society (AIES)*, 2020.

[27] T. Senevirathna, B. Siniarski, M. Liyanage, and S. Wang, "Deceiving post-hoc explainable AI (XAI) methods in network intrusion detection," in *IEEE Consumer Communications and Networking Conference (CCNC)*, 2024.

[28] J. Adebayo, J. Gilmer, M. Muelly, I. Goodfellow, M. Hardt, and B. Kim, "Sanity checks for saliency maps," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

[29] P.-J. Kindermans, S. Hooker, J. Adebayo, M. Alber, K. T. Schütt, S. Dähne, D. Erhan, and B. Kim, "The (un)reliability of saliency methods," in *Explainable AI: Interpreting, Explaining and Visualizing Deep Learning*. Springer, 2019.

[30] D. Alvarez-Melis and T. S. Jaakkola, "On the robustness of interpretability methods," in *ICML Workshop on Human Interpretability in Machine Learning (WHI)*, 2018.

[31] S. Krishna, T. Han, A. Gu, J. Pombra, S. Jabbari, S. Wu, and H. Lakkaraju, "The disagreement problem in explainable machine learning: A practitioner's perspective," *Transactions on Machine Learning Research*, 2024, preprint arXiv:2202.01602 (2022).

[32] S. Hooker, D. Erhan, P.-J. Kindermans, and B. Kim, "A benchmark for interpretability methods in deep neural networks," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[33] L. Breiman, "Statistical modeling: The two cultures," *Statistical Science*, vol. 16, no. 3, pp. 199–231, 2001.

[34] A. Fisher, C. Rudin, and F. Dominici, "All models are wrong, but many are useful: Learning a variable's importance by studying an entire class

of prediction models simultaneously," *Journal of Machine Learning Research*, vol. 20, no. 177, pp. 1–81, 2019.

[35] C. T. Marx, F. d. P. Calmon, and B. Ustun, "Predictive multiplicity in classification," in *International Conference on Machine Learning (ICML)*, 2020.

[36] E. Black, M. Raghavan, and S. Barocas, "Model multiplicity: Opportunities, concerns, and solutions," in *ACM Conference on Fairness, Accountability, and Transparency (FAccT)*, 2022.

[37] C. Rudin, "Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead," *Nature Machine Intelligence*, vol. 1, no. 5, pp. 206–215, 2019.

[38] Z. C. Lipton, "The mythos of model interpretability," *Communications of the ACM*, vol. 61, no. 10, pp. 36–43, 2018.

[39] F. Doshi-Velez and B. Kim, "Towards a rigorous science of interpretable machine learning," *arXiv preprint arXiv:1702.08608*, 2017.

[40] T. Miller, "Explanation in artificial intelligence: Insights from the social sciences," *Artificial Intelligence*, vol. 267, pp. 1–38, 2019.

[41] A. Jacovi, A. Marasović, T. Miller, and Y. Goldberg, "Formalizing trust in artificial intelligence: Prerequisites, causes and goals of human trust in ai," in *ACM Conference on Fairness, Accountability, and Transparency (FAccT)*, 2021.

[42] L. Kästner, M. Langer, V. Lazar, A. Schomäcker, T. Speith, and S. Sterz, "On the relation of trust and explainability: Why to engineer for trustworthiness," *arXiv preprint arXiv:2108.05379*, 2021.

[43] Z. Liu, Y. Wang, S. Vaidya, F. Ruehle, J. Halverson, M. Soljačić, T. Y. Hou, and M. Tegmark, "KAN: Kolmogorov-arnold networks," *arXiv preprint arXiv:2404.19756*, 2024.

[44] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus, "Intriguing properties of neural networks," in *International Conference on Learning Representations (ICLR)*, 2014.

[45] B. Biggio and F. Roli, "Wild patterns: Ten years after the rise of adversarial machine learning," *Pattern Recognition*, vol. 84, pp. 317–331, 2018.

[46] N. Carlini and D. Wagner, "Towards evaluating the robustness of neural networks," in *IEEE Symposium on Security and Privacy (S&P)*, 2017.

[47] G. Apruzzese, M. Andreolini, L. Ferretti, M. Marchetti, and M. Colajanni, "Modeling realistic adversarial attacks against network intrusion detection systems," in *Digital Threats: Research and Practice*, vol. 3, no. 3, 2022.

[48] A. Ghorbani, J. Wexler, J. Zou, and B. Kim, "Towards automatic concept-based explanations," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[49] N. Moustafa and J. Slay, "UNSW-NB15: A comprehensive data set for network intrusion detection systems," in *Military Communications and Information Systems Conference (MilCIS)*, 2015.

[50] I. Sharafaldin, A. Habibi Lashkari, and A. A. Ghorbani, "Toward generating a new intrusion detection dataset and intrusion traffic characterization," in *International Conference on Information Systems Security and Privacy (ICISSP)*, 2018.

[51] G. Engelen, V. Rimmer, and W. Joosen, "Troubleshooting an intrusion detection dataset: The cicids2017 case study," in *IEEE Security and Privacy Workshops (SPW)*, 2021.

[52] S. Samarakoon, Y. Siriwardhana, P. Porambage, M. Liyanage, S.-Y. Chang, J. Kim, J. Kim, and M. Ylianttila, "5G-NIDD: A comprehensive network intrusion detection dataset generated over a 5g wireless network," in *arXiv preprint arXiv:2212.01298*, 2022.

[53] A. Alsaedi, N. Moustafa, Z. Tari, A. Mahmood, and A. Anwar, "TON_IoT telemetry dataset: A new generation dataset of IoT and IIoT for data-driven intrusion detection systems," *IEEE Access*, vol. 8, pp. 165 130–165 150, 2020.

[54] E. C. P. Neto, S. Dadkhah, R. Ferreira, A. Zohourian, R. Lu, and A. A. Ghorbani, "CICIoT2023: A real-time dataset and benchmark for large-scale attacks in IoT environment," *Sensors*, vol. 23, no. 13, p. 5941, 2023.

[55] A. E. Muhammad, K.-C. Yow, N. Bacanin-Dzakula, and M. A. Khan, "L-XAIDS: A LIME-based explainable ai framework for intrusion detection systems," *Cluster Computing*, 2025.

[56] Y. A. Farrukh, S. Wali, I. Khan, and N. D. Bastian, "XG-NID: Dual-modality network intrusion detection using a heterogeneous graph neural network and large language model," *Expert Systems with Applications*, vol. 287, p. 128089, 2025.

[57] F. Uccello and S. Nadjm-Tehrani, "Feature attribution in 5G intrusion detection: A statistical vs. logic-based comparison," *Journal of Information Security and Applications*, vol. 99, p. 104448, 2026.

[58] P. Barnard, N. Marchetti, and L. A. DaSilva, "Robust network intrusion detection through explainable artificial intelligence (XAI)," *IEEE Networking Letters*, vol. 4, no. 3, pp. 167–171, 2022.

[59] K. P. Sharma, T. Nagpal, T. Vora, A. Yadav, M. I. Abdullah, B. Jayaprakash, A. Kashyap, G. Sridevi, A. Bhowmik, and B. B. Bukate, "Interpretable intrusion detection for IoT environments using a self-attention-based explainable AI framework," *Scientific Reports*, vol. 15, no. 1, p. 39937, 2025.

[60] V. Z. Mohale and I. C. Obagbuwa, "Evaluating machine learning-based intrusion detection systems with explainable AI: Enhancing transparency and interpretability," *Frontiers in Computer Science*, vol. 7, p. 1520741, 2025.

[61] J. Dong, H. Chen, S. Shen, H. Xu, and Z. Liu, "Interpretable intrusion detection for IoT security: A SHAP-enhanced NGBoost model," *Computer Networks*, vol. 275, p. 111937, 2026.

[62] R. Faqihi, P. Nanda, M. Mohanty, S. Alqahtani, and B. Alrashed, "Towards trustworthy cybersecurity: Reclassifying insider threat detection using SHAP," *Future Generation Computer Systems*, vol. 183, p. 108543, 2026.