

XLNet: Generalized Autoregressive Pretraining for Language Understanding

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Ruslan Salakhutdinov, Quoc V. Le
Carnegie Mellon University, Google Brain


Presented by
Junho Lee, AI LAB Kor
saitros2@gmail.com

소개

이번 강의는 한국 인공지능 연구소 C' est La Vie 랩에서
최근 발표된 XLNet paper를 이해할 수 있도록 공부한
내용을 기반으로 합니다.

다루는 내용은 XLNet의 Core Idea 를 기준으로 합니다.

별다른 출처가 표시되어있지 않은 그림 및 자료는
원문 <https://arxiv.org/pdf/1906.08237.pdf> 을 참고하였습니다.




영화 자막 PCA(2D)




영화 자막 SOM (10x10)

소개



영화 시나리오 PCA(2D)



영화 시나리오 SOM(50x50)

Overview

- **NLP Trends**
- **Autoregressive vs Autoencoding**
- **XLNet**
 - **Permutation Language model**
 - **Two-stream self-attention mechanism**
 - **Recurrence mechanism**

Overview

- **NLP Trends**
- **Autoregressive vs Autoencoding**
- **XLNet**
 - **Permutation Language model**
 - **Two-stream self-attention mechanism**
 - **Recurrence mechanism**

2018 NLP



SESAME STREET



ELMo
2018년 3월



BERT
2018년 10월



BigBird
2018년 12월



ELMo

- 풀 네임 : **E**MBEDDINGS FROM **L**ANGUAGE **M**ODELS
- 등 장 : 2018년 3월
- 특 징 :
 1. Context 정보를 반영하는 방법 제시
 2. 같은 성과를 위한 필요 데이터를 감소
 3. 추가적인 성능 향상

TASK	PREVIOUS SOTA		OUR BASELINE	ELMo + BASELINE	INCREASE (ABSOLUTE/ RELATIVE)
SQuAD	Liu et al. (2017)	84.4	81.1	85.8	4.7 / 24.9%
SNLI	Chen et al. (2017)	88.6	88.0	88.7 ± 0.17	0.7 / 5.8%
SRL	He et al. (2017)	81.7	81.4	84.6	3.2 / 17.2%
Coref	Lee et al. (2017)	67.2	67.2	70.4	3.2 / 9.8%
NER	Peters et al. (2017)	91.93 ± 0.19	90.15	92.22 ± 0.10	2.06 / 21%
SST-5	McCann et al. (2017)	53.7	51.4	54.7 ± 0.5	3.3 / 6.8%

SQuAD : Q&A

SNLI(Textual entailment) : 두 문장 간의 상관 관계를 판별

Semantic Role Labeling : 행위주, 피동작주, 원인, 목적, 시제 등을 판별

Coreference resolution : 같은 개체를 의미하는 것을 묶는 과제

Named Entity Recognition : 개체명 인식, 인물, 날짜, 동물, 의학 용어 등

SST-5 : 감정 분석



BERT

- 풀 네임 : **B**idirectional **E**ncoder
Representations from **T**ransformers
- 등 장 : 2018년 10월
- 특 징 :
 1. 11월에 pretrain data를 오픈소스로 공개
 2. 가장 치열한 분야인 SQuAD에서 1위 등극
 3. 무려 11개 NLP Task에서 SOTA 달성
 4. BERT를 활용한 모델이 계속 등장
(Bert for multi-label classification,
Bert for History Answer Embedding,
Bert for Re-Rank 등등...)

2018 NLP

Rank	Model	EM	F1
	Human Performance <i>Stanford University</i> (Rajpurkar & Jia et al. '18)	86.831	89.452
1 Mar 20, 2019	BERT + DAE + AoA (ensemble) <i>Joint Laboratory of HIT and iFLYTEK Research</i>	87.147	89.474
2 Mar 15, 2019	BERT + ConvLSTM + MTL + Verifier (ensemble) <i>Layer 6 AI</i>	86.730	89.286
3 Mar 05, 2019	BERT + N-Gram Masking + Synthetic Self- Training (ensemble) <i>Google AI Language</i> https://github.com/google-research/bert	86.673	89.147
4 May 21, 2019	XLNet (single model) <i>Google Brain & CMU</i>	86.346	89.133
5 Apr 13, 2019	SemBERT(ensemble) <i>Shanghai Jiao Tong University</i>	86.166	88.886

2018 NLP

- 기존 BERT Embedding에 HAE 추가
- HAE 가 기존 BERT의 token 정보를 수정
BERT가 대화의 history를 자연스럽게 수용
- Fine tuning을 통해서 specific 하게 학습을 진행
- 논문은 Bert-Base (Uncased) model이 사용
max sequence length set 384
batch size set 12
learning rate set 3e-5
stride set 128
max question length set 64
max answer length set 30

Table 1: A part of an information-seeking dialog from QuAC.
“R”, “U”, and “A” denotes role, user, and agent respectively.

Topic: Augusto Pinochet: Intellectual life

#	ID	R	Utterance
1	Q ₁	U	Was he known for being intelligent
	A ₁	A	No, Pinochet was publicly known as a man with a lack of culture.
2	Q ₂	U	Why did people feel that way?
	A ₂	A	reinforced by the fact that he also portrayed himself as a common man




Figure 2: Architecture of the ConvQA model with HAE.
 E_H/E_N in HAE denote the token is in/not in history answers.

2018 NLP

- 기존 BERT Embedding에 HAE 추가
- HAE 가 기존 BERT의 token 정보를 수정
BERT가 대치한 history를 지전스럽게 수정
- Fine tuning을 통해서 specific 하게 학습을 진행
- 논문은 Bert-Base (Uncased) model이 사용
max sequence length set 384
batch size set 12
learning rate set $3e-5$
stride set 128
max question length set 64
max answer length set 30

Table 1: A part of an information-seeking dialog from QuAC. "Q", "U", and "A" denotes role, user, and agent respectively.

Topic: Augustus Pausanias Intellectual life		
Q	U	A
1	Q	U
2	A	A
3	Q	U
4	A	A





Figure 2: Architecture of the ConvQA model with HAE. E_H/E_N in HAE denote the token is in/not in history answers.

The New York Times

TECHNOLOGY | Finally, a Machine That Can Finish Your Sentence

Finally, a Machine That Can Finish Your Sentence



Completing someone else's thought is not an easy trick for A.I.
But new systems are starting to crack the code of natural
language.










Big Bird

- 실명 : MT-DNN
- 등장 : 2018년 12월
- 특징 :
 1. 논문은 19년도 1월에 공개
 2. Elmo 와 BERT를 의식한 이름 선정
 3. 학습데이터가 적은 상황에서 좋은 성능



Rank	Name	Model	URL	Score
1	bigbird he	Microsoft D365 AI & MSR AI		81.9
+	2	Jacob Devlin	BERT: 24-layers, 1024-hidden, 16-heads 	80.4
	3	Jason Phang	GPT on STILTs 	76.9
	4	Alec Radford	Singletask Pretrain Transformer 	72.8
+	5	Samuel Bowman	BiLSTM+ELMo+Attn 	70.5
	6	GLUE Baselines	BiLSTM+ELMo+Attn 	68.9

GLUE Benchmark, 2018.12.27

Multi-Task Deep Neural Networks for Natural Language Understanding

Xiaodong Liu, Pengcheng He, Weizhu Chen, Jianfeng Gao

(Submitted on 31 Jan 2019 (v1), last revised 30 May 2019 (this version, v2))

GLUE dataset

CoLA	SST-2	MRPC	STS-B	QQP	MNLI-m	MNLI-mm	QNLI	RTE	WNLI	AX
------	-------	------	-------	-----	--------	---------	------	-----	------	----

CoLA : The Corpus of Linguistic Acceptability (언어 적합성 판단 - 문법)

Corpus Sample

```
clc95  0 * In which way is Sandy very anxious to see if the students will be able to solve
          the homework problem?
c-05   1  The book was written by John.
c-05   0 * Books were sent to each other by the students.
swb04  1  She voted for herself.
swb04  1  I saw that gas can explode.
```

SST-2 : Stanford Sentiment Treebank (binary label classification problem)

-1 : (multi label classification problem)

MRPC : Microsoft Research Paraphrase Corpus (문장의 sentiment 가 같은지 판단)

STS-B : Semantic Textual Similarity Benchmark(문장의 유사도를 점수로 판단)

QQP : Quora Question Pair(두 질문이 같은 의미인지 파악)

SQuAD : Stanford Question Answering Database (질문을 보고 지문에서 정답 구간을 찾아낸다)

Unsupervised Learning




2018년 1월

1 GPU days

fast.ai

Making neural nets
uncool again



GPT

2018년 6월

240 GPU days



BERT

2018년 10월

256 TPU days
320~560 GPU days



OpenAI
Transformer

GPT-2

2019년 2월

2048 TPU days



Large Batch

Table 1: We use the F1 score on SQuAD-v1 as the accuracy metric. The baseline F1 score is the score obtained by the pre-trained model (BERT-Large) provided on BERT’s public repository (as of February 1st, 2019). We use TPUv3s in our experiments. We use the same setting as the baseline: the first 9/10 of the total epochs used a sequence length of 128 and the last 1/10 of the total epochs used a sequence length of 512. All the experiments run the same number of epochs. Dev set means the test data. It is worth noting that we can achieve better results by manually tuning the hyperparameters.

Solver	batch size	steps	F1 score on dev set	TPUs	Time
Baseline	512	1000k	90.395	16	81.4h
LAMB	512	1000k	91.752	16	82.8h
LAMB	1k	500k	91.761	32	43.2h
LAMB	2k	250k	91.946	64	21.4h
LAMB	4k	125k	91.137	128	693.6m
LAMB	8k	62500	91.263	256	390.5m
LAMB	16k	31250	91.345	512	200.0m
LAMB	32k	15625	91.475	1024	101.2m
LAMB	64k/32k	8599	90.584	1024	76.19m

Table 2: ADAMW stops scaling at the batch size of 16K. The target F1 score is 90.5. LAMB achieves a F1 score of 91.345.

Solver	batch size	warmup steps	LR	last step information	F1 score on dev set
ADAMW	16K	0.05×31250	0.0001	loss=8.04471, step=28126	diverged
ADAMW	16K	0.05×31250	0.0002	loss=7.89673, step=28126	diverged
ADAMW	16K	0.05×31250	0.0003	loss=8.35102, step=28126	diverged
ADAMW	16K	0.10×31250	0.0001	loss=2.01419, step=31250	86.034
ADAMW	16K	0.10×31250	0.0002	loss=1.04689, step=31250	88.540
ADAMW	16K	0.10×31250	0.0003	loss=8.05845, step=20000	diverged
ADAMW	16K	0.20×31250	0.0001	loss=1.53706, step=31250	85.231
ADAMW	16K	0.20×31250	0.0002	loss=1.15500, step=31250	88.110
ADAMW	16K	0.20×31250	0.0003	loss=1.48798, step=31250	85.653

Overview

- NLP Trends
- **Autoregressive vs Autoencoding**
- XLNet
 - Permutation Language model
 - Two-stream self-attention mechanism
 - Recurrence mechanism

Autoregressive language model (AR)

- 일반적인 Language Model의 학습방법
- 이전 token을 보고 다음 token을 예상 하는 방식
- 주어진 문장 $X = [x_1, x_2, \dots, x_T]$ 일때

정방향 AR 모델

$$\max_{\theta} \log p_{\theta}(X) = \sum_{t=1}^T \log p_{\theta}(x_t | x_{<t})$$

- AR 모델은 방향성(forward, backward)
- 한쪽 방향의 정보만 이용 가능
- 양방향성(bi-directional) 모델도 각 방향에 대해 독립적인 학습

Autoregressive Language Model

$[x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8]$

$[x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8]$





Figure 1: The Transformer - model architecture

Autoencoding language model (AE)

- 주어진 문장을 훼손시키고 복원시키는 방식
- [MASK] 토큰을 맞추기 위해 양방향 정보를 이용
- 오토인코더 모델은 [MASK] 토큰에 대해서만 예측을 진행

- 훼손시킨 문장(\hat{X}), 훼손된 token(\bar{X}) 이라 할 때 AE모델 수식은 다음과 같다.

$$\max_{\theta} \log p_{\theta}(\bar{X} | \hat{X}) \approx \sum_{t=1}^T m_t \log p_{\theta}(x_t | \hat{X})$$

- Token이 [MASK] 일때 $m_t = 1$, 나머지 경우에는 $m_t = 0$
- [MASK] token 에 대해서 prediction을 진행

Autoencoding Language Model

[$x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8$]

[$x_1, x_2, \blacksquare, x_4, x_5, x_6, x_7, x_8$]


[$x_1, x_2, \blacksquare, x_4, x_5, x_6, x_7, x_8$]

autoencoding

Overview

- NLP Trends
- Autoregressive vs Autoencoding
- **XLNet**
 - Permutation Language model
 - Two-stream self-attention mechanism
 - Recurrence mechanism

Hello, XLNet!



Experiments

- **Pretraining Datasets**

- BERT : BookCorpus + English Wikipedia

(총: 33억 token)

- XLNet : BookCorpus + English Wikipedia + Giga5 + ClueWeb 2012-B + Common Crawl

(2.78B)

(1.09B)

(4.75B)

(4.30B)

(19.97B)

(총: 328억 token)

- **Model Size**

- $XLNet - Large \approx BERT - Large$

- **Training Time**

- 512TPU v3 chips for 500K steps with adam optimizer(batch size 2048) → 2.5days







→ 약 245,000\$ (한화 2억 4500만원)

→ Still underfits, 계속된 학습이 NLP task 에 대해서 도움이 되지 않는다고 판단

XLNet is good

XLNet: Generalized Autoregressive Pretraining for Language Understanding

GLUE dataset

	Rank	Name	Model	URL	Score	CoLA	SST-2	MRPC	STS-B	QQP	MNLI-m	MNLI-mm	QNLI	RTE	WNLI	AX
+	1	XLNet Team	XLNet-Large (ensemble)		88.4	67.8	96.8	93.0/90.7	91.6/91.1	74.2/90.3	90.2	89.8	98.6	86.3	90.4	47.5
	2	Microsoft D365 AI & MSR AI	MT-DNN-ensemble		87.6	68.4	96.5	92.7/90.3	91.1/90.7	73.7/89.9	87.9	87.4	96.0	86.3	89.0	42.8
	3	GLUE Human Baselines	GLUE Human Baselines		87.1	66.4	97.8	86.3/80.8	92.7/92.6	59.5/80.4	92.0	92.8	91.2	93.6	95.9	-
+	4	王玮	ALICE large ensemble (Alibaba DAMO NLP)		86.3	68.6	95.2	92.6/90.2	91.1/90.6	74.4/90.7	88.2	87.9	95.7	83.5	80.8	43.9
	5	Stanford Hazy Research	Snorkel MeTaL		83.2	63.8	96.2	91.5/88.5	90.1/89.7	73.1/89.9	87.6	87.2	93.9	80.9	65.1	39.9
	6	XLM Systems	XLM (English only)		83.1	62.9	95.6	90.7/87.1	88.8/88.2	73.2/89.8	89.1	88.5	94.0	76.0	71.9	44.7
	7	张倬胜	SemBERT		82.9	62.3	94.6	91.2/88.3	87.8/86.7	72.8/89.8	87.6	86.3	94.6	84.5	65.1	42.4

XLNet is good good

SQuAD1.1	EM	F1	SQuAD2.0	EM	F1
<i>Dev set results without data augmentation</i>					
BERT [10]	84.1	90.9	BERT† [10]	78.98	81.77
XLNet	88.95	94.52	XLNet	86.12	88.79
<i>Test set results on leaderboard, with data augmentation (as of June 19, 2019)</i>					
Human [27]	82.30	91.22	BERT+N-Gram+Self-Training [10]	85.15	87.72
ATB	86.94	92.64	SG-Net	85.23	87.93
BERT* [10]	87.43	93.16	BERT+DAE+AoA	85.88	88.62
XLNet	89.90	95.08	XLNet	86.35	89.13

Table 2: A single model XLNet outperforms human and the best ensemble by 7.6 EM and 2.5 EM on SQuAD1.1.

* means ensembles, † marks our runs with the official code.

Model	IMDB	Yelp-2	Yelp-5	DBpedia	AG	Amazon-2	Amazon-5
CNN [14]	-	2.90	32.39	0.84	6.57	3.79	36.24
DPCNN [14]	-	2.64	30.58	0.88	6.87	3.32	34.81
Mixed VAT [30, 20]	4.32	-	-	0.70	4.95	-	-
ULMFiT [13]	4.6	2.16	29.98	0.80	5.01	-	-
BERT [35]	4.51	1.89	29.32	0.64	-	2.63	34.17
XLNet	3.79	1.55	27.80	0.62	4.49	2.40	32.26

Table 3: Comparison with state-of-the-art error rates on the test sets of several text classification datasets. All BERT and XLNet results are obtained with a 24-layer architecture with similar model sizes (aka BERT-Large).

XLNet is good good

RACE	Accuracy	Middle	High
GPT [25]	59.0	62.9	57.4
BERT [22]	72.0	76.6	70.1
BERT+OCN* [28]	73.5	78.4	71.5
BERT+DCMN* [39]	74.1	79.5	71.8
XLNet	81.75	85.45	80.21

Table 1: Comparison with state-of-the-art results on the test set of RACE, a reading comprehension task. * indicates using ensembles. “Middle” and “High” in RACE are two subsets representing middle and high school difficulty levels. All BERT and XLNet results are obtained with a 24-layer architecture with similar model sizes (aka BERT-Large). Our single model outperforms the best ensemble by 7.6 points in accuracy.

#	Model	RACE	SQuAD2.0		MNLI	SST-2
			F1	EM	m/mm	
1	BERT-Base	64.3	76.30	73.66	84.34/84.65	92.78
2	DAE + Transformer-XL	65.03	79.56	76.80	84.88/84.45	92.60
3	XLNet-Base ($K = 7$)	66.05	81.33	78.46	85.84/85.43	92.66
4	XLNet-Base ($K = 6$)	66.66	80.98	78.18	85.63/85.12	93.35
5	- memory	65.55	80.15	77.27	85.32/85.05	92.78
6	- span-based pred	65.95	80.61	77.91	85.49/85.02	93.12
7	- bidirectional data	66.34	80.65	77.87	85.31/84.99	92.66
8	+ next-sent pred	66.76	79.83	76.94	85.32/85.09	92.89

Table 6: Ablation study. The results of BERT on RACE are taken from [39]. We run BERT on the other datasets using the official implementation and the same hyperparameter search space as XLNet. K is a hyperparameter to control the optimization difficulty (see Section 2.3). All models are pretrained on the same data.

XLNet Summary

Generalized Autoregressive Pretraining for Language Understanding

- AR 모델과 AE 모델의 장점을 합친 새로운 Language model
 - ➔ Permutation Language Model (순열 언어 모델)
- Two-stream attention mechanism을 제안
- Recurrence Mechanism

다양한 NLP task에서 뛰어난 성능 향상을 보이며 State-of-the-art 달성

Autoencoding language model (AE) Problem

1. Independence Assumption

무작위로 [MASK]를 손상시키고 복원하는 방식을 위해서

Independence Assumption 을 가정함 → [MASK] token 의 확률을 계산하기 위해서 독립시행으로 구분

각 token을 독립적으로 예측을 하면서 단어 사이의 dependency가 학습되지 않는다

Train sentence(X) : 나는 남산에 가서 남산 케이블카를 봤다

Corrupted version(\hat{X}) : 나는 [MASK] 에 가서 [MASK] [MASK] 를 봤다

Reconstruct : 나는 남산에 가서 남산 케이블카 를 봤다 (O)

나는 음식점에 가서 모집 공고 를 봤다 (O)

나는 남산에 가서 모집 공고 를 봤다 (X)

나는 음식점에 가서 모집 케이블카 를 봤다 (X)

Autoencoding language model (AE) Problem

2. Input noise

AE모델에서는 정상적인 문장을 학습을 위해서 [MASK] token으로 훼손

이후 복원하는 작업을 통해서 context에 대한 정보를 학습함 (Pre-training)

하지만 downstream task를 위해서 fine-tuning시 [MASK] token은 사용되지 않음

→ Pre-training 과 fine-tuning 시 학습방법에 대한 불일치

Overview

- NLP Trends
- Autoregressive vs Autoencoding
- **XLNet**
 - **Permutation Language model**
 - Two-stream self-attention mechanism
 - Recurrence mechanism

Permutation Language Modeling

Input sequence 의 모든 permutation을 고려

$$\text{input sequence} = [x_1, x_2, x_3, x_4]$$

Permutation 집합은 총 $4! = 24$ 개 가 존재

x_3 를 예측하기 위해서 오른쪽 그림과 같은 계산

모든 permutation 에 대해서 이 과정을 반복

→ 양방향에서 정보를 수집

→ bi-directional 한 AR 모델

→ Independent Assumption 필요 X


→ Pre-training 과 fine-tuning 사이의 불일치 X

→ 기존 모델의 단점을 극복


Permutation Language Model

$$[x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8]$$

$$[x_2, x_5, x_1, x_6, x_8, x_3, x_7, x_4]$$



autoregressive



Factorization order: $2 \rightarrow 4 \rightarrow 3 \rightarrow 1$

$$p(x) = p(x_2 | \text{mem})p(x_4 | \text{mem}, x_2)p(x_3 | \text{mem}, x_2, x_4)$$

Permutation Language Modeling

input sequence 와 모든 permutation을 고려

$$\text{input sequence} = [x_1, x_2, x_3, x_4]$$

Permutation 집합은 총 $4! = 24$ 개 가 존재

x_3 를 예측하기 위해서 오른쪽 그림과 같은 계산

모든 permutation 에 대해서 이 과정을 반복

→ 양방향에서 정보를 수집

→ bi-directional 한 AR 모델

→ Independent Assumption 필요 X

→ Pre-training 과 fine-tuning 사이의 불일치 X

→ 기존 모델의 단점을 극복

Permutation Language Model

$$[x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8]$$

$$[x_2, x_5, x_1, x_6, x_8, x_3, x_7, x_4]$$

$$[x_2, x_5, x_1, x_6, x_8, x_3, x_7, x_4]$$

autoregressive



$$p(x) = p(x_2 | \text{mem})p(x_4 | \text{mem}, x_2)p(x_3 | \text{mem}, x_2, x_4)$$

Permutation Language Modeling


Permutation Language Model

$[x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8]$

$[x_2, x_5, x_1, x_6, x_8, x_3, x_7, x_4]$

$[x_2, x_5, x_1, x_6, x_8, x_3, x_7, x_4]$

autoregressive



Permutation Language Modeling

Permutation language model의 수식 표현

Z_t is all possible permutations of length $- T$ index sequence $([1, 2, 3, \dots, T])$

$$\max_{\theta} \mathbb{E}_{z \sim z_T} \left[\sum_{t=1}^T \log p_{\theta}(x_{z_t} \mid x_{z_{<t}}) \right]$$

$[x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8]$ 8개의 토큰 $\rightarrow 8!(40,320)$ 개의 permutations order 생성 \rightarrow 연산량 

부분 예측(Partial Prediction)

- Hyper parameter K - 토큰의 $1/K$ 만 예측

$K = 8$

$[x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8] \rightarrow$

$[x_2, x_5, x_1, x_6, x_8, x_3, x_7, x_4]$	}	40,320개
$[x_3, x_7, x_6, x_1, x_8, x_2, x_4, x_5]$		
\vdots		

BERT와 XLNet 모델 비교

Sequence : New York is a city

$$\mathcal{J}_{BERT} = \log p(\text{New} \mid \text{is a city}) + \log p(\text{York} \mid \text{is a city}),$$

$$\mathcal{J}_{XLNet} = \log p(\text{New} \mid \text{is a city}) + \log p(\text{York} \mid \text{New is a city})$$

Permutation Language Modeling Problem

Input sequence 의 token의 order를 permutation 하기 때문에 기존 AR 모델에서 관측되지 않는

Position 구분에 문제가 발생

기존의 AR 모델은 방향성이 존재 (forward, backward) 하기 때문에 position 구분할 필요가 없었음

Example)

Input sequence : [New, York, is, a, city]


Factorization order : $1 \rightarrow 2 \rightarrow 5 \rightarrow \dots$ $p(\text{New} \mid \text{mem})p(\text{York} \mid \text{mem}, \text{New})p(\text{city} \mid \text{mem}, \text{New}, \text{York})$
 $1 \rightarrow 2 \rightarrow \mathbf{3} \rightarrow \dots$ $p(\text{New} \mid \text{mem})p(\text{York} \mid \text{mem}, \text{New})p(\mathbf{is} \mid \text{mem}, \text{New}, \text{York})$

같은 representation 을 이용해서 다른 token을 예측해야 하는 문제가 발생

Overview

- NLP Trends
- Autoregressive vs Autoencoding
- **XLNet**
 - Permutation Language model
 - **Two-stream self-attention mechanism**
 - Recurrence mechanism

Two-Stream Self-Attention



Two-Stream Self-Attention

문제 해결을 위해서 새로운 next-token distribution 을 제안

$$h_{\theta}(x_{z<t}) \rightarrow g_{\theta}(x_{z<t}, z_t) \quad \text{context information } (x_{z<t}), \text{ target position } z_t$$

기존에 context information 만 사용하던 $h_{\theta}(x_{z<t})$ 을 개선하여

Target position 을 반영한 $g_{\theta}(x_{z<t}, z_t)$ 를 사용

$g_{\theta}(x_{z<t}, z_t)$ 를 표현하기 위해 Two-Stream Self-Attention을 제안

Two-Stream

- *query stream* : $g_{zt}^{(m)}$ 으로 표시되는 *Attention stream* (Permutation 계산시 본인 제외)
무작위로 생성된 가중치 값, 위치 정보
- *content stream* : $h_{zt}^{(m)}$ 으로 표시되는 *Attention stream* (Permutation 계산시 본인 포함)
워드 임베딩 값

Two-Stream Self-Attention




Figure 2: (a): Content stream attention, which is the same as the standard self-attention. (b): Query stream attention, which does not have access information about the content x_{z_t} . (c): Overview of the permutation language modeling training with two-stream attention.

Attention score

Input

Embedding

Queries

Keys

Values

Score

Divide by 8 ($\sqrt{d_k}$)

Softmax

Softmax
X
Value

Sum

Thinking

x_1 

q_1 

k_1 

v_1 

$q_1 \cdot k_1 = 112$

14

0.88

v_1 

z_1 

Machines

x_2 

q_2 


k_2 

v_2 

$q_1 \cdot k_2 = 96$

12

0.12

v_2 

z_2 

Two-Stream Self-Attention




Figure 2: (a): Content stream attention, which is the same as the standard self-attention. (b): Query stream attention, which does not have access information about the content x_{z_t} . (c): Overview of the permutation language modeling training with two-stream attention.

Two-Stream Self-Attention




Figure 2: Two-Stream Self-Attention, which is the same as the standard self-attention. The input stream, which does not have access information about the context x_i , can be used for the generative language modeling training with two-stream attention.

Overview

- NLP Trends
- Autoregressive vs Autoencoding
- **XLNet**
 - Permutation Language model
 - Two-stream self-attention mechanism
 - **Recurrence mechanism**

Vanilla Transformer




Figure 1: Illustration of the vanilla model with a segment length 4.

Transformer-XL






Figure 2: Illustration of the Transformer-XL model with a segment length 4.

Segment Recurrence

- RNNs 의 Hidden 처럼 이전 segment 의 결과를 다음 segment 계산에 반영

Transformer-XL



TRANSFORMER-XL: ATTENTIVE LANGUAGE MODELS BEYOND A FIXED-LENGTH CONTEXT

**Zihang Dai^{*1}, Zhilin Yang^{*2}, Yiming Yang¹, William W. Cohen³, Jaime Carbonell¹,
Quoc V. Le², Ruslan Salakhutdinov¹**

¹Carnegie Mellon University, ²Google Brain, ³Google AI

{dzihang, yiming, jgc, rsalakhu}@cs.cmu.edu, {zhiliny, wcohen, qvl}@google.com

XLNet: Generalized Autoregressive Pretraining for Language Understanding

**Zhilin Yang^{*1}, Zihang Dai^{*12}, Yiming Yang¹, Jaime Carbonell¹,
Ruslan Salakhutdinov¹, Quoc V. Le²**

¹Carnegie Mellon University, ²Google Brain

{zhiliny, dzihang, yiming, jgc, rsalakhu}@cs.cmu.edu, qvl@google.com

Transformer-XL




hardmaru @hardmaru · Jan 10

Transformer-XL: Attentive Language Models Beyond a Fixed-Length Context

Up to 1800x faster than vanilla Transformer during evaluation. New SoTA results on Wikipedia (enwik8, text8, WikiText-103), One Billion Words, and PennTree Bank. 🔥

arxiv.org/abs/1901.02860



7



110



453



Jeremy Howard

@jeremyphoward

Follow

Replying to @hardmaru


This paper was rejected by iclr, right?

8:42 PM - 10 Jan 2019

Why Transformer XL is rejected?

- 좋은 모델인건 알겠지만, downstream task에 대해서 좋은 결과를 보여줄지 미지수
- Document generation 에 관련한 결과가 없다
- 비슷한 시기에 OpenAI GPT-2 가 뛰어난 성능 입증 잘 함

Transformer XL 의 유혹



참고문헌

원문 : <https://arxiv.org/pdf/1906.08237.pdf>

7 : <https://www.nytimes.com/2018/11/18/technology/artificial-intelligence-language.html>

11 : <http://jalamar.github.io/illustrated-bert/>

18 : <https://mlexplained.com/2019/06/30/paper-dissected-xl-net-generalized-autoregressive-pretraining-for-language-understanding-explained/>

33 : <https://www.youtube.com/watch?v=naOue9gLbZo>

Transformer-XL paper : <https://arxiv.org/pdf/1901.02860.pdf>

LAMB optimizer paper : <https://arxiv.org/pdf/1904.00962.pdf>