

Haoming MA, Zhe SUN, Zhenqian XUE, Chi ZHANG, Zhangxing CHEN

A systemic review of hydrogen supply chain in energy transition

© Higher Education Press 2023

Abstract Targeting the net-zero emission (NZE) by 2050, the hydrogen industry is drastically developing in recent years. However, the technologies of hydrogen upstream production, midstream transportation and storage, and downstream utilization are facing obstacles. In this paper, the development of hydrogen industry from the production, transportation and storage, and sustainable economic development perspectives were reviewed. The current challenges and future outlooks were summarized consequently. In the upstream, blue hydrogen is dominating the current hydrogen supply, and an implementation of carbon capture and sequestration (CCS) can raise its cost by 30%. To achieve an economic feasibility, green hydrogen needs to reduce its cost by 75% to approximately 2 \$/kg at the large scale. The research progress in the midterm sector is still in a preliminary stage, where experimental and theoretical investigations need to be conducted in addressing the impact of embrittlement, contamination, and flammability so that they could provide a solid support for material selection and large-scale feasibility studies. In the downstream utilization, blue hydrogen will be used in producing value-added chemicals in the short-term. Over the long-term, green hydrogen will dominate the market owing to its high energy intensity and zero carbon intensity which provides a promising option for energy storage. Technologies in the hydrogen industry require a comprehensive understanding of their economic and environmental benefits over the whole life cycle in supporting operators and policymakers.

Keywords hydrogen production, hydrogen transportation and storage, hydrogen economy, carbon capture and sequestration (CCS), technology assessment

Received Oct. 16, 2022; accepted Dec. 28, 2022; online Feb. 28, 2023

Haoming MA, Zhe SUN, Zhenqian XUE, Chi ZHANG, Zhangxing CHEN (✉)
Department of Chemical and Petroleum Engineering, University of Calgary, Calgary, AB T2N 1N4, Canada
E-mail: zhachen@ucalgary.ca

1 Introduction

The global energy demand is drastically rebounding after experiencing the largest decline of 4% since World War II due to the COVID-19 according to International Energy Agency (IEA) [1]. The rising supply of renewable energy and diminishing demand of fossil fuels not only diversify the energy sources from the supply side but also push the energy industry to the low-carbon fuels for the CO₂ mitigation purpose. Under the global goal of net-zero emission (NZE), the demand for hydrogen will rise from less than 90 Mt in 2020 to over 200 Mt in 2030. Especially, the demand of low-carbon hydrogen is predicted to rise from 10% to 70% by 2030 as shown in Fig. 1 [2]. The global average of 15% volumetric hydrogen blend can reduce the CO₂ emissions from gas consumption by 6%.

Hydrogen derived from fossil fuels was entirely meeting the global demand of 90 Mt in 2020, whereas 80% was directly produced from hydrogen plants and the rest was the by-product associated with other sources. The steam methane reforming (SMR) with the primary feedstock of natural gas dominates the hydrogen supply in the current industry, and corresponds to 900 Mt CO₂ emissions (2.5% of global emissions) in 2020 as shown in Fig. 2 according to IEA [3]. Therefore, the low-carbon hydrogen supply is projected to grow rapidly in the next few decades. The promising technologies include the hydrogen production from electrolysis and fossil fuel-based hydrogen with carbon dioxide capture and sequestration (CCS). By 2030, the NZE scenario will require 80 Mt of electrolytic H₂ and 60 Mt of H₂ from natural gas with CCS [3]. The strong policy support will prompt the sustainable development of the hydrogen market in the next few decades [4].

As the lightest, simplest, and most abundant chemical substance in nature, hydrogen is the most reliable renewable energy to address environmental problems [5]. The advantages of using hydrogen mainly include zero greenhouse gas (GHG) emissions and high energy




Fig. 1 Global hydrogen use in the NZE scenario (adapted from Ref. [2]).




Fig. 2 Source of hydrogen supply (adapted from Ref. [3]).

density between 120 MJ/kg (lower heating value, LHV) to 142 MJ/kg (higher heating value, HHV). However, the current hydrogen industry is facing challenges from the production, transportation, storage, and utilization perspectives. This paper is keen to seek the answers for two questions by reviewing the state-of-the-art hydrogen development technologies in the current energy transition era. First, why the hydrogen supply chain will play an essential role in the clean energy transition? Then, to what extent will the technology assessment be focused on systematically estimating the hydrogen technologies over its supply chain as emerging technologies? Especially, the challenges and outlooks were addressed from the production, transportation, storage, and economic perspectives in the context of achieving the NZE goal by 2050. The remaining of this paper is structured as follows: First, Section 2 provided the general perception of the hydrogen spectrum. Second, Section 3 reviewed the hydrogen production technologies. Third, Section 4 discussed the development of hydrogen storage and transportation. Fourth, Section 5 summarized the economic expansion of the hydrogen supply chain. Finally, Section 6 outlined the conclusion of this investigation.

2 Color of hydrogen

During a manufacturing process, rainbow color codes are often utilized to distinguish between the various forms of hydrogen synthesis and electricity consumption [6,7]. In the contemporary industry, there are ten colors of hydrogen that may be divided into three groups. First, white hydrogen identifies the subsurface geological hydrogen that occurs naturally. However, there is insufficient data to show the white hydrogen exploitation tactics. Second, the hydrogen derived from fossil fuels is the dominant source in the present hydrogen market [8–16]. Grey hydrogen describes the hydrogen generated by SMR from natural gas without CCS, while blue hydrogen describes the hydrogen produced by SMR from natural gas with CCS. The terms black and brown hydrogen refer to the hydrogen generated from black coal and lignite, respectively. The turquoise hydrogen represents the hydrogen generated by the pyrolysis of methane (MP) [17]. Finally, green hydrogen refers to the generation of hydrogen without GHG emissions using electrolysis [6,14,18–20]. Pink hydrogen refers especially to the creation of green hydrogen using nuclear energy. Orange and yellow hydrogen represent the green hydrogen powered by wind and solar electricity, respectively. As seen in Fig. 3, the path of future technological development is turning toward the use of renewable power sources and green hydrogen [8]. As a result, blue hydrogen will dominate the market in the near future with the matured production techniques associated with CCS technologies. Green hydrogen will be widely considered in the long-term with the significant penetration of renewable electricity to achieve the NZE goal at a large scale.

3 Hydrogen production

Hydrogen is manufactured mostly from fossil fuels and


renewable resources through chemical processes, since the amount of naturally occurring hydrogen is limited. Production of gray hydrogen is the most resourceful commercialized technique in the current industry. With the successful commercial application of CCS, industrial-scale blue hydrogen is maturing into low-CO₂ hydrogen. As a result of robust legislative support for the development of renewable energy, green hydrogen has reached commercial scale in recent years. In this Section, the most advanced methods for producing blue and green hydrogen are discussed as summarized in Fig. 4.

3.1 Steam methane reforming (SMR)

Today, SMR is a mature large-scale technique for producing hydrogen by converting natural gas at a specified temperature and pressure [3,21–23]. Typically, a SMR process consists of four steps, removal of impurities, catalytically reforming or synthesis gas (syn-gas, Eq. (1)) production, water gas shifting (WGS, Eq. (2)), and methanation or gas purification [21,22]. The

needed parameters for SMR are 700 to 900 °C of temperature, 0.3 to 3 MPa of pressure, and a steam-to-carbon ratio of 2.5 to 3.5 [12,23–27]. Using natural gas as a hydrocarbon feedstock typically necessitates a molar fraction of methane between 75% and 99% [28]. The yield efficiency can reach up to 75% and the estimated cost can be as low as 1.80 \$/kg H₂ [29]. To improve a hydrogen production rate, heterogeneous catalysts like non-precious metal nickel (Ni), precious metal platinum (Pt) or rhodium (Rh) and precious metal alloys like Ni/Al₂O₃ or ruthenium (Ru)/zirconium oxide (Ru/ZrO₂) are frequently utilized on an industrial scale [30–34]. In addition, natural gas can be composed of higher alkanes, inert gas, and acidic gases (i.e., CO₂ and H₂S). Consequently, a pre-treatment, such as hydrotreating or absorption on activated zinc oxide, is often necessary to remove hydrogen sulphide (H₂S) because of its detrimental effects on further processing. Pressure swing adsorption (PSA) units are often considered to filter the hydrogen generated by chemical processes. The primary chemical reactions of SMR are [35]


Syn-gas generation:



WGS:



Methanation:



Both syn-gas generation and methanation are highly endothermic chemical processes. Therefore, external heat is necessary for these processes. In general, the reforming step may produce more than 10% of CO by volume. The WGS is an exothermic reaction. Regarding a temperature range and catalyst choice, a variety of catalysts selections of WGS can be categorized into two distinct directions. For example, a high-temperature shift occurs between 310 and 500 °C of temperature and 2.5 and 3.5 MPa of pressure when utilizing Fe/Cr or Co/Mo as catalysts [32]. A low-temperature shift for CuO/ZnO or brass catalysts occurs between 190 and 280 °C [8]. Both high-temperature and low-temperature operations need a two-stage reactor. The SMR procedure is shown in Fig. 5 [8]. SMR is a mature technology with a technology readiness level (TRL) of 9. The largest SMR plants have a production




Fig. 3 Hydrogen color spectrum.




Fig. 4 Hydrogen production technologies with hydrogen spectrum.






Fig. 5 SMR process (adapted with permission from Ref. [8]).

capacity of 120000 Nm³/h H₂ and are operating for downstream ammonia production [21]. Due to the excessive heat produced as steam by SMR, the by-product in the form of high-temperature steam may be utilized to power up the neighboring steam turbines for the electricity production. As SMR is a matured hydrogen production technology at large scale, the net-zero solution for SMR is capturing and sequestering emitted CO₂ to geological formations (e.g., hydrocarbon reservoirs and saline aquifers) to offset the emissions to produce the zero-emission hydrogen over its lifecycle. The advantage of SMR is that it is a mature large-scale technology. However, the CCS would be required to reduce its CO₂ emissions.


3.2 Partial oxidation (POX)

A POX process (Fig. 6) is categorized as either catalytic or non-catalytic [36]. Catalytic POX can operate at a lower temperature (950 °C) with feedstocks ranging from methane to naphtha [37,38]. Non-catalytic POX is more sulfur tolerant and can take a wider range of feedstocks than SMR, but requires a much higher temperature (i.e., 1150 to 1135 °C) [36]. The primary feedstock for non-catalytic POX is methane from natural gas, although other hydrocarbons, such as heavy oil and coal, may also be used [39]. In general, oxygen is used to partially oxidize hydrocarbons and produce syn-gas, as shown in Eqs. (4) and (5), and complete oxidation occurs for a small portion of hydrocarbon feedstock as shown in Eq. (6) [40, 41]. This exothermic reaction generates sufficient heat to supply the WGS reaction to increase a hydrogen production rate [28]. Similar to SMR, desulfurization is necessary as a pre-treatment procedure before proceeding hydrocarbons with a restricted quantity of oxygen to a high-pressure reactor to produce syngas. Controlling an oxygen-carbon ratio in this stage is crucial since it has a direct effect on maximizing a syn-gas production rate and preventing coke formation [28]. POX is the most suitable method for producing H₂ from heavier hydrocarbon feedstocks like heavy oil and coal. Furthermore, an implementation of WGS generates significant CO₂ emissions [42]. Thus, the contemporary industry is using a CCS technology to transform hydrogen from gray to blue. According to previous studies, the use of CCS may raise the cost of producing hydrogen from 1.34 to

1.63 \$/kg but mitigate CO₂ emissions at a significant level [43]. Although POX has a lower cost compared to SMR, its high temperature requirement is a severe concern for operators.



Complete oxidation :



3.3 Autothermal reforming (ATR)

An ATR process describes a merged SMR and POX procedure [5]. POX is exothermic while SMR is endothermic, as explained in Sections 3.1 and 3.2. In ATR, the heat from POX is used to provide thermal energy to SMR, hence enhancing hydrogen production and achieving thermodynamic equilibrium [39]. In its operation, high-temperature steam and oxygen/air are fed to a reformer, where reforming and oxidation reactions occur simultaneously [30]. A reactor is specially designed with a ceramic-lined, fixed-bed catalytic and combustion zone so that hydrocarbons can react with steam and oxygen at temperatures between 900 and 1100 °C [36,44,45]. Its chemical process is described by Eq. (7), and the flow diagram is illustrated in Fig. 7 [46]. An oxygen-carbon ratio and inlet temperature can be optimized to maximize the hydrogen yield. Additionally, large-scale ATR plants will generate a substantial quantity of CO₂. Consequently, appropriate capturing methods will also be required. The cost of H₂ is typically approximated at 1.48 \$/kg [47]. Both POX and ATR can be implemented at industrial scale with an estimated TRL of about 7–8 currently, but the disadvantage is that a significant amount of thermal energy would be required.





Fig. 6 Flow diagram of POX process.

3.4 Coal gasification

A process of coal gasification explains the transformation of carbon into gas [48]. Gasifiers can be characterized in three types including fixed bed, fluidized bed, and entrained flow gasifiers [49]. To increase hydrogen yield, high temperature entrained flow is often chosen by industrial operators. Equation (8) describes a reaction and Fig. 8 describes the process of coal gasification to produce H_2 , in which syn-gas is generated and H_2 is extracted. CO is proceeded to a WGS process to maximize H_2 production. This is also an endothermic process that requires thermal energy input. The capital investment in a coal gasification process is usually much higher than that in ATR, POX, and SMR [47]. Moreover, the underground coal gasification (UCG) is an alternative

pathway for converting coal to syngas *in situ* by the injection of oxidants, as presented in Fig. 9 [36,50–52]. As coal seam is combusted underground, syn-gas is produced and collected from a producer [36]. Recent development of UCG incorporated directional drilling technologies to drill two boreholes in deep coal seams. By injecting the oxidant for the purpose of *in situ* combustion, the syngas can be produced without generating a large amount of GHG emission [52]. The coal gasification technology is not as mature as SMR with an estimated TRL of around 5–7 currently. The UCG process can be considered as a zero-emission hydrogen production route as the CO_2 produced is immediately sequestered to coalbed subsurface [52]. However, since the process requires a high temperature (i.e., $> 500\text{ }^\circ\text{C}$), its feasibility still needs to be addressed.




Fig. 7 Flow diagram of ATR process.




Fig. 8 Flow diagram of coal gasification process.





Fig. 9 Schematic of UCG (adapted from Ref. [52] under the terms of CC BY).

Although numbers of pilot test projects have been conducted around the world since 1935, the low gas production rates and gas quality suggest that the development of the UCG technology is still at the early stage [53].



3.5 Methane pyrolysis (MP)

MP, also known as thermal cracking, directly splits methane into carbon and hydrogen as demonstrated in Eq. (9) [54]. The turquoise hydrogen is generated in this process because no CO₂ is released directly and the WGS is not required [17]. Figure 10 depicts a MP flow diagram [8]. In this process, considerable quantities of methane are delivered to a reactor to convert into solid carbon and hydrogen gas [54]. This method is in its infancy at the industrial scale, and the ongoing studies are investigating the reaction mechanism, kinetics, and appropriate catalysts for scaling up the laboratory concept [55–58]. According to the literature, a high temperature is primarily required to upscale MP owing to the stable chemical properties of CH₄ [59–61]. For example, a catalytic process requires a temperature of over 800 °C, a non-catalytic process requires the temperatures of above 1000 °C, and a plasma-based process requires a temperature of above 2000 °C to assure a high yield rate as it is proportional to temperature [36,62]. With a right choice of a catalyst, the temperature requirement can be reduced to 500 °C [63]. Recent studies have suggested several reactor concepts, such as plasma, packed bed, circulating fluidized bed, monolithic, liquid bubble column, and moving bed reactors [64–77]. However, these concepts are still in their infancy without proof of industrial applications. To improve the methane conversion rate and H₂ selectivity, metal catalysts primarily based on nickel, iron, and cobalt, as well as carbonaceous materials and molten media, have been investigated [78–99]. However, a catalyst must be regenerated periodically because of an adverse impact by deposition of solid carbon [100–107]. The H₂ selectivity at moderate temperatures is the most important factor to consider when choosing appropriate catalysts [108–110]. The carbon by-product generated from a MP process is recognized as a carbon black that can be used in the production of merchandise [111–113]. MP is the cleanest

method of producing hydrogen from fossil fuel as no CO₂ is directly emitted. However, the TRL of the MP process still lies in a research and development stage with a TRL of 2–4 and the process still present obstacles from three angles. First, there is no mature design of large-scale reactors and the proper strategies for catalysts selection to reduce the required temperature. Second, there is no clear understanding of the effects of methane purity on the production of hydrogen. Lastly, the current research lacks an economic and environmental evaluation of MP as the emerging technologies to compete with established hydrogen production technologies.



3.6 Role of CCS

The methods outlined in Sections 3.1 to 3.4 yield gray hydrogen. To achieve the global NZEs goal, CCS is the only solution to the gray hydrogen sector shifting to blue hydrogen [2,3,11,114–116]. During a CCS process, CO₂ is captured from either a pre-combustion or post-combustion stage and either permanently sequestered to the subsurface porous media (i.e., hydrocarbon reservoirs and saline aquifers) or used in the production of commercial goods [117–133]. Currently, 26 commercial scale CCS facilities with a total annual capture capacity of 40 Mt are in operation around the world [1,10,114,134–137]. Six of the 26 projects are devoted to geological storage, while the other 20 are employed for CO₂ enhanced oil recovery [135]. Additionally, there are also 34 pilot CCS projects in a demonstration or development phase. To minimize global warming to 1.5 °C, the global capture capacity must exceed 1200 Gt annually [2,138,139]. Thus, CO₂ capture is extremely important to the existing hydrogen production plants owing to its large emissions [140]. As shown in Fig. 11, five main processes have been used to the CO₂ flue gas capture facilities over decades [141,142]. Capturing CO₂ from flue gas is a mature technology with a TRL of 7–9 [137,143–148]. The capture rate at the industrial scale ranges from 53% to 95%, and the greatest efficiency achievable with a cryogenic separation technique is 99.99% [142,143,145,146,149–154]. However, an increased capture rate will result in higher expenses [137,149,155–158]. The current cost of flue gas capture is estimated between 70 and 100 \$/t [141,142]. In recent years, direct air capture (DAC) has been researched with a TRL of 6 to 7 [159–166]. However, the CO₂ capture from DAC plants requires a much higher cost between 300 and 600 \$/t [161,166,167]. The CCS market is a policy-driven market in which operators cannot gain profits directly. The establishment of a higher carbon price will give operators possibilities to earn additional revenues and promote the industries transforming toward the NZEs target by 2050. According to the United States




Fig. 10 Flow diagram of MP process (adapted with permission from Ref. [8]).

current carbon pricing policy, carbon credits may only be issued if the collected CO₂ is effectively utilized or sequestered. If CO₂ is emitted, the carbon tax will be charged. Industrial emitters can avoid the carbon tax by adopting a CO₂ capture technology, while downstream operators can gain carbon credits by sequestering or utilizing captured CO₂. The price of carbon will increase dramatically in the future. For instance, the US 45Q indicates that the price would rise from 31.77 to 50 \$/t by 2050, and Canada will increase its carbon price from 40 to 170 CAD per ton [168,169]. SMR-CCS is an industrially validated technology that has reached maturity (TRL 8 to 9). As shown in Fig. 12, CO₂ emissions may be collected by three options during SMR [170].

3.7 Green hydrogen from biomass

Biomass can be used to produce green hydrogen. Its

technologies can be classified into two categories (i.e., thermochemical and biological) with a variety of biomass feedstocks [48,171–174]. The thermochemical process is comprised of the pyrolysis and gasification conversion processes, which convert biomass to hydrocarbons before proceeding to the hydrogen production unit detailed in earlier sections [130,175,176]. The use of feedstocks and catalysts may have a direct effect on a hydrogen yield. Figure 13 depicts a process flow diagram. The biological processes include three fundamental mechanisms: bio-photolysis, photo and dark fermentation, and biological WGS responses. The mechanisms for direct and indirect bio-photolysis are shown in Figs. 14 and 15, respectively. Fermentation operations may occur with or without oxygen and include the microbial transformation of organic feedstocks into alcohols, acetone, H₂ and CO₂. These technologies can convert waste into bio-hydrogen. In the near future, however, bio-hydrogen pathways




Fig. 11 CO₂ capture mechanisms (adapted from Ref. [142] under the terms of CC BY).




Fig. 12 SMR-CCS options (adapted from Ref. [170]).




Fig. 13 Flow diagram of thermochemical biomass conversion (adapted with permission from Ref. [28]).




Fig. 14 Direct bio-photolysis (adapted with permission from Ref. [177]).




Fig. 15 Indirect bio-photolysis (adapted with permission from Ref. [177]).


cannot compete with fossil fuel-based hydrogen routes due to their low yield rate and extensive biomass consumption [5].

3.8 Green hydrogen from water electrolysis

Given the abundance of water and the growth of renewable energy, the production of green hydrogen by splitting water or even sea water is gaining attention and becoming a renewable power storage alternative for the energy sector [178–180]. Three promising methods are commonly applied to split water: electrolysis,

thermolysis, and photo-electrolysis [181–183].

The most well-established and effective approach is electrolysis [184–187]. A typical electrolyzer consists of a cathode and an anode [36]. As shown in Eq. (10), green hydrogen is generated by using a significant amount of electricity with water as a feedstock. Currently, there are three common electrolysis approaches being studied [36,178]. They are alkaline water electrolysis (AEL), polymer electrolyte membrane water electrolysis (PEM), and solid oxide water electrolysis (SOEL). Recent advancements proved that H_2 can be produced from sea-water, but its economic feasibility needs to be addressed at the large scale [180,188]. The commercialized AEL is capable of producing 380 tonnes of green hydrogen per year at a maximum efficiency of 73% while consuming 53.4 kW·h/kg of electricity [189,190]. Therefore, the choice of an electricity source considerably influences the carbon intensity and cost of H_2 delivery [43]. Electrolysis costs vary from 4.15 \$/kg to 10.49 \$/kg of H_2 supply, which is much more than blue hydrogen. Green hydrogen from electrolysis is one of the most promising solutions for storing renewable energy due to the exceptionally low carbon intensity of renewable power.



The thermolysis or thermochemical technology describes a process that splits water into hydrogen and oxygen by heating water to high temperatures until it breaks down into hydrogen and oxygen [44,191]. In order for its Gibbs function to reach zero and hydrogen to be produced, this process requires a high temperature of approximately 2500 °C. The thermochemical cycles consist of a series of chemical reactions that can reduce the required temperature lowest to 550 °C [192,193]. Cu–Cl and Mg–Cl are the two most promising cycles that also do not release GHG. A high temperature needs strong heat sources such as solar or nuclear energy [194]. The cost of green hydrogen via thermolysis is cheaper than electrolysis, ranging between 2.17 and 8.20 \$/kg [192, 195–197].

Photo-electrolysis, also known as photolysis absorbing visible light, is associated with photo-catalysts to trigger an electrolysis process. In general, semiconducting materials are often used to absorb sunlight. The electrodes material selection for cells has been studied to improve the conversion efficiency. The average cost of

hydrogen production by photo-electrolysis is estimated to be about 10.36 \$/kg [198–205].



4 Hydrogen transportation and storage

The rising demand and productivity of hydrogen need the development of efficient transport and storage systems. Safe, trustworthy, and cost-effective strategies are required as the hydrogen sector continues to face obstacles. Due to the unique properties of hydrogen, such as a low density and a small molecular size, transportation, and storage are remaining challenges to industry. In this Section, the methods of hydrogen transportation and storage are discussed [206].

4.1 Transportation

The techniques for transporting hydrogen are divided into two categories: direct and indirect transportation. The direct transporting approach entails transporting hydrogen without altering its chemical composition. Common transport techniques include containers and pipelines [207–209]. Hydrogen is compressed at a high pressure (up to 20 MPa) and transported by gas cylinders, hydrogen vehicle tanks, and pressure vessels [210]. The optimal container design materials should possess three characteristics: high tensile strength, low density, and not reacting with hydrogen or allowing diffusion. However, their ineffectiveness is questioned by the industry due to their poor carrying capacity and expensive price. As the most efficient route for the direct transfer of hydrogen, pipeline networks are being investigated and constructed in recent years. The indirect transport techniques explained the process of transporting H₂ utilizing liquid organic hydrogen carriers [211,212]. In this process, H₂ reacts with an organic material to generate a new compound, which dehydrates back into H₂ once the liquid carrier reaches its destination. As carriers, cycloalkanes, N-heterocycles, B-N-based heterocycles, and formic acid have been studied [211, 213–221]. However, the carrying capacity is quite low (usually less than 6 wt.%), and the dehydration process often requires a high temperature. Using ammonia and related chemicals (e.g., ammonia borane, liquid ammonia, and 35 wt.% ammonia solution) as the hydrogen carriers can reach a carrying capacity of up to 19.6 wt.%. The carrying capacity can meet the US Department of Energy (DOE) target (9 wt.%), but the cost is relatively unaffordable [212]. The most common process is named the Haber-Bosch process shown in Eq. (11). Haber won the Nobel Prize in 1918. In this process, ammonia is synthesized from hydrogen and nitrogen in a reactor designed with a pressure of 20 to 35 MPa and a temperature of 300 to 500 °C with two to four catalysts [222]. Since ammonia is unstable and decomposes at over

200 °C, the decomposition process as depicted in Eq. (12) is usually required when the ammonia is transported to a destination as a hydrogen carrier.



Additionally, long distance transportation of hydrogen from an offshore wind farm is needed in the future owing to the rising installed capacity of wind energy. A high grid connection cost makes the green hydrogen one of the most promising options for energy storage. However, transportation and distribution of H₂ offshore is facing economic challenges owing to its high cost. Liquid H₂ (LH₂) is commonly transported by a ship to onshore storage tanks, and distributed to end-users via tube trailers or LH₂ semitrailers, which are mature technologies [223]. Pipelines are not commonly used owing to the corrosion of seawater and challenges of long-distance construction in the ocean. In 2019, the first LH₂ carrier ship in the world was launched in Japan with the capability of 75 t and longest ferrying distance of 5600 m [224].

In brief, hydrogen can be transported directly or indirectly via pipelines, ground transportation, marine transportation, and liquid hydrogen carriers. However, the hydrogen industry lacks an understanding of the impact of interfacial reactions of hydrogen and carrier materials such as hydrogen embrittlement and corrosion. Liquid hydrogen carriers need to improve the transportation efficiency by improving their carrying capability and reducing their cost.

4.2 Storage

Hydrogen can be stored both on the surface and underground [38,206,225]. There are three potential solutions to store hydrogen on the surface [226–228]. First, compressing hydrogen at a high pressure is presently the most popular and mature technology for surface storage. Due to the extraordinarily low density of hydrogen in the atmosphere (i.e., 0.09 kg/m³), a high pressure of up to 77 MPa is necessary to compress it [226]. Another solution is to store liquid hydrogen (also named the cryogenic hydrogen) in a cryogenic tank, which needs temperatures below its boiling point of −253 °C [210]. Lastly, solid-state storage is being considered as an effective large-scale storage option based on the hydrogen adsorption and desorption mechanisms especially in recent years [229, 230]. The advantages of solid-state storage include high storage capacity, high purity, and high safety [5,231]. For instance, metal hydrides have an ability to absorb and desorb hydrogen molecules with a high capacity for the storage purpose [232,233]. In general, a desorption procedure requires the temperature in a range between 120 to 200 °C. Another potential material is

carbon nanotubes. Due to their complex porous structure, hydrogen can be, therefore, stored and extracted through adsorption and desorption, respectively [234–238]. The storage capacity of a carbon nanotube varies according to the processing uncertainties during preparation and synthetic purity when manufacturing the materials. Metal-organic frameworks (MOFs) are another type of material for hydrogen storage purpose [239–246]. MOF is a synthetic material with a high porosity and specified surface area that has a high hydrogen absorption capacity and has garnered considerably more interest in recent years. MOF materials are still difficult to synthesize, and their characteristics have a significant influence on hydrogen storage capacity.

Underground hydrogen storage (UHS) has been proposed as a large-scale option to store hydrogen to geological porous media [225,247–251]. Potential candidate formations include empty salt caverns, deep aquifers, depleted hydrocarbon reservoirs, and coal seams. This is a novel application to the energy industry and the feasibility of this approach has been studied in recent years. Therefore, there is not sufficient industrial application data up to date. However, owing to the different fluid properties of hydrogen compared with CO₂ and natural gas, the evaluation schemes are different. Additionally, geological properties such as rock properties, fluid properties, and solid-fluid interactions can significantly impact the performance of UHS. On the operational side, the storage efficiency poses another challenge to industry as it is easier for hydrogen to leak than other molecules.

5 Hydrogen economy

Hydrogen economists analyze production, transportation,

and storage systems primarily from two perspectives: techno-economic and environmental effects. To achieve the cost-effective and sustainable development goals, a variety of technologies have been evaluated [10,16,29]. During the manufacturing phase, matured blue hydrogen technologies have been successfully evaluated, and costs have decreased to an economical level (less than 2 \$/kg) over the past decades [252–254]. The cost of green hydrogen routes is still relatively expensive compared to blue hydrogen pathways, posing an economic obstacle. Other emerging H₂ production methods are still in the progress of development, and an industrial-scale techno-economic assessment will be required in the near future. The feedstocks used to produce hydrogen will be a crucial factor in determining the cost, since they will directly influence the selection of technologies (Fig. 16) [187]. Current research lacks evidence of the economic assessment of transportation and storage because the demand for these technologies has been relatively low in the past years but is expected to increase considerably in the near future [254–257]. Figure 17 depicts the future hydrogen market supply chain [258]. Similar to the market for fossil fuels, the whole value chain can be divided into upstream production, midstream transportation and storage, and downstream use.

In the downstream utilization phase, hydrogen can be directly utilized as a clean fuel because it is a zero GHG emission energy source. Its applications include hydrogen fuel vehicles in ground transportation, retrofitting hydrogen plants in electricity generation and heating supply, and high energy intensive fuel for aviation and space crafts [259,260]. Although using hydrogen fuel in space crafts has been successfully deployed, the aviation sector still requires further investigations in terms of the safety, economics, and retrofitting feasibility. Similarly,




Fig. 16 Feedstocks of hydrogen production (adapted from Ref. [187] under the terms of CC BY).




Fig. 17 Hydrogen value chain (adapted from Ref. [258]).

the retrofitting feasibilities of internal combustion engines and coal and natural gas plants need to be estimated economically and technically. The utilization of hydrogen fuel cells can potentially improve the energy conversion efficiency for transportation and heavy-duty applications. Hydrogen can also be indirectly used to produce value added chemical products, such as ammonia, methanol, and carbon-free fuels. Additionally, using hydrogen as a feedstock in petroleum refineries can remove sulfur and other impurities as well as in other industries such as plastic material production, manufacturing of vacuum tubes, the glass industry, and the food industry [259]. The demand of different colors of hydrogen will be a challenge in the short-, mid- and long-terms. As stated in the previous sections, blue hydrogen accounts for about half of current hydrogen supply, where most of them are used in the chemical industry in purposes of producing value added products. In the mid-term, the market will diversify its supply by incorporating the blue and green hydrogen while the large-scale industrial applications will be employed toward the clean energy transition, such as constructing hydrogen plants and energy cogeneration. In the long-term, green hydrogen will dominate the market and industrial utilization including transportation, fuel cells, and energy storage [261,262].

The cost of producing hydrogen will be a major problem for industrial-scale production, and policy-driven incentives will be advocated. A learning curve suggests that with adequate research and development, the long-term cost of green hydrogen may be reduced to an affordable level [263–265]. Prior to that, fossil fuel-based hydrogen plus CCS is the best choice in the immediate and medium future (Fig. 18) due to its cheap cost and potential capability to offset CO₂ emissions [266].

As upscaling a low-carbon green hydrogen technology is still a challenge for industry, the environmental effect of blue hydrogen must be carefully evaluated in order to achieve the NZE goal in a short future. The

environmental performance of the whole hydrogen supply chain must be evaluated using the approach of life cycle assessment (LCA) in order to determine the lifetime carbon emissions of hydrogen [267–270]. The selection of low-carbon electricity is essential for low-carbon technologies, and each unit process must be included in the detailed examination of the environmental effect [16,271–275]. The adoption of LCA can facilitate rational decision-making and assess the environmental implications of emerging technologies over time. Challenges associated with LCA for emerging technologies include a lack of data, scale-up, a lack (in some cases) of incumbents against which to compare, and uncertainties with respect to both how an emerging technology will be deployed and the market conditions into which it will be deployed [275]. An early-stage assessment can help set targets for technology development, influence design, and ensure that environmental goals of innovation are met [276]. The cradle-to-gate global warming potential of hydrogen generation ranges between 3.94 and 34.85 kgCO₂eq/kg H₂ [8]. However, several parameters, such as a carbon intensity of power, the selection of catalysts, and the manufacturing process design, might alter this estimate.

6 Conclusions

The growth of the hydrogen industry, comprising production, transportation and storage, and the economy, was reviewed, based on which, the following conclusions, as well as future outlooks, are given.

For the hydrogen production sector, efforts in the research and development sector will be required to upscale green hydrogen technologies to meet the long-term increasing hydrogen demand. Over the years, fossil fuel-based hydrogen has dominated the market. However, the GHG emissions cannot be ignored owing to its




Fig. 18 Projection of hydrogen production technologies (adapted from Ref. [266]).

significantly adverse impact on global warming. CCS will be the only solution to the current gray hydrogen generation routes to fulfill the NZE target. Turquoise hydrogen generation is a promising method to obtain hydrogen as the transitional substitute from “blue” to “green”. The majority of the research efforts will be focused on reactor designs and catalyst selections so that the process may be efficiently scaled up. Successful adoption of CCS can guarantee the blue hydrogen production to meet the increasing hydrogen demand in a short-term. With the renewable electricity and green hydrogen production technologies, the industry can achieve the NZE goal in a long-term. The cost-effective hydrogen production will pose a major challenge to the hydrogen industry, while the CCS can raise the blue hydrogen cost by 30%. The current blue hydrogen production processes are economic feasible, but the green hydrogen technologies need to reduce their cost by 75% to 2 \$/kg in the coming decades so that it can be competitive with blue hydrogen to meet the future market demand. Future research needs to focus on upscaling the green hydrogen by discovering cost effective catalysts and diversifying feedstocks and electricity usage. Techno-economic analysis is recommended associated with the proposed emerging technologies.

Due to a rising market demand, hydrogen transportation and storage have actively been developed in recent years. However, pipeline network transportation could be an effective strategy but will considerably differ from CO₂ and natural gas pipelines due to the different properties of hydrogen. Additionally, addressing the challenges will be a crucial milestone in future research. For instance, quantifying the impacts of embrittlement, contamination, and flammability can provide a solid support

in the selection of materials for the transportation safety and development of new materials for transportation and storage. The research and development sector should concentrate on solid-state hydrogen storage feasibility studies on the surface and feasibility investigations of UHS to assure storing hydrogen on a large scale.

The hydrogen market is confronted with two biggest barriers, particularly in terms of technology assessment. First, precise techno-economic appraisals of new technologies must be conducted to guide the development of cost-effective blue hydrogen and green hydrogen production techniques. Second, a cradle to grave LCA at various TRLs must be conducted to estimate the carbon footprint of a hydrogen supply chain in order to achieve the NZE goal by 2050.

References

1. International Energy Agency. Global Energy Review 2021. Technical Report, IEA, 2021
2. International Energy Agency. Net Zero by 2050. Technical Report, IEA, 2021
3. International Energy Agency. Global Hydrogen Review 2021. Technical Report, IEA, 2021
4. British Petroleum. BP Energy Outlook 2022 edition. Technical Report, British Institute of Energy Economics, 2022
5. Abdalla A M, Hossain S, Nisfindy O B, et al. Hydrogen production, storage, transportation and key challenges with applications: a review. *Energy Conversion and Management*, 2018, 165: 602–627
6. Dincer I. Green methods for hydrogen production. *International Journal of Hydrogen Energy*, 2012, 37(2): 1954–1971
7. Longden T, Beck F J, Jotzo F, et al. ‘Clean’ hydrogen? –

- Comparing the emissions and costs of fossil fuel versus renewable electricity based hydrogen *Applied Energy*, 2022, 306: 118145
8. Hermesmann M, Müller T E. Green, turquoise, blue, or grey? Environmentally friendly hydrogen production in transforming energy systems *Progress in Energy and Combustion Science*, 2022, 90: 100996
 9. Bauer C, Treyer K, Antonini C, et al. On the climate impacts of blue hydrogen production. *Sustainable Energy & Fuels*, 2021, 6(1): 66–75
 10. van der Spek M, Banet C, Bauer C, et al. Perspective on the hydrogen economy as a pathway to reach net-zero CO₂ emissions in Europe. *Energy & Environmental Science*, 2022, 15(3): 1034–1077
 11. Howarth R W, Jacobson M Z. How green is blue hydrogen? *Energy Science & Engineering*, 2021, 9(10): 1676–1687
 12. Yan Y, Thanganadar D, Clough P T, et al. Process simulations of blue hydrogen production by upgraded sorption enhanced steam methane reforming (SE-SMR) processes. *Energy Conversion and Management*, 2020, 222: 113144
 13. Lau H C. The color of energy: the competition to be the energy of the future. In: *International Petroleum Technology Conference*, 2021
 14. Yu M, Wang K, Vredenburg H. Insights into low-carbon hydrogen production methods: Green, blue and aqua hydrogen. *International Journal of Hydrogen Energy*, 2021, 46(41): 21261–21273
 15. Ehlig-Economides C, Hatzignatiou D G. Blue hydrogen economy—A new look at an old idea. In: *SPE Annual Technical Conference and Exhibition*, Dubai, the UAE, 2021
 16. Bauer C, Treyer K, Antonini C, et al. On the climate impacts of blue hydrogen production. *Sustainable Energy & Fuels*, 2021, 6(1): 66–75
 17. Newborough M, Cooley G. Developments in the global hydrogen market: the spectrum of hydrogen colours. *Fuel Cells Bulletin*, 2020, 2020(11): 16–22
 18. Mosca L, Medrano Jimenez J A, Wassie S A, et al. Process design for green hydrogen production. *International Journal of Hydrogen Energy*, 2020, 45(12): 7266–7277
 19. Palmer G, Roberts A, Hoadley A, et al. Life-cycle greenhouse gas emissions and net energy assessment of large-scale hydrogen production via electrolysis and solar PV. *Energy & Environmental Science*, 2021, 14(10): 5113–5131
 20. Jin L, Monforti Ferrario A, Cigolotti V, et al. Evaluation of the impact of green hydrogen blending scenarios in the Italian gas network: Optimal design and dynamic simulation of operation strategies. *Renewable and Sustainable Energy Transition*, 2022, 2: 100022
 21. Godula-Jopek A, Jehle W, Wellnitz J. *Hydrogen Storage Technologies: New Materials, Transport, and Infrastructure*. Hoboken: John Wiley & Sons, 2012
 22. Zohuri B. *Hydrogen Energy: Challenges and Solutions for a Cleaner Future*. Cham: Springer, 2019
 23. Adris A M, Pruden B B, Lim C J, et al. On the reported attempts to radically improve the performance of the steam methane reforming reactor. *Canadian Journal of Chemical Engineering*, 1996, 74(2): 177–186
 24. Oliveira E L G, Grande C A, Rodrigues A E. Effect of catalyst activity in SMR-SERP for hydrogen production: Commercial vs. large-pore catalyst. *Chemical Engineering Science*, 2011, 66(3): 342–354
 25. Collodi G, Azzaro G, Ferrari N, et al. Techno-economic evaluation of deploying CCS in SMR based merchant H₂ production with NG as feedstock and fuel. *Energy Procedia*, 2017, 114: 2690–2712
 26. Stenberg V, Rydén M, Mattisson T, et al. Exploring novel hydrogen production processes by integration of steam methane reforming with chemical-looping combustion (CLC-SMR) and oxygen carrier aided combustion (OCAC-SMR). *International Journal of Greenhouse Gas Control*, 2018, 74: 28–39
 27. Yan Y, Manovic V, Anthony E J, et al. Techno-economic analysis of low-carbon hydrogen production by sorption enhanced steam methane reforming (SE-SMR) processes. *Energy Conversion and Management*, 2020, 226: 113530
 28. Nikolaidis P, Poullikkas A. A comparative overview of hydrogen production processes. *Renewable & Sustainable Energy Reviews*, 2017, 67: 597–611
 29. van der Spek M, Fout T, Garcia M, et al. Uncertainty analysis in the techno-economic assessment of CO₂ capture and storage technologies. *Critical review and guidelines for use*. *International Journal of Greenhouse Gas Control*, 2020, 100: 103113
 30. Carapellucci R, Giordano L. Steam, dry and autothermal methane reforming for hydrogen production: A thermodynamic equilibrium analysis. *Journal of Power Sources*, 2020, 469: 228391
 31. Chen H L, Lee H M, Chen S H, et al. Review of plasma catalysis on hydrocarbon reforming for hydrogen production—interaction, integration, and prospects. *Applied Catalysis B: Environmental*, 2008, 85(1–2): 1–9
 32. LeValley T L, Richard A R, Fan M. The progress in water gas shift and steam reforming hydrogen production technologies—A review. *International Journal of Hydrogen Energy*, 2014, 39(30): 16983–17000
 33. Liu C, Ye J, Jiang J, et al. Progresses in the preparation of coke resistant Ni-based catalyst for steam and CO₂ reforming of methane. *ChemCatChem*, 2011, 3(3): 529–541
 34. Yoo J, Bang Y, Han S J, et al. Hydrogen production by tri-reforming of methane over nickel–alumina aerogel catalyst. *Journal of Molecular Catalysis A Chemical*, 2015, 410: 74–80
 35. Ersöz A. Investigation of hydrocarbon reforming processes for micro-cogeneration systems. *International Journal of Hydrogen Energy*, 2008, 33(23): 7084–7094
 36. Scipioni A, Manzardo A, Ren J. *Hydrogen Economy: Supply Chain, Life Cycle Analysis and Energy Transition for Sustainability*. Academic Press, 2017
 37. Steinberg M, Cheng H C. Modern and prospective technologies for hydrogen production from fossil fuels. *International Journal of Hydrogen Energy*, 1989, 14(11): 797–820
 38. Faye O, Szpunar J, Eduok U. A critical review on the current technologies for the generation, storage, and transportation of hydrogen. *International Journal of Hydrogen Energy*, 2022,

- 47(29): 13771–13802
39. Holladay J D, Hu J, King D L, et al. An overview of hydrogen production technologies. *Catalysis Today*, 2009, 139(4): 244–260
 40. Dai H, Zhu H. Enhancement of partial oxidation reformer by the free-section addition for hydrogen production. *Renewable Energy*, 2022, 190: 425–433
 41. Caudal J, Fiorina B, Labégorre B, et al. Modeling interactions between chemistry and turbulence for simulations of partial oxidation processes. *Fuel Processing Technology*, 2015, 134: 231–242
 42. Jahromi A F, Ruiz-López E, Dorado F, et al. Electrochemical promotion of ethanol partial oxidation and reforming reactions for hydrogen production. *Renewable Energy*, 2022, 183: 515–523
 43. Bartels J R, Pate M B, Olson N K. An economic survey of hydrogen production from conventional and alternative energy sources. *International Journal of Hydrogen Energy*, 2010, 35(16): 8371–8384
 44. De Falco L, Marrelli L, Laquaniello G. *Membrane Reactors for Hydrogen Production Processes*. London: Springer, 2011
 45. Lattner J R, Harold M P. Comparison of conventional and membrane reactor fuel processors for hydrocarbon-based PEM fuel cell systems. *International Journal of Hydrogen Energy*, 2004, 29(4): 393–417
 46. Kim J, Park J, Qi M, et al. Process integration of an autothermal reforming hydrogen production system with cryogenic air separation and carbon dioxide capture using liquefied natural gas cold energy. *Industrial & Engineering Chemistry Research*, 2021, 60(19): 7257–7274
 47. Damen K, van Troost M, Faaij A, et al. A comparison of electricity and hydrogen production systems with CO₂ capture and storage. Part A: Review and selection of promising conversion and capture technologies. *Progress in Energy and Combustion Science*, 2006, 32(2): 215–246
 48. Demirbaş A. Biomass resource facilities and biomass conversion processing for fuels and chemicals. *Energy Conversion and Management*, 2001, 42(11): 1357–1378
 49. Krishnamoorthy V, Pisupati S V. A critical review of mineral matter related issues during gasification of coal in fixed, fluidized, and entrained flow gasifiers. *Energies*, 2015, 8(9): 10430–10463
 50. Jiang L, Chen Z, Farouq Ali S M. Thermal-hydro-chemical-mechanical alteration of coal pores in underground coal gasification. *Fuel*, 2020, 262: 116543
 51. Ma H, Chen S, Xue D, et al. Outlook for the coal industry and new coal production technologies. *Advances in Geo-Energy Research*, 2021, 5(2): 119–120
 52. Jiang L, Xue D, Wei Z, et al. Coal decarbonization: a state-of-the-art review of enhanced hydrogen production in underground coal gasification. *Energy Reviews*, 2022, 1(1): 100004
 53. Perkins G. Underground coal gasification—Part I: Field demonstrations and process performance. *Progress in Energy and Combustion Science*, 2018, 67: 158–187
 54. Weger L, Abánades A, Butler T. Methane cracking as a bridge technology to the hydrogen economy. *International Journal of Hydrogen Energy*, 2017, 42(1): 720–731
 55. Schneider S, Bajohr S, Graf F, et al. State of the art of hydrogen production via pyrolysis of natural gas. *ChemBioEng Reviews*, 2020, 7(5): 150–158
 56. Plevan M, Geißler T, Abánades A, et al. Thermal cracking of methane in a liquid metal bubble column reactor: Experiments and kinetic analysis. *International Journal of Hydrogen Energy*, 2015, 40(25): 8020–8033
 57. Geißler T, Abánades A, Heinzel A, et al. Hydrogen production via methane pyrolysis in a liquid metal bubble column reactor with a packed bed. *Chemical Engineering Journal*, 2016, 299: 192–200
 58. Sánchez-Bastardo N, Schlögl R, Ruland H. Methane pyrolysis for CO₂-free H₂ production: A green process to overcome renewable energies unsteadiness. *Chemieingenieurtechnik (Weinheim)*, 2020, 92(10): 1596–1609
 59. Ashik U P M, Wan Daud W M A, Abbas H F. Production of greenhouse gas free hydrogen by thermocatalytic decomposition of methane—A review. *Renewable & Sustainable Energy Reviews*, 2015, 44: 221–256
 60. Amin A M, Croiset E, Epling W. Review of methane catalytic cracking for hydrogen production. *International Journal of Hydrogen Energy*, 2011, 36(4): 2904–2935
 61. Dagle R A, Dagle V, Bearden M D, et al. An Overview of Natural Gas Conversion Technologies for Co-production of Hydrogen and Value-added Solid Carbon Products. Technical Report, USDOE Office of Energy Efficiency and Renewable Energy, 2017
 62. Guéret C, Daroux M, Billaud F. Methane pyrolysis: thermodynamics. *Chemical Engineering Science*, 1997, 52(5): 815–827
 63. Muradov N, Veziroğlu T. From hydrocarbon to hydrogen-carbon to hydrogen economy. *International Journal of Hydrogen Energy*, 2005, 30(3): 225–237
 64. Gautier M, Rohani V, Fulcheri L. Direct decarbonization of methane by thermal plasma for the production of hydrogen and high value-added carbon black. *International Journal of Hydrogen Energy*, 2017, 42(47): 28140–28156
 65. Bakken J A, Jensen R, Monsen B, et al. Thermal plasma process development in Norway. *Pure and Applied Chemistry*, 1998, 70(6): 1223–1228
 66. Gaudernack B, Lynum S. Hydrogen from natural gas without release of CO₂ to the atmosphere. *International Journal of Hydrogen Energy*, 1998, 23(12): 1087–1093
 67. Pudukudy M, Yaakob Z, Takriff M S. Methane decomposition over unsupported mesoporous nickel ferrites: Effect of reaction temperature on the catalytic activity and properties of the produced nanocarbon. *RSC Advances*, 2016, 6(72): 68081–68091
 68. Lee K K, Han G Y, Yoon K J, et al. Thermocatalytic hydrogen production from the methane in a fluidized bed with activated carbon catalyst. *Catalysis Today*, 2004, 93–95: 81–86
 69. Dunker A M, Kumar S, Mulawa P A. Production of hydrogen by thermal decomposition of methane in a fluidized-bed reactor—Effects of catalyst, temperature, and residence time. *International Journal of Hydrogen Energy*, 2006, 31(4): 473–484

70. Keipi T, Tolvanen H, Konttinen J. Economic analysis of hydrogen production by methane thermal decomposition: comparison to competing technologies. *Energy Conversion and Management*, 2018, 159: 264–273
71. Gatica J M, Cifredo G A, Blanco G, et al. Unveiling the source of activity of carbon integral honeycomb monoliths in the catalytic methane decomposition reaction. *Catalysis Today*, 2015, 249: 86–93
72. Gatica J M, Gómez D M, Harti S, et al. Monolithic honeycomb design applied to carbon materials for catalytic methane decomposition. *Applied Catalysis A, General*, 2013, 458: 21–27
73. Serban M, Lewis M A, Marshall C L, et al. Hydrogen production by direct contact pyrolysis of natural gas. *Energy & Fuels*, 2003, 17(3): 705–713
74. Geißler T, Plevan M, Abánades A, et al. Experimental investigation and thermo-chemical modeling of methane pyrolysis in a liquid metal bubble column reactor with a packed bed. *International Journal of Hydrogen Energy*, 2015, 40(41): 14134–14146
75. Kang D, Rahimi N, Gordon M J, et al. Catalytic methane pyrolysis in molten $\text{MnCl}_2\text{-KCl}$. *Applied Catalysis B: Environmental*, 2019, 254: 659–666
76. Palmer C, Tarazkar M, Kristoffersen H H, et al. Methane pyrolysis with a molten Cu–Bi alloy catalyst. *ACS Catalysis*, 2019, 9(9): 8337–8345
77. Upham D C, Agarwal V, Khechfe A, et al. Catalytic molten metals for the direct conversion of methane to hydrogen and separable carbon. *Science*, 2017, 358(6365): 917–921
78. Pudukudy M, Yaakob Z, Jia Q, et al. Catalytic decomposition of undiluted methane into hydrogen and carbon nanotubes over Pt promoted Ni/CeO₂ catalysts. *New Journal of Chemistry*, 2018, 42(18): 14843–14856
79. Bayat N, Rezaei M, Meshkani F. CO_x-free hydrogen and carbon nanofibers production by methane decomposition over nickel-alumina catalysts. *Korean Journal of Chemical Engineering*, 2016, 33(2): 490–499
80. Bayat N, Rezaei M, Meshkani F. Hydrogen and carbon nanofibers synthesis by methane decomposition over Ni–Pd/Al₂O₃ catalyst. *International Journal of Hydrogen Energy*, 2016, 41(12): 5494–5503
81. Fakeeha A H, Ibrahim A A, Khan W U, et al. Hydrogen production via catalytic methane decomposition over alumina supported iron catalyst. *Arabian Journal of Chemistry*, 2018, 11(3): 405–414
82. Avdeeva L B, Reshetenko T V, Ismagilov Z R, et al. Iron-containing catalysts of methane decomposition: Accumulation of filamentous carbon. *Applied Catalysis A, General*, 2002, 228(1–2): 53–63
83. Ayillath Kutteri D, Wang I W, Samanta A, et al. Methane decomposition to tip and base grown carbon nanotubes and CO_x-free H₂ over mono- and bimetallic 3d transition metal catalysts. *Catalysis Science & Technology*, 2018, 8(3): 858–869
84. Silva R R, Oliveira H A, Guarino A C P F, et al. Effect of support on methane decomposition for hydrogen production over cobalt catalysts. *International Journal of Hydrogen Energy*, 2016, 41(16): 6763–6772
85. Pinilla J, Suelves I, Lázaro M, et al. Influence on hydrogen production of the minor components of natural gas during its decomposition using carbonaceous catalysts. *Journal of Power Sources*, 2009, 192(1): 100–106
86. Zhang J, Li X, Chen H, et al. Hydrogen production by catalytic methane decomposition: Carbon materials as catalysts or catalyst supports. *International Journal of Hydrogen Energy*, 2017, 42(31): 19755–19775
87. Fidalgo B, Muradov N, Menéndez J. Effect of H₂S on carbon-catalyzed methane decomposition and CO₂ reforming reactions. *International Journal of Hydrogen Energy*, 2012, 37(19): 14187–14194
88. Guil-Lopez R, Botas J, Fierro J, et al. Comparison of metal and carbon catalysts for hydrogen production by methane decomposition. *Applied Catalysis A, General*, 2011, 396(1–2): 40–51
89. Abánades A, Rubbia C, Salmieri D. Thermal cracking of methane into Hydrogen for a CO₂-free utilization of natural gas. *International Journal of Hydrogen Energy*, 2013, 38(20): 8491–8496
90. Ermakova M, Ermakov D Y. Ni/SiO₂ and Fe/SiO₂ catalysts for production of hydrogen and filamentous carbon via methane decomposition. *Catalysis Today*, 2002, 77(3): 225–235
91. Ouyang M, Boldrin P, Maher R C, et al. A mechanistic study of the interactions between methane and nickel supported on doped ceria. *Applied Catalysis B: Environmental*, 2019, 248: 332–340
92. Bayat N, Rezaei M, Meshkani F. Methane decomposition over Ni–Fe/Al₂O₃ catalysts for production of CO_x-free hydrogen and carbon nanofiber. *International Journal of Hydrogen Energy*, 2016, 41(3): 1574–1584
93. Rastegarpanah A, Rezaei M, Meshkani F, et al. Influence of group VIB metals on activity of the Ni/MgO catalysts for methane decomposition. *Applied Catalysis B: Environmental*, 2019, 248: 515–525
94. Bayat N, Meshkani F, Rezaei M. Thermocatalytic decomposition of methane to CO_x-free hydrogen and carbon over Ni–Fe–Cu/Al₂O₃ catalysts. *International Journal of Hydrogen Energy*, 2016, 41(30): 13039–13049
95. Al-Fatesh A S, Fakeeha A H, Ibrahim A A, et al. Decomposition of methane over alumina supported Fe and Ni–Fe bimetallic catalyst: Effect of preparation procedure and calcination temperature. *Journal of Saudi Chemical Society*, 2018, 22(2): 239–247
96. Moliner R, Suelves I, Lázaro M, et al. Thermocatalytic decomposition of methane over activated carbons: Influence of textural properties and surface chemistry. *International Journal of Hydrogen Energy*, 2005, 30(3): 293–300
97. Lee E K, Lee S Y, Han G Y, et al. Catalytic decomposition of methane over carbon blacks for CO₂-free hydrogen production. *Carbon*, 2004, 42(12–13): 2641–2648
98. Takenaka S, Ogihara H, Yamanaka I, et al. Decomposition of methane over supported-Ni catalysts: Effects of the supports on the catalytic lifetime. *Applied Catalysis A, General*, 2001, 217(1–2): 101–110
99. Zhang J, Li X, Xie W, et al. K₂CO₃-promoted methane pyrolysis on nickel/coal-char hybrids. *Journal of Analytical and Applied*

- Pyrolysis, 2018, 136: 53–61
100. Parkinson B, Tabatabaei M, Upham D C, et al. Hydrogen production using methane: techno-economics of decarbonizing fuels and chemicals. *International Journal of Hydrogen Energy*, 2018, 43(5): 2540–2555
 101. Abánades A, Ruiz E, Ferruelo E M, et al. Experimental analysis of direct thermal methane cracking. *International Journal of Hydrogen Energy*, 2011, 36(20): 12877–12886
 102. Abánades A, Rathnam R K, Geißler T, et al. Development of methane decarbonisation based on liquid metal technology for CO₂-free production of hydrogen. *International Journal of Hydrogen Energy*, 2016, 41(19): 8159–8167
 103. Zhou L, Enakonda L R, Li S, et al. Iron ore catalysts for methane decomposition to make CO_x free hydrogen and carbon nano material. *Journal of the Taiwan Institute of Chemical Engineers*, 2018, 87: 54–63
 104. Pudukudy M, Yaakob Z. Methane decomposition over Ni, Co and Fe based monometallic catalysts supported on sol gel derived SiO₂ microflakes. *Chemical Engineering Journal*, 2015, 262: 1009–1021
 105. Ermakova M, Ermakov D Y, Kuvshinov G. Effective catalysts for direct cracking of methane to produce hydrogen and filamentous carbon: Part I. Nickel catalysts. *Applied Catalysis A, General*, 2000, 201(1): 61–70
 106. Al-Fatesh A S, Amin A, Ibrahim A, et al. Effect of Ce and Co addition to Fe/Al₂O₃ for catalytic methane decomposition. *Catalysts*, 2016, 6(3): 40
 107. Wang J, Jin L, Li Y, et al. Preparation of Fe-doped carbon catalyst for methane decomposition to hydrogen. *Industrial & Engineering Chemistry Research*, 2017, 56(39): 11021–11027
 108. Zhou L, Enakonda L R, Saih Y, et al. Catalytic methane decomposition over Fe-Al₂O₃. *ChemSusChem*, 2016, 9(11): 1243–1248
 109. Cunha A, Órfão J, Figueiredo J. Methane decomposition on Fe–Cu Raney-type catalysts. *Fuel Processing Technology*, 2009, 90(10): 1234–1240
 110. Schultz I, Agar D W. Decarbonisation of fossil energy via methane pyrolysis using two reactor concepts: Fluid wall flow reactor and molten metal capillary reactor. *International Journal of Hydrogen Energy*, 2015, 40(35): 11422–11427
 111. Postels S, Abánades A, von der Assen N, et al. Life cycle assessment of hydrogen production by thermal cracking of methane based on liquid-metal technology. *International Journal of Hydrogen Energy*, 2016, 41(48): 23204–23212
 112. Voll M, Kleinschmit P. Carbon, 6. Carbon Black. In: Elvers B, eds. *Ullmann's Encyclopedia of Industrial Chemistry*. Hoboken: Wiley-VCH Verlag GmbH & Co, 2000
 113. Fau G, Gascoin N, Gillard P, et al. Methane pyrolysis: literature survey and comparisons of available data for use in numerical simulations. *Journal of Analytical and Applied Pyrolysis*, 2013, 104: 1–9
 114. International Energy Agency. *Global Energy & CO₂ Status Report 2019*. Technical Report, IEA, 2019
 115. International Energy Agency. *The Future of Hydrogen*. Technical Report, IEA, 2019
 116. International Energy Agency. *Achieving Net Zero Heavy Industry Sectors in G7 Members*. Technical Report, IEA, 2022
 117. White C M, Strazisar B R, Granite E J, et al. Separation and capture of CO₂ from large stationary sources and sequestration in geological formations—coalbeds and deep saline aquifers. *Journal of the Air & Waste Management Association*, 2003, 53(6): 645–715
 118. Riahi K, Rubin E S, Schratzenholzer L. Prospects for carbon capture and sequestration technologies assuming their technological learning. *Energy*, 2004, 29(9–10): 1309–1318
 119. Davidson O, Metz B. *Special Report on Carbon Dioxide Capture and Storage*. Technical Report, IPCC, 2005
 120. Middleton, R, Ogland-Hand J, et al. Identifying geologic characteristics and operational decisions to meet global carbon sequestration goals. *Energy & Environmental Science*, 2020, 13(12): 5000–5016
 121. Chaffee A L, Knowles G P, Liang Z, et al. CO₂ capture by adsorption: materials and process development. *International Journal of Greenhouse Gas Control*, 2007, 1(1): 11–18
 122. Bachu S, Bonijoly D, Bradshaw J, et al. CO₂ storage capacity estimation: methodology and gaps. *International Journal of Greenhouse Gas Control*, 2007, 1(4): 43–443
 123. Faltinson J, Gunter B. Integrated economic model CO₂ capture, transport, ECBM and saline aquifer storage. *Energy Procedia*, 2009, 1(1): 4001–4005
 124. MacDowell N, Florin N, Buchard A, et al. An overview of CO₂ capture technologies. *Energy & Environmental Science*, 2010, 3(11): 1645
 125. Yu C H, Huang C H, Tan C S. A review of CO₂ capture by absorption and adsorption. *Aerosol and Air Quality Research*, 2012, 12(5): 745–769
 126. Morgan M G, McCoy S T. *Carbon Capture and Sequestration: Removing the Legal and Regulatory Barriers*. New York: Routledge, 2012
 127. Espinal L, Poster D L, Wong-Ng W, et al. Measurement, standards, and data needs for CO₂ capture materials: A critical review. *Environmental Science & Technology*, 2013, 47(21): 11960–11975
 128. Rubin E S, Short C, Booras G, et al. A proposed methodology for CO₂ capture and storage cost estimates. *International Journal of Greenhouse Gas Control*, 2013, 17: 488–503
 129. Zhang X, Fan J L, Wei Y M. Technology roadmap study on carbon capture, utilization and storage in China. *Energy Policy*, 2013, 59: 536–550
 130. Leung D Y C, Caramanna G, Maroto-Valer M M. An overview of current status of carbon dioxide capture and storage technologies. *Renewable & Sustainable Energy Reviews*, 2014, 39: 426–443
 131. Allinson W G G, Cinar Y, Neal P R R, et al. CO₂-storage capacity—Combining geology, engineering and economics. *SPE Economics & Management*, 2014, 6(1): 15–27
 132. Ma H, Yang Y, Zhang Y, et al. Optimized schemes of enhanced shale gas recovery by CO₂-N₂ mixtures associated with CO₂ sequestration. *Energy Conversion and Management*, 2022, 268: 116062
 133. Ma H, McCoy S, Chen Z. Economic and engineering co-optimization of CO₂ storage and enhanced oil recovery. In:

- Proceedings of the 16th Greenhouse Gas Control Technologies Conference, Lyon, France, 2022
134. International Energy Agency. Global Energy and CO₂ Status Report 2018. Technical Report, IEA, 2018
 135. Global CCS Institute. Global Status of CCS 2020. Technical Report, Global CCS Institute, 2020
 136. British Petroleum. Statistical Review of World Energy 2021. Technical Report, BP, 2021
 137. Bui M, Adjiman C S, Bardow A, et al. Carbon capture and storage (CCS): The way forward. *Energy & Environmental Science*, 2018, 11(5): 1064–1065
 138. Intergovernmental Panel on Climate Change. Future Global Climate: Scenario-based Projections and Near Term Information. Technical Report, IPCC, 2021
 139. International Renewable Energy Agency. World Energy Transitions Outlook. Technical Report, IRENA, 2022
 140. International Renewable Energy Agency. Hydrogen: A Renewable Energy Perspective. Technical Report, IRENA, 2019
 141. Song C, Liu Q, Ji N, et al. Alternative pathways for efficient CO₂ capture by hybrid processes—A review. *Renewable & Sustainable Energy Reviews*, 2018, 82: 215–231
 142. Wang X, Song C. Carbon capture from flue gas and the atmosphere: A perspective. *Frontiers in Energy Research*, 2020, 8: 560849
 143. Evans T, Grynia E. Carbon capture—purpose and technologies. 2020, available at website of gasliquids
 144. Sekera J, Lichtenberger A. Assessing carbon capture: Public policy, science, and societal need. *Biophysical Economics and Sustainability*, 2020, 5(3): 14
 145. Wei Y M, Kang J N, Liu L C, et al. A proposed global layout of carbon capture and storage in line with a 2 °C climate target. *Nature Climate Change*, 2021, 11(2): 112–118
 146. Becattini V, Gabrielli P, Mazzotti M. Role of carbon capture, storage, and utilization to enable a net-zero-CO₂-emissions aviation sector. *Industrial & Engineering Chemistry Research*, 2021, 60(18): 6848–6862
 147. Zhang K, Bokka H K, Lau H C. Decarbonizing the energy and industry sectors in Thailand by carbon capture and storage. *Journal of Petroleum Science Engineering*, 2022, 209: 109979
 148. Hao Z, Barecka M H, Lapkin A A. Accelerating net zero from the perspective of optimizing a carbon capture and utilization system. *Energy & Environmental Science*, 2022, 15(5): 2139–2153
 149. Brandl P, Bui M, Hallett J P, et al. Beyond 90% capture: Possible, but at what cost? *International Journal of Greenhouse Gas Control*, 2021, 105: 103239
 150. Ostovari H, Muller L, Skoceck J, et al. From unavoidable CO₂ source to CO₂ sink? A cement industry based on CO₂ mineralization. *Environmental Science & Technology*, 2021, 55(8): 5212–5223
 151. Sun S, Sun H, Williams P T, et al. Recent advances in integrated CO₂ capture and utilization: A review. *Sustainable Energy & Fuels*, 2021, 5(18): 4546–4559
 152. Wang N, Akimoto K, Nemet G F. What went wrong? Learning from three decades of carbon capture, utilization and sequestration (CCUS) pilot and demonstration projects. *Energy Policy*, 2021, 158: 112546
 153. Hanein T, Simoni M, Woo C L, et al. Decarbonisation of calcium carbonate at atmospheric temperatures and pressures, with simultaneous CO₂ capture, through production of sodium carbonate. *Energy & Environmental Science*, 2021, 14(12): 6595–6604
 154. Subraveti S G, Roussanaly S, Anantharaman R, et al. How much can novel solid sorbents reduce the cost of post-combustion CO₂ capture? A techno-economic investigation on the cost limits of pressure–vacuum swing adsorption. *Applied Energy*, 2022, 306: 117955
 155. Mohsin I, Al-Attas T A, Sumon K Z, et al. Economic and environmental assessment of integrated carbon capture and utilization. *Cell Reports Physical Science*, 2020, 1(7): 100104
 156. Dake L P. *Fundamentals of Reservoir Engineering*. Elsevier Science, 1983
 157. Balogun H A, Bahamon D, AlMenhali S, et al. Are we missing something when evaluating adsorbents for CO₂ capture at the system level? *Energy & Environmental Science*, 2021, 14(12): 6360–6380
 158. Dixon J, Bell K, Brush S. Which way to net zero? A comparative analysis of seven UK 2050 decarbonisation pathways. *Renewable and Sustainable Energy Transition*, 2022, 2: 100016
 159. Adams B, Sutter D, Mazzotti M, et al. Combining direct air capture and geothermal heat and electricity generation for net-negative carbon dioxide emissions. In: *Proceedings of the World Geothermal Congress*, Reykjavik, Iceland, 2020
 160. Deutz S, Bardow A. Life-cycle assessment of an industrial direct air capture process based on temperature–vacuum swing adsorption. *Nature Energy*, 2021, 6(2): 203–213
 161. McQueen N, Gomes K V, McCormick C, et al. A review of direct air capture (DAC): Scaling up commercial technologies and innovating for the future. *Progress in Energy*, 2021, 3(3): 032001
 162. McQueen N, Desmond M J, Socolow R H, et al. Natural gas vs. electricity for solvent-based direct air capture. *Frontiers in Climate*, 2021, 2: 618644
 163. Bistline J E T, Blanford G J. Impact of carbon dioxide removal technologies on deep decarbonization of the electric power sector. *Nature Communications*, 2021, 12(1): 3732
 164. Terlouw T, Treyer K, Bauer C, et al. Life cycle assessment of direct air carbon capture and storage with low-carbon energy sources. *Environmental Science & Technology*, 2021, 55(16): 11397–11411
 165. Erans M, Sanz-Pérez E S, Hanak D P, et al. Direct air capture: process technology, techno-economic and socio-political challenges. *Energy & Environmental Science*, 2022, 15(4): 1360–1405
 166. International Energy Agency. *Direct Air Capture*. Technical Report, IEA, 2022
 167. McQueen N, Psarras P, Pilorgé H, et al. Cost analysis of direct air capture and sequestration coupled to low-carbon thermal energy in the United States. *Environmental Science & Technology*, 2020, 54(12): 7542–7551
 168. International Energy Agency. *Canada 2022*. Technical Report,

- IEA, 2022
169. Congressional Research Service. The Tax Credit for Carbon Sequestration (Section 45Q). Technical Report, CRS, 2021
 170. Collidi G. Reference Data and Supporting Literature Reviews for SMR Based Hydrogen Production with CCS. Technical Report, IEAGHG, 2017
 171. Mathiesen B V, Lund H, Karlsson K. 100% renewable energy systems, climate mitigation and economic growth. *Applied Energy*, 2011, 88(2): 488–501
 172. Flamos A, Georgallis P, Doukas H, et al. Using biomass to achieve European Union Energy Targets—A review of biomass status, potential, and supporting policies. *International Journal of Green Energy*, 2011, 8(4): 411–428
 173. Demirbaş A. Yields of hydrogen-rich gaseous products via pyrolysis from selected biomass samples. *Fuel*, 2001, 80(13): 1885–1891
 174. Parthasarathy P, Narayanan K S. Hydrogen production from steam gasification of biomass: influence of process parameters on hydrogen yield—A review. *Renewable Energy*, 2014, 66: 570–579
 175. Fremaux S, Beheshti S M, Ghassemi H, et al. An experimental study on hydrogen-rich gas production via steam gasification of biomass in a research-scale fluidized bed. *Energy Conversion and Management*, 2015, 91: 427–432
 176. Balat M. Hydrogen-rich gas production from biomass via pyrolysis and gasification processes and effects of catalyst on hydrogen yield. *Energy Sources. Part A, Recovery, Utilization, and Environmental Effects*, 2008, 30(6): 552–564
 177. Ni M, Leung D Y, Leung M K, et al. An overview of hydrogen production from biomass. *Fuel Processing Technology*, 2006, 87(5): 461–472
 178. Godula-Jopek A. Hydrogen Production: By Electrolysis. John Wiley & Sons, 2015
 179. Rakousky C, Reimer U, Wippermann K, et al. Polymer electrolyte membrane water electrolysis: Restraining degradation in the presence of fluctuating power. *Journal of Power Sources*, 2017, 342: 38–47
 180. Khan M A, Al-Attas T, Roy S, et al. Seawater electrolysis for hydrogen production: A solution looking for a problem? *Energy & Environmental Science*, 2021, 14(9): 4831–4839
 181. Zhang Y, Ying Z, Zhou J, et al. Electrolysis of the Bunsen reaction and properties of the membrane in the sulfur–iodine thermochemical cycle. *Industrial & Engineering Chemistry Research*, 2014, 53(35): 13581–13588
 182. Rossmeisl J, Logadottir A, Nørskov J K. Electrolysis of water on (oxidized) metal surfaces. *Chemical Physics*, 2005, 319(1–3): 178–184
 183. Levene J I, Mann M K, Margolis R M, et al. An analysis of hydrogen production from renewable electricity sources. *Solar Energy*, 2007, 81(6): 773–780
 184. Khan S U, Al-Shahry M, Ingler W B Jr. Efficient photochemical water splitting by a chemically modified *n*-TiO₂. *Science*, 2002, 297(5590): 2243–2245
 185. Yan Z, Hitt J L, Turner J A, et al. Renewable electricity storage using electrolysis. *Proceedings of the National Academy of Sciences of the United States of America*, 2020, 117(23): 12558–12563
 186. Chatenet M, Pollet B G, Dekel D R, et al. Water electrolysis: from textbook knowledge to the latest scientific strategies and industrial developments. *Chemical Society Reviews*, 2022, 51(11): 4583–4762
 187. Nnabuiife S G, Ugbeh-Johnson J, Okeke N E, et al. Present and projected developments in hydrogen production: A technological review. *Carbon Capture Science & Technology*, 2022, 100042
 188. Xie H, Zhao Z, Liu T, et al. A membrane-based seawater electrolyser for hydrogen generation. *Nature*, 2022, 612(7941): 673–678
 189. Diéguez P, Ursúa A, Sanchis P, et al. Thermal performance of a commercial alkaline water electrolyzer: Experimental study and mathematical modeling. *International Journal of Hydrogen Energy*, 2008, 33(24): 7338–7354
 190. Zeng K, Zhang D. Recent progress in alkaline water electrolysis for hydrogen production and applications. *Progress in Energy and Combustion Science*, 2010, 36(3): 307–326
 191. Funk J E. Thermochemical hydrogen production: Past and present. *International Journal of Hydrogen Energy*, 2001, 26(3): 185–190
 192. Orhan M F, Dincer I, Rosen M A. Energy and exergy assessments of the hydrogen production step of a copper–chlorine thermochemical water splitting cycle driven by nuclear-based heat. *International Journal of Hydrogen Energy*, 2008, 33(22): 6456–6466
 193. Abanades S, Charvin P, Lemont F, et al. Novel two-step SnO₂/SnO water-splitting cycle for solar thermochemical production of hydrogen. *International Journal of Hydrogen Energy*, 2008, 33(21): 6021–6030
 194. Ratlamwala T, Dincer I. Comparative energy and exergy analyses of two solar-based integrated hydrogen production systems. *International Journal of Hydrogen Energy*, 2015, 40(24): 7568–7578
 195. Schultz K R. Use of the Modular Helium Reactor for Hydrogen Production. General Atomics Report: GA-A24428, 2003
 196. Orhan M, Dincer I, Naterer G. Cost analysis of a thermochemical Cu–Cl pilot plant for nuclear-based hydrogen production. *International Journal of Hydrogen Energy*, 2008, 33(21): 6006–6020
 197. Charvin P, Stéphane A, Florent L, et al. Analysis of solar chemical processes for hydrogen production from water splitting thermochemical cycles. *Energy Conversion and Management*, 2008, 49(6): 1547–1556
 198. Kothari R, Buddhi D, Sawhney R. Comparison of environmental and economic aspects of various hydrogen production methods. *Renewable & Sustainable Energy Reviews*, 2008, 12(2): 553–563
 199. Navarro R M, Pena M, Fierro J. Hydrogen production reactions from carbon feedstocks: Fossil fuels and biomass. *Chemical Reviews*, 2007, 107(10): 3952–3991
 200. Laurinavichene T V, Kosourov S N, Ghirardi M L, et al. Prolongation of H₂ photoproduction by immobilized, sulfur-limited *Chlamydomonas reinhardtii* cultures. *Journal of Biotechnology*, 2008, 134(3–4): 275–277

201. Kovács K L, Maróti G, Rákhely G. A novel approach for biohydrogen production. *International Journal of Hydrogen Energy*, 2006, 31(11): 1460–1468
202. Bak T, Nowotny J, Rekas M, et al. Photo-electrochemical properties of the TiO₂-Pt system in aqueous solutions. *International Journal of Hydrogen Energy*, 2002, 27(1): 19–26
203. Aroutiounian V, Arakelyan V, Shahnazaryan G. Metal oxide photoelectrodes for hydrogen generation using solar radiation-driven water splitting. *Solar Energy*, 2005, 78(5): 581–592
204. Akikusa J, Khan S U. Photoelectrolysis of water to hydrogen in *p*-SiC/Pt and *p*-SiC/*n*-TiO₂ cells. *International Journal of Hydrogen Energy*, 2002, 27(9): 863–870
205. Ibrahim M N M, Koederitz L F. Two-phase relative permeability prediction using a linear regression model. In: SPE Eastern Regional Meeting, West Virginia, USA, 2000
206. Züttel A. Materials for hydrogen storage. *Materials Today*, 2003, 6(9): 24–33
207. Ogden J, Jaffe A M, Scheitrum D, et al. Natural gas as a bridge to hydrogen transportation fuel: Insights from the literature. *Energy Policy*, 2018, 115: 317–329
208. Conte M, Iacobazzi A, Ronchetti M, et al. Hydrogen economy for a sustainable development: State-of-the-art and technological perspectives. *Journal of Power Sources*, 2001, 100(1–2): 171–187
209. Krishna R, Titus E, Salimian M, et al. Hydrogen storage for energy application. In: LIU J, eds. *Hydrogen Storage*. London: IntechOpen, 2012
210. Barthélémy H, Weber M, Barbier F. Hydrogen storage: recent improvements and industrial perspectives. *International Journal of Hydrogen Energy*, 2017, 42(11): 7254–7262
211. Okada Y, Sasaki E, Watanabe E, et al. Development of dehydrogenation catalyst for hydrogen generation in organic chemical hydride method. *International Journal of Hydrogen Energy*, 2006, 31(10): 1348–1356
212. Lan R, Irvine J T S, Tao S. Ammonia and related chemicals as potential indirect hydrogen storage materials. *International Journal of Hydrogen Energy*, 2012, 37(2): 1482–1494
213. He T, Pei Q, Chen P. Liquid organic hydrogen carriers. *Journal of Energy Chemistry*, 2015, 24(5): 587–594
214. Clot E, Eisenstein O, Crabtree R H. Computational structure–activity relationships in H₂ storage: How placement of N atoms affects release temperatures in organic liquid storage materials. *Chemical Communications (Cambridge)*, 2007(22), 2231–2233
215. Forberg D, Schwob T, Zaheer M, et al. Single-catalyst high-weight% hydrogen storage in an N-heterocycle synthesized from lignin hydrogenolysis products and ammonia. *Nature Communications*, 2016, 7(1): 13201
216. Fujita K i, Tanaka Y, Kobayashi M, et al. Homogeneous perdehydrogenation and perhydrogenation of fused bicyclic N-heterocycles catalyzed by iridium complexes bearing a functional bipyridonate ligand. *Journal of the American Chemical Society*, 2014, 136(13): 4829–4832
217. Luo W, Zakharov L N, Liu S Y. 1, 2-BN cyclohexane: Synthesis, structure, dynamics, and reactivity. *Journal of the American Chemical Society*, 2011, 133(33): 13006–13009
218. Luo W, Campbell P G, Zakharov L N, et al. A single-component liquid-phase hydrogen storage material. *Journal of the American Chemical Society*, 2011, 133(48): 19326–19329
219. Brückner N, Obesser K, Bösmann A, et al. Evaluation of Industrially applied heat-transfer fluids as liquid organic hydrogen carrier systems. *ChemSusChem*, 2014, 7(1): 229–235
220. Enthaler S, von Langermann J, Schmidt T. Carbon dioxide and formic acid—The couple for environmental-friendly hydrogen storage? *Energy & Environmental Science*, 2010, 3(9): 1207–1217
221. Grasemann M, Laurenczy G. Formic acid as a hydrogen source—recent developments and future trends. *Energy & Environmental Science*, 2012, 5(8): 8171–8181
222. Veziroglu T N, Zaginachenko S Y, Schur D V, et al. Hydrogen materials science and chemistry of carbon nanomaterials. In: *Proceedings of the NATO Advanced Research Workshop on Hydrogen Materials Science and Chemistry of Carbon Nanomaterials*, Sudak, 2006
223. Babarit A, Gilloteaux J C, Clodic G, et al. Techno-economic feasibility of fleets of far offshore hydrogen-producing wind energy converters. *International Journal of Hydrogen Energy*, 2018, 43(15): 7266–7289
224. Blackstock E. Kawasaki launches the world's first liquid hydrogen transport ship. 2019-12-15, available at website of newatlas
225. Pan B, Yin X, Ju Y, et al. Underground hydrogen storage: influencing parameters and future outlook. *Advances in Colloid and Interface Science*, 2021, 294: 102473
226. Zheng J, Liu X, Xu P, et al. Development of high pressure gaseous hydrogen storage technologies. *International Journal of Hydrogen Energy*, 2012, 37(1): 1048–1057
227. Zhou L. Progress and problems in hydrogen storage methods. *Renewable & Sustainable Energy Reviews*, 2005, 9(4): 395–408
228. Sakintuna B, Lamari-Darkrim F, Hirscher M. Metal hydride materials for solid hydrogen storage: a review. *International Journal of Hydrogen Energy*, 2007, 32(9): 1121–1140
229. Schulz R, Huot J, Liang G X, et al. Structure and hydrogen sorption properties of ball milled Mg dihydride. *Journal of Metastable and Nanocrystalline Materials*, 1999, 2: 615–622
230. Niaz S, Manzoor T, Pandith A H. Hydrogen storage: Materials, methods and perspectives. *Renewable & Sustainable Energy Reviews*, 2015, 50: 457–469
231. David E. An overview of advanced materials for hydrogen storage. *Journal of Materials Processing Technology*, 2005, 162–163: 169–177
232. Grochala W, Edwards P P. Thermal decomposition of the non-interstitial hydrides for the storage and production of hydrogen. *Chemical Reviews*, 2004, 104(3): 1283–1316
233. Huot J, Liang G, Boily S, et al. Structural study and hydrogen sorption kinetics of ball-milled magnesium hydride. *Journal of Alloys and Compounds*, 1999, 293–295: 495–500
234. Darkrim F L, Malbrunot P, Tartaglia G. Review of hydrogen storage by adsorption in carbon nanotubes. *International Journal of Hydrogen Energy*, 2002, 27(2): 193–202
235. Darkrim F, Levesque D. High adsorptive property of opened carbon nanotubes at 77 K. *Journal of Physical Chemistry B*,

- 2000, 104(29): 6773–6776
236. Dillon A, Heben M. Hydrogen storage using carbon adsorbents: past, present and future. *Applied Physics. A, Materials Science & Processing*, 2001, 72(2): 133–142
 237. Chen P, Wu X, Lin J, et al. High H₂ uptake by alkali-doped carbon nanotubes under ambient pressure and moderate temperatures. *Science*, 1999, 285(5424): 91–93
 238. Chen C H, Huang C C. Hydrogen storage by KOH-modified multi-walled carbon nanotubes. *International Journal of Hydrogen Energy*, 2007, 32(2): 237–246
 239. Zhao Q, Yuan W, Liang J, et al. Synthesis and hydrogen storage studies of metal–organic framework UiO-66. *International Journal of Hydrogen Energy*, 2013, 38(29): 13104–13109
 240. Li J, Cheng S, Zhao Q, et al. Synthesis and hydrogen-storage behavior of metal–organic framework MOF-5. *International Journal of Hydrogen Energy*, 2009, 34(3): 1377–1382
 241. Xia L, Liu Q, Wang F, et al. Improving the hydrogen storage properties of metal-organic framework by functionalization. *Journal of Molecular Modeling*, 2016, 22(10): 254
 242. Bobbitt N S, Chen J, Snurr R Q. High-throughput screening of metal–organic frameworks for hydrogen storage at cryogenic temperature. *Journal of Physical Chemistry C*, 2016, 120(48): 27328–27341
 243. Ozturk Z, Kose D A, Sahin Z S, et al. Novel 2D micro-porous metal-organic framework for hydrogen storage. *International Journal of Hydrogen Energy*, 2016, 41(28): 12167–12174
 244. Railey P, Song Y, Liu T, et al. Metal organic frameworks with immobilized nanoparticles: Synthesis and applications in photocatalytic hydrogen generation and energy storage. *Materials Research Bulletin*, 2017, 96: 385–394
 245. Rahali S, Belhocine Y, Seydou M, et al. Multiscale study of the structure and hydrogen storage capacity of an aluminum metal-organic framework. *International Journal of Hydrogen Energy*, 2017, 42(22): 15271–15282
 246. Chen Z, Chen J, Li Y. Metal–organic-framework-based catalysts for hydrogenation reactions. *Chinese Journal of Catalysis*, 2017, 38(7): 1108–1126
 247. Tarkowski R. Underground hydrogen storage: characteristics and prospects. *Renewable & Sustainable Energy Reviews*, 2019, 105: 86–94
 248. Lankof L, Urbańczyk K, Tarkowski R. Assessment of the potential for underground hydrogen storage in salt domes. *Renewable & Sustainable Energy Reviews*, 2022, 160: 112309
 249. Lankof L, Tarkowski R. Assessment of the potential for underground hydrogen storage in bedded salt formation. *International Journal of Hydrogen Energy*, 2020, 45(38): 19479–19492
 250. Sáinz-García A, Abarca E, Rubi V, et al. Assessment of feasible strategies for seasonal underground hydrogen storage in a saline aquifer. *International Journal of Hydrogen Energy*, 2017, 42(26): 16657–16666
 251. Hemme C, Van Berk W. Hydrogeochemical modeling to identify potential risks of underground hydrogen storage in depleted gas fields. *Applied Sciences (Basel, Switzerland)*, 2018, 8(11): 2282
 252. Rosa L, Mazzotti M. Potential for hydrogen production from sustainable biomass with carbon capture and storage. *Renewable & Sustainable Energy Reviews*, 2022, 157: 112123
 253. English J M, English K L. An overview of carbon capture and storage and its potential role in the energy transition. *First Break*, 2022, 40(4): 35–40
 254. Agaton C B, Batac K I T, Reyes E M Jr. Prospects and challenges for green hydrogen production and utilization in the Philippines. *International Journal of Hydrogen Energy*, 2022, 47(41): 17859–17870
 255. Ahmed A, Al-Amin A Q, Ambrose A F, et al. Hydrogen fuel and transport system: A sustainable and environmental future. *International Journal of Hydrogen Energy*, 2016, 41(3): 1369–1380
 256. Ball M, Wietschel M. The future of hydrogen—opportunities and challenges. *International Journal of Hydrogen Energy*, 2009, 34(2): 615–627
 257. Li Y, Taghizadeh-Hesary F. The economic feasibility of green hydrogen and fuel cell electric vehicles for road transport in China. *Energy Policy*, 2022, 160: 112703
 258. International Energy Agency. Hydrogen Projects Database. Technical Report, IEA, 2021
 259. Ratnakar R R, Gupta N, Zhang K, et al. Hydrogen supply chain and challenges in large-scale LH₂ storage and transportation. *International Journal of Hydrogen Energy*, 2021, 46(47): 24149–24168
 260. Scott R B, Denton W H, Nicholls C M. Technology and Uses of Liquid Hydrogen. Pergamon: Elsevier, 2013
 261. Zhang K, Lau H C, Chen Z. Using blue hydrogen to decarbonize heavy oil and oil sands operations in Canada. *ACS Sustainable Chemistry & Engineering*, 2022, 10(30): 10003–10013
 262. International Energy Agency. Global Hydrogen Review. Technical Report, IEA, 2022
 263. Schoots K, Ferioli F, Kramer G, et al. Learning curves for hydrogen production technology: An assessment of observed cost reductions. *International Journal of Hydrogen Energy*, 2008, 33(11): 2630–2645
 264. Pastore L M, Lo Basso G, Sforzini M, et al. Technical, economic and environmental issues related to electrolyzers capacity targets according to the Italian Hydrogen Strategy: A critical analysis. *Renewable & Sustainable Energy Reviews*, 2022, 166: 112685
 265. Lane B, Reed J, Shaffer B, et al. Forecasting renewable hydrogen production technology shares under cost uncertainty. *International Journal of Hydrogen Energy*, 2021, 46(54): 27293–27306
 266. US Department of Education. DOE technical targets for hydrogen production from electrolysis. 2022–10, available at website of energy government
 267. Zhang X, Bauer C, Mutel C L, et al. Life cycle assessment of power-to-gas: Approaches, system variations and their environmental implications. *Applied Energy*, 2017, 190: 326–338
 268. Algunaibet I M, Guillén-Gosálbez G. Life cycle burden-shifting in energy systems designed to minimize greenhouse gas emissions: Novel analytical method and application to the United States. *Journal of Cleaner Production*, 2019, 229:

- 886–901
269. González-Garay A, Frei M S, Al-Qahtani A, et al. Plant-to-planet analysis of CO₂-based methanol processes. *Energy & Environmental Science*, 2019, 12(12): 3425–3436
270. Parkinson B, Balcombe P, Speirs J, et al. Levelized cost of CO₂ mitigation from hydrogen production routes. *Energy & Environmental Science*, 2019, 12(1): 19–40
271. Sleep S, Munjal R, Leitch M, et al. Carbon footprinting of carbon capture and utilization technologies: Discussion of the analysis of carbon XPRIZE competition team finalists. *Clean Energy*, 2021, 5(4): 587–599
272. Motazed K, Salkuyeh Y K, Laurenzi I J, et al. Economic and environmental competitiveness of high temperature electrolysis for hydrogen production. *International Journal of Hydrogen Energy*, 2021, 46(41): 21274–21288
273. Liu C M, Sandhu N K, McCoy S T, et al. A life cycle assessment of greenhouse gas emissions from direct air capture and Fischer–Tropsch fuel production. *Sustainable Energy & Fuels*, 2020, 4(6): 3129–3142
274. Kolb S, Plankenbühler T, Hofmann K, et al. Life cycle greenhouse gas emissions of renewable gas technologies: A comparative review. *Renewable & Sustainable Energy Reviews*, 2021, 146: 111147
275. Bergerson J A, Brandt A, Cresko J, et al. Life cycle assessment of emerging technologies: Evaluation techniques at different stages of market and technical maturity. *Journal of Industrial Ecology*, 2020, 24(1): 11–25
276. Bergerson J, Cucurachi S, Seager T P. Bringing a life cycle perspective to emerging technology development. *Journal of Industrial Ecology*, 2020, 24(1): 6–10