

Parameter	Unitree G1 (Humanoid)	Rainbow RB-Y1 (Mobile Manipulator)
<i>Robot Configuration</i>		
DoF; breakdown	29; 6/leg, 3 waist, 7/arm	22; 2 wheel, 6 torso, 7/arm
Low-level policy π (type); hidden param h_k	FALCON [9] (RL); state-action history	Differential drive (proportional control); gain K_p (fixed)
<i>High-Level Action a_k</i>		
Retargeter commands (same as inputs to π)	$h^1, \phi^3, V^2, \Omega^1$ (7-dim, from T_{head})	V1: $V^1, \Omega^1, q_{\text{torso}}^6$ (8-dim, from T_{head}); V2: $q_{\text{leftarm}}^7, q_{\text{torso}}^6$ (13-dim, from T_{lw})
IK commands	q_{arm}^{14} (from T_{lw}, T_{rw})	V1: q_{arm}^{14} (from T_{lw}, T_{rw}); V2: N/A
Mode switch σ	Standing / Walking (from ς)	Stationary / Mobile (from ς)
<i>State Estimation (Real World)</i>		
p, θ, v, ω	LiDAR-Inertial SLAM [18] (p, θ, v); IMU (ω)	LiDAR-Inertial SLAM [18] (p, θ, v); IMU (ω)
$q, \dot{q}$	Motor encoders	Motor encoders
<i>MPPI Parameters</i>		
Horizon H (low-level control step); samples N	3; 30 (Standing), 5; 30 (Walking)	V1: 3; 30 (Stationary), 10; 30 (Mobile); V2: 3; 50
Temperature λ ; noise std σ_{mppi}	0.001; 0.001 (Standing), 0.001; 0.05 (Walking)	V1: 0.001, 0.01 (Stationary), 0.001, 0.01 (Mobile); V2: 0.001; 0.01
Control rate (Hz): MPC / low-level policy	25 / 50 (Standing), 10 / 50 (Walking)	25 / 50 (Stationary), 10 / 50 (Mobile)
<i>Cost Function Weights (Eq. 3)</i>		
Tracking: w_p ; w_θ ; Energy w_a ; Contact: w_s	1.0; 1.0; 0.1; 0.1	1.0; 1.0; 0.1; 0.1
Collision: w_c ; w_v ; α ; β	N/A	1.0; 1.0; 1.0; 10.0
Upright constraint (V2 only)	N/A	1.0
Primary safety concern	Balance (measured by ABP)	Collision avoidance (measured by CR)