

Input: $\mathcal{M}_{\text{pri}}$: 2D Prior Map, $\mathcal{M}_{\text{obs}}$: Online Observation Map, X_r : Robot Position, $\mathcal{X}_{\text{cand}}$: Sampled Location Sets, s_g : Scale Guess

Output: $\mathcal{T}_f$: Refined Transformations

```

1: // Phase 1: Descriptor Pre-computation
2:  $\mathcal{F}_{\text{pri}} \leftarrow \{\}$ 
3: for each sampled location  $x_j$  in  $\mathcal{X}_{\text{cand}}$  do
4:    $\mathcal{M}_{\text{visible},j} \leftarrow \text{HPR}(\mathcal{M}_{\text{pri}}, x_j)$ 
5:    $\mathbf{d}_{\text{pri},j} \leftarrow \text{CALCDESC}(\mathcal{M}_{\text{visible},j})$ 
6:    $\mathcal{F}_{\text{pri}}.\text{insert}(\mathbf{d}_{\text{pri},j})$ 
7: end for
8: // Phase 2: Online Registration
9:  $\mathcal{P}_{\text{robot}}, \mathcal{C}, \mathcal{T}_{\text{pot}} \leftarrow \{\}$ 
10: while receive  $\mathcal{M}_{\text{obs}}$  and  $X_r$  do
11:    $\mathcal{P}_{\text{robot}}.\text{insert}(X_r)$ 
12:    $\mathcal{M}_{\text{visible}} \leftarrow \text{HPR}(\mathcal{M}_{\text{obs}}, X_r)$ 
13:    $\mathbf{d}_i \leftarrow \text{CALCDESC}(\mathcal{M}_{\text{visible}})$ 
14:    $C_i \leftarrow \text{FINDCAND}(\mathcal{F}_{\text{pri}}, \mathbf{d}_i)$ 
15:    $\mathcal{C}.\text{insert}(C_i)$ 
16:   if  $\mathcal{C}.\text{size}() < 3$  then
17:     continue
18:   else if  $\mathcal{C}.\text{size}() == 3$  then
19:      $\mathcal{T}_{\text{pot}} \leftarrow \text{GETPOTTRAN}(\mathcal{C}, \mathcal{P}_{\text{robot}}, s_g)$ 
20:   else if  $\mathcal{C}.\text{size}() > 3$  then
21:      $\mathcal{T}_{\text{pot}} \leftarrow \text{FILTEROUTLIERS}(\mathcal{T}_{\text{pot}}, \mathcal{C}, \mathcal{P}_{\text{robot}})$ 
22:   end if
23:    $\mathcal{T}_f \leftarrow \text{SCALE-ICP}(\mathcal{T}_{\text{pot}}, \mathcal{M}_{\text{obs}}, \mathcal{M}_{\text{pri}})$ 
24: end while

```