


Stage 1: Pose following → Stage 2: Dynamic refs + view-count extrapolation → Stage 3: Temporal rollout

Stage 1: $1r1t$ @ 256^2 (PRoPE + view RoPE)

Set the new positional encoding under the simplest single-ref / single-target setting.


r : reference views
 t : target views



randomly draw two cameras; assign one as reference, the other as target

Reference view

Target view



Stage 2.1: $N_{ref}r(16 - N_{ref})t$ @ 256^2 (dynamic N_{ref} + random background drop)

Learn dense multi-view consistency under any ref count; mix matted and un-matted samples to support both background modes.

Init from previous

example of draw of 2 reference views and 14 target views; training redraw $N_{ref} \in \{1 \dots 15\}$ per batch

Background-drop augmentation



randomly applied with probability p_{bg} per batch



Reference views

Target views

matched to Stage2.1, increase the resolution to 512^2



Reference views



Target views

Init from previous

Stage 3: dynamic $V \times T$ @ 512^2 (teacher-forced history)


V : number of cameras views per sample
 T : temporal length per camera
 $V \times T$: total frames denoised jointly

Round A:
(32-frame budget)



Round B:
(64-frame budget)
Long-T

$V \times T$ shapes in the training



Example teacher-forced history modes
no history 1 history

