









Exercises for *Foundations in Data Engineering*, WiSe 19/20



Timo Kersten (kersten@in.tum.de)
<http://db.in.tum.de/teaching/>

Sheet Nr. 02




Exercise 1 For the following SQL keywords, which GNU tools are useful to implement a similar functionality?

- FROM 
- LIMIT 
- SELECT 
- WHERE 
- ORDER BY 
- GROUP BY 

Exercise 2 Answer the following queries for the Linux Kernel Mailing List data set using GNU utils and bash functionality:


1. Of how many lines does the longest mail consist? Challenge: Compute the number of lines in each mail without using the 'Lines:' attribute in the dataset. 
2. Which mail received most (direct) replies? 


Exercise 3 Answer the following queries for the TPC-H data set using GNU utils and bash functionality:

1. According to the data set, which nations are in Europe? 
2. How many lines are in lineitem.tbl? 
3. Determine for each part how often it has been bought. (Hint: Sum up the quantities in lineitem.tbl, grouped by part_id) 

Now use the command `time real 0m23.417s` to compute query 3.

`time` takes the command to `user 0m23.922s` example `time echo hi` runs the command `echo hi`, which writes `hi` to the standard out stream, and then prints resource usage information to the standard error stream.

The measured command produces a lot of output. In this case, execution time will most likely be dominated by printing to the terminal. Of course we are not interested in measuring how long it takes to print to the terminal. Rather we want to measure how long the computation takes. Therefore, please redirect the output to `/dev/null`. The latter is a device which discards all data written to it. Luckily for us, it is very fast. Usage looks like this `time echo hi > /dev/null`. 

Now, pipe the command's output through `head` (by removing `> /dev/null` and appending `| head`) and perform the time measurement on this modified variant again. Why does the modified command take much shorter to execute? 

Exercise 4 In this exercise, we will compare a GNU utils based query on the TPC-H dataset against a simple C++ implementation. You will gain some experience in setting up a C++ toolchain, in the language itself as well as in performance analysis tools such as **perf** in this exercise.

Start by answering the following query for the TPC-H dataset using GNU utils and bash functionality:

```
select sum(l_extendedprice) from lineitem
```



Now that you have a working **awk** based solution it is time to clone the project at <https://gitlab.db.in.tum.de/Josef/tpchjoin> and implement the missing code fragments in the section marked by "TODO". You will find further instructions on how to build and run this project in the provided Readme file.

Once the implementation is done, do simple performance measurements:

- Compare this to **awk** execution time.
- Estimate how fast the program can possibly be on your local machine. Assume that the input file is read from memory.
- Find out where most of the time is spent and why this program is not as fast of your estimate. Tools that can help here: **perf stat**, **perf record**, **perf report**. Which part would be a good candidate for optimization? (This exercise will be continued on the next sheet.)

perf provides useful performance analysis tools for Linux. With **perf stat** you can obtain an analysis of certain kernel and CPU relevant statistics like the ratio between CPU cycles spent within your program and the kernel itself. **perf record** and **perf report** should be used pairwise. The former allows you to generate a profile of your program by issuing **perf record <your program>**. The latter is used to analyse the generated profile. You will find an estimate of how much time your program spent within a certain function down to the individual CPU instructions among each function call/instruction. It is advisable to compile your program with debug information (add the **-g** argument for **g++**) in order to obtain the original code lines together with the corresponding symbols.