

STAPpp

1.0

Generated by Doxygen 1.8.13

Contents

1	Hierarchical Index	1
1.1	Class Hierarchy	1
2	Class Index	3
2.1	Class List	3
3	File Index	5
3.1	File List	5
4	Class Documentation	7
4.1	CBar Class Reference	7
4.1.1	Detailed Description	8
4.1.2	Constructor & Destructor Documentation	8
4.1.2.1	CBar()	9
4.1.2.2	~CBar()	9
4.1.3	Member Function Documentation	9
4.1.3.1	ElementStiffness()	9
4.1.3.2	ElementStress()	9
4.1.3.3	GenerateLocationMatrix()	9
4.1.3.4	Read()	10
4.1.3.5	SizeOfStiffnessMatrix()	10
4.1.3.6	Write()	10
4.2	CBarMaterial Class Reference	11
4.2.1	Detailed Description	12
4.2.2	Member Function Documentation	12

4.2.2.1	Read()	12
4.2.2.2	Write()	12
4.2.3	Member Data Documentation	12
4.2.3.1	Area	12
4.3	CDomain Class Reference	13
4.3.1	Detailed Description	15
4.3.2	Constructor & Destructor Documentation	16
4.3.2.1	CDomain()	16
4.3.2.2	~CDomain()	16
4.3.3	Member Function Documentation	16
4.3.3.1	AllocateMatrices()	16
4.3.3.2	AssembleForce()	16
4.3.3.3	AssembleStiffnessMatrix()	16
4.3.3.4	CalculateColumnHeights()	17
4.3.3.5	CalculateDiagnoalAddress()	17
4.3.3.6	CalculateEquationNumber()	17
4.3.3.7	GetDisplacement()	17
4.3.3.8	GetElementSetList()	17
4.3.3.9	GetElementTypes()	17
4.3.3.10	GetForce()	18
4.3.3.11	GetLoadCases()	18
4.3.3.12	GetMaterialSetList()	18
4.3.3.13	GetMK()	18
4.3.3.14	GetMODEX()	18
4.3.3.15	GetNEQ()	18
4.3.3.16	GetNLCASE()	19
4.3.3.17	GetNLOAD()	19
4.3.3.18	GetNodeList()	19
4.3.3.19	GetNUME()	19
4.3.3.20	GetNUMEG()	19

4.3.3.21	GetNUMMAT()	19
4.3.3.22	GetNUMNP()	20
4.3.3.23	GetNWK()	20
4.3.3.24	GetStiffnessMatrix()	20
4.3.3.25	GetTitle()	20
4.3.3.26	Instance()	20
4.3.3.27	ReadBarElementData()	20
4.3.3.28	ReadData()	21
4.3.3.29	ReadElements()	21
4.3.3.30	ReadLoadCases()	21
4.3.3.31	ReadNodalPoints()	21
4.3.4	Member Data Documentation	21
4.3.4.1	_instance	21
4.3.4.2	ElementSetList	22
4.3.4.3	ElementTypes	22
4.3.4.4	Force	22
4.3.4.5	Input	22
4.3.4.6	LoadCases	22
4.3.4.7	MaterialSetList	22
4.3.4.8	MK	23
4.3.4.9	MODEX	23
4.3.4.10	NEQ	23
4.3.4.11	NLCASE	23
4.3.4.12	NLOAD	23
4.3.4.13	NodeList	23
4.3.4.14	NUME	24
4.3.4.15	NUMEG	24
4.3.4.16	NUMMAT	24
4.3.4.17	NUMNP	24
4.3.4.18	NWK	24

4.3.4.19	StiffnessMatrix	24
4.3.4.20	Title	25
4.4	CElement Class Reference	25
4.4.1	Detailed Description	26
4.4.2	Constructor & Destructor Documentation	27
4.4.2.1	CElement()	27
4.4.3	Member Function Documentation	27
4.4.3.1	assembly()	27
4.4.3.2	CalculateColumnHeight()	27
4.4.3.3	ElementStiffness()	27
4.4.3.4	ElementStress()	28
4.4.3.5	GenerateLocationMatrix()	28
4.4.3.6	GetElementMaterial()	28
4.4.3.7	GetNodes()	28
4.4.3.8	Read()	28
4.4.3.9	SizeOfStiffnessMatrix()	29
4.4.3.10	Write()	29
4.4.4	Friends And Related Function Documentation	29
4.4.4.1	CDomain	29
4.4.5	Member Data Documentation	29
4.4.5.1	ElementMaterial	29
4.4.5.2	LocationMatrix	29
4.4.5.3	ND	30
4.4.5.4	NEN	30
4.4.5.5	nodes	30
4.5	CLDLTSolver Class Reference	30
4.5.1	Detailed Description	31
4.5.2	Constructor & Destructor Documentation	31
4.5.2.1	CLDLTSolver()	31
4.5.3	Member Function Documentation	32

4.5.3.1	BackSubstitution()	32
4.5.3.2	LDLT()	32
4.6	CLoadCaseData Class Reference	32
4.6.1	Detailed Description	33
4.6.2	Constructor & Destructor Documentation	33
4.6.2.1	CLoadCaseData()	33
4.6.2.2	~CLoadCaseData()	33
4.6.3	Member Function Documentation	33
4.6.3.1	Allocate()	33
4.6.3.2	Read()	33
4.6.3.3	Write()	33
4.6.4	Member Data Documentation	34
4.6.4.1	dof	34
4.6.4.2	load	34
4.6.4.3	nloads	34
4.6.4.4	node	34
4.7	Clock Class Reference	34
4.7.1	Detailed Description	35
4.7.2	Constructor & Destructor Documentation	35
4.7.2.1	Clock()	35
4.7.3	Member Function Documentation	35
4.7.3.1	Clear()	36
4.7.3.2	ElapsedTime()	36
4.7.3.3	Resume()	36
4.7.3.4	Start()	36
4.7.3.5	Stop()	36
4.7.4	Member Data Documentation	36
4.7.4.1	ct_	36
4.7.4.2	st0_	37
4.7.4.3	st1_	37

4.7.4.4	t0_	37
4.7.4.5	t1_	37
4.8	CMaterial Class Reference	37
4.8.1	Detailed Description	38
4.8.2	Member Function Documentation	38
4.8.2.1	Read()	38
4.8.2.2	Write()	38
4.8.3	Member Data Documentation	39
4.8.3.1	E	39
4.8.3.2	nset	39
4.9	CNode Class Reference	39
4.9.1	Detailed Description	40
4.9.2	Constructor & Destructor Documentation	40
4.9.2.1	CNode()	40
4.9.3	Member Function Documentation	40
4.9.3.1	Read()	40
4.9.3.2	Write()	40
4.9.3.3	WriteEquationNo()	41
4.9.3.4	WriteNodalDisplacement()	41
4.9.4	Member Data Documentation	41
4.9.4.1	bcode	41
4.9.4.2	NDF	41
4.9.4.3	NodeNumber	41
4.9.4.4	XYZ	42
4.10	COutputter Class Reference	42
4.10.1	Detailed Description	43
4.10.2	Constructor & Destructor Documentation	43
4.10.2.1	COutputter()	43
4.10.3	Member Function Documentation	43
4.10.3.1	GetOutputFile()	43

4.10.3.2	Instance()	44
4.10.3.3	OutputElementInfo()	44
4.10.3.4	OutputElementStress()	44
4.10.3.5	OutputEquationNumber()	44
4.10.3.6	OutputHeading()	44
4.10.3.7	OutputLoadInfo()	44
4.10.3.8	OutputNodalDisplacement()	45
4.10.3.9	OutputNodeInfo()	45
4.10.3.10	OutputTotalSystemData()	45
4.10.3.11	PrintBarElementData()	45
4.10.3.12	PrintTime()	45
4.10.4	Member Data Documentation	45
4.10.4.1	_instance	46
4.10.4.2	OutputFile	46
4.11	CSkylineMatrix< T_ > Class Template Reference	46
4.11.1	Detailed Description	47
4.11.2	Constructor & Destructor Documentation	47
4.11.2.1	CSkylineMatrix() [1/2]	48
4.11.2.2	CSkylineMatrix() [2/2]	48
4.11.2.3	~CSkylineMatrix()	48
4.11.3	Member Function Documentation	48
4.11.3.1	Allocate()	48
4.11.3.2	dim()	48
4.11.3.3	GetColumnHeights()	49
4.11.3.4	GetDiagonalAddress()	49
4.11.3.5	operator() [1/2]	49
4.11.3.6	operator() [2/2]	49
4.11.3.7	size()	49
4.11.4	Member Data Documentation	49
4.11.4.1	ColumnHeights_	50
4.11.4.2	data_	50
4.11.4.3	DiagonalAddress_	50
4.11.4.4	NEQ_	50
4.11.4.5	NWK_	50
4.12	CSolver Class Reference	51
4.12.1	Detailed Description	51
4.12.2	Constructor & Destructor Documentation	52
4.12.2.1	CSolver()	52
4.12.3	Member Data Documentation	52
4.12.3.1	K	52

5	File Documentation	53
5.1	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Bar.cpp File Reference	53
5.2	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Clock.cpp File Reference	53
5.3	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Domain.cpp File Reference	54
5.3.1	Function Documentation	55
5.3.1.1	clear()	55
5.4	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Element.cpp File Reference	55
5.5	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/LoadCaseData.cpp File Reference	55
5.6	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/main.cpp File Reference	56
5.6.1	Function Documentation	56
5.6.1.1	main()	57
5.7	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Material.cpp File Reference	57
5.8	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Node.cpp File Reference	57
5.9	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Outputter.cpp File Reference	58
5.10	/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Solver.cpp File Reference	58
5.11	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Bar.h File Reference	59
5.12	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Clock.h File Reference	60
5.13	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Domain.h File Reference	61
5.13.1	Function Documentation	62
5.13.1.1	clear()	62
5.14	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Element.h File Reference	63
5.14.1	Function Documentation	64
5.14.1.1	clear()	64
5.15	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/LoadCaseData.h File Reference	64
5.16	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Material.h File Reference	65
5.17	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Node.h File Reference	66
5.18	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Outputter.h File Reference	67
5.19	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/SkylineMatrix.h File Reference	68
5.20	/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Solver.h File Reference	69

Chapter 1

Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

CDomain	13
CElement	25
CBar	7
CLoadCaseData	32
Clock	34
CMaterial	37
CBarMaterial	11
CNode	39
COutputter	42
CSkylineMatrix< T_ >	46
CSkylineMatrix< double >	46
CSolver	51
CLDLTSolver	30

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

CBar	Bar element class	7
CBarMaterial	Material class for bar element	11
CDomain	Domain class : Define the problem domain	13
CElement	Element base class	25
CLDLTSolver	LDLT solver: A in core solver using skyline storage and column reduction scheme	30
CLoadCaseData	Class LoadData is used to store load data	32
Clock	Clock class for timing	34
CMaterial	Material base class which only define one data member	37
CNode	Node class	39
COutputter	Outputter class is used to output results	42
CSkylineMatrix< T_ >	CSkylineMatrix class is used to store the FEM stiffness matrix in skyline storage	46
CSolver	Base class for a solver	51

Chapter 3

File Index

3.1 File List

Here is a list of all files with brief descriptions:

/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Bar.cpp	53
/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Clock.cpp	53
/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Domain.cpp	54
/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Element.cpp	55
/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/LoadCaseData.cpp	55
/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/main.cpp	56
/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Material.cpp	57
/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Node.cpp	57
/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Outputter.cpp	58
/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Solver.cpp	58
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Bar.h	59
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Clock.h	60
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Domain.h	61
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Element.h	63
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/LoadCaseData.h	64
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Material.h	65
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Node.h	66
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Outputter.h	67
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/SkylineMatrix.h	68
/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Solver.h	69

Chapter 4


Class Documentation

4.1 CBar Class Reference


Bar element class.

```
#include <Bar.h>
```

Inheritance diagram for CBar:



Collaboration diagram for CBar:



Public Member Functions

- [CBar](#) ()
Constructor.
- [~CBar](#) ()
Destructor.
- virtual bool [Read](#) (ifstream &Input, unsigned int Ele, [CMaterial](#) *MaterialSets, [CNode](#) *NodeList)
Read element data from stream Input.
- virtual void [Write](#) (ofstream &OutputFile, unsigned int Ele)
Write element data to stream OutputFile.
- virtual void [GenerateLocationMatrix](#) ()
Generate location matrix: the global equation number that corresponding to each DOF of the element.
- virtual void [ElementStiffness](#) (double *Matrix)
Calculate element stiffness matrix.
- virtual void [ElementStress](#) (double *stress, double *Displacement)
Calculate element stress.
- virtual unsigned int [SizeOfStiffnessMatrix](#) ()
Return the size of the element stiffness matrix (stored as an array column by column)

Additional Inherited Members

4.1.1 Detailed Description

Bar element class.

4.1.2 Constructor & Destructor Documentation

4.1.2.1 CBar()

```
CBar::CBar ( )
```

Constructor.

4.1.2.2 ~CBar()

```
CBar::~~CBar ( )
```

Desconstructor.

4.1.3 Member Function Documentation

4.1.3.1 ElementStiffness()

```
void CBar::ElementStiffness (
    double * Matrix ) [virtual]
```

Calculate element stiffness matrix.

Implements [CElement](#).

4.1.3.2 ElementStress()

```
void CBar::ElementStress (
    double * stress,
    double * Displacement ) [virtual]
```

Calculate element stress.

Implements [CElement](#).

4.1.3.3 GenerateLocationMatrix()

```
void CBar::GenerateLocationMatrix ( ) [virtual]
```

Generate location matrix: the global equation number that corresponding to each DOF of the element.

Implements [CElement](#).

4.1.3.4 Read()

```
bool CBar::Read (
    ifstream & Input,
    unsigned int Ele,
    CMaterial * MaterialSets,
    CNode * NodeList ) [virtual]
```

Read element data from stream Input.

Implements [CElement](#).

4.1.3.5 SizeOfStiffnessMatrix()

```
unsigned int CBar::SizeOfStiffnessMatrix ( ) [virtual]
```

Return the size of the element stiffness matrix (stored as an array column by column)

Implements [CElement](#).

4.1.3.6 Write()

```
void CBar::Write (
    ofstream & OutputFile,
    unsigned int Ele ) [virtual]
```

Write element data to stream OutputFile.

Implements [CElement](#).

The documentation for this class was generated from the following files:


- [/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Bar.h](#)
- [/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Bar.cpp](#)

4.2 CBarMaterial Class Reference


Material class for bar element.

```
#include <Material.h>
```

Inheritance diagram for CBarMaterial:



Collaboration diagram for CBarMaterial:



Public Member Functions

- virtual bool [Read](#) (ifstream &Input, unsigned int mset)
Read material data from stream Input.
- virtual void [Write](#) (ofstream &OutputFile, unsigned int mset)
Write material data to Stream OutputFile.

Public Attributes

- double [Area](#)
Sectional area of a bar element.

4.2.1 Detailed Description

Material class for bar element.

4.2.2 Member Function Documentation

4.2.2.1 Read()

```
bool CBarMaterial::Read (
    ifstream & Input,
    unsigned int mset ) [virtual]
```

Read material data from stream *Input*.

Implements [CMaterial](#).

4.2.2.2 Write()

```
void CBarMaterial::Write (
    ofstream & OutputFile,
    unsigned int mset ) [virtual]
```

Write material data to Stream *OutputFile*.

Implements [CMaterial](#).

4.2.3 Member Data Documentation

4.2.3.1 Area

```
double CBarMaterial::Area
```

Sectional area of a bar element.

The documentation for this class was generated from the following files:


- [/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Material.h](#)
- [/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Material.cpp](#)

4.3 CDomain Class Reference

Domain class : Define the problem domain.

```
#include <Domain.h>
```

Collaboration diagram for CDomain:



Public Member Functions

- [CDomain \(\)](#)
Constructor.
- [~CDomain \(\)](#)
Destructor.
- [bool ReadData \(string FileName, string OutFile\)](#)
Read domain data from the input data file.
- [bool ReadNodalPoints \(\)](#)
Read nodal point data.
- [bool ReadLoadCases \(\)](#)
Read load case data.
- [bool ReadElements \(\)](#)
Read element data.
- [bool ReadBarElementData \(unsigned int EleGrp\)](#)
Read bar element data from the input data file.
- [void CalculateEquationNumber \(\)](#)
Calculate global equation numbers corresponding to every degree of freedom of each node.
- [void CalculateColumnHeights \(\)](#)
Calculate column heights.
- [void CalculateDiagnoalAddress \(\)](#)
Calculate address of diagonal elements in banded matrix.
- [void AllocateMatrices \(\)](#)
Allocate storage for matrices.
- [void AssembleStiffnessMatrix \(\)](#)
Assemble the banded gloabl stiffness matrix.
- [bool AssembleForce \(unsigned int LoadCase\)](#)
Assemble the global nodal force vector for load case LoadCase.
- [unsigned int GetMODEX \(\)](#)
Return solution mode.

- string [GetTitle](#) ()
Return the title of problem.
- unsigned int [GetNEQ](#) ()
Return the total number of equations.
- unsigned int [GetNUMNP](#) ()
Return the total number of nodal points.
- unsigned int [GetNWK](#) ()
Return the number of banded global stiffness matrix elements.
- unsigned int [GetMK](#) ()
Return the maximum half bandwith.
- [CNode](#) * [GetNodeList](#) ()
Return the node list.
- unsigned int * [GetNUME](#) ()
Return the number of elements in each element group.
- unsigned int [GetNUMEG](#) ()
Return total number of element groups.
- unsigned int * [GetElementTypes](#) ()
Element type of each group.
- [CElement](#) ** [GetElementSetList](#) ()
Return element Set List.
- unsigned int * [GetNUMMAT](#) ()
Return number of different sets of material/section properties in each element group.
- [CMaterial](#) ** [GetMaterialSetList](#) ()
Return material set list.
- double * [GetForce](#) ()
Return pointer to the global nodal force vector.
- double * [GetDisplacement](#) ()
Return pointer to the global nodal displacement vector.
- unsigned int [GetNLCASE](#) ()
Return the total number of load cases.
- unsigned int * [GetNLOAD](#) ()
Return the number of concentrated loads applied in each load case.
- [CLoadCaseData](#) * [GetLoadCases](#) ()
Return the list of load cases.
- [CSkylineMatrix](#)< double > * [GetStiffnessMatrix](#) ()
Return pointer to the banded stiffness matrix.

Static Public Member Functions

- static [CDomain](#) * [Instance](#) ()
Return pointer to the instance of the Domain class.

Private Attributes

- ifstream [Input](#)
Input file stream for reading data from input data file.
- char [Title](#) [256]
Heading information for use in labeling the output.
- unsigned int [MODEX](#)
Solution MODEX.
- unsigned int [NUMNP](#)
Total number of nodal points.
- [CNode](#) * [NodeList](#)
List of all nodes in the domain.
- unsigned int [NUMEG](#)
Total number of element groups.
- unsigned int * [ElementTypes](#)
Element type of each group.
- unsigned int * [NUME](#)
Number of elements in each element group.
- [CElement](#) ** [ElementSetList](#)
Element Set List.
- unsigned int * [NUMMAT](#)
Number of different sets of material/section properties in each element group.
- [CMaterial](#) ** [MaterialSetList](#)
Material set list.
- unsigned int [NLCASE](#)
Number of load cases.
- [CLoadCaseData](#) * [LoadCases](#)
List of all load cases.
- unsigned int * [NLOAD](#)
Number of concentrated loads applied in each load case.
- unsigned int [NEQ](#)
Total number of equations in the system.
- unsigned int [NWK](#)
Number of elements in banded global stiffness matrix.
- unsigned int [MK](#)
Maximum half bandwidth.
- [CSkylineMatrix](#)< double > * [StiffnessMatrix](#)
Banded stiffness matrix.
- double * [Force](#)
Global nodal force/displacement vector.

Static Private Attributes

- static [CDomain](#) * [_instance](#) = NULL
The instance of the Domain class.

4.3.1 Detailed Description

Domain class : Define the problem domain.

Only a single instance of Domain class can be created

4.3.2 Constructor & Destructor Documentation

4.3.2.1 CDomain()

```
CDomain::CDomain ( )
```

Constructor.

4.3.2.2 ~CDomain()

```
CDomain::~~CDomain ( )
```

Desconstructor.

4.3.3 Member Function Documentation

4.3.3.1 AllocateMatrices()

```
void CDomain::AllocateMatrices ( )
```

Allocate storage for matrices.

Allocate Force, ColumnHeights, DiagonalAddress and StiffnessMatrix and calculate the column heights and address of diagonal elements

4.3.3.2 AssembleForce()

```
bool CDomain::AssembleForce (
    unsigned int LoadCase )
```

Assemble the global nodal force vector for load case LoadCase.

4.3.3.3 AssembleStiffnessMatrix()

```
void CDomain::AssembleStiffnessMatrix ( )
```

Assemble the banded gloabl stiffness matrix.

4.3.3.4 CalculateColumnHeights()

```
void CDomain::CalculateColumnHeights ( )
```

Calculate column heights.

4.3.3.5 CalculateDiagnoalAddress()

```
void CDomain::CalculateDiagnoalAddress ( )
```

Calculate address of diagonal elements in banded matrix.

4.3.3.6 CalculateEquationNumber()

```
void CDomain::CalculateEquationNumber ( )
```

Calculate global equation numbers corresponding to every degree of freedom of each node.

4.3.3.7 GetDisplacement()

```
double* CDomain::GetDisplacement ( ) [inline]
```

Return pointer to the global nodal displacement vector.

4.3.3.8 GetElementSetList()

```
CElement** CDomain::GetElementSetList ( ) [inline]
```

Return element Set List.

4.3.3.9 GetElementTypes()

```
unsigned int* CDomain::GetElementTypes ( ) [inline]
```

Element type of each group.

4.3.3.10 GetForce()

```
double* CDomain::GetForce ( ) [inline]
```

Return pointer to the global nodal force vector.

4.3.3.11 GetLoadCases()

```
CLoadCaseData* CDomain::GetLoadCases ( ) [inline]
```

Return the list of load cases.

4.3.3.12 GetMaterialSetList()

```
CMaterial** CDomain::GetMaterialSetList ( ) [inline]
```

Return material set list.

4.3.3.13 GetMK()

```
unsigned int CDomain::GetMK ( ) [inline]
```

Return the maximum half bandwidth.

4.3.3.14 GetMODEX()

```
unsigned int CDomain::GetMODEX ( ) [inline]
```

Return solution mode.

4.3.3.15 GetNEQ()

```
unsigned int CDomain::GetNEQ ( ) [inline]
```

Return the total number of equations.

4.3.3.16 GetNLCASE()

```
unsigned int CDomain::GetNLCASE ( ) [inline]
```

Return the total number of load cases.

4.3.3.17 GetNLOAD()

```
unsigned int* CDomain::GetNLOAD ( ) [inline]
```

Return the number of concentrated loads applied in each load case.

4.3.3.18 GetNodeList()

```
CNode* CDomain::GetNodeList ( ) [inline]
```

Return the node list.

4.3.3.19 GetNUME()

```
unsigned int* CDomain::GetNUME ( ) [inline]
```

Return the number of elements in each element group.

4.3.3.20 GetNUMEG()

```
unsigned int CDomain::GetNUMEG ( ) [inline]
```

Return total number of element groups.

4.3.3.21 GetNUMMAT()

```
unsigned int* CDomain::GetNUMMAT ( ) [inline]
```

Return number of different sets of material/section properties in each element group.

4.3.3.22 GetNUMNP()

```
unsigned int CDomain::GetNUMNP ( ) [inline]
```

Return the total number of nodal points.

4.3.3.23 GetNWK()

```
unsigned int CDomain::GetNWK ( ) [inline]
```

Return the number of banded global stiffness matrix elements.

4.3.3.24 GetStiffnessMatrix()

```
CSkylineMatrix<double>* CDomain::GetStiffnessMatrix ( ) [inline]
```

Return pointer to the banded stiffness matrix.

4.3.3.25 GetTitle()

```
string CDomain::GetTitle ( ) [inline]
```

Return the title of problem.

4.3.3.26 Instance()

```
CDomain * CDomain::Instance ( ) [static]
```

Return pointer to the instance of the Domain class.

4.3.3.27 ReadBarElementData()

```
bool CDomain::ReadBarElementData (
    unsigned int EleGrp )
```

Read bar element data from the input data file.

4.3.3.28 ReadData()

```
bool CDomain::ReadData (
    string FileName,
    string OutFile )
```

Read domain data from the input data file.

4.3.3.29 ReadElements()

```
bool CDomain::ReadElements ( )
```

Read element data.

4.3.3.30 ReadLoadCases()

```
bool CDomain::ReadLoadCases ( )
```

Read load case data.

4.3.3.31 ReadNodalPoints()

```
bool CDomain::ReadNodalPoints ( )
```

Read nodal point data.

4.3.4 Member Data Documentation

4.3.4.1 _instance

```
CDomain * CDomain::_instance = NULL [static], [private]
```

The instance of the Domain class.

4.3.4.2 ElementSetList

```
CElement** CDomain::ElementSetList [private]
```

Element Set List.

ElementSetList[i] - ith element set

ElementSetList[i][j] - jth element in ith set

4.3.4.3 ElementTypes

```
unsigned int* CDomain::ElementTypes [private]
```

Element type of each group.

4.3.4.4 Force

```
double* CDomain::Force [private]
```

Global nodal force/displacement vector.

4.3.4.5 Input

```
ifstream CDomain::Input [private]
```

Input file stream for reading data from input data file.

4.3.4.6 LoadCases

```
CLoadCaseData* CDomain::LoadCases [private]
```

List of all load cases.

4.3.4.7 MaterialSetList

```
CMaterial** CDomain::MaterialSetList [private]
```

Material set list.

MaterialSetList[i] - ith material set

MaterialSetList[i][j] - jth material in ith set

4.3.4.8 MK

```
unsigned int CDomain::MK [private]
```

Maximum half bandwidth.

4.3.4.9 MODEX

```
unsigned int CDomain::MODEX [private]
```

Solution MODEX.

0 : Data check only; 1 : Execution

4.3.4.10 NEQ

```
unsigned int CDomain::NEQ [private]
```

Total number of equations in the system.

4.3.4.11 NLCASE

```
unsigned int CDomain::NLCASE [private]
```

Number of load cases.

4.3.4.12 NLOAD

```
unsigned int* CDomain::NLOAD [private]
```

Number of concentrated loads applied in each load case.

4.3.4.13 NodeList

```
CNode* CDomain::NodeList [private]
```

List of all nodes in the domain.

4.3.4.14 NUME

```
unsigned int* CDomain::NUME [private]
```

Number of elements in each element group.

4.3.4.15 NUMEG

```
unsigned int CDomain::NUMEG [private]
```

Total number of element groups.

An element group consists of a convenient collection of elements with same type

4.3.4.16 NUMMAT

```
unsigned int* CDomain::NUMMAT [private]
```

Number of different sets of material/section properties in each element group.

4.3.4.17 NUMNP

```
unsigned int CDomain::NUMNP [private]
```

Total number of nodal points.

4.3.4.18 NWK

```
unsigned int CDomain::NWK [private]
```

Number of elements in banded global stiffness matrix.

4.3.4.19 StiffnessMatrix

```
CSkylineMatrix<double>* CDomain::StiffnessMatrix [private]
```

Banded stiffness matrix.

A one-dimensional array storing only the elements below the skyline of the global stiffness matrix.

4.3.4.20 Title

```
char CDomain::Title[256] [private]
```

Heading information for use in labeling the output.

The documentation for this class was generated from the following files:


- [/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Domain.h](#)
- [/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Domain.cpp](#)

4.4 CElement Class Reference


Element base class.

```
#include <Element.h>
```

Inheritance diagram for CElement:



Collaboration diagram for CElement:



Public Member Functions

- [CElement](#) ()
Constructor.
- virtual bool [Read](#) (ifstream &Input, unsigned int Ele, [CMaterial](#) *MaterialSets, [CNode](#) *NodeList)=0
Read element data from stream Input.
- virtual void [Write](#) (ofstream &OutputFile, unsigned int Ele)=0
Write element data to stream OutputFile.
- virtual void [GenerateLocationMatrix](#) ()=0
Generate location matrix: the global equation number that corresponding to each DOF of the element.
- void [CalculateColumnHeight](#) (unsigned int *ColumnHeight)
Calculate the column height, used with the skyline storage scheme.
- void [assembly](#) (double *Matrix, [CSkylineMatrix](#)< double > *StiffnessMatrix)
Assemble the element stiffness matrix to the global stiffness matrix.
- virtual void [ElementStiffness](#) (double *stiffness)=0
Calculate element stiffness matrix (Upper triangular matrix, stored as an array column by column)
- virtual void [ElementStress](#) (double *stress, double *Displacement)=0
Calculate element stress.
- [CNode](#) ** [GetNodes](#) ()
Return nodes of the element.
- [CMaterial](#) * [GetElementMaterial](#) ()
Return material of the element.
- virtual unsigned int [SizeOfStiffnessMatrix](#) ()=0
Return the size of the element stiffness matrix (stored as an array column by column)

Protected Attributes

- unsigned int [NEN](#)
Number of nodes per element.
- [CNode](#) ** [nodes](#)
Nodes of the element.
- [CMaterial](#) * [ElementMaterial](#)
Material of the element.
- unsigned int * [LocationMatrix](#)
Location Matrix of the element.
- unsigned int [ND](#)
Dimension of the location matrix.

Friends

- class [CDomain](#)

4.4.1 Detailed Description

Element base class.

All type of element classes should be derived from this base class

4.4.2 Constructor & Destructor Documentation

4.4.2.1 CElement()

```
CElement::CElement ( ) [inline]
```

Constructor.

4.4.3 Member Function Documentation

4.4.3.1 assembly()

```
void CElement::assembly (
    double * Matrix,
    CSkylineMatrix< double > * StiffnessMatrix )
```

Assemble the element stiffness matrix to the global stiffness matrix.

4.4.3.2 CalculateColumnHeight()

```
void CElement::CalculateColumnHeight (
    unsigned int * ColumnHeight )
```

Calculate the column height, used with the skyline storage scheme.

4.4.3.3 ElementStiffness()

```
virtual void CElement::ElementStiffness (
    double * stiffness ) [pure virtual]
```

Calculate element stiffness matrix (Upper triangular matrix, stored as an array column by column)

Implemented in [CBar](#).

4.4.3.4 ElementStress()

```
virtual void CElement::ElementStress (
    double * stress,
    double * Displacement ) [pure virtual]
```

Calculate element stress.

Implemented in [CBar](#).

4.4.3.5 GenerateLocationMatrix()

```
virtual void CElement::GenerateLocationMatrix ( ) [pure virtual]
```

Generate location matrix: the global equation number that corresponding to each DOF of the element.

Implemented in [CBar](#).

4.4.3.6 GetElementMaterial()

```
CMaterial* CElement::GetElementMaterial ( ) [inline]
```

Return material of the element.

4.4.3.7 GetNodes()

```
CNode** CElement::GetNodes ( ) [inline]
```

Return nodes of the element.

4.4.3.8 Read()

```
virtual bool CElement::Read (
    ifstream & Input,
    unsigned int Ele,
    CMaterial * MaterialSets,
    CNode * NodeList ) [pure virtual]
```

Read element data from stream Input.

Implemented in [CBar](#).

4.4.3.9 SizeOfStiffnessMatrix()

```
virtual unsigned int CElement::SizeOfStiffnessMatrix ( ) [pure virtual]
```

Return the size of the element stiffness matrix (stored as an array column by column)

Implemented in [CBar](#).

4.4.3.10 Write()

```
virtual void CElement::Write (
    ostream & OutputFile,
    unsigned int Ele ) [pure virtual]
```

Write element data to stream *OutputFile*.

Implemented in [CBar](#).

4.4.4 Friends And Related Function Documentation

4.4.4.1 CDomain

```
friend class CDomain [friend]
```

4.4.5 Member Data Documentation

4.4.5.1 ElementMaterial

```
CMaterial* CElement::ElementMaterial [protected]
```

Material of the element.

Pointer to an element of [MaterialSetList](#)[][]

4.4.5.2 LocationMatrix

```
unsigned int* CElement::LocationMatrix [protected]
```

Location Matrix of the element.

4.4.5.3 ND

```
unsigned int CElement::ND [protected]
```

Dimension of the location matrix.

4.4.5.4 NEN

```
unsigned int CElement::NEN [protected]
```

Number of nodes per element.

4.4.5.5 nodes

```
CNode** CElement::nodes [protected]
```

Nodes of the element.

The documentation for this class was generated from the following files:


- /Users/xzhang/git/FEM-Projects/STAPpp/src/h/[Element.h](#)
- /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/[Element.cpp](#)

4.5 CLDLTSolver Class Reference


LDLT solver: A in core solver using skyline storage and column reduction scheme.

```
#include <Solver.h>
```

Inheritance diagram for CLDLTSolver:



Collaboration diagram for CLDLTSolver:



Public Member Functions

- `CLDLTSolver` (`CSkylineMatrix< double > *K`)
Constructor.
- void `LDLT` ()
*Perform $L*D*L(T)$ factorization of the stiffness matrix.*
- void `BackSubstitution` (`double *Force`)
Reduce right-hand-side load vector and back substitute.

Additional Inherited Members

4.5.1 Detailed Description

LDLT solver: A in core solver using skyline storage and column reduction scheme.

4.5.2 Constructor & Destructor Documentation

4.5.2.1 CLDLTSolver()

```
CLDLTSolver::CLDLTSolver (
    CSkylineMatrix< double > * K ) [inline]
```

Constructor.

4.5.3 Member Function Documentation

4.5.3.1 BackSubstitution()

```
void CLDLTSolver::BackSubstitution (
    double * Force )
```

Reduce right-hand-side load vector and back substitute.

4.5.3.2 LDLT()

```
void CLDLTSolver::LDLT ( )
```

Perform $L \cdot D \cdot L^T$ factorization of the stiffness matrix.

The documentation for this class was generated from the following files:

- [/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Solver.h](#)
- [/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Solver.cpp](#)

4.6 CLoadCaseData Class Reference

Class LoadData is used to store load data.

```
#include <LoadCaseData.h>
```

Public Member Functions

- [CLoadCaseData](#) ()
- [~CLoadCaseData](#) ()
- void [Allocate](#) (unsigned int num)
Set nloads, and new array node, dof and load.
- bool [Read](#) (ifstream &Input, unsigned int lcase)
Read load case data from stream Input.
- void [Write](#) (ofstream &OutputFile, unsigned int lcase)
Write load case data to stream OutputFile.

Public Attributes

- unsigned int [nloads](#)
Number of concentrated loads in this load case.
- unsigned int * [node](#)
Node number to which this load is applied.
- unsigned int * [dof](#)
Degree of freedom number for this load component.
- double * [load](#)
Magnitude of load.

4.6.1 Detailed Description

Class LoadData is used to store load data.

4.6.2 Constructor & Destructor Documentation

4.6.2.1 CLoadCaseData()

```
CLoadCaseData::CLoadCaseData ( ) [inline]
```

4.6.2.2 ~CLoadCaseData()

```
CLoadCaseData::~~CLoadCaseData ( )
```

4.6.3 Member Function Documentation

4.6.3.1 Allocate()

```
void CLoadCaseData::Allocate (
    unsigned int num )
```

Set nloads, and new array node, dof and load.

4.6.3.2 Read()

```
bool CLoadCaseData::Read (
    ifstream & Input,
    unsigned int lcase )
```

Read load case data from stream Input.

4.6.3.3 Write()

```
void CLoadCaseData::Write (
    ofstream & OutputFile,
    unsigned int lcase )
```

Write load case data to stream OutputFile.

4.6.4 Member Data Documentation

4.6.4.1 dof

```
unsigned int* CLoadCaseData::dof
```

Degree of freedom number for this load component.

4.6.4.2 load

```
double* CLoadCaseData::load
```

Magnitude of load.

4.6.4.3 nloads

```
unsigned int CLoadCaseData::nloads
```

Number of concentrated loads in this load case.

4.6.4.4 node

```
unsigned int* CLoadCaseData::node
```

Node number to which this load is applied.

The documentation for this class was generated from the following files:

- [/Users/xzhang/git/FEM-Projects/STAPpp/src/h/LoadCaseData.h](#)
- [/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/LoadCaseData.cpp](#)

4.7 Clock Class Reference

[Clock](#) class for timing.

```
#include <Clock.h>
```

Public Member Functions

- [Clock](#) ()
Constructor.
- void [Start](#) ()
Start the clock.
- void [Stop](#) ()
Stop the clock.
- void [Resume](#) ()
Resume the stoped clock.
- void [Clear](#) ()
Clear the clock.
- double [ElapsedTime](#) ()
Return the elapsed time since the clock started.

Private Attributes

- clock_t [t0_](#)
- clock_t [t1_](#)
- double [ct_](#)
- bool [st0_](#)
Flag for Start method.
- bool [st1_](#)
Flag for Stop method.

4.7.1 Detailed Description

[Clock](#) class for timing.

4.7.2 Constructor & Destructor Documentation

4.7.2.1 Clock()

```
Clock::Clock ( )
```

Constructor.

4.7.3 Member Function Documentation

4.7.3.1 Clear()

```
void Clock::Clear ( )
```

Clear the clock.

4.7.3.2 ElapsedTime()

```
double Clock::ElapsedTime ( )
```

Return the elapsed time since the clock started.

4.7.3.3 Resume()

```
void Clock::Resume ( )
```

Resume the stoped clock.

4.7.3.4 Start()

```
void Clock::Start ( )
```

Start the clock.

4.7.3.5 Stop()

```
void Clock::Stop ( )
```

Stop the clock.

4.7.4 Member Data Documentation

4.7.4.1 ct_

```
double Clock::ct_ [private]
```

4.7.4.2 st0_

```
bool Clock::st0_ [private]
```

Flag for Start method.

4.7.4.3 st1_

```
bool Clock::st1_ [private]
```

Flag for Stop method.

4.7.4.4 t0_

```
clock_t Clock::t0_ [private]
```

4.7.4.5 t1_

```
clock_t Clock::t1_ [private]
```

The documentation for this class was generated from the following files:


- [/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Clock.h](#)
- [/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Clock.cpp](#)

4.8 CMaterial Class Reference

Material base class which only define one data member.

```
#include <Material.h>
```

Inheritance diagram for CMaterial:



Public Member Functions

- virtual bool [Read](#) (ifstream &Input, unsigned int mset)=0
Read material data from stream Input.
- virtual void [Write](#) (ofstream &OutputFile, unsigned int mset)=0
Write material data to Stream OutputFile.

Public Attributes

- unsigned int [nset](#)
Number of set.
- double [E](#)
Young's modulus.

4.8.1 Detailed Description

Material base class which only define one data member.

All type of material classes should be derived from this base class

4.8.2 Member Function Documentation

4.8.2.1 Read()

```
virtual bool CMaterial::Read (  
    ifstream & Input,  
    unsigned int mset ) [pure virtual]
```

Read material data from stream Input.

Implemented in [CBarMaterial](#).

4.8.2.2 Write()

```
virtual void CMaterial::Write (  
    ofstream & OutputFile,  
    unsigned int mset ) [pure virtual]
```

Write material data to Stream OutputFile.

Implemented in [CBarMaterial](#).

4.8.3 Member Data Documentation

4.8.3.1 E

`double CMaterial::E`

Young's modulus.

4.8.3.2 nset

`unsigned int CMaterial::nset`

Number of set.

The documentation for this class was generated from the following file:

- [/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Material.h](#)

4.9 CNode Class Reference

Node class.

```
#include <Node.h>
```

Public Member Functions

- [CNode](#) (double X=0, double Y=0, double Z=0)
Constructor.
- bool [Read](#) (ifstream &Input, unsigned int np)
Read nodal point data from stream Input.
- void [Write](#) (ofstream &OutputFile, unsigned int np)
Output nodal point data to stream OutputFile.
- void [WriteEquationNo](#) (ofstream &OutputFile, unsigned int np)
Output equation numbers of nodal point to stream OutputFile.
- void [WriteNodalDisplacement](#) (ofstream &OutputFile, unsigned int np, double *Displacement)
Write nodal displacement.

Public Attributes

- unsigned int [NodeNumber](#)
Node numer.
- double [XYZ](#) [[NDF](#)]
x, y and z coordinates of the node
- unsigned int [bcode](#) [[NDF](#)]
Boundary code of each degree of freedom of the node.

Static Public Attributes

- static const unsigned int **NDF** = 3
Maximum number of degrees of freedom per node.

4.9.1 Detailed Description

Node class.

4.9.2 Constructor & Destructor Documentation

4.9.2.1 CNode()

```
CNode::CNode (
    double X = 0,
    double Y = 0,
    double Z = 0 )
```

Constructor.

4.9.3 Member Function Documentation

4.9.3.1 Read()

```
bool CNode::Read (
    ifstream & Input,
    unsigned int np )
```

Read nodal point data from stream Input.

4.9.3.2 Write()

```
void CNode::Write (
    ofstream & OutputFile,
    unsigned int np )
```

Output nodal point data to stream OutputFile.

4.9.3.3 WriteEquationNo()

```
void CNode::WriteEquationNo (
    ostream & OutputFile,
    unsigned int np )
```

Output equation numbers of nodal point to stream *OutputFile*.

4.9.3.4 WriteNodalDisplacement()

```
void CNode::WriteNodalDisplacement (
    ostream & OutputFile,
    unsigned int np,
    double * Displacement )
```

Write nodal displacement.

4.9.4 Member Data Documentation

4.9.4.1 bcode

```
unsigned int CNode::bcode[NDF]
```

Boundary code of each degree of freedom of the node.

0: The corresponding degree of freedom is active (defined in the global system)

1: The corresponding degree of freedom is nonactive (not defined)

After call *Domain::CalculateEquationNumber()*, *bcode* stores the global equation number corresponding to each degree of freedom of the node

4.9.4.2 NDF

```
const unsigned int CNode::NDF = 3 [static]
```

Maximum number of degrees of freedom per node.

For 3D bar and solid elements, NDF = 3. For 3D beam or shell elements, NDF = 5 or 6

4.9.4.3 NodeNumber

```
unsigned int CNode::NodeNumber
```

Node number.

4.9.4.4 XYZ

```
double CNode::XYZ[NDF]
```

x, y and z coordinates of the node

The documentation for this class was generated from the following files:

- /Users/xzhang/git/FEM-Projects/STAPpp/src/h/Node.h
- /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Node.cpp

4.10 COutputter Class Reference

Outputter class is used to output results.

```
#include <Outputter.h>
```

Collaboration diagram for COutputter:



Public Member Functions

- ofstream * [GetOutputFile](#) ()
Return pointer to the output file stream.
- void [PrintTime](#) (const struct tm *ptm, ostream &output)
Output current time and date.
- void [OutputHeading](#) ()
Output logo and heading.
- void [OutputNodeInfo](#) ()
Output nodal point data.
- void [OutputEquationNumber](#) ()
Output equation numbers.
- void [OutputElementInfo](#) ()
Output element data.
- void [PrintBarElementData](#) (unsigned int EleGrp)
Output bar element data.
- void [OutputLoadInfo](#) ()
Output load data.
- void [OutputNodalDisplacement](#) (unsigned int lcase)
Output displacement data.
- void [OutputElementStress](#) ()
Output element stresses.
- void [OutputTotalSystemData](#) ()
Print total system data.

Static Public Member Functions

- static [COutputter](#) * [Instance](#) (string FileName=" ")
Return the single instance of the class.

Protected Member Functions

- [COutputter](#) (string FileName)
Constructor.

Static Protected Attributes

- static [COutputter](#) * [_instance](#) = NULL
Designed as a single instance class.

Private Attributes

- ofstream [OutputFile](#)
File stream for output.

4.10.1 Detailed Description

Outputter class is used to output results.

4.10.2 Constructor & Destructor Documentation

4.10.2.1 COutputter()

```
COutputter::COutputter (
    string FileName ) [protected]
```

Constructor.

4.10.3 Member Function Documentation

4.10.3.1 GetOutputFile()

```
ofstream* COutputter::GetOutputFile ( ) [inline]
```

Return pointer to the output file stream.

4.10.3.2 Instance()

```
COutputter * COutputter::Instance (
    string FileName = " " ) [static]
```

Return the single instance of the class.

4.10.3.3 OutputElementInfo()

```
void COutputter::OutputElementInfo ( )
```

Output element data.

4.10.3.4 OutputElementStress()

```
void COutputter::OutputElementStress ( )
```

Output element stresses.

4.10.3.5 OutputEquationNumber()

```
void COutputter::OutputEquationNumber ( )
```

Output equation numbers.

4.10.3.6 OutputHeading()

```
void COutputter::OutputHeading ( )
```

Output logo and heading.

4.10.3.7 OutputLoadInfo()

```
void COutputter::OutputLoadInfo ( )
```

Output load data.

4.10.3.8 OutputNodalDisplacement()

```
void COutputter::OutputNodalDisplacement (
    unsigned int lcase )
```

Output displacement data.

4.10.3.9 OutputNodeInfo()

```
void COutputter::OutputNodeInfo ( )
```

Output nodal point data.

4.10.3.10 OutputTotalSystemData()

```
void COutputter::OutputTotalSystemData ( )
```

Print total system data.

4.10.3.11 PrintBarElementData()

```
void COutputter::PrintBarElementData (
    unsigned int EleGrp )
```

Output bar element data.

4.10.3.12 PrintTime()

```
void COutputter::PrintTime (
    const struct tm * ptm,
    ostream & output )
```

Output current time and date.

4.10.4 Member Data Documentation

4.10.4.1 `_instance`

```
COutputter * COutputter::_instance = NULL [static], [protected]
```

Designed as a single instance class.

4.10.4.2 `OutputFile`

```
ofstream COutputter::OutputFile [private]
```

File stream for output.

The documentation for this class was generated from the following files:


- [/Users/xzhang/git/FEM-Projects/STAPpp/src/h/Outputter.h](#)
- [/Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Outputter.cpp](#)

4.11 CSkylineMatrix< T_ > Class Template Reference

[CSkylineMatrix](#) class is used to store the FEM stiffness matrix in skyline storage.

```
#include <SkylineMatrix.h>
```

Collaboration diagram for CSkylineMatrix< T_ >:



Public Member Functions

- [CSkylineMatrix](#) ()
constructors
- [CSkylineMatrix](#) (unsigned int N)
- [~CSkylineMatrix](#) ()
destructor
- T_ & [operator](#)() (unsigned int i, unsigned int j)
operator function (i,j) where i and j number from 1
- T_ [operator](#)() (unsigned int i)
operator function (i) where i numbers from 1
- void [Allocate](#) ()
Allocate storage for the skyline matrix.
- unsigned int * [GetColumnHeights](#) ()
Return pointer to the ColumnHeights_.
- unsigned int * [GetDiagonalAddress](#) ()
Return pointer to the DiagonalAddress_.
- unsigned int [dim](#) () const
Return the dimension of the stiffness matrix.
- unsigned int [size](#) () const
Return the size of the storage used to store the stiffness matrix in skyline.

Private Attributes

- T_ * [data_](#)
Store the stiffness matrix in skyline storage.
- unsigned int [NEQ_](#)
Dimension of the stiffness matrix.
- unsigned int [NWK_](#)
Size of the storage used to store the stiffness matrix in skyline.
- unsigned int * [ColumnHeights_](#)
Column heights.
- unsigned int * [DiagonalAddress_](#)
Diagonal address of all columns in data_.

4.11.1 Detailed Description

```
template<class T_>
class CSkylineMatrix< T_ >
```

[CSkylineMatrix](#) class is used to store the FEM stiffness matrix in skyline storage.

4.11.2 Constructor & Destructor Documentation

4.11.2.1 CSkylineMatrix() [1/2]

```
template<class T_ >
CSkylineMatrix< T_ >::CSkylineMatrix ( ) [inline]
```

constructors

constructor functions

4.11.2.2 CSkylineMatrix() [2/2]

```
template<class T_ >
CSkylineMatrix< T_ >::CSkylineMatrix (
    unsigned int N ) [inline]
```

4.11.2.3 ~CSkylineMatrix()

```
template<class T_ >
CSkylineMatrix< T_ >::~~CSkylineMatrix< T_ > ( ) [inline]
```

destructor

destructor function

4.11.3 Member Function Documentation

4.11.3.1 Allocate()

```
template<class T_ >
void CSkylineMatrix< T_ >::Allocate ( ) [inline]
```

Allocate storage for the skyline matrix.

Allocate storage for the matrix.

4.11.3.2 dim()

```
template<class T_ >
unsigned int CSkylineMatrix< T_ >::dim ( ) const [inline]
```

Return the dimension of the stiffness matrix.

4.11.3.3 GetColumnHeights()

```
template<class T_ >
unsigned int * CSkylineMatrix< T_ >::GetColumnHeights ( ) [inline]
```

Return pointer to the ColumnHeights_.

4.11.3.4 GetDiagonalAddress()

```
template<class T_ >
unsigned int * CSkylineMatrix< T_ >::GetDiagonalAddress ( ) [inline]
```

Return pointer to the DiagonalAddress_.

4.11.3.5 operator>() [1/2]

```
template<class T_ >
T_ & CSkylineMatrix< T_ >::operator() (
    unsigned int i,
    unsigned int j ) [inline]
```

operator function (i,j) where i and j number from 1

operator (i,j) where i and j number from 1 For the sake of efficiency, the index bounds are not checked

4.11.3.6 operator>() [2/2]

```
template<class T_ >
T_ CSkylineMatrix< T_ >::operator() (
    unsigned int i ) [inline]
```

operator function (i) where i numbers from 1

operator (i) where i numbers from 1 For the sake of efficiency, the index bounds are not checked

4.11.3.7 size()

```
template<class T_ >
unsigned int CSkylineMatrix< T_ >::size ( ) const [inline]
```

Return the size of the storage used to store the stiffness matrkix in skyline.

4.11.4 Member Data Documentation

4.11.4.1 ColumnHeights_

```
template<class T_>
unsigned int* CSkylineMatrix< T_ >::ColumnHeights_ [private]
```

Column hights.

4.11.4.2 data_

```
template<class T_>
T_* CSkylineMatrix< T_ >::data_ [private]
```

Store the stiffness matrrix in skyline storage.

4.11.4.3 DiagonalAddress_

```
template<class T_>
unsigned int* CSkylineMatrix< T_ >::DiagonalAddress_ [private]
```

Diagonal address of all columns in data_.

4.11.4.4 NEQ_

```
template<class T_>
unsigned int CSkylineMatrix< T_ >::NEQ_ [private]
```

Dimension of the stiffness matrix.

4.11.4.5 NWK_

```
template<class T_>
unsigned int CSkylineMatrix< T_ >::NWK_ [private]
```

Size of the storage used to store the stiffness matrrix in skyline.

The documentation for this class was generated from the following file:


- [/Users/xzhang/git/FEM-Projects/STAPpp/src/h/SkylineMatrix.h](#)

4.12 CSolver Class Reference


Base class for a solver.

```
#include <Solver.h>
```

Inheritance diagram for CSolver:



Collaboration diagram for CSolver:



Public Member Functions

- [CSolver](#) ([CSkylineMatrix< double > *K](#))

Protected Attributes

- [CSkylineMatrix< double > * K](#)

4.12.1 Detailed Description

Base class for a solver.

4.12.2 Constructor & Destructor Documentation

4.12.2.1 CSolver()

```
CSolver::CSolver (
    CSkylineMatrix< double > * K )
```

4.12.3 Member Data Documentation

4.12.3.1 K

```
CSkylineMatrix<double>* CSolver::K [protected]
```

The documentation for this class was generated from the following files:

- /Users/xzhang/git/FEM-Projects/STAPpp/src/h/[Solver.h](#)
- /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/[Solver.cpp](#)


Chapter 5

File Documentation

5.1 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Bar.cpp File Reference

```
#include "Bar.h"  
#include <iostream>  
#include <iomanip>  
#include <cmath>
```


Include dependency graph for Bar.cpp:



5.2 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Clock.cpp File Reference

```
#include "Clock.h"
```

Include dependency graph for Clock.cpp:




5.3 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Domain.cpp File Reference

```

#include "Domain.h"
#include "Bar.h"
#include "Material.h"
#include <iomanip>
#include <iostream>

```

Include dependency graph for Domain.cpp:



Functions

- `template<class type >`
`void clear (type *a, unsigned int N)`
Clear an array.

5.3.1 Function Documentation

5.3.1.1 clear()


```
template<class type >
void clear (
    type * a,
    unsigned int N )
```

Clear an array.

5.4 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Element.cpp File Reference

```
#include <algorithm>
#include "Element.h"
```

Include dependency graph for Element.cpp:




5.5 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/LoadCaseData.cpp File Reference

```
#include "LoadCaseData.h"
#include <iomanip>
```

```
#include <iostream>
```


Include dependency graph for LoadCaseData.cpp:



5.6 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/main.cpp File Reference

```
#include <string>
#include <iostream>
#include "Domain.h"
#include "Bar.h"
#include "Outputter.h"
#include "Clock.h"
```

Include dependency graph for main.cpp:



Functions

- int [main](#) (int argc, char *argv[])

5.6.1 Function Documentation


5.6.1.1 main()

```
int main (
    int argc,
    char * argv[] )
```

5.7 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Material.cpp File Reference

```
#include "Material.h"
#include <iostream>
#include <fstream>
#include <iomanip>
```


Include dependency graph for Material.cpp:



5.8 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Node.cpp File Reference

```
#include <iostream>
#include <iomanip>
#include "Node.h"
```

Include dependency graph for Node.cpp:




5.9 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Outputter.cpp File Reference

```

#include "Domain.h"
#include "Outputter.h"
#include "SkylineMatrix.h"
#include <iostream>
#include <iomanip>
#include <ctime>

```

Include dependency graph for Outputter.cpp:



5.10 /Users/xzhang/git/FEM-Projects/STAPpp/src/cpp/Solver.cpp File Reference


```

#include "Solver.h"
#include <cmath>
#include <cmath>

```

```
#include <iostream>
```


Include dependency graph for Solver.cpp:




5.11 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/Bar.h File Reference

```
#include "Element.h"
```

Include dependency graph for Bar.h:



This graph shows which files directly or indirectly include this file:



Classes


- class [CBar](#)

Bar element class.


5.12 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/Clock.h File Reference

```
#include <time.h>
#include <iostream>
```

Include dependency graph for Clock.h:



This graph shows which files directly or indirectly include this file:



Classes


- class [Clock](#)

[Clock](#) class for timing.


5.13 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/Domain.h File Reference

```
#include <string>
#include <fstream>
#include <vector>
#include "Node.h"
#include "Bar.h"
#include "Outputter.h"
#include "Solver.h"
#include "LoadCaseData.h"
#include "SkylineMatrix.h"
```

Include dependency graph for Domain.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [CDomain](#)

Domain class : Define the problem domain.

Functions

- `template<class type >`
`void clear (type *a, unsigned int N)`

Clear an array.

5.13.1 Function Documentation

5.13.1.1 `clear()`


```

template<class type >
void clear (
    type * a,
    unsigned int N )
  
```


Clear an array.

5.14 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/Element.h File Reference

```
#include <stddef.h>
#include <vector>
#include <string>
#include <iostream>
#include <fstream>
#include "Node.h"
#include "Material.h"
#include "SkylineMatrix.h"
Include dependency graph for Element.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [CElement](#)
Element base class.

Functions

- `template<class type >`
`void clear (type *a, unsigned int N)`

Clear an array.

5.14.1 Function Documentation


5.14.1.1 clear()

```
template<class type >
void clear (
    type * a,
    unsigned int N )
```


Clear an array.

5.15 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/LoadCaseData.h File Reference

```
#include <string>
#include <fstream>
Include dependency graph for LoadCaseData.h:
```



This graph shows which files directly or indirectly include this file:



Classes


- class [CLoadCaseData](#)

Class LoadData is used to store load data.


5.16 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/Material.h File Reference

```
#include <stddef.h>
#include <iostream>
#include <fstream>
```

Include dependency graph for Material.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [CMaterial](#)

Material base class which only define one data member.


- class [CBarMaterial](#)

Material class for bar element.


5.17 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/Node.h File Reference

```
#include <iostream>
#include <fstream>
```

Include dependency graph for Node.h:



This graph shows which files directly or indirectly include this file:



Classes


- class [CNode](#)
Node class.

5.18 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/Outputter.h File Reference


```
#include <fstream>
#include <iostream>
```

```
#include <string>
```

Include dependency graph for Outputter.h:



This graph shows which files directly or indirectly include this file:



Classes


- class [COutputter](#)

Outputter class is used to output results.


5.19 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/SkylineMatrix.h File Reference

```
#include <string>
```

Include dependency graph for SkylineMatrix.h:



This graph shows which files directly or indirectly include this file:



Classes


- class [CSkylineMatrix< T_>](#)

CSkylineMatrix class is used to store the FEM stiffness matrix in skyline storage.


5.20 /Users/xzhang/git/FEM-Projects/STAPpp/src/h/Solver.h File Reference

```
#include "SkylineMatrix.h"
```

Include dependency graph for Solver.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [CSolver](#)
Base class for a solver.
- class [CLDLTSolver](#)
LDLT solver: A in core solver using skyline storage and column reduction scheme.