


Using HAPI to enable uniform access to Space Weather timeseries data

Jon Vandegriff, Johns Hopkins Applied Physics Lab Robert Weigel, George Mason University Jeremy Faden, Cottage Systems and University of Iowa Todd King, University of California Los Angeles D Aaron Roberts, NASA Goddard Space Flight Center Bernard Harris, NASA Goddard Space Flight Center Robert Candey, NASA Goddard Space Flight Center Nand Lal, NASA Goddard Space Flight Center Scott Boardsen, NASA Goddard Space Flight Center Doug Lindholm, University of Colorado, LASP Chris Lindholm, University of Colorado, LASP Thomas Baltzer, University of Colorado, LASP Larry Brown, Johns Hopkins Applied Physics Lab Eric Grimes, University of California Los Angeles Baptiste Cecconi, Observatoire de Paris/PSL Vincent Génot, IRAP, CNRS-CNES-UPS, Toulouse, France Benjamin Renard, AKKA Technologies, Toulouse, France Arnaud Masson, Tpz UK for ESA, ESAC, Madrid, Spain Beatriz Martinez, RHEA Group for ESA, ESAC

HAPI is being adopted internationally






















Motivating the need for interoperability

- lots of data sources needed for Space Weather!
 - model input (indices, solar wind properties), model output, spacecraft trajectories, sensor measurements (for comparison with models)
- these usually come from disparate sources
- example: Omniweb data as input to a magnetic field model, whose output should be compared to GOES magnetometer data along the spacecraft trajectory
 - all of these could have a different access method and format

Putting data online is easy, so diverse options exist


- creating an online data access mechanism has been done many times
- different groups have made similar but not identical access mechanisms
- even if everyone had used the same standard access mechanism, these standards are flexible enough that they would not automatically support interoperability





Interoperability requires a simple, common access mechanism: HAPI

- nothing new in terms of technology or complexity
- just need everyone to agree to use the same lowest common denominator
- can add a HAPI mechanism alongside existing services



Focus is Timeseries

- conceptually a table, like a spreadsheet
- time column with any number of variables (data columns)
- each variable can be multidimensional

Time	data1	scalar2	array	multiDimArray
t0	d0	s0	a0[11]	m0[3,8]
t1	d1	s1	a1[11]	m1[3,8]
t1	d2	s2	a2[11]	m2[3,8]
t2	d3	s3	a3[11]	m3[3,8]
t4	d4	s4	a4[11]	m4[3,8]
t5	d5	s5	a5[11]	m5[3,8]
t6	d6	s6	a6[11]	m6[3,8]

Existing Types of Data Access (non-HAPI)

direct access to files: http or ftp

- obvious standards needed: file format, file names, directory structure
- more subtle standards needed for full interoperability:
 - file metadata
 - variable layout
 - time value format

2. service-based access: CGI, web services (RESTful or custom)

- obvious standards needed:
 - request format (how to ask for data)
 - response format (what does the returned data look like?)
 - collection of files, OR
 - stream of numbers (JSON, XML, CSV binary, etc)
- more subtle standards:
 - file metadata
 - variable layout
 - time value format



HAPI Heliophysics Application Programmer's Interface

first and foremost it is a specification – a server API to make your data interoperable

```
main page for all-things HAPI: https://hapi-server.github.io/
```

- two aspects standardized
 - request interface
 - response format
- key standardizations includes a common format for the time values
 - subset of ISO 8601 standard for time as a string
 - same format for time values on input and output
 - examples: 2009-315T15:39:30.500Z 2021-03-17 2025-01-01T12:00:00Z

The request interface: 5 HAPI Endpoints

All endpoints must be directly below a URL that ends with 'hapi'

- http://example.com/hapi/about
 - contact info for technical issues and description of server
- http://example.com/hapi/capabilities
 - describes options implemented by the server
- http://example.com/hapi/catalog
 - list of datasets at the server
- http://example.com/hapi/info
 - show metadata for one dataset at a time (basically a data header).
- http://example.com/hapi/data
 - retrieve a stream of data content for one dataset over a specific time range

small JSON response

possibly large response: CSV (required) JSON(optional) binary (optional)

Working examples

Servers

George Mason

GSFC

Univ. of Iowa

JHU/APL

AMDA

Provisional / Coming Soon:

ESAC

CCMC

LASP

PDS / PPI Node at UCLA

Try this interactive list:

http://hapi-server.org/servers/

Clients

Python client

IDL client

Matlab Client

Applications:

Autoplot

SPFDAS


PySPEDAS

MIDL4

Client codes as open-source projects:

https://github.com/hapi-server

Autoplot with panels from several HAPI servers



If you want to serve data using HAPI

- read the specification -- it is very complete
- ways to get to HAPI compliance:
 - modify your existing access mechanism codebase to add HAPI protocols
 OR-
 - use an existing front end server for managing HAPI details
 https://github.com/hapi-server/server-nodejs
 This is a very well-documented and tested code that can get you up and running quickly!
- For either option above, test your server using this extremely useful verifier tool
 - http://tsds.org/verify-hapi
 - this checks all of the important parts of the spec, and many corner cases
 - can also test your server in an existing client (Python, Autoplot, SPEDAS, MIDL4)
- sign up on the mailing list: hapi-news@hapi-server.org
- ask for help
 - email anyone involved in making the spec (authors on this paper)
 - contact other early adopters


These two have proven to be very useful!

New and Coming Soon or Eventually

- AMDA HAPI server is up and running
- ESAC HAPI server
 - inevitable, but takes time
 - start with Node is front end, eventually migrate to native HAPI implementation
- HAPI 3.0 specification final edits being made
- Some changes in 3.0:
 - regularizing some keywords in the actual API (not backward compatible)
 - time varying bins
 - references in JSON metadata for repeated quantities
 - new about endpoint
- HAPI paper being written
- More focused promotion and support for NASA projects
 - add higher level view "What HAPI servers are out there?" "Are they up right now?" "What data do they have?"
 - integration of HAPI within SpacePy and SunPy
 - support for instrument teams help them use HAPI on their native data systems
 - improve the generic server capability (Python and Java full servers)
 - add layers on top of HAPI for data mining

HAPI and **Data** Mining

A Python-based, data fusing application is now not too difficult.



Using the uniformity afforded by HAPI, precursor steps to Machine Learning (access, cleaning, regularizing) can be simplified.

Would be possible to use HAPI in a cloud-based environment (streaming access).

Next-Level of Uniform Access Beyond HAPI

- HAPI defines an interoperable way to get to the numbers
- Still lots of variability between datasets with similar measurements
- Can we define science-specific, semantically identical, machine readable interfaces to data based on the type of science measurements => Science Data Interfaces
- Create generic API that captures the lowest common denominator of every measurement type:
 - magnetic field
 - plasma wave data
 - plasma moments
 - energetic particles
 - energetic neutral atoms
- Also need similar APIs for numeric ancillary info:
 - spacecraft ephemeris
 - coordinate frames for vectors:
 - spacecraft position (it's a vector)
 - magnetic field direction
 - plasma velocity
 - particle flow direction

Layers of Interoperability

Generic Data Cleaning Routines **Uniform Semantic Data** Semantic API **Uniform Syntactic Data HAPI** Access Layer Raw Data

