

# Chapter 8: Network Security

## *Chapter goals:*

- ❖ understand principles of network security:
  - cryptography and its *many* uses beyond “confidentiality”
  - authentication
  - message integrity
- ❖ security in practice:
  - firewalls and intrusion detection systems
  - security in application, transport, network, link layers

# Chapter 8 roadmap

*8.1 What is network security?*

8.2 Principles of cryptography

8.3 Message integrity, authentication

8.4 Securing e-mail

8.5 Securing TCP connections: SSL

8.6 Network layer security: IPsec

8.7 Securing wireless LANs

8.8 Operational security: firewalls and IDS

# What is network security?

*confidentiality:* only sender, intended receiver should “understand” message contents

- sender encrypts message
- receiver decrypts message


*authentication:* sender, receiver want to confirm identity of each other

*message integrity:* sender, receiver want to ensure message not altered (in transit, or afterwards) without detection

*access and availability:* services must be accessible and available to users

# Friends and enemies: Alice, Bob, Trudy


- ❖ well-known in network security world
- ❖ Bob, Alice (lovers!) want to communicate “securely”
- ❖ Trudy (intruder) may intercept, delete, add messages



# Who might Bob, Alice be?

- ❖ ... well, *real-life* Bobs and Alices!
- ❖ Web browser/server for electronic transactions (e.g., on-line purchases)
- ❖ on-line banking client/server
- ❖ DNS servers
- ❖ routers exchanging routing table updates
- ❖ other examples?

# The language of cryptography




$m$  plaintext message

$K_A(m)$  ciphertext, encrypted with key  $K_A$

$m = K_B(K_A(m))$

# Symmetric key cryptography



**symmetric key crypto:** Bob and Alice share same (symmetric) key:  $K_S$

- ❖ e.g., key is knowing substitution pattern in mono alphabetic substitution cipher

Q: how do Bob and Alice agree on key value?

# Symmetric key crypto: DES

## DES: Data Encryption Standard

- ❖ US encryption standard [NIST 1993]
- ❖ 56-bit symmetric key, 64-bit plaintext input
- ❖ block cipher with cipher block chaining
- ❖ how secure is DES?
  - DES Challenge: 56-bit-key-encrypted phrase decrypted (brute force) in less than a day
  - no known good analytic attack
- ❖ making DES more secure:
  - 3DES: encrypt 3 times with 3 different keys



# Public Key Cryptography



## *symmetric key crypto*

- ❖ requires sender, receiver know shared secret key
- ❖ Q: how to agree on key in first place (particularly if never “met”)?

## *public key crypto*

- ❖ radically different approach [Diffie-Hellman76, RSA78]
- ❖ sender, receiver do *not* share secret key
- ❖ *public* encryption key known to *all*
- ❖ *private* decryption key known only to receiver

## RSA: another important property

The following property will be *very* useful later:

$$\underbrace{K_B^-(K_B^+(m))}_{\text{use public key first, followed by private key}} = m = \underbrace{K_B^+(K_B^-(m))}_{\text{use private key first, followed by public key}}$$

use public key  
first, followed by  
private key

use private key  
first, followed by  
public key


*result is the same!*

# Authentication: yet another try

*Goal:* avoid playback attack

*nonce:* number (R) used only *once-in-a-lifetime*

*ap4.0:* to prove Alice “live”, Bob sends Alice *nonce*, R. Alice must return R, encrypted with shared secret key




Failures, drawbacks?

# Digital signatures

simple digital signature for message  $m$ :

- ❖ Bob signs  $m$  by encrypting with his private key  $K_B^-$ , creating “signed” message,  $K_B^-(m)$




# Message digests

computationally expensive to  
public-key-encrypt long  
messages

*goal:* fixed-length, easy- to-  
compute digital  
“fingerprint”

- ❖ apply hash function  $H$  to  $m$ , get fixed size message digest,  $H(m)$ .




## Hash function properties:


- ❖ many-to-1
- ❖ produces fixed-size msg digest (fingerprint)
- ❖ given message digest  $x$ , computationally infeasible to find  $m$  such that  $x = H(m)$

# Digital signature = signed message digest

Bob sends digitally signed message:



Alice verifies signature, integrity of digitally signed message:



# Public key cryptography

