How do loss and delay occur?

packets *queue* in router buffers

- packet arrival rate to link exceeds output link capacity
- packets queue, wait for turn



HTTP overview

HTTP: hypertext transfer protocol

- Web's application layer protocol
- client/server model
  - *client:* browser that requests, receives, (using HTTP protocol) and "displays" Web objects
  - *server:* Web server sends (using HTTP protocol) objects in response to requests

HTTP connections

non-persistent HTTP

- at most one object sent over TCP connection
  - connection then closed
- downloading multiple objects required multiple connections

persistent HTTP

- multiple objects can be sent over single TCP connection between client, server

Sample problem

- What's end-to-end delay using <u>persistent HTTP</u>?
  - Control messages (e.g. TCP handshake, HTTP request) = **K** bit long
  - Base HTML object = **L** bits
  - **N** reference objects, each **L** bit long
  - Link bandwidth = **R** bps
  - Propagation delay = **d** seconds

UDP: more

- often used for streaming multimedia apps
  - loss tolerant
  - rate sensitive
- other UDP uses
  - DNS
  - SNMP
- reliable transfer over UDP: add reliability at application layer
  - application-specific error recovery!



UDP segment format

Recap: Principles of Reliable Data Transfer

- What can happen over unreliable channel?
  - Packet error, packet loss
- What mechanisms for **packet error**?
  - Error detection, feedback, retransmission, sequence#
- What mechanisms for **packet loss**?
  - Timeout!
- We built simple reliable data transfer protocol
  - Real-world protocol (e.g., TCP) is more complex, but *with same principles!*

Pipelined protocols

Pipelining: sender allows multiple, "in-flight", yet-to-be-acknowledged pkts

- range of sequence numbers must be increased
- buffering at sender and/or receiver



(a) a stop-and-wait protocol in operation (b) a pipelined protocol in operation

- Two generic forms of pipelined protocols: *go-Back-N, selective repeat*

Go-Back-N

Sender:

- k-bit seq # in pkt header
- "window" of up to N, consecutive unack'ed pkts allowed



- ACK(n): ACKs all pkts up to, including seq # n - "cumulative ACK"
  - may receive duplicate ACKs (see receiver)
- timer for each in-flight pkt
- *timeout(n):* retransmit pkt n **and all higher seq # pkts in window**

Selective Repeat

- receiver *individually* acknowledges all correctly received pkts
  - buffers pkts, as needed, for eventual in-order delivery to upper layer
- sender only resends pkts for which ACK not received
  - sender timer for each unACKed pkt
- sender window
  - N consecutive seq #'s
  - again limits seq #s of sent, unACKed pkts

TCP: Overview RFCs: 793, 1122, 1323, 2018, 2581

- point-to-point:
  - one sender, one receiver
- reliable, in-order *byte stream:*
  - no "message boundaries"
- pipelined:
  - TCP congestion and flow control set window size
- *send & receive buffers*



- full duplex data:
  - bi-directional data flow in same connection
  - MSS: maximum segment size
- connection-oriented:
  - handshaking (exchange of control msgs) init's sender, receiver state before data exchange
- flow controlled:
  - sender will not overwhelm receiver

TCP segment structure



TCP seq. #'s and ACKs

Seq. #'s:

- byte stream "number" of first byte in segment's data

ACKs:

- seq # of next byte expected from other side
- cumulative ACK

Q: how receiver handles out-of-order segments

- A: TCP spec doesn't say, - up to implementor



simple telnet scenario

TCP retransmission scenarios (more)



Cumulative ACK scenario

Fast Retransmit

- Time-out period often relatively long:
  - long delay before resending lost packet
- Detect lost segments via duplicate ACKs.
  - Sender often sends many segments back-to-back
  - If segment is lost, there will likely be many duplicate ACKs.

- If sender receives 3 ACKs for the same data, it supposes that segment after ACKed data was lost:
  - fast retransmit: resend segment before timer expires

TCP congestion control: additive increase, multiplicative decrease

- *Approach:* increase transmission rate (window size), probing for usable bandwidth, until loss occurs
  - *additive increase:* increase **CongWin** by 1 MSS every RTT until loss detected
  - *multiplicative decrease*: cut **CongWin** in half after loss

Saw tooth behavior: probing for bandwidth



TCP Tahoe vs. TCP Reno



Chapter 4: network layer

chapter goals:

- understand principles behind network layer services:
  - network layer service models
  - forwarding versus routing
  - how a router works
  - routing (path selection)
  - broadcast, multicast
- instantiation, implementation in the Internet

Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol

- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms

- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet

- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

Network layer

- transport segment from sending to receiving host
- on sending side encapsulates segments into datagrams
- on receiving side, delivers segments to transport layer
- network layer protocols in *every* host, router
- router examines header fields in all IP datagrams passing through it



Two key network-layer functions

- *forwarding:* move packets from router's input to appropriate router output
- *routing:* determine route taken by packets from source to dest.
  - *routing algorithms*

analogy:

- *routing:* process of planning trip from source to dest
- *forwarding:* process of getting through single interchange

Interplay between routing and forwarding



routing algorithm determines end-end-path through network

forwarding table determines local forwarding at this router

Datagram networks

- no call setup at network layer
- routers: no state about end-to-end connections
  - no network-level concept of "connection"
- packets forwarded using destination host address



Datagram forwarding table

routing algorithm

local forwarding table

dest address	output link
address-range 1	3
address-range 2	2
address-range 3	2
address-range 4	1

4 billion IP addresses, so rather than list individual destination address
list *range* of addresses (aggregate table entries)



Datagram forwarding table

Destination Address Range	Link Interface
11001000 00010111 00010000 00000000 through 11001000 00010111 00010111 11111111	0
11001000 00010111 00011000 00000000 through 11001000 00010111 00011000 11111111	1
11001000 00010111 00011001 00000000 through 11001000 00010111 00011111 11111111	2
otherwise	3

Q: but what happens if ranges don't divide up so nicely?

Longest prefix matching

longest prefix matching

when looking for forwarding table entry for given destination address, use *longest* address prefix that matches destination address.

Destination Address Range	Link interface
11001000 00010111 00010*** *********	0
11001000 00010111 00011000 *********	1
11001000 00010111 00011*** *********	2
otherwise	3

examples:

DA: 11001000 00010111 00010110 10100001 which interface?

DA: 11001000 00010111 00011000 10101010 which interface?