8163B Lightwave Multimeter
8164B Lightwave Measurement System
8166B Lightwave Multichannel System

Data Sheet

KEYSIGHT
TECHNOLOGIES

Keysight 8163B Mainframe

The Keysight Lightwave Multimeter system includes the mainframe and a variety of plug-in modules, suited for set-ups requiring:
 – Single or dual channel power meters
 – Single or dual wavelength fixed or tunable sources
 – Loss test sets
 – Return loss test sets

Specifications

Display	Graphical active color display 300 x 240 points visible, 4 updates per second
Display resolution (power meters)	0.0001 dB/dBm, 0.0 1pW to 10 pW (depending on power meter), up to 6.5 digits (user definable)
Chipset	Mobile Intel QM57Express
Compatibility	The Keysight 8163B mainframe supports all 8153A Series and 8163A & B Series modules. [1]
Trigger	True synchronous on all channels. Max. 100 kHz for triggering and 1 MHz (50% duty cycle) for external digital modulation.

Environmental
   Storage temperature
   Operating temperature
   Humidity
	
	–40 °C to +70 °C
	0 °C to +45 °C
	< 95% rH from 0 °C to 55 °C
	The products are designed for pollution degree 2
	The maximum operation altitude is 2000 m

Power	AC 100 to 240 V ± 10%, 50 to 60 Hz 5%, 120 VA max.
Dimensions (height x width x length) Weight	88 mm x 213 mm x 380 mm (3.5" x 8.4" x 15") net 4.200 kg (9.3 lbs), shipping 6.5 kg (14.5 lbs)
GPIB capability	All modes and parameters accessible via GP-IB interface
GPIB interface function codes [2]	SH1, AH1, T6, L4, SR0, RL1, PP0, DC1, DT0, C0. SCPI Standard
GPIB interface performance	Max. 300 kB/sec (burst data rate during read of 12001 data points from power meter)
Local Area Network (LAN)	10/100BASE-T Ethernet port
Parallel printer interface	Centronics
RS232 interface: max. baud rate	115200 bps
Number of modules	2 modules

Ordering information
   8163B
   8163B-1CM
   08163-44101
	
	Lightwave Multimeter, Mainframe
	Rack mount kit (5063-9240)
	Filler panel for empty slots

1. Keysight 8163B Series modules are NOT compatible with the HP 8153A Lightwave Multimeter.
2. For code compatibility to the HP 8153A Lightwave Multimeter please refer to the mainframe's Programming Guide, part number 08164-90B65.

Keysight 8164B Mainframe

The Keysight 8164B mainframe, supports a range of high-performance tunable laser modules, as well as all of the fixed source and sensor modules of the 8153A and 8163A/B Lightwave Multimeter Series.

Specifications

Display	Graphical active color display, 640 x 480 points visible, 4 updates per second, VGA connector for external monitor
Compatibility	The Keysight 8164B mainframe supports all 8153A Series and 8163A & B Series modules. [1]
Trigger	True synchronous on all channels. Max. 100 kHz for triggering and 1 MHz (50% duty cycle) for external digital modulation.

Environmental
   Storage temperature
   Operating temperature
   Humidity
	
	–40 °C to +70 °C
	+10 °C to +35 °C
	< 80% rH from 10 °C to 35 °C
	The products are designed for pollution degree 2
	The maximum operation altitude is 2000 m

Power	AC 100 to 240 V ± 10%, 50/60 Hz , 280 VA max.
Dimensions (height x width x length) Weight	145 mm x 426 mm x 545 mm (5.8" x 16.9" x 21.6") net 20 kg, shipping 23 kg
GPIB capability	All modes and parameters accessible via GP-IB interface
GPIB interface function codes [2]	SH1, AH1, T6, L4, SR0, RL1, PP0, DC1, DT0, C0. SCPI Standard
GPIB interface performance	Max. 300 kB/sec (burst data rate during read of 12001 data points from power meter)
Local Area Network (LAN)	10/100BASE-T Ethernet port
Parallel printer interface	Centronics
RS232 interface: max. baud rate	115200 bps
Number of modules	4/1 modules

Ordering information
  8164B
  8164B-1CM
  8164B-1CN
  08163-44101
  81645A
	
	Lightwave Measurement System, Mainframe
	Rack mount kit (5063-9214)
	Front handle kit (5063-9227)
	Filler panel for empty slots (compact slots only)
	Filler module for 8164B mainframe (Slot 0)

1. Keysight 8163B Series modules are NOT compatible with the HP 8153A Lightwave Multimeter.
2. For code compatibility to the HP 8153A Lightwave Multimeter please refer to the mainframe's Programming Guide, part number 08164-90B65.

Keysight 8166B Mainframe (Discontinued)

The Keysight 8166B mainframe can be easily integrated into test environments by using plug and play drivers over GPIB, or by using the configurable hardware input and output trigger ports.

All modules of the 8163A/B Lightwave Multimeter family can be used in any combination in the Multichannel System.

Specifications

Display	Graphical active color display, 300 x 240 points visible, 4 updates per second, VGA connector for external monitor
Display resolution (power meters)	0.0001 dB/dBm, 0.01 pW to 10 pW (depending on power range), up to 6.5 digits (user definable)
Compatibility	The Keysight 8166B mainframe supports all modules from the 8163A/B Lightwave Multimeter series. [1]
Trigger	True synchronous on all channels. Max. 100 kHz for triggering and 1 MHz (50% duty cycle) for external digital modulation.
Environmental Storage temperature Operating temperature Humidity	−40 °C to +70 °C 0 °C to +45 °C < 95% rH from 0 °C to 45 °C The products are designed for pollution degree 2 The maximum operation altitude is 2000 m
Power	AC 100 to 240 V ± 10%, 50/60 Hz, 450 VA max.
Dimensions (height x width x length) Weight	240 mm x 430 mm x 580 mm (9.5" x 17" x 23") net 23 kg, shipping 45 kg
GPIB capability	All modes and parameters accessible via GP-IB interface
GPIB interface function codes [2]	SH1, AH1, T6, L4, SR0, RL1, PP0, DC1, DT0, C0. SCPI Standard
GPIB interface performance	Max. 300 kB/sec (burst data rate during read of 12001 data points from power meter)
Parallel printer Interface	Centronics
RS232 interface: max. baud rate	115200 bps
Number of modules	17 modules
Ordering information 8166B 8166B-1CM 08163-44101	Lightwave Multichannel System, Mainframe (discontinued) Rack mount kit (5063-9216) Filler panel for empty slots

1. Modules designed for the HP 8153A Lightwave Multimeter are NOT compatible with the Keysight 8166A/B Lightwave Multichannel System.
2. For code compatibility to the HP 8153A Lightwave Multimeter please refer to the mainframe's Programming Guide, part number 08164-90B65.

Evolving Since 1939

Our unique combination of hardware, software, services, and people can help you reach your next breakthrough. We are unlocking the future of technology.
From Hewlett-Packard to Agilent to Keysight.

myKeysight

myKeysight
www.keysight.com/find/mykeysight
A personalized view into the information most relevant to you.

http://www.keysight.com/find/emt_product_registration
Register your products to get up-to-date product information and find warranty information.

KEYSIGHT SERVICES
*Accelerate Technology Adoption.
Lower costs.*

Keysight Services
www.keysight.com/find/service
Keysight Services can help from acquisition to renewal across your instrument's lifecycle. Our comprehensive service offerings—one-stop calibration, repair, asset management, technology refresh, consulting, training and more—helps you improve product quality and lower costs.

Keysight Assurance Plans
www.keysight.com/find/AssurancePlans
Up to ten years of protection and no budgetary surprises to ensure your instruments are operating to specification, so you can rely on accurate measurements.

Keysight Channel Partners
www.keysight.com/find/channelpartners
Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

www.keysight.com/find/lightwave
www.keysight.com/find/oct

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at:
www.keysight.com/find/contactus

Americas
Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

Asia Pacific
Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 11 2626
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

Europe & Middle East
Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:
www.keysight.com/find/contactus
(BP-9-7-17)

DEKRA Certified
ISO9001 Quality Management System

www.keysight.com/go/quality
Keysight Technologies, Inc.
DEKRA Certified ISO 9001:2015
Quality Management System

KEYSIGHT
TECHNOLOGIES