

## 9.2 Regression with ARIMA errors in R

---

The R function `Arima()` will fit a regression model with ARIMA errors if the argument `xreg` is used. The `order` argument specifies the order of the ARIMA error model. If differencing is specified, then the differencing is applied to all variables in the regression model before the model is estimated. For example, the R command

```
fit <- Arima(y, xreg=x, order=c(1,1,0))
```

will fit the model  $y'_t = \beta_1 x'_t + \eta'_t$ , where  $\eta'_t = \phi_1 \eta'_{t-1} + \varepsilon_t$  is an AR(1) error. This is equivalent to the model

$$y_t = \beta_0 + \beta_1 x_t + \eta_t,$$

where  $\eta_t$  is an ARIMA(1,1,0) error. Notice that the constant term disappears due to the differencing. To include a constant in the differenced model, specify

```
include.drift=TRUE .
```

The `auto.arima()` function will also handle regression terms via the `xreg` argument. The user must specify the predictor variables to include, but `auto.arima()` will select the best ARIMA model for the errors. If differencing is required, then all variables are differenced during the estimation process, although the final model will be expressed in terms of the original variables.

The AICc is calculated for the final model, and this value can be used to determine the best predictors. That is, the procedure should be repeated for all subsets of predictors to be considered, and the model with the lowest AICc value selected.

### Example: US Personal Consumption and Income

Figure 9.1 shows the quarterly changes in personal consumption expenditure and personal disposable income from 1970 to 2016 Q3. We would like to forecast changes in expenditure based on changes in income. A change in income does not necessarily translate to an instant change in consumption (e.g., after the loss of a job, it may take a few months for expenses to be reduced to allow for the new circumstances). However,

we will ignore this complexity in this example and try to measure the instantaneous effect of the average change of income on the average change of consumption expenditure.

```
autoplot(uschange[,1:2], facets=TRUE) +  
  xlab("Year") + ylab("") +  
  ggtitle("Quarterly changes in US consumption  
    and personal income")
```




Figure 9.1: Percentage changes in quarterly personal consumption expenditure and personal disposable income for the USA, 1970 to 2016 Q3.

```
(fit <- auto.arima(uschange[, "Consumption"],
  xreg=uschange[, "Income"]))
#> Series: uschange[, "Consumption"]
#> Regression with ARIMA(1,0,2) errors
#>
#> Coefficients:
#>          ar1      ma1      ma2  intercept    xreg
#>       0.692  -0.576   0.198      0.599   0.203
#> s.e.  0.116   0.130   0.076      0.088   0.046
#>
#> sigma^2 estimated as 0.322:  log likelihood=-156.9
#> AIC=325.9  AICc=326.4  BIC=345.3
```

The data are clearly already stationary (as we are considering percentage changes rather than raw expenditure and income), so there is no need for any differencing. The fitted model is

$$\begin{aligned}
 y_t &= 0.599 + 0.203x_t + \eta_t, \\
 \eta_t &= 0.692\eta_{t-1} + \varepsilon_t - 0.576\varepsilon_{t-1} + 0.198\varepsilon_{t-2}, \\
 \varepsilon_t &\sim \text{NID}(0, 0.322).
 \end{aligned}$$

We can recover estimates of both the  $\eta_t$  and  $\varepsilon_t$  series using the `residuals()` function.

```
cbind("Regression Errors" = residuals(fit, type="regression"),
      "ARIMA errors" = residuals(fit, type="innovation")) %>%
  autoplot(facets=TRUE)
```




Figure 9.2: Regression errors ( $\eta_t$ ) and ARIMA errors ( $\varepsilon_t$ ) from the fitted model.

It is the ARIMA errors that should resemble a white noise series.

```
checkresiduals(fit)
```

### Residuals from Regression with ARIMA(1,0,2) errors




Figure 9.3: The residuals (i.e., the ARIMA errors) are not significantly different from white noise.

```
#>
#>  Ljung-Box test
#>
#> data:  Residuals from Regression with ARIMA(1,0,2) errors
#> Q* = 5.89, df = 3, p-value = 0.12
#>
#> Model df: 5.    Total lags used: 8
```