

Augmented Dickey Fuller Test (ADF Test)

– Must Read Guide

by [Selva Prabhakaran](https://www.machinelearningplus.com/author/selva86/) (https://www.machinelearningplus.com/author/selva86/)

[f](#) (/#facebook) [t](#) (/#twitter) [w](#) (/#whatsapp) [in](#) (/#linkedin) [r](#) (/#reddit)

[G](#) (/#google_bookmarks)

[+](https://www.addtoany.com/share?url=https%3A%2F%2Fwww.machinelearningplus.com%2Ftime-series%2Faugmented-dickey-fuller-test%2F&title=Augmented%20Dickey%20Fuller%20Test%20(ADF%20Test)%20%E2%80%93%20Must%20Read%20Guide) (https://www.addtoany.com/share?url=https%3A%2F%2Fwww.machinelearningplus.com%2Ftime-series%2Faugmented-dickey-fuller-test%2F&title=Augmented%20Dickey%20Fuller%20Test%20(ADF%20Test)%20%E2%80%93%20Must%20Read%20Guide)

Augmented Dickey Fuller test (ADF Test) is a common statistical test used to test whether a given Time series is stationary or not. It is one of the most commonly used statistical test when it comes to analyzing the stationary of a series.

1. Introduction

In [ARIMA time series forecasting](https://www.machinelearningplus.com/time-series/arima-model-time-series-forecasting-python/) (https://www.machinelearningplus.com/time-series/arima-model-time-series-forecasting-python/), the first step is to determine the number of differencing required to make the series stationary.

Since testing the stationarity of a time series is a frequently performed activity in autoregressive models, the ADF test along with [KPSS test](https://www.machinelearningplus.com/time-series/kpss-test-for-stationarity/) (https://www.machinelearningplus.com/time-series/kpss-test-for-stationarity/) is something that you need to be fluent in when performing [time series analysis](https://www.machinelearningplus.com/time-series/time-series-analysis-python/) (https://www.machinelearningplus.com/time-series/time-series-analysis-python/).

Another point to remember is the ADF test is fundamentally a statistical significance test. That means, there is a hypothesis testing involved with a null and alternate hypothesis and as a result a test statistic is computed and [p-values](https://www.machinelearningplus.com/statistics/p-value/) (https://www.machinelearningplus.com/statistics/p-value/) get reported.

It is from the test statistic and the p-value, you can make an inference as to whether a given series is stationary or not.

Recommended

Time Series Analysis in Python – A Comprehensive Guide with Examples (https://www.machinelearningplus.com/time-series/time-series-analysis-python/)

Vector Autoregression (VAR) – Comprehensive Guide with Examples in Python (https://www.machinelearningplus.com/time-series/vector-autoregression-examples-python/)

ARIMA Model – Complete Guide to Time Series Forecasting in Python (https://www.machinelearningplus.com/time-series/arima-model-time-series-forecasting-python/)

Augmented Dickey Fuller Test (ADF Test) – Must Read Guide (https://www.machinelearningplus.com/time-series/augmented-dickey-fuller-test/)

KPSS Test for Stationarity (https://www.machinelearningplus.com/time-series/kpss-test-for-stationarity/)



[ezoic](https://www.ezoic.com/what-is-ezoic/) (https://www.ezoic.com/what-is-ezoic/)

Top Posts & Pages

[report this ad](#)

ARIMA Model - Complete Guide to Time Series Forecasting in Python (https://www.machinelearningplus.com/time-series/arima-model-time-series-forecasting-python/)

Parallel Processing in Python - A Practical Guide with Examples (https://www.machinelearningplus.com/python/parallel-processing-python/)


So, how exactly does the ADF test work? let's see the mathematical intuition behind the test with clear examples.

Let's begin.

2. What is a Unit Root Test?

The ADF test belongs to a category of tests called 'Unit Root Test', which is the proper method for testing the stationarity of a time series.

So what does a 'Unit Root' mean?



Unit root is a characteristic of a time series that makes it non-stationary. Technically speaking, a unit root is said to exist in a time series if the value of $\alpha = 1$ in the below equation.

(https://www.machinelearningplus.com/wp-content/uploads/2019/11/equation_1.png)

where, y_t is the value of the time series at time t and X_t is an exogenous variable (a separate explanatory variable, which is also a time series).

What does this mean to us?

The presence of a unit root means the time series is non-stationary. Besides, the number of unit roots contained in the series corresponds to the number of differencing operations required to make the series stationary.

Alright, let's come back to topic.

3. Dickey-Fuller Test

Before going into ADF test, let's first understand what is the Dickey-Fuller test.

A Dickey-Fuller test is a unit root test that tests the null hypothesis that $\alpha=1$ in the following model equation. α is the coefficient of the first lag on Y .

Null Hypothesis (H_0): $\alpha=1$

(https://www.machinelearningplus.com/wp-content/uploads/2019/11/equation_2.png)

where,

Time Series Analysis in Python - A Comprehensive Guide with Examples (<https://www.machinelearningplus.com/time-series/time-series-analysis-python/>)

Topic Modeling with Gensim (Python) (<https://www.machinelearningplus.com/nlp/topic-modeling-gensim-python/>)

Top 50 matplotlib Visualizations - The Master Plots (with full python code) (<https://www.machinelearningplus.com/plots/top-50-matplotlib-visualizations-the-master-plots-python/>)

Machine Learning Better Explained! (<https://www.machinelearningplus.com/>)

Cosine Similarity - Understanding the math and how it works (with python codes) (<https://www.machinelearningplus.com/nlp/cosine-similarity/>)

Matplotlib Histogram - How to Visualize Distributions in Python (<https://www.machinelearningplus.com/plots/matplotlib-histogram-python-examples/>)

101 Pandas Exercises for Data Analysis (<https://www.machinelearningplus.com/python/101-pandas-exercises-python/>)

Lemmatization Approaches with Examples in Python (<https://www.machinelearningplus.com/nlp/lemmatization-examples-python/>)

Recent Posts

Matplotlib Plotting Tutorial – Complete overview of Matplotlib library (<https://www.machinelearningplus.com/plots/matplotlib-plotting-tutorial/>)

How to implement Linear Regression in TensorFlow (<https://www.machinelearningplus.com/deep-learning/linear-regression-tensorflow/>)

Brier Score – How to measure accuracy of probabilistic predictions (<https://www.machinelearningplus.com/statistics/brier-score/>)

Modin – How to speedup pandas by changing one line of code (<https://www.machinelearningplus.com/python/modin-speedup-pandas/>)

Dask – How to handle large dataframes in python using parallel computing (<https://www.machinelearningplus.com/python/dask-tutorial/>)

Text Summarization Approaches for NLP – Practical Guide with Generative Examples (<https://www.machinelearningplus.com/nlp/text-summarization-approaches-nlp-example/>)

Bias Variance Tradeoff – Clearly Explained (<https://www.machinelearningplus.com/machine-learning/bias-variance-tradeoff/>)

Gradient Boosting – A Concise Introduction from Scratch (<https://www.machinelearningplus.com/machine-learning/gradient-boosting/>)

- $y(t-1)$ = lag 1 of time series
- $\Delta Y(t-1)$ = first difference of the series at time $(t-1)$

Fundamentally, it has a similar null hypothesis as the unit root test. That is, the coefficient of $Y(t-1)$ is 1, implying the presence of a unit root. If not rejected, the series is taken to be non-stationary.

The Augmented Dickey-Fuller test evolved based on the above equation and is one of the most common form of Unit Root test.

4. How does Augmented Dickey Fuller (ADF) Test work?

As the name suggest, the ADF test is an 'augmented' version of the Dickey Fuller test.

The ADF test expands the Dickey-Fuller test equation to include high order regressive process in the model.

(https://www.machinelearningplus.com/wp-content/uploads/2019/11/equation_3.png).

If you notice, we have only added more differencing terms, while the rest of the equation remains the same. This adds more thoroughness to the test.

The null hypothesis however is still the same as the Dickey Fuller test.

A key point to remember here is: Since the null hypothesis assumes the presence of unit root, that is $\alpha=1$, the p-value obtained should be less than the significance level (say 0.05) in order to reject the null hypothesis. Thereby, inferring that the series is stationary.

However, this is a very common mistake analysts commit with this test. That is, if the p-value is less than significance level, people mistakenly take the series to be non-stationary.

5. ADF Test in Python

So, how to perform a Augmented Dickey-Fuller test in Python?

The `statsmodel` package provides a reliable implementation of the ADF test via the `adfuller()` function in `statsmodels.tsa.stattools`. It returns the following outputs:

1. The p-value

Complete Guide to Natural Language Processing (NLP) – with Practical Examples (<https://www.machinelearningplus.com/nlp/natural-language-processing-guide/>)

Portfolio Optimization with Python using Efficient Frontier with Practical Examples (<https://www.machinelearningplus.com/machine-learning/portfolio-optimization-python-example/>)

What does Python Global Interpreter Lock – (GIL) do? (<https://www.machinelearningplus.com/python/python-global-interpreter-lock-gil/>)

Logistic Regression in Julia – Practical Guide with Examples (<https://www.machinelearningplus.com/julia/logistic-regression-in-julia-practical-guide-with-examples/>)

Tags

Chatbot

(<https://www.machinelearningplus.com/tag/chatbot/>)

Classification

(<https://www.machinelearningplus.com/tag/classification/>)

Confidence Interval

(<https://www.machinelearningplus.com/tag/confidence-interval/>)

dask

(<https://www.machinelearningplus.com/tag/dask/>)

data.table

(<https://www.machinelearningplus.com/tag/data-table/>)

Data Manipulation

(<https://www.machinelearningplus.com/tag/data-manipulation/>)

Debugging

(<https://www.machinelearningplus.com/tag/debugging/>)

Evaluation Metrics

(<https://www.machinelearningplus.com/tag/evaluation-metrics/>)

Exercises

(<https://www.machinelearningplus.com/tag/exercises/>)

FastText

(<https://www.machinelearningplus.com/tag/fasttext/>)

Gensim

(<https://www.machinelearningplus.com/tag/gensim/>)

HuggingFace

(<https://www.machinelearningplus.com/tag/huggingface/>)

Julia

(<https://www.machinelearningplus.com/tag/julia/>)

Julia Packages

(<https://www.machinelearningplus.com/tag/julia-packages/>)

LDA

(<https://www.machinelearningplus.com/tag/lda/>)

Lemmatization

(<https://www.machinelearningplus.com/tag/lemmatization/>)

Linear Regression

(<https://www.machinelearningplus.com/tag/linear-regression/>)

Logistic

(<https://www.machinelearningplus.com/tag/logistic/>)

Loop

(<https://www.machinelearningplus.com/tag/loop/>)

Machine Learning

(<https://www.machinelearningplus.com/tag/machine-learning/>)

2. The value of the test statistic
3. Number of lags considered for the test
4. The critical value cutoffs.

When the test statistic is lower than the critical value shown, you reject the null hypothesis and infer that the time series is stationary.

Alright, let's run the ADF test on the `a10` dataset from the `fpp` package from R. This dataset counts the total monthly scripts for pharmaceutical products falling under ATC code A10. The original source of this dataset is the Australian Health Insurance Commission.

As seen earlier, the null hypothesis of the test is the presence of unit root, that is, the series is non-stationary.

```
# Setup and Import data
from statsmodels.tsa.stattools import adfuller
import pandas as pd
import numpy as np
%matplotlib inline

url = 'https://raw.githubusercontent.com/selva86/datasets/master/a10.csv'
df = pd.read_csv(url, parse_dates=['date'], index_col='date')
series = df.loc[:, 'value'].values
df.plot(figsize=(14,8), legend=None, title='a10 - Drug Sales Series');
```

(https://www.machinelearningplus.com/wp-content/uploads/2019/11/a10_series.png)

The packages and the data is loaded, we have everything needed to perform the test using `adfuller()`.

An optional argument the `adfuller()` accepts is the number of lags you want to consider while performing the OLS regression.

By default, this value is $12 \cdot (\text{nobs}/100)^{1/4}$, where `nobs` is the number of observations in the series. But, optionally you can specify either the maximum number of lags with `maxlags` parameter or let the algorithm compute the optimal number iteratively.

This can be done by setting the `autolag='AIC'`. By doing so, the `adfuller` will choose a the number of lags that yields the lowest AIC. This is usually a good option to follow.

learning/) Matplotlib

(<https://www.machinelearningplus.com>.

NLP

(<https://www.machinelearningplus.com>

NLTK

(<https://www.machinelearningplus.com/tag/nltk/>)

Numpy

(<https://www.machinelearningplus.com/tag/numpy/>)

P-Value

(<https://www.machinelearningplus.com/tag/p-value/>)

plots

(<https://www.machinelearningplus.com/tag/plots/>)

Practice Exercise

(<https://www.machinelearningplus.com/tag/practice-exercise/>)

Python

(<https://www.machinelearningplus.com/tag/python/>)

R

(<https://www.machinelearningplus.com/tag/r/>)

Regex (<https://www.machinelearningplus.com/tag/regex/>)

Regression

(<https://www.machinelearningplus.com/tag/regression/>)

Residual Analysis

(<https://www.machinelearningplus.com/tag/residual-analysis/>)

Significance Tests

(<https://www.machinelearningplus.com/tag/significance-tests/>)

Soft Cosine Similarity

(<https://www.machinelearningplus.com/tag/soft-cosine-similarity/>)

spaCy

(<https://www.machinelearningplus.com/tag/spacy/>)

Stationarity

(<https://www.machinelearningplus.com/tag/stationarity/>)

Statistics

(<https://www.machinelearningplus.com/tag/statistics/>)

Tensorflow

(<https://www.machinelearningplus.com/tag/tensorflow/>)

TextBlob

(<https://www.machinelearningplus.com/tag/textblob/>)

TextSummarization

(<https://www.machinelearningplus.com/tag/textsummarization/>)

Text Summarization

(<https://www.machinelearningplus.com/tag/text-summarization/>)

Time Series

(<https://www.machinelearningplus.com/tag/time-series/>)

Topic Modeling

(<https://www.machinelearningplus.com/tag/topic-modeling/>)

T Test

(<https://www.machinelearningplus.com/tag/t-test/>)

Visualization

(<https://www.machinelearningplus.com/tag/visualization/>)

```
# ADF Test
result = adfuller(series, autolag='AIC')
print(f'ADF Statistic: {result[0]}')
print(f'n_lags: {result[1]}')
print(f'p-value: {result[2]}')
for key, value in result[4].items():
    print('Critical Values:')
    print(f' {key}, {value}')
```

Result:

```
ADF Statistic: 3.1451856893067296
n_lags: 1.0
p-value: 1.0
Critical Values:
1%, -3.465620397124192
Critical Values:
5%, -2.8770397560752436
Critical Values:
10%, -2.5750324547306476
```

The p-value is obtained is greater than significance level of 0.05 and the ADF statistic is higher than any of the critical values.

Clearly, there is no reason to reject the null hypothesis. So, the time series is in fact non-stationary.

6. ADF Test on stationary series

Now, let's see another example of performing the test on a series of random numbers which is usually considered as stationary.

Let's use `np.random.randn()` to generate a randomized series.

```
# ADF test on random numbers
series = np.random.randn(100)
result = adfuller(series, autolag='AIC')
print(f'ADF Statistic: {result[0]}')
print(f'p-value: {result[1]}')
for key, value in result[4].items():
    print('Critical Values:')
    print(f' {key}, {value}')
```

Result:

```
ADF Statistic: -7.4715740767231456
p-value: 5.0386184272419386e-11
Critical Values:
1%, -3.4996365338407074
Critical Values:
5%, -2.8918307730370025
Critical Values:
10%, -2.5829283377617176
```

The p-value is very less than the significance level of 0.05 and hence we can reject the null hypothesis and take that the series is stationary.

Let's visualise the series as well to confirm.

```
import matplotlib.pyplot as plt
%matplotlib inline
fig, axes = plt.subplots(figsize=(10,7))
plt.plot(series);
plt.title('Random');
```

https://www.machinelearningplus.com/wp-content/uploads/2019/11/random_series.png

7. Conclusion

We saw how the Augmented Dickey Fuller Test works and how to perform it using `statsmodels`. Now given any time series, you should be in a position to perform the ADF Test and make a fair inference on whether the series is stationary or not.

In the next one we'll see how to perform the [KPSS test](https://www.machinelearningplus.com/time-series/kpss-test-for-stationarity/)

Understanding the math and how it works? ...

2 years ago • 15 comments

Cosine similarity is a metric used to measure how similar the documents are ...

List Comprehensions in Python – My ...

2 years ago • 6 comments

List comprehensions is a pythonic way of expressing a 'For Loop' that appends to a ...

Parallel Processing in Python – A Practical ...

2 years ago • 11 comments

Parallel processing is when the task is executed simultaneously in multiple processors. In ...

Simplified C

Clear Exam

2 years ago • 2 c

datetime is the for working wi python. It prov

What do you think?

6 Responses

Upvote

Love

3 Comments

machinelearningplus.com

Disqus' Privacy Policy

1

 Login ▾

Recommend

Tweet

Share

Sort by Newest ▾

Join the discussion...

LOG IN WITH

OR SIGN UP WITH DISQUS

Name

Samurai Fox • a year ago

Great Article on ADFuller !

I ran the adfuller and output is as below:

```
`ADF Statistic: -2.457146`  
`p-value: 0.126252`  
`Critical Values: 1%: -3.438, 5%: -2.865, 10%: -2.569`
```

<https://github.com/RSwarnka...>

Is series stationary or non-stationary?

(<https://www.ezoic.com/what-is-ezoic/>)
report this ad

Search ...

Search

Subscribe to Blog

Enter your email address to receive notifications of new posts by email.

Email Address

Subscribe

Copyright ML+ (<https://www.machinelearningplus.com/>). All rights reserved.

[Home \(https://www.machinelearningplus.com\)](https://www.machinelearningplus.com/) [Contact Us \(https://www.machinelearningplus.com/contact-us/\)](https://www.machinelearningplus.com/contact-us/)

[Privacy Policy \(https://www.machinelearningplus.com/privacy-policy/\)](https://www.machinelearningplus.com/privacy-policy/) [About Selva \(https://www.machinelearningplus.com/about/\)](https://www.machinelearningplus.com/about/)

[Terms and Conditions \(https://www.machinelearningplus.com/terms-of-use/\)](https://www.machinelearningplus.com/terms-of-use/)