Mavzu: **JavaScriptni faol veb-sahifalar uchun dasturlash.**

Reja:

1. DOM tushunchasi
2. DOM Window obyekti
3. DOM stillar bilan ishlash
4. DOM Document obyekti

DOM tushunchasi

HTML DOM bilan JavaScript HTML hujjatining barcha elementlariga kirish va o'zgartirish imkoniyatiga ega

Boshqacha qilib aytganda: HTML DOM HTML elementlarini qanday olish, o'zgartirish, qo'shish yoki yo'q qilish uchun standartdir.

```
<h2>My First Page</h2>
```

```
<p id="demo"></p>

<script>

document.getElementById("demo").
innerHTML = "Hello World!";

</script>
```

DOM Window (print)

```
<p>Click the button to print the current page.</p>

<button onclick="myFunction()">Print this page</button>

<script>

function myFunction() {

  window.print(); }

</script>
```

DOM Window (open)

```
<p>Click the button to open a new browser window.</p>

<button onclick="myFunction()">Try it</button>

<script>

function myFunction() {

window.open("https://www.kun.uz"); }

</script>
```

DOM Window (prompt)

```
<p>Click the button to demonstrate the prompt box.</p>

<button onclick="myFunction()">Try it</button>

<p id="demo"></p>

<script>

function myFunction() {

  var person = prompt("Please enter your name", "Harry Potter");

  if (person != null) {

    document.getElementById("demo").innerHTML =

    "Hello " + person + "! How are you today?";   }  }

</script>
```

DOM Window (confirm)

```
<p>Click the button to display a confirm box. </p>

<button onclick="myFunction()">Try it</button>

<script>

function myFunction() {

  confirm("Press a button!"); }

</script>
```

DOM Window (close)

```
<button onclick="openWin()">Open "myWindow"</button>

<button onclick="closeWin()">Close "myWindow"</button>

<script>

var myWindow;

function openWin() {

  myWindow = window.open("", "myWindow",
"width=200,height=100");

  myWindow.document.write("<p>This is 'myWindow'</p>");}

function closeWin() {

  myWindow.close(); }

</script>
```

DOM Window (focus)

```
<p>Click the button to open a new window, and assure that the new window GETS focus (send the new window to the front).</p>

<button onclick="myFunction()">Try it</button>

<script>

function myFunction() {

  var myWindow = window.open("", "", "width=200,height=100");

  myWindow.document.write("<p>A new window!</p>");

  myWindow.focus(); }

</script>
```

DOM style (backgroundColor)

```
<h1>Hello World!</h1>

<button type="button"
onclick="myFunction()">Set background
color</button>

<script>

function myFunction() {

 document.body.style.backgroundColor = "red";
}

</script>
```

DOM Style (bakcgroundimage)

```
<h1>Hello World!</h1>

<button type="button" onclick="myFunction()"> Set background image</button>

<script>

function myFunction() {

  document.body.style.backgroundColor = "#f3f3f3";

  document.body.style.backgroundImage = "url('img_tree.png')"; }

</script>
```

DOM Document (close)

```
<p>Click the button to open an output stream, add some text, and close the output stream.</p>

<button onclick="myFunction()">Try it</button>

<script>
function myFunction() {
  document.open();
  document.write("<h1>Hello World</h1>");
  document.close(); }
</script>
```